

# Intro to Quarto and Tidyverse

Philip Loewen

09/01/26

## Table of contents

<b>By the end of this lab you should know the basics of</b>	<b>1</b>
<b>RStudio Projects</b>	<b>2</b>
<b>Quarto</b>	<b>2</b>
Writing math . . . . .	3
<b>Tidyverse</b>	<b>3</b>
Important tidyverse functions . . . . .	4
Piping, filtering, selecting, arranging . . . . .	4
Grouping, summarizing, mutating . . . . .	7
Pivoting . . . . .	9
Using ggplot . . . . .	10
More than one group . . . . .	13
Faceting . . . . .	15
<b>Lab Exercises</b>	<b>16</b>
Question 1 . . . . .	17
Question 2 . . . . .	17
Question 3 . . . . .	18
Question 4 . . . . .	19

**By the end of this lab you should know the basics of**

- RStudio Projects
- Quarto
- Main tidyverse functions
- ggplot

## RStudio Projects

RStudio projects are associated with R working directories. They are good to use for several reasons:

- Each project has their own working directory, so make dealing with file paths easier
- Make it easy to divide your work into multiple contexts
- Can open multiple projects at one time in separate windows

To make a new project in RStudio, go to File → New Project. If you've already set up a repo for this class, then select 'Existing Directory' and choose the folder that will contain all your class materials. This will open a new RStudio window, that will be called the name of your folder.

In future, when you want to do work for this class, go to your class folder and open the .Rproj file. This will open an RStudio window, with the correct working directory, and show the files you were last working on.

## Quarto

This is a Quarto document. Quarto allows you to create nicely formatted documents (HTML, PDF, Word) that also include code and output of the code. This is good because it's reproducible, and also makes reports easier to update when new data comes in. Each of the grey chunks contains R code, just like a normal R script. You can choose to run each chunk separately, or knit the whole document using Knit the button above, which creates your document.

To start a new Quarto file in Rstudio, go to File → New File → Quarto, then select Document and whatever you want to compile the document as (I chose pdf, and that's generally what we'll be doing in this class). Notice that this and the other inputs (title, author) are used to create the 'yaml', the bit at the start of the document. You can edit this, like I have for example to include table of contents.

When you hit 'Render' a pdf will be created and saved in the same folder as your `qmd` file. There are various options for output code, results, etc. For example, if you don't want your final report to include the code (but just the output, e.g. graphs or tables) then you can specify `#| echo=FALSE` at the top of the chunk (note: this syntax is different R Markdown).

Quarto is a newer version of R Markdown. It's the first year I'm switching and so I'm fine if people would rather stick to R Markdown for now. A helpful intro is here: <https://quarto.org/docs/get-started/hello/rstudio.html>

## Writing math

Writing equations is essentially the same as in LaTeX. You can write inline equations using the `$` e.g.  $y = ax + b$ . You can write equations on a separate line with two `$`s e.g.

$$y = ax + b$$

In pdf documents you can have numbered equations using

$$y = ax + b \tag{1}$$

Getting greek letters, symbols, subscripts, bars etc is the same as LaTeX. A few examples are below

- $Y_{i,j}$
- $\bar{X} = \frac{\sum_{i=1}^n X_i}{n}$
- $\alpha\beta\gamma$
- $X \rightarrow Y$
- $Y \sim N(\mu, \sigma^2)$

## Tidyverse

Read in some packages that we'll be using:

```
#install.packages("tidyverse")  
library(tidyverse)
```

On top of the base R functionality, there's lots of different packages that different people have made to improve the usability of the language. One of the most successful suite of packages is now called the 'tidyverse'. The tidyverse contains a range of functionality that help to manipulate and visualize data.

Read in mortality rates for Ontario. These data come from the [Canadian Human Mortality Database](https://www.prhh.umontreal.ca/BDLC/data/ont/Mx_1x1.txt).

```
dm <- read_table("https://www.prhh.umontreal.ca/BDLC/data/ont/Mx_1x1.txt", skip = 2, col_type  
head(dm)
```

```
# A tibble: 6 x 5  
  Year Age   Female   Male   Total  
<dbl> <chr>   <dbl>   <dbl>   <dbl>
```

1	1921	0	0.0978	0.129	0.114
2	1921	1	0.0129	0.0144	0.0137
3	1921	2	0.00521	0.00737	0.00631
4	1921	3	0.00471	0.00457	0.00464
5	1921	4	0.00461	0.00433	0.00447
6	1921	5	0.00372	0.00361	0.00367

The object `dm` is a data frame, or tibble. Every column can be a different data type (e.g. we have integers and characters).

## Important tidyverse functions

You should feel comfortable using the following functions

- The pipe `|>` or `%>%`
- `filter`
- `select`
- `arrange`
- `mutate`
- `group_by`
- `summarize`
- `pivot_longer` and `pivot_wider`

## Piping, filtering, selecting, arranging

A central part of manipulating tibbles is using the `|>` function. This is a pipe, but should be read as saying ‘and then’. Note that the `|>` syntax is the base version of the pipe (new last year). Previously the syntax was `%>%` through the `magrittr` package. They essentially function the same.

For example, say we just want to pull out mortality rates for 1935. We would take our tibble *and then* filter to only include 1935:

```
dm |>
  filter(Year==1935) # two equals signs logical
```

```
# A tibble: 111 x 5
   Year Age      Female      Male      Total
  <dbl> <chr>    <dbl>    <dbl>    <dbl>
1  1935 0      0.0513   0.0652   0.0584
2  1935 1      0.00607  0.00742  0.00676
```

```

3  1935 2      0.00350  0.00321  0.00336
4  1935 3      0.00187  0.00321  0.00255
5  1935 4      0.0013   0.00238  0.00185
6  1935 5      0.00152  0.00186  0.00169
7  1935 6      0.00136  0.00174  0.00155
8  1935 7      0.00120  0.00154  0.00137
9  1935 8      0.000984 0.00130  0.00114
10 1935 9      0.000996 0.00140  0.00120
# i 101 more rows

```

```

# we could say
filter(dm, Year==1935)

```

```

# A tibble: 111 x 5
   Year Age      Female      Male      Total
  <dbl> <chr>    <dbl>    <dbl>    <dbl>
1  1935 0      0.0513   0.0652   0.0584
2  1935 1      0.00607  0.00742  0.00676
3  1935 2      0.00350  0.00321  0.00336
4  1935 3      0.00187  0.00321  0.00255
5  1935 4      0.0013   0.00238  0.00185
6  1935 5      0.00152  0.00186  0.00169
7  1935 6      0.00136  0.00174  0.00155
8  1935 7      0.00120  0.00154  0.00137
9  1935 8      0.000984 0.00130  0.00114
10 1935 9      0.000996 0.00140  0.00120
# i 101 more rows

```

You can also filter by more than one condition; say we just wanted to look at 10 year olds in 1935:

```

dm |>
  filter(Year==1935, Age==10)

```

```

# A tibble: 1 x 5
   Year Age      Female      Male      Total
  <dbl> <chr>    <dbl>    <dbl>    <dbl>
1  1935 10      0.000884 0.00143  0.00116

```

If we only wanted to look at 10 year olds in 1935 who were female, we could filter *and then* select the female column.

```
dm |>
  filter(Year==1935, Age==10) |>
  select(Female)
```

```
# A tibble: 1 x 1
  Female
  <dbl>
1 0.000884
```

You can also remove columns by selecting the negative of that column name.

```
colnames(dm)
```

```
[1] "Year"    "Age"     "Female"  "Male"    "Total"
```

```
dm |>
  select(-Total)
```

```
# A tibble: 11,433 x 4
   Year Age   Female   Male
  <dbl> <chr>   <dbl>   <dbl>
1  1921 0     0.0978  0.129
2  1921 1     0.0129  0.0144
3  1921 2     0.00521 0.00737
4  1921 3     0.00471 0.00457
5  1921 4     0.00461 0.00433
6  1921 5     0.00372 0.00361
7  1921 6     0.00265 0.00393
8  1921 7     0.00295 0.00351
9  1921 8     0.00237 0.00285
10 1921 9     0.00198 0.00255
# i 11,423 more rows
```

Sort the tibble according to a particular column using **arrange**, for example, Year in descending order:

```
dm |>
  arrange(-Year)
```

```
# A tibble: 11,433 x 5
  Year Age   Female   Male   Total
  <dbl> <chr>   <dbl>   <dbl>   <dbl>
1  2023 0     0.00387 0.00482 0.00436
2  2023 1     0.000177 0.00035 0.000266
3  2023 2     0.000146 0.000195 0.000171
4  2023 3     0.000167 0.000134 0.00015
5  2023 4     0.000095 0.000223 0.00016
6  2023 5     0.00008 0.000164 0.000123
7  2023 6     0.000104 0.000037 0.00007
8  2023 7     0.000153 0.000073 0.000112
9  2023 8     0.000076 0.000024 0.00005
10 2023 9     0.000076 0.00006 0.000068
# i 11,423 more rows
```

NOTE: none of the above operations are saving. To save, you need to assign the output to an object. You can call it something new or overwrite the original.

## Grouping, summarizing, mutating

In addition to `filter` and `select`, two useful functions are `mutate`, which allows you to create new variables, and `summarize`, which allows you to produce summary statistics. These are particularly powerful when combined with `group_by()` which allows you to do any operation on a tibble by group.

For example, let's create a new variable that is the ratio of male to female mortality at each age and year:

```
dm <- dm |>
mutate(mf_ratio = Male/Female)
```

Now, let's calculate the mean female mortality rate by age over all the years. To do this, we need to `group_by` Age, and then use `summarize` to calculate the mean:

```
summary_mean <- dm |>
  group_by(Age) |>
  summarize(mean_mortality = mean(Female, na.rm = TRUE))

dim(summary_mean)
```

```
[1] 111  2
```

```
dim(dm)
```

```
[1] 11433      6
```

Mean of males and females by age

```
dm |>
  group_by(Age) |>
  summarize(mean_mortality_f = mean(Female, na.rm = TRUE),
            mean_mortality_m = mean(Male, na.rm = TRUE))
```

```
# A tibble: 111 x 3
  Age   mean_mortality_f mean_mortality_m
<chr>         <dbl>         <dbl>
1 0           0.0245           0.0311
2 1           0.00253          0.00287
3 10          0.000413          0.000571
4 100          0.424           0.462
5 101          0.446           0.492
6 102          0.491           0.564
7 103          0.529           0.640
8 104          0.651           0.768
9 105          0.796           0.883
10 106          0.791           0.705
# i 101 more rows
```

Alternatively using across

```
dm |>
  group_by(Age) |>
  summarize(across(Male:Female, mean))
```

```
# A tibble: 111 x 3
  Age      Male      Female
<chr>    <dbl>    <dbl>
1 0      0.0311    0.0245
2 1      0.00287   0.00253
3 10     0.000571   0.000413
4 100     0.462     0.424
5 101     0.492     0.446
```



```

6 102    0.564    0.491
7 103    0.640    0.529
8 104    NA      0.651
9 105    NA      NA
10 106   NA      NA
# i 101 more rows

```

## Pivoting

We often need to switch between wide and long data format. The `dm` tibble is currently in wide format. To get it in long format we can use `pivot_longer`

```

dm_long <- dm |>
  select(-mf_ratio) |>
  pivot_longer(Female:Total, names_to = "sex", values_to = "mortality")
dm_long

```

```

# A tibble: 34,299 x 4
   Year Age  sex    mortality
  <dbl> <chr> <chr>      <dbl>
1  1921 0    Female  0.0978
2  1921 0    Male    0.129
3  1921 0    Total   0.114
4  1921 1    Female  0.0129
5  1921 1    Male    0.0144
6  1921 1    Total   0.0137
7  1921 2    Female  0.00521
8  1921 2    Male    0.00737
9  1921 2    Total   0.00631
10 1921 3    Female  0.00471
# i 34,289 more rows

```

Revert this

```

dm_long |>
  pivot_wider(names_from = "sex", values_from = "mortality")

```

```

# A tibble: 11,433 x 5
   Year Age  Female  Male  Total
  <dbl> <chr>   <dbl> <dbl> <dbl>

```

```

1  1921 0      0.0978 0.129  0.114
2  1921 1      0.0129 0.0144 0.0137
3  1921 2      0.00521 0.00737 0.00631
4  1921 3      0.00471 0.00457 0.00464
5  1921 4      0.00461 0.00433 0.00447
6  1921 5      0.00372 0.00361 0.00367
7  1921 6      0.00265 0.00393 0.00330
8  1921 7      0.00295 0.00351 0.00323
9  1921 8      0.00237 0.00285 0.00262
10 1921 9      0.00198 0.00255 0.00227
# i 11,423 more rows

```

## Using ggplot

You can plot things in R using the base `plot` function, but plots using `ggplot` are much prettier.

Say we wanted to plot the mortality rates for 30 year old males over time. In the function `ggplot`, we need to specify our data (in this case, a filtered version of `dm`), an x axis (Year) and y axis (Male). The axes are defined withing the `aes()` function, which stands for 'aesthetics'.

First let's get our data:

```

d_to_plot <- dm |>
  filter(Age==30) |>
  select(Year, Male)
d_to_plot

```


```

# A tibble: 103 x 2
   Year      Male
  <dbl>   <dbl>
1  1921 0.00375
2  1922 0.00462
3  1923 0.00497
4  1924 0.00412
5  1925 0.00308
6  1926 0.00308
7  1927 0.00327
8  1928 0.00356
9  1929 0.00393
10 1930 0.00418
# i 93 more rows

```


Now start the ggplot:

```
p <- ggplot(data = d_to_plot, aes(x = Year, y = Male))  
p
```



Notice the object `p` is just an empty box. The key to ggplot is layering: we now want to specify that we want a line plot using `geom_line()`:

```
p +  
  geom_line()
```



Let's change the color of the line, and the y-axis label, and give the plot a title:

```
p +  
  geom_line(color = "firebrick4")+  
  labs(title = "30 year old Male mortality rates over time, Ontario",  
        subtitle = "this is a subtitle",  
        y = "Mortality rate") +  
  theme_bw(base_size = 14)
```

## 30 year old Male mortality rates over time, Or this is a subtitle




### More than one group

Now say we wanted to have trends for 30-year old males and females on the one plot. The easiest way to do this is to first reshape our data so it's in long format: so instead of having a column for each sex, we have one column indicating the sex, and another column indicating the Mx value

```
dp <- dm |>
  filter(Age==30) |>
  select(Year:Male) |>
  pivot_longer(Female:Male, names_to = "Sex", values_to = "Mortality")
```


Now we can do a similar plot to before but we now have an added component in the `aes()` function: color, which is determined by sex:

```
dp |>
  ggplot(aes(x = Year, y = Mortality, color = Sex)) +
  geom_line() +
  scale_color_brewer(palette = "Set1")
```



```
dp <- dm |>
  filter(Age==30|Age==60) |>
  select(Year:Male) |>
  pivot_longer(Female:Male, names_to = "Sex", values_to = "Mortality")

dp |>
  ggplot(aes(x = Year, y = Mortality, color = Sex, linetype = Age)) +
  geom_line() +
  scale_color_brewer(palette = "Set1")
```



## Faceting


A neat thing about ggplot is that it's relatively easy to create 'facets' or smaller graphs divided by groups. Say we wanted to look at trends for 30 year olds and 60 year olds for both males and females. Let's get the data ready to plot:

```
dp
```

```
# A tibble: 412 x 4
  Year Age  Sex  Mortality
  <dbl> <chr> <chr>    <dbl>
1  1921  30   Female  0.00486
2  1921  30   Male    0.00375
3  1921  60   Female  0.0231
4  1921  60   Male    0.0228
5  1922  30   Female  0.00510
6  1922  30   Male    0.00462
7  1922  60   Female  0.0194
8  1922  60   Male    0.0212
9  1923  30   Female  0.00429
10 1923  30   Male    0.00497
# i 402 more rows
```

Now let's plot, with a separate facet for each sex:

```
dp |>
  ggplot(aes(x = Year, y = Mortality, color = Age)) +
  geom_line()+
  facet_grid(~Sex)
```



## Lab Exercises

1. Plot the ratio of male to female mortality rates over time for ages 10,20,30 and 40 (different color for each age) and change the theme
2. Find the age that has the highest female mortality rate each year
3. Use the `summarize(across())` syntax to calculate the standard deviation of mortality rates by age for the Male, Female and Total populations.
4. The Canadian HMD also provides population sizes over time (<https://www.prhdh.umontreal.ca/BDLC/data/ont/Population.txt>). Use these to calculate the population weighted average mortality rate separately for males and females, for every year. Make a nice line plot showing the result (with meaningful labels/titles) and briefly comment on what you see (1 sentence). Hint: `left_join` will probably be useful here.




## Question 1

Plot the ratio of male to female mortality rates over time for ages 10,20,30 and 40 (different color for each age) and change the theme

```
dn <- dm |>
  filter(Age==10|Age==20|Age==30|Age==40)

dn |>
  ggplot(aes(x = Year, y = mf_ratio, color = Age)) +
  geom_line() +
  scale_color_brewer(palette = "Set1") +
  theme_bw(base_size = 14)
```



## Question 2

Find the age that has the highest female mortality rate each year

```
dm |>
  select(Year:Female) |>
  group_by(Year) |>
  summarise(Highest_mortality_age = Age[which.max(Female)])
```

```
# A tibble: 103 x 2
  Year Highest_mortality_age
  <dbl> <chr>
1 1921 106
2 1922 98
3 1923 104
4 1924 107
5 1925 98
6 1926 106
7 1927 106
8 1928 104
9 1929 104
10 1930 105
# i 93 more rows
```

### Question 3

Use the `summarize(across())` syntax to calculate the standard deviation of mortality rates by age for the Male, Female and Total populations.

```
dm |>
  select(Year:Total) |>
  group_by(Age) |>
  summarise(across(Female:Total, sd))
```

```
# A tibble: 111 x 4
  Age      Female      Male      Total
  <chr>    <dbl>    <dbl>    <dbl>
1 0       0.0255    0.0328    0.0292
2 1       0.00348  0.00392    0.00370
3 10      0.000469  0.000558    0.000506
4 100     0.0915    0.136     0.0719
5 101     0.123     0.156     0.0978
6 102     0.141     0.210     0.112
7 103     0.248     0.365     0.205
8 104     0.442     NA        0.358
9 105     NA        NA        NA
10 106     NA        NA        NA
# i 101 more rows
```

## Question 4


The Canadian HMD also provides population sizes over time (<https://www.prhh.umontreal.ca/BDLC/data/ont/Population.txt>). Use these to calculate the population weighted average mortality rate separately for males and females, for every year. Make a nice line plot showing the result (with meaningful labels/titles) and briefly comment on what you see (1 sentence). Hint: `left_join` will probably be useful here.

```
pcan <- read_table("https://www.prhh.umontreal.ca/BDLC/data/ont/Population.txt",
                   skip = 1, col_types = "dcddd")
```

```
joined <- dm |>
  left_join(pcan, by = join_by(Year, Age))

fwamr <- joined |>
  group_by(Year) |>
  summarise(Female = weighted.mean(Female.x, Female.y))
mwamr <- joined |>
  group_by(Year) |>
  summarise(Male = weighted.mean(Male.x, Male.y))

left_join(fwamr, mwamr, by = join_by(Year)) |>
  pivot_longer(cols = Female:Male,
               names_to = "Sex", values_to = "Weighted_Average_Mortality") |>
  ggplot(aes(x = Year, y = Weighted_Average_Mortality, color = Sex)) +
  geom_line() +
  scale_color_brewer(palette = "Set1") +
  theme_bw(base_size = 14) +
  labs(y = "Weighted Average Mortality Rate")
```



We notice that the population weighted average mortality rate is higher than the non-weighted average mortality rate, with a steeper decrease until the late 20th century, followed by a short period of increased mortality rates.