

VarioHyve Language Specification

Ciprian Teodorov

07-10-2026

Contents

I. Motivation	1
1. Behavioral Federation	2
II. Specification	6
2. Program Structure	7
3. Literals	10
4. Objects and Classes	14
5. Slots and Accessors	22
6. Message Sends	25
7. Apply and Callable Values	29
8. Syntactic Sugar	30
9. Name Resolution	32
10. Recursion	37
11. Descriptors	39
12. Foreign Semantic Values and the Alien/Expat Boundary	41
III. Implementation	50
13. Runtime Object Representation	51
14. Java Interpreter	56
15. Tooling Architecture	63
IV. Future	65
16. Future Directions	66

V. Related Works	73
17.Connections and Comparisons	74
VI. Appendix	77
A. Formal Rules	78

Part I.

Motivation

1. Behavioral Federation

VarioHyve investigates how programs can coordinate systems that keep their own meaning, execution mechanisms and authority. A model repository, a simulator and a running controller can cooperate without becoming objects of one universal model or processes of one execution engine. The difficult part is making the agreements between them explicit enough to understand, change and examine.

We call this **behavioral federation**. The experiment combines an object language, a native/foreign boundary and an explicit execution model. Its working hypothesis is that a small, coherent set of mechanisms can make coordination behavior easier to reuse and its assumptions easier to inspect. An executable bootstrap now allows that hypothesis to be investigated through programs and tests. Whether the combination improves real engineering workflows remains an empirical question.

1.1. Cooperation Without Complete Control

A system-of-systems brings together participants that retain substantial operational and managerial independence. Their owners, release cycles and objectives need not coincide. Engineering environments encounter a related problem when requirements, designs, simulations and operational records live in different tools. The engineered product need not itself be a system-of-systems for its engineering models to require federation.

Consider a pumping station. A requirements model states a minimum flow, a hydraulic simulator predicts performance, and maintenance records describe the installed equipment. Each may refer to the same pump while expressing different facts about it. Assessing a proposed replacement requires a correspondence between those references, compatible units, an agreed revision of the design and a policy for interpreting the analysis. Authorizing the replacement requires additional authority. A successful assessment alone does not supply it.

API connectivity solves only part of this problem. A simulator may finish after the relevant design has changed. A service may fail after accepting a request, leaving its effects uncertain. A callback may arrive while the coordinator is waiting for a result. The engineer needs to know which observations support a decision, which assumptions remain in force and what a failed interaction means. Replacing the simulator with a recorded trace should expose the changed assumptions while preserving the intended coordination protocol.

These needs become language and tooling questions when the workflow must be maintained across many projects. Builders of modeling environments need reusable behavior over heterogeneous models, traceable evidence and controlled access to tools. Moving every model into a new metamodel can be expensive or inappropriate; reimplementing every participant's behavior can lose exactly the semantics that made it useful. Existing federation and model-management tools already address substantial parts of this problem. VarioHyve asks what a compact coordination language can contribute alongside them,

and what it costs compared with their own workflows or direct host-language code.

1.2. Agreements Expressed Through Objects

The approach starts with supplied capabilities: objects whose behavior grants access to particular services or resources. A coordinator receives the capabilities it needs and exchanges objects by sending messages. Its inputs can represent a narrow model query, an analysis operation or permission to record evidence. The supplying system determines the available authority; the coordinator’s source makes its use visible.

This is also a commitment to semantic sovereignty. Foreign participants retain their own execution and interpretation of operations. The boundary states how messages, values, identity, failures and callbacks cross between them. An operation may return an ordinary value or promise an explicit outcome protocol, just as a native method may. A shared message syntax does not establish agreement about units, revisions or successful completion: those remain part of the supplied operation’s contract.

Here, “contract” means an agreement about behavior and authority, not an implemented contract language or automatic proof system. The boundary makes such agreements a subject of design. It also makes their limits visible. For example, foreign code running in the same host process can terminate that process; a capability interface alone does not provide process containment.

1.3. A Language for Explicit Dependencies

The following module illustrates the shape of a coordinator:

```
class Assessment(modelSource, checker, evidenceSink) {
  models = modelSource;
  analysis = checker;
  evidence = evidenceSink;

  assess(item) {
    var snapshot = models.snapshot(item);
    evidence.record(snapshot, analysis.check(snapshot))
  }
}
```

The host supplies three existing objects when it constructs `Assessment`; it later requests an assessment by sending `assess`. The module retains its inputs in slots because constructor parameters belong to initialization, rather than becoming instance-method bindings. Nothing in this code requires the three services to be implemented in VarioHyve. Their selectors are application agreements, and the example deliberately leaves their failure and evidence policies to those agreements.

A normal module begins over an empty top activation. It receives external capabilities through explicit constructor inputs and, subsequently, message arguments and the behavior of objects already available to it. There is no ambient application namespace. Supplied objects keep their own authority and captured scopes, so a short parameter list is

not by itself an isolation proof. The [program-structure chapter](#) defines this entry contract precisely.

Within the language, objects and message sends also organize access and reuse. Slots are accessed through messages; lexical scopes are activation objects and ordinary objects. Classes are first-class values. Composition uses reified contributions and application occurrences, retaining the declaration origins that determine scope and invocation. A reusable analysis stage can therefore keep access to its defining provider even when applied in a receiving module with similarly named bindings. The rules aim to make that behavior predictable without merging independently defined models into a deep class family.

For language design, the question is whether these mechanisms work together without hidden exceptions at each point of reuse. Definition scope, receiver identity and contribution selection must remain intelligible when code moves between modules or across a foreign boundary. The specification fixes these rules independently of the Java representation, giving alternative implementations a contract to preserve. That precision also exposes costs in notation, implementation and debugging that the experiments must assess.

Foreign values appear inside the language as **Aliens**; native behavior is exported as **Ex-pats**. Sending a message to an Alien uses the ordinary source syntax. The adapter mediates the operation, and foreign code may call an Expat while the native caller waits. Language-visible VM services use this same boundary, with separately granted privileged capabilities. Explicit mirrors can offer information beyond ordinary behavior. The [boundary chapter](#) defines these interactions, including identity, failure and the default prohibition on non-local returns crossing a foreign call.

1.4. Making Execution Available for Inquiry

Coordination becomes easier to investigate when execution itself has a precise description. VarioHyve's machine exposes configurations and transitions for evaluation, invocation, storage and control. This supports a correspondence between language rules, executable behavior and observations made by tools. It does not by itself establish that correspondence as a proved theorem.

The current sequential execution agreement uses a conceptual **control token** for ordinary native execution. A native-to-foreign call transfers control to the foreign side; an admitted callback can return it to native execution before the original call completes. Multiple callback workers must negotiate admission, and the current implementation serializes their native execution. The token need not be a runtime object. Its purpose is to describe an agreement that an implementation must realize.

That agreement leaves room for explicitly confined extensions. A collector may perform concurrent maintenance if it preserves the required abstract behavior. A monitor may have a separately specified intervention capability. A future parallel machine may execute proven-independent transitions under an appropriate execution agreement. These possibilities have distinct obligations; granting one does not silently grant unrestricted execution authority. The [formal appendix](#) states the model and its limits, while [Future Directions](#) separates accepted extension principles from mechanisms still to be developed.

This opens two different lines of inquiry for formal methods. A coordinator can call an external checker as a supplied capability. Separately, an analyzer can be derived for the co-

ordinator’s own execution semantics. The first requires an agreement about the checker’s inputs, results and assumptions; the second needs an abstraction and soundness argument, including a treatment of foreign effects. Neither alone verifies a complete federation or its physical environment. Descriptors can carry tooling information, but attaching information does not establish its truth. Keeping these distinctions explicit makes proposed claims testable and clarifies the evidence still required.

1.5. What the Bootstrap Establishes

The present result is an executable language bootstrap centered on `VisitorSemanticsVM`. It includes parsing and lowering, explicit module entry, object and class construction, reified composition, lexical lookup, closures and return-home checks, a native heap collector, and a synchronous Java Alien/Expat boundary. Semantic regressions exercise the interactions between these mechanisms. The implementation chapters identify concrete policies and remaining limitations; executable tests are evidence about those policies, not a substitute for their specification.

The [composition case study](#) provides a small but concrete federation slice. Native source coordinates Java fixture services for model observations, validation, capacity checking and evidence. Reusable stages preserve their defining checker capabilities despite competing bindings in the receiving module. Its acceptance cases cover successful and rejected assessments, early failure and a selected foreign operation failing without being replayed. This tests capability flow and composition using controlled participants.

The slice does not yet integrate an industrial model repository or simulator, and it establishes no comparative productivity or performance advantage. The [case-study catalog](#) develops the next experiments around explicit baselines, measurable outcomes and failure conditions. Useful findings include cases where an existing tool or direct adapter is simpler. Current measurement infrastructure also supports language implementation experiments, with workload and measurement boundaries documented separately.

1.6. Positioning and Reading the Experiment

VarioHyve draws on object languages, capability security, behavioral reflection and explicit operational semantics. Openflexo, Epsilon and CorrLang provide important comparisons for model federation and coordination; Smalltalk and Newspeak inform the language lineage. Work on monitoring and analysis supplies ways to formulate the questions raised by observable execution. The [Related Works part](#) explains the relevant connections and differences without treating them as delivered integrations or inherited proofs.

The rest of the book moves from agreement to realization. **Specification** defines language behavior, including the foreign boundary. **Implementation** describes the Java bootstrap and its tooling. **Future** records extension principles, proposals and unresolved work. **Related Works** situates the experiment, and the **Appendix** gives the formal rules. This opening **Motivation** supplies the questions behind those parts: can explicit capabilities and preserved semantic boundaries make coordination easier to understand, and can explicit execution make its behavior easier to investigate?

Part II.

Specification

2. Program Structure

Operational definition: [SOS entry rules](#).

2.1. A Program Is a Single Expression

The grammar entry is `top: expression? EOF`. Empty input is an empty expression; normal expression evaluation returns canonical null. A named or anonymous **class literal** can instead serve as a module. Naming it retains declaration metadata without creating an ambient binding. Module instantiation requires a class literal and rejects empty input or other expression forms without executing them.

The introductory [Assessment example](#) is such a module. Its instantiation service supplies the three existing objects `modelSource`, `checker` and `evidenceSink`; a caller later sends `assess(item)`. These selectors are application contracts, not built-in services.

2.2. Sources of an Object's Capabilities

An object's behavior can access capabilities through inherited behavior, mixin contributions, lexical nesting and explicitly supplied inputs. Inputs include constructor arguments during initialization and arguments to later messages. Further capabilities may become available through message results.

These routes do not change [lookup order](#). Contributions retain their definition scopes; calling a class from another scope does not supply the caller's bindings.

Constructor parameters are available only during initialization. Retaining these inputs for later use requires slots or deliberate captures, as specified by the [definition-scope rules](#). These rules apply equally to native and foreign capabilities.

A capability can be a native object, including a class with factory behavior, or an [Alien](#). Its offered behavior may return further objects or create new ones. Authority therefore includes behavior and captured scopes, not merely objects present in an initial heap. Nesting shares enclosing capabilities; it is not an isolation boundary.

2.3. Top-Level Classes and Instantiation

Normal module definition evaluates the class over a **fresh empty top activation**. The execution frame exists, but has no capability accessors, lexical parent, receiver or enclosing application scope. The class inherits only from structural root `Object` and composes no mixins. This structural relationship supplies neither an `Object` binding nor a platform namespace. Every explicit top-level superclass or mixin clause is rejected before its expressions execute, including a clause spelled `Object`.

At entry, the module's declared constructor arguments are its only external capability

inputs. Zero, one or multiple arguments are allowed, with exact arity. The service passes existing objects, preserving identity and sharing through the ordinary boundary. It does not lend the module its own scope, registry or other services. Supplied objects retain their capabilities and captures; later explicit message arguments are additional inputs.

Class definition precedes construction, so constructor arguments cannot provide that top-level class's superclass or mixins. They can be stored and used when realizing **nested** classes:

```
class Module(baseClass, loggingMixin) {
  Base = baseClass;
  Logging = loggingMixin;
  class Worker(identifier) <: Logging < Base { id = identifier; }
}
```

The host receives the constructed module instance and explicitly chooses any entry message. Instantiation does not guess or send `main` or `run`. Construction failure does not return a successful instance; effects already performed are not rolled back, and an initializer may deliberately share `self`.

2.4. The Kernel Parameter

A kernel is an optional ordinary bundle, not a reserved name, mandatory parameter or global lookup mechanism. Services may be separate inputs or grouped in native/Alien bundles. Passing a narrow object does not remove authority already retained by its methods, enclosing scopes or composed contributions.

2.4.1. Optional Bootstrap Bundle

A platform may bundle canonical values, libraries and I/O capabilities. Bundle inventory and the behavior of its selectors are platform contracts. Source names such as `null`, `true` and `false` select behavior through ordinary lookup; their spelling establishes no canonical identity. See [names and contracts](#). The current tooling bundle is described in [the Java implementation](#).

2.5. Bootstrap Conformance Requirements

Definition, construction and synchronous callbacks share the requested execution budget. Host sends supply an empty caller activation; the target's definition supplies its lexical scope. The concrete APIs and validation are documented under [module entry](#) and in the [implemented entry decision](#).

2.6. Development and Debugging Contexts

Richer [tool evaluation contexts](#) are distinct from normal module entry. A class created with tooling authority retains those captures and cannot silently be treated as an isolated module.

2.7. Error Handling

Current execution failures abort their native continuation; they are not catchable language values. A failed FN callback reports its diagnostic to foreign code, which may handle it and complete the enclosing NF call normally. Missing dispatch does not invoke a language-level `doesNotUnderstand` handler. Uninitialized reads, unresolved holes, invalid contributors and invalid returns also fail explicitly; [return rules](#) specify dead homes, initializer completion and callback barriers. Public diagnostics expose neither raw activation addresses nor host exceptions. The boundary preserves its [defined failure kinds](#). [Conditions and restarts](#) remain proposed work.

3. Literals

The literal forms are numbers, strings, holes, lambdas, classes and objects. Class and object syntax is defined in [Objects and Classes](#); this chapter owns scalar syntax, closure returns and initializer completion.

`null`, `true` and `false` are ordinary source names, not literal forms. Their occurrences are message sends under [name resolution](#). Canonical `null` for omitted initializers or empty bodies is supplied directly by the language; it does not depend on a declaration named `null`.

Operational definition: [SOS evaluation](#) and [return rules](#).

3.1. Number Literals

```
numberLiteral : '-'? NUMBER ;
NUMBER       : NATURAL ('.' NATURAL)? ;
fragment NATURAL : [0-9]+ ;
```

Examples: 42, -7, 3.14159 and -0.5. Numbers use decimal notation; arithmetic and comparisons are messages such as `x.plus(1)` and `x.greaterThan(0)`. The syntax does not settle the numeric domain, precision or overflow behavior. The prototype's supported subset is documented under [implementation limits](#).

3.2. String Literals

Single and double quotes produce the same runtime kind of value. Both support:

Escape	Meaning
\\	Backslash
\", \'	Double or single quote
\/	Slash
\b, \f	Backspace, form feed
\n, \r, \t	Newline, carriage return, tab
\uXXXX	Unicode escape with four hexadecimal digits

```
"hello"
'it\'s fine'
"line one\nline two"
"\u0041" // A
```

3.2.1. Multi-Line Strings

Raw newlines are allowed inside either quoted form. They preserve all whitespace between the quotes, including indentation; "a\nb" and the corresponding two-line literal have the same content. See the lexer in [vh.g4](#).

3.3. Hole Literals

? is an explicit incomplete expression, valid wherever an expression is expected. It has its own AST node and differs from both an omitted initializer and canonical null. A missing initializer supplies null; a hole remains unresolved.

3.3.1. Descriptors on Holes

Use parenthesized [descriptor syntax](#), for example (? : expected(Controller) : reason("integration input")). Descriptors can inform diagnostics or a separately selected analysis tool; they do not silently change raw execution.

3.3.2. Runtime Semantics

A hole supplies no normal value by itself. Reaching it must invoke the execution context's explicit hole policy. The concrete bootstrap reports UnresolvedHole. Interactive suspension, externally supplied replacements, abstract values, branching and synthesis are possible richer tooling policies, not implemented guarantees. Their interpretation must be specified by that context; accepting partial syntax does not imply an abstract interpreter.

3.3.3. Hole Identity

Each syntactic occurrence denotes a distinct hole. Tools should retain a stable internal identity, normally based on AST/source identity, for diagnostics, annotations, filling, traces or replay. A descriptor-supplied name or qualified source path may identify a hole to a tool. Two occurrences of ? do not become one hole merely because their spelling is equal.

3.4. Lambda Literals

fun and λ introduce lambdas. Parentheses around the parameter list are optional when it is empty. Bodies are semicolon-separated statement lists; an empty body and a trailing semicolon are allowed.

```
fun { 42 }
fun(x) { x.plus(1) }
λ(x, y) { x.plus(y) }
```

A lambda captures its evaluation scope, current receiver, contribution origin and lexical return home. It does not capture its later caller's scope. Captured activation data can outlive the creating invocation. A lambda supplies exact `apply/N` at its declared parameter count; binding invocation uses the [ordinary eligibility rules](#). Optional descriptors follow the closing brace.

A lambda is a native object with its own identity and the inherited [root Object protocol](#). Distinct evaluations create distinct objects. Object-method sends use the lambda as receiver; its `apply/N` body instead uses the captured receiver and return home. Inheritance neither changes lexical `self` nor exposes captures. There is no public Lambda factory or ambient Lambda binding; the private representation is described in [Core Structures](#).

3.4.1. Implicit Return

Methods and lambdas return their final expression's value on normal completion. An empty body returns canonical null. This normal result returns from the current invocation; it does not perform a non-local return.

3.4.2. Early Return with `^`

`^` expression first evaluates its operand, then returns to the lexically enclosing method or initializer home. Lambda invocation creates no new home.

Creation context	Target of <code>^</code>
Method body or a lambda created there	That method invocation
Initializer or a lambda created there	That initializer contribution invocation
Supplied outside lambda	Its original home, even when called during construction

A missing or retired home causes a dead-context error. Captured data does not preserve return authority. A return crossing foreign execution is governed by the [boundary agreement](#). The default agreement requires a live home reachable without crossing an active Alien callback barrier; supporting agreements must preserve these native home and initializer rules. Successful unwinding retires intervening invocation homes. Operand failure propagates as failure rather than completing a return.

Class expressions retain definition-time bindings, but each later initializer invocation creates a fresh home. An outside lambda can unwind construction to its own live accessible home; it is never rebound to the initializer.

3.5. Class Literals

The `class` keyword creates a named or anonymous class value. See [class literal syntax](#) and the distinction between [member declarations](#) and [class expressions](#).

3.6. Object Literals

`{ body }`, optionally prefixed by mixin and superclass clauses such as `<: M(p) < S(q)`
`{ body }`, realizes a fresh anonymous zero-parameter class and immediately sends its primary `new/0`. It has no constructor parameter list or factories; contributor arguments and initialization follow the class rules. See [object literals](#).

3.7. Initializer completion

A class or object body may end with `|` and an optional ordinary statement list. This section executes after that contribution's ordered slot initializers:

```
class Config(input) {
  saved = input;
  value { saved }
  |
  ^ "done"
}
```

Primary construction returns the allocated receiver, not "done". No member, method, factory or slot declarations follow the delimiter; ordinary statements, including `var` and class expressions, are allowed. An empty `|` section is valid.

Descriptor lists also use `|`. Terminate a preceding described member, method or factory with `;` to separate post-slot code: `value { saved } : Tag; | performWork`.

Each contribution invocation has a fresh private return home:

- **Slot phase:** returning to that home is an error, including during the final slot expression. The phase ends only after its final value is written.
- **Post-slot phase:** normal completion or `^ value` completes that contribution and ignores the value. Subsequent contributions still run.
- **Every exit:** normal completion, early return, failure and unwinding retire the home. Escaped data remain usable without retaining return authority.

Constructor parameters are visible in both initialization phases, under the [construction scope rules](#). An outside lambda retains its original home. The default Alien callback barrier remains in force; any future crossing support must preserve these initializer phase restrictions. Failures neither replay initialization nor roll back effects or retract an escaped receiver. See the [accepted policy](#).

4. Objects and Classes

This chapter defines class and object literals, member declarations, composition, and factories. [Name Resolution](#) defines lexical receivers; [Message Sends](#) defines invocation; [Literals](#) defines initializer completion and returns. Backend records belong to [Runtime Object Representation](#).

Operational definition: [SOS class and construction rules](#).

4.1. Top and the Class Algebra

Top is the empty constructor of the mixin–class algebra. At the level of instance-side composition, the inductive structure is:

```
ClassShape ::= Top | Apply(Mixin, ClassShape)
Object      = Apply(ObjectMixin, Top)
```

Like zero in an inductive definition of natural numbers, Top supplies the base case. Every nonempty class shape is a mixin applied to another shape, so even Object follows the same construction rule. Apply here is mathematical composition, not the source apply selector or a factory invocation.

Top contributes no methods, slots, member declarations, definition scope, capabilities or initialization. Lookup ends there with a miss and its layout is empty. Only Object has Top as its direct superclass; other native class chains reach it through Object. The owned Object mixin supplies the root protocol below. Thus adding the empty base does not remove that protocol or change the capabilities available through it.

The algebra describes composition structure, not class identity. A realized class retains its owned contribution, ordered direct applications, superclass, routes and metaclass. Expanding its shape neither manufactures intermediate class objects nor erases contribution scopes or occurrence identities. The [formal rules](#) give this projection precisely.

Top is a distinguished semantic base, not an instantiable class or a language-visible value in the current contract. It has no metaclass, factory, owned mixin to import, or public mirror reference. The class/metaclass rules below apply to realized classes. No built-in Top binding or new reserved name is introduced, and omitted superclass clauses still select Object. The empty **top activation** for module entry is a separate execution frame. Aliens acquire no native hierarchy through this definition.

The VM may represent the terminal case without allocating an object: [the implementation refinement](#) states the mapping and the conditions for reconsidering runtime reification.

4.2. The class Keyword

class distinguishes an instantiable class from an immediately evaluated object:

Form	Result
<code>class { body } or class() { body }</code>	Anonymous zero-parameter class
<code>class(params) { body }</code>	Anonymous class with constructor parameters
<code>class Name { body } or class Name() { body }</code>	Named zero-parameter class
<code>class Name(params) { body }</code>	Named class with constructor parameters
<code>{ body }</code>	One object, allocated and initialized on each evaluation
<code><: Mixins(args) < Base(args) { body }</code>	One object with the selected mixins and superclass

4.2.1. Class Literal Syntax

```

namedClassLiteral
  : CLASS IDENT arguments mixinApplications superclassApplication
    LB classBodyElement* initializerBody? RB (COLON descriptorList)* ;
anonymousClassLiteral
  : CLASS arguments mixinApplications superclassApplication
    LB classBodyElement* initializerBody? RB (COLON descriptorList)* ;
classLiteral      : namedClassLiteral | anonymousClassLiteral ;
arguments         : (LP formalList? RP)? ;
mixinApplications : (WITH expressionList)? ;
superclassApplication: (EXTENDS expression)? ;
classBodyElement  : namedClassLiteral SEMICOLON? | methodDecl SEMICOLON?
                  | slotDecl SEMICOLON | factoryDecl SEMICOLON? ;
factoryDecl       : FACTORY methodDecl ;
initializerBody   : PIPE statementList? ;

```

WITH is <: or with; EXTENDS is < or extends. Empty parameter parentheses are optional. Class bodies contain slots, methods, member classes and factories, followed by an optional final | statement section. Slot declarations require semicolons; methods, members and factories permit them. Descriptor chains retain their [annotation syntax](#).

4.2.2. Object Literals

```

objectLiteral      : mixinApplications superclassApplication
                  LB objectBodyElement* initializerBody? RB (COLON
↪ descriptorList)* ;
objectBodyElement: namedClassLiteral SEMICOLON? | methodDecl SEMICOLON?
                  | slotDecl SEMICOLON ;

```

An object literal has no constructor parameter list or factories. Its optional mixin and superclass clauses have the same syntax, order and meaning as class clauses: mixins precede

the superclass; `<:/with` and `</extends` are synonyms. Omitting the superclass selects structural root `Object`, without name lookup. Slot declarations still require their terminating semicolon.

```
<: M1(p1), M2(p2) < S(p3) { x = 5; }
< S(p) { x = 5; }
with M(p) { x = 5; }
```

Each evaluation realizes a fresh anonymous zero-parameter class, then immediately sends its generated primary `new/0` using ordinary exact message dispatch. Thus `<: M(p) < S(q) { body }` is equivalent to `(class <: M(p) < S(q) { body }).new`, with a factory-free body. Successful evaluation returns the initialized object. Repeated evaluation creates distinct class, metaclass and instance identities; it does not cache a singleton. Contributor factories and custom apply methods are not called or imported.

All [constructor-clause rules](#) apply. Targets resolve left-to-right for direct mixins, then the superclass, in the literal's evaluation scope before allocation. Routed arguments run later in its own initializer activation, immediately before their contribution is initialized. In particular, `self` in a target computation denotes the enclosing receiver, while `self` in a routed argument denotes the new object. Ordinary initializer lookup also applies: an own slot can shadow an enclosing name and is still uninitialized during routing. For example, `< S(x) { x = 5; }` cannot use its own pending `x` as an argument; use a distinct captured binding or a qualified outer receiver when that is intended.

The anonymous class captures the literal's evaluation scope, including deliberate creation inside another initializer. Contributors retain their own definition scopes and initializer-only constructor parameters; parameters are not added to instance-method bindings. Each contribution keeps its normal initialization order, occurrence, storage rules and private return home. Anonymous objects introduce no new outer qualifier.

An object literal remains an expression, not a valid normal module entry. Nested literals may use explicitly supplied module inputs, under the existing [module restrictions](#).

4.2.3. Zero-Parameter Classes vs Singletons

For class `Config { debug = false; }`, `Config()` invokes its `apply/0` factory; `Config.new` and `Config.new()` each perform primary construction once. For `config = { debug = false; };`, the slot already holds the initialized object. See [zero-arity invocation](#).

4.3. Root Object Protocol

In the current runtime seed, native objects, including lambdas, inherit these ordinary methods from root `Object`:

```
equals(other) { _vm.same(self, other) }
hash { _vm.identityHash(self) }
toString { "an Object" }
```

These are normative defaults of this seed. Another seed may choose different root methods without changing lookup, invocation or boundary laws. Replacing an application kernel does not replace the structural root; selecting another seed is not a current runtime API.

Root Object does not supply `same` or `identityHash`. Reliable identity and classification observations belong to an explicitly supplied [IdentityMirror capability](#). The mirror observes subjects without invoking their methods. Defining these selector names on an application object cannot intercept mirror observations or the root defaults' direct use of `_vm`; no selector is thereby reserved on Aliens.

`equals` defaults to native identity equality, including identity recovered from an owned Expat. Canonical null and Booleans participate with their native identities. The default hash returns an integer stable for the identity's lifetime; equal identities have equal hashes, but collisions are permitted. Hashes are neither addresses nor persistent identifiers across runtime sessions.

`equals`, `hash` and `toString` remain overridable. Equality overrides should define a reflexive, symmetric, transitive relation with compatible hashes. The defaults provide identity-derived results without a separately supplied mirror; the mirror grants observation independent of subject behavior.

The default `toString` returns exactly "an Object". It reveals neither a class name nor an instance or class identity hash. Named and anonymous instances, class objects, meta-classes and lambdas retain this generic answer unless they override it. Canonical values keep their explicit null, true and false overrides. Diagnostic detail is therefore chosen by the object's own protocol.

`_vm` is a narrow seed capability in Object's detached definition scope, not an inherited slot, ambient module binding or accessor for IdentityMirror. Its operations cross the normal Alien/Expat boundary and expose no backend representation. Aliens retain their own protocols and do not acquire these methods by inheritance. Scalar Object behavior and identity remain subject to [the scalar design decision](#).

4.4. Capabilities and Definition Scope

The [capability sources](#) do not change definition scope: calling a class does not capture its caller's scope. Named and anonymous classes follow the same rule. Examples with custom contributors or enclosing bindings assume an appropriate enclosing context; [isolated modules](#) and [tooling evaluation](#) have distinct entry contracts.

Constructor parameters are immutable bindings available only during initialization. Methods cannot resolve their own constructor arguments, even when called during initialization. Store persistent dependencies in slots. Lambdas and class expressions deliberately evaluated in an initializer may capture its parameters. Each contribution receives its own argument bindings; composition does not replace its captured definition dependencies.

4.4.1. Member Declarations and Class Expressions

A named class in body-declaration position declares a **member class**:

```

class Container(input) {
  value = input;
  class Member { read { value } }
  Captured = class { read { input } };
  NamedCapture = class Snapshot { read { input } };
}

```

Member binds to the enclosing receiver and its declaration/application origin. Its zero-argument accessor lazily realizes and caches one class per enclosing receiver and declaration occurrence. Repeated access returns that identity; different enclosing receivers or application occurrences obtain distinct classes. The member binds to the actual enclosing receiver while retaining the selected occurrence's captured lexical ancestry at every depth, including when selected through `super`. Its factories retain that same definition parent. Ordinary messages to the enclosing receiver still honor overrides; retaining ancestry does not restrict virtual sibling selection to the originating contribution. See [lexical receiver selection](#).

The member can use stored value, but cannot acquire Container's constructor binding input. Members are available regardless of their position among slot initializers.

Captured and NamedCapture are slots initialized by class expressions. Both capture the evaluation scope, including input. An expression's optional name is declaration metadata, not a binding introduced in the surrounding body. Anonymous forms occur only as expressions; named forms can be expressions or member declarations. Lowering must preserve this distinction.

Member and slot names share a namespace; duplicates in one body are errors. A member also conflicts with a zero-argument method of the same name and has no setter. A stored class is callable through its current value; a member advertises the selected declaration's constructor and owned factory apply arities before realization. Wrong-arity invocation evaluates no contributor targets. Selected realization failures, including cycles or abandonment during non-local return, are cached without replay. See [member invocation](#) for selection and overriding.

4.4.2. Initializer Bodies

The optional `final |` section executes after the contribution's ordered slots. Constructor parameters remain available. No member, method, slot or factory declarations follow the delimiter; ordinary statements, including local `var` and class expressions, may occur there. Its ordinary result or permitted early-return value is ignored. The complete phase, home-lifetime and failure rules are in [Initializer completion](#).

4.5. Inheritance

`< Base(args)` selects a native class and inherits its complete instance-side chain: owned contribution, applied mixins and ancestors. Omitting the clause uses structural root `Object`, without looking up the name `Object`. An instance or `Alien` is not a class target; no implicit `instance.class` conversion occurs. Native `super` cannot be a contributor target.

Construction runs the superclass's complete initializer schedule on the newly allocated receiver. Inheritance imports no factories; factories belong to the [declaring class](#).

4.6. Mixins

`<: A(args), B(args)` applies the **owned reified contribution** of each selected native class: directly declared methods, slots, member classes, constructor formals and own initializer. It imports no source superclass, applied mixins, factories or argument routes. The definition scope remains captured. Resolving the source class itself still realizes its targets normally; applying its owned contribution does not evaluate those original constructor argument routes.

For example, if `A <: M1, M2 < S1`, `B <: M3, M4 < S2`, and `C <: A < B`, the contribution order is:

```
own(C), own(A), own(B), own(M3), own(M4), then the complete S2 chain
```

`own(X)` means `X`'s owned contribution. No intermediate classes are introduced. Repeated applications share the reified definition but have distinct application occurrences and initializer invocations. A contributed method's super resumes from its application occurrence; see [Name Resolution](#). Public mixin extraction and reflection are not part of the current language.

4.7. Constructor Clauses

The terminal application in a superclass or mixin clause has construction semantics. It selects a contributor during class realization and retains the argument expressions for each later construction; it does not call a factory. Bare targets route zero arguments, and parentheses around the whole clause do not change its meaning.

4.7.1. Computed Contributor Targets

For `< registry.choose(kind).Base(x)`, realization evaluates `registry.choose(kind)` and reads `Base`; construction later evaluates `x`. Receiver subexpressions perform ordinary computations. Direct mixin targets run left-to-right, then the superclass target. Their choices are fixed for the realized class. This applies to class expressions and cached member classes.

4.7.2. Construction Order

For class `C(x) <: A(a), B(b) < S(s) { ... }`, successful primary construction:

1. Allocates one receiver with fresh uninitialized storage for its complete layout.
2. Evaluates `s` and runs `S`'s complete initialization schedule on that receiver.
3. Evaluates `b` and runs `B`'s owned initializer, then does the same for `a` and `A`.
4. Runs `C`'s own ordered slots and final body, then returns the allocated receiver.

Each argument list is evaluated once, left-to-right, immediately before its private target invocation. Argument expressions run in the declaring contribution's initializer activation, with its constructor parameters bound. Superclass and applied-mixin calls receive their own bindings and fresh homes. The declaring routes and owned body share one logical home, established before routing begins. Routing precedes slot completion, so returning to that home from a route cannot finish construction early. Each contribution completes its slots and final body before the next contribution runs.

These calls are private identity-bound routines, never selectors named `initialize` or public operations on arbitrary receivers. Initializer writes bypass overridable setters. No component instances are allocated, no effects are replayed or rolled back, and escaped partial receivers are not retracted. Return and failure handling follows [Initializer completion](#).

4.7.3. Ordered Overrides and Shared State

Own declarations have precedence, followed by direct mixins left-to-right, then the superclass recursively. At each contribution, selector/accessor choice follows [Message Sends](#). A member override selects the whole declaration and its origin; it does not merge nested families automatically. Duplicate slots, members or exact method selectors within one body remain errors; an explicit method may override a generated slot accessor.

Every slot retains its logical identity (applying `class`, `occurrence`, `local slot`). **Same-named contributions share storage.** Initialization runs in the reverse contribution order above, so later writes replace earlier values. Every occurrence still initializes, including repeated applications. Surviving methods may therefore observe shared state; this policy does not promise independent stateful mixins. Getter/setter eligibility and mutability belong to the selected declaration, even when storage is shared. Renaming, explicit state mapping and deep family composition require future rules.

4.8. Factories

A factory method is sent to the class object; an ordinary method is sent to its instances. Both use ordinary method invocation and lexical scope.

4.8.1. The Primary Factory (`new`)

Every source class and root `Object` has a generated, non-overridable primary `new/N`, where `N` is its constructor arity. Successful invocation allocates a fresh receiver, executes the complete construction schedule and returns that receiver. Its selector uses ordinary lookup; only its generated body contains private construction operations. Object literals automatically send this primary `new/0` to their newly realized anonymous class.

`factory new` is forbidden. An ordinary instance method named `new` is allowed. This restriction preserves a primary entry that guarantees fresh allocation and the complete initialization schedule, while `apply` and named factories retain control over their results. It does not make an arbitrary `new` send an allocation primitive. Inheriting `Object` does not add `new/0` to a class with parameters, and neither inheritance nor mixin application imports contributor factories.

4.8.2. The Callable Protocol (**apply**)

At constructor arity N , the default `apply/N` makes an exact `self.new/N` send. An owned factory `apply` at N replaces that default; factories at other arities coexist with it. A custom factory controls its result and causes no automatic allocation or initialization. It may call `new`, return a cached instance, or return another value.

```
class Point(xInput, yInput) {
  x = xInput;
  y = yInput;
  factory apply() { new(0, 0) }
  factory copy(point) { new(point.x, point.y) }
}
```

`Point(2, 3)` uses default `apply/2`; `Point()` uses the custom `apply/0`; `Point.new(2, 3)` performs primary construction directly. General callable selection belongs to [Message Sends](#).

4.8.3. Named Factory Methods (**factory**)

Named factories such as `Point.copy(p)` are ordinary class-side methods with full result control. In a factory, `self` is the class object; lexical sends and qualified outer use the factory's declaration origin and the class's definition scope. A factory on a member class can therefore access its bound enclosing receiver. Invoking it does not capture the caller or instantiation service.

4.8.4. Bootstrap Metaclasses

Each source class C has a distinct metaclass `C class`, containing only C 's owned factories, with direct superclass `Class` and structural class `Metaclass`. Factory super continues at `Class`, independently of C 's instance superclass. The root relationships are:

Identity	Structural class	Direct superclass
Object	Object class	Top
Class	Class class	Object
Metaclass	Metaclass class	Class
Each of the three root metaclasses	Metaclass	Class

Thus `Metaclass` and `Metaclass class` form a shared two-object class-of cycle. `Top` terminates superclass chains without participating in this class-of graph. `Object` retains its empty initializer and `new/0/default apply/0`. `Class`, `Metaclass` and `metaclass` objects have no public construction factories; the common instance protocol of `Class` is initially empty. Structural links create no public class or outer selector, ambient binding or reflection API.

5. Slots and Accessors

Slots hold object state and expose it through generated accessor messages.

Operational definition: [SOS accessor rules](#).

5.1. Slot Declaration

```
class Point(a, b) {  
  x = a;  
  y = b;  
  label;  
}
```

A slot declaration ends with `;`. `Its =` introduces initialization, whereas [expression assignment](#) invokes a setter. An omitted initializer supplies canonical null; storage awaiting its initializer is uninitialized, and reading it is an error.

5.2. Contribution Slots and Storage

Each contributed slot retains its application occurrence and local position. The actual receiver's complete layout maps these logical identities to storage. The current policy shares one location among same-named slots, while preserving their separate initializers and effects. A selected accessor uses its own logical identity in that layout.

Declaration initialization writes through this mapping without calling an overridable setter. Later initializer writes to shared storage replace earlier ones. Sharing and construction order are specified in [Objects and Classes](#); explicit sharing policies and contribution-private access remain deferred.

5.3. Synthesized Accessors

Source instance slots and var locals supply:

Send	Selector	Result
x	x/0	Current stored value
x! (v)	x!/1	Store and return v

`x/1` and `x!/1` are different selectors. `x(args)` is invocation syntax, not a third synthesized accessor.

5.4. The apply Protocol and Callable Objects

Generated getters may supply invocation through their returned value. Eligibility, exact arity, zero-argument behavior and retained selection evidence are defined by [Message Sends](#); the [Apply guide](#) introduces callable values.

5.5. Setter Return Value

A generated setter returns the new value, not `self`. Consequently `p.x!(2).y!(3)` sends `y!/1` to 2. Use `p..x!(2)..y!(3)` to keep both messages on `p`. A custom setter returns its body result; assignment syntax does not force it to return the argument or perform a storage write.

5.6. Shadowing Accessors

An explicit method with the same selector overrides a generated accessor. Generated-accessor invocation eligibility then follows the [masking rule](#).

Calling `x!(v)` inside a custom `x!/1` dispatches normally, potentially back to that method; it does not expose the overridden storage primitive. There is no public raw-slot operation. Use a distinct backing slot when needed:

```
{
  _x = 0;
  x { _x }
  x!(v) { validate(v); _x!(v) }
}
```

The underscore is only a naming convention, not access control.

5.7. var Locals

`var count = 0;` declares a mutable local with getter/setter messages on a backend-private activation object. All locals in a source scope are reserved before its initializers run. A reference to a later local therefore selects that local and fails if it is still uninitialized; it does not fall through to an outer name. This supports [mutual recursion](#) when the lambdas run after their bindings are initialized.

5.8. Parameter Immutability

Parameters have immutable getter accessors and no synthesized setter. A request for `parameter!` therefore cannot mutate the parameter; ordinary lookup may find another applicable setter or fail. Use a `var` local for a mutable copy. Constructor-parameter lifetime is specified with [construction scopes](#).

5.9. The ! Convention

! suffixes are allowed only on method/message selectors, including repeated suffixes. Slot, parameter and local names are plain identifiers. A slot `x` thus generates unambiguous selector `x!`.

The suffix convention signals mutation or effects; it is not a static effect system. A plain-named slot may hold an effectful lambda, and invoking that lambda need not display ! at the call site. An explicit forwarding method such as `commit!(v) { callback(v) }` can communicate that intent. User-defined bang methods need not be setters.

5.10. Descriptors on Slots

[Descriptors](#) may annotate slots and locals. They do not change raw accessor behavior or make a slot immutable.

6. Message Sends

A selector is a name/arity pair. Ordinary access, invocation and assignment all send messages; there is no public direct field access or separate binding namespace. Receiver origins are defined in [Name Resolution](#).

Operational definition: [SOS selection rules](#).

6.1. Implicit Message Send

Form	Request
<code>x</code>	Exact <code>x/0</code> : return the selected accessor or method result.
<code>x()</code>	Invocation at arity zero.
<code>x(a, b)</code>	Invocation at arity two.
<code>x!(v)</code>	Invocation of <code>x!/1</code> , a distinct selector from <code>x/1</code> .

Parentheses remain semantically significant through lowering and dispatch. In particular, invocation cannot always be lowered to getter-then-apply.

6.2. Self-Dispatch Message Send (Leading Dot)

`.m(args)` is equivalent to `self.m(args)`; both skip lexical receiver selection. Leading `..` likewise cascades on `self`. Prefer the explicit forms when nested scopes would make the receiver unclear.

6.3. Explicit Message Send (Dot)

`receiver.name` is an exact zero-argument send. `receiver.name(args)` invokes at the written arity. Evaluate the receiver first, then arguments once from left to right, then select behavior. Dot chains send each message to the previous result: `a.b.c(3)` sends `c/1` to the result of `a.b`.

6.3.1. No Operator Precedence

Arithmetic and comparisons use messages. Consequently `3.plus(4).times(2)` groups as `(3.plus(4)).times(2)`; use `3.plus(4.times(2))` for the other grouping. General operator syntax is [deferred](#).

6.4. Dispatch Rules

The following rules own invocation selection for methods, generated accessors, lambdas, native callable objects and member factories. Invocation preserves the selected behavior's receiver, declaration origin, lexical captures and return home. Parameters and locals expose generated accessors on private activation objects; direct backend reads may implement these messages.

6.4.1. Candidate Selection

For name/N, examine each searched hierarchy contribution in order: owned contribution, direct mixins left-to-right, then the superclass recursively.

1. Prefer an exact operation name/N. At $N = 0$, a generated getter goes through the next rule instead of satisfying invocation by returning a value.
2. Otherwise consider the effective generated name/0 accessor. A storage accessor qualifies when its value supplies exactly apply/N. A member accessor qualifies through its effective declaration's factory signatures.
3. Continue only on a miss. Exhausting the search produces a missing-selector diagnostic.

Exact-operation preference is local to each contribution: a nearer eligible accessor can beat a farther method. super starts after the executing contribution's exact occurrence.

Getter masking. The first name/0 operation masks later getters in that hierarchy search, even when its candidate is ineligible. An ordinary overriding getter is never executed to discover a callable, and its hidden storage is never inspected. Later exact name/N methods can still match. A super search starts masking afresh at its redirected origin.

Callable capability. Native values qualify through an exact apply/N method, including inherited methods, or a lambda's declared arity. A stored apply accessor does not recursively make its containing object callable. A stored Alien can qualify through effect-free boundary selection of apply/N, including ForeignCallable. An explicit Alien receiver instead selects the requested foreign name/arity directly: no foreign getter is probed for a callable result.

Implicit invocation. First perform [declaration-relative receiver selection](#), using these same candidates. Then dispatch the original invocation on that selected receiver. Method and eligible-accessor overrides both participate. Eligibility does not freeze the implementation, and final dispatch failure does not resume lexical search.

Evidence and failures. Retain an eligible accessor's value and selected callable operation through final dispatch. Revisiting the same candidate reuses them without rereading storage or resolving a foreign operation. Changing a stored value can change eligibility for a later invocation.

Miss: continue lookup	Error: stop the operation
Absent selector; wrong-arity lambda; non-callable value; unsupported member factory arity	Uninitialized read; foreign selection failure; selected realization or execution failure; boundary conversion/ownership failure

Eligibility errors precede dispatch: an uninitialized read or foreign selection failure remains fatal even when the receiver has an overriding `name/N` method. Neither errors nor non-local returns restart lookup or replay evaluation.

6.4.2. Invocation at Arity Zero

Declaration	Bare <code>f</code>	<code>f()</code>
<code>f { 7 }</code>	7	7
<code>f = fun { 7 };</code>	Lambda	7
<code>f { fun { 7 } }</code>	Lambda	Lambda
<code>f = 7;</code>	7	Miss at this accessor
<code>class f {}</code>	Cached class	Instance from <code>apply/0</code>

A selected method executes exactly once; its returned callable is not implicitly invoked. Write `obj.f().apply()` to invoke that result explicitly. Replacing a generated getter with a computed getter can therefore preserve bare reads while changing invocation behavior.

6.4.3. Member-Class Invocation

A generated member accessor advertises its effective declaration's constructor arity and owned factory `apply` arities. An overriding declaration supplies its own signatures. Flat metaclasses import no contributor factories, so candidate testing needs neither contributor lookup nor class realization.

`class Widget(x, y) { factory apply(x) { new(x, x) } }` supplies invocation arities one and two. `Widget()` is a miss without evaluating definition clauses, whether its cache is empty, successful or failed.

Metadata eligibility first selects the lexical receiver. If final dispatch chooses an overriding method, the member remains unrealized, even if its cache already holds a failure. When dispatch selects the member factory, commit to that candidate, realize it through its receiver-and-declaration-occurrence cache, then invoke exact `apply/N` with the saved arguments. Bare access also realizes through that cache. A selected failure is cached and propagated.

Realization evaluates direct mixin targets left-to-right, then the superclass target; their computations may have effects and must produce native classes, excluding metaclasses. Terminal constructor arguments remain deferred until construction. See [class realization](#) and the [accepted decision](#).

6.5. Cascade (..)

A cascade evaluates its receiver once and sends every arm to that saved receiver. Arms execute left-to-right; each arm's arguments execute immediately before its send. Preserve each arm's exact-access versus invocation mode and any setter sugar:

```
p..x!(2)..y!(3)..describe
```

The intermediate results are discarded. By contrast, `p.x!(2).y!(3)` sends `y!/1` to the result of `x!/1`, which is 2 for a generated setter. A failed arm or non-local return prevents later arms and their arguments from running. Earlier effects are neither undone nor replayed.

Lowering uses a fresh private temporary and ordinary sends; it must preserve captures and return homes without exposing the temporary scope to programs.

6.6. Cascade Return Value

The whole cascade returns its last arm's result, not necessarily the receiver. To return an existing receiver, write `p..a..b; p`.

6.7. Implicit-Receiver Cascade (Leading ..)

`..m..n` means `self..m..n` and skips lexical receiver selection. `m..n..p` instead evaluates implicit `m` first, then sends `n` and `p` to its result. Thus a leading cascade and a cascade whose receiver is an implicit send select different receivers.

6.8. Combining Dot and Cascade

Expression	Meaning
<code>a.b..c..d</code>	Save <code>a.b</code> ; send <code>c</code> and <code>d</code> to it.
<code>(a..b..c).d</code>	Send <code>d</code> to the last cascade result.
<code>a..b..c.d</code>	Invalid without the parentheses above.
<code>a..take(b..x..y)..finish</code>	Arguments admit nested cascades directly.
<code>super.make..a..b</code>	Cascade on the result of the completed super send.

There is no `super..a..b` syntax: `super` is not a receiver value. Assignment has a separate [cascade fence](#). The precise grammar is [vh.g4](#).

7. Apply and Callable Values

`apply/N` is the callable capability at arity `N`. A lambda supplies it at its declared arity; a class's generated `apply/N` delegates to primary `new/N`; an ordinary object can define it as a method. Owned custom class factories may replace or add `apply` arities; see [factories](#).

The language fixes `apply/N` as the protocol connecting invocation syntax to callable values, so methods and stored callables can participate in the same [selection rules](#). Its implementation and result belong to the selected receiver; the spelling does not imply allocation, lambda execution or any other particular body on an arbitrary object.

```
{
  handler = fun(request) { request };
  run(request) { handler(request) }
}
```

Retrieving `handler` returns the lambda. `handler(request)` can use the generated getter and invoke its result. Exact methods and accessor routes compete under the [selection rules](#), so invocation is not unconditional getter-then-apply. A computed getter's result can be called explicitly with `object.handler.apply(request)`.

Bare `object.m` sends `m/0`; it does not produce a bound method. For the distinction between `f` and `f()`, see [zero-argument invocation](#). Member declarations use [deferred factory selection](#).

Method reification is a [future tear-off proposal](#). No tear-off syntax or public method-reification API is part of the executable language.

8. Syntactic Sugar

Sugar preserves ordinary selector dispatch, receiver origins, evaluation order and failure behavior. [Name Resolution](#) defines receiver forms; [Message Sends](#) defines invocation and cascades.

8.1. = Setter Sugar

In a declaration, = introduces slot/local initialization. In expression position, name = expr requests name!/1; it creates no binding and grants no direct storage access.

8.1.1. Desugaring

```
x = v           // x!(v)
p.x = v         // p.x!(v)
a = b = 3       // a!(b!(3))
```

Evaluate an explicit receiver first, then the RHS once, then invoke the setter. Chaining is right-associative. Custom and foreign setters use normal dispatch.

8.1.2. Valid Contexts

Sugar	Canonical form
x = v	x!(v)
.x = v	.x!(v)
self.x = v	self.x!(v)
p.x = v	p.x!(v)
super.x = v	super.x!(v)
outer C.x = v	outer C.x!(v)
p..x=v..y=w	p..x!(v)..y!(w)
..x=v..y=w	self..x!(v)..y!(w)

The cascade receiver is evaluated once. super.. is invalid because super is not a value; an ordinary super send remains valid. Explicit Alien selectors such as alien.outer = v request the foreign selector outer!/1.

The selector before = must have no bang suffix. Write a canonical send for additional bangs; x! = v is not assignment sugar.

Assignments are expressions, including in arguments, returns and initializer bodies: consume(x = 7) and var result = x = 7; are valid.

8.1.3. Return Value

Assignment returns exactly the setter result. A generated setter stores and returns its argument. Custom setters may return something else or perform no write. If `b!/1` returns 7, then `a = b = 3` passes 7 to `a!/1`. A missing setter fails normally; parameters gain no writable accessor from assignment syntax.

8.1.4. The Cascade Fence

An assignment RHS is a `nonCascadeExpr`, so an unparenthesized `..` ends it:

Expression	Grouping/result
<code>r..a=3..b=5</code>	Two setter arms on <code>r</code> .
<code>x = p..a..b</code>	<code>(x = p)..a..b</code> : cascade on the setter result.
<code>x = (p..a..b)</code>	Pass the last cascade result to <code>x!/1</code> .

This is a grouping boundary, not a ban on cascades after assignments. Declaration initializers and canonical invocation arguments accept full expressions: `var x = p..a..b;`, slot declaration `x = p..a..b`; and `x!(p..a..b)` all use the cascade's final result directly.

The authoritative syntax is in the message, `explicitMessage`, `expression` and `nonCascadeExpr` rules of [vh.g4](#).

9. Name Resolution

Implicit sends first select a receiver from lexical declarations, then dispatch on that receiver. Lookup is fixed by the language; there is no global environment or platform-selectable lookup policy.

Operational definition: [SOS lexical receiver selection](#).

9.1. Names and Contracts

An ordinary name selects behavior through message lookup; its spelling alone does not identify a value, grant authority or impose a protocol. The selected object's behavior and the contract with its clients give that name meaning. This applies equally to `null`, `true`, `false`, `Object`, `kernel` and application selectors such as `ifTrue` or `plus`. They introduce no ambient bindings. Parameters, locals, slots and methods may use these names, subject to the ordinary declaration rules. Without an applicable declaration, a send fails under the ordinary lookup rules.

Canonical null and Boolean identities, and structural root `Object`, are governed by the seed and core-object contracts. Those identities do not reserve source names for obtaining them. An omitted initializer supplies canonical null directly; an explicit initializer `null` sends `null/0` in its lexical context. A name or a matching protocol never establishes canonical identity at the foreign boundary.

The specification explicitly fixes grammar keywords and the receiver forms below. It also fixes the callable selector `apply/N`, the generated primary factory `new/N` and the setter selector mapping `x!/1`. These contracts connect syntax to messages; the selected operations still use ordinary dispatch. They do not give other selectors intrinsic behavior. Seed methods and explicitly supplied foreign/tooling capabilities have their own stated contracts, not meanings inferred from names on arbitrary objects.

9.2. Lookup Order

Search the current method/lambda's parameter and local accessors, then enclosing lexical scope objects from nearest to farthest. An activation contributes its own accessors. A lexical object scope contributes only declarations from its originating contribution, associated with its bound receiver. Arbitrary members added by a subclass do not become lexical declarations.

A selected contribution and its member classes retain their exact application occurrence and captured lexical ancestry at every nesting depth. Qualified outer and implicit lexical receiver selection follow that ancestry. Messages dispatch normally on the selected receiver, and super continues after the executing occurrence. Repeated applications of one declaration remain distinct; lexical traversal never reselects an earlier application on the same receiver.

For an exact send, the nearest scope declaring the selector selects its receiver; exact dispatch then honors overrides on that receiver. For invocation, use the [candidate rules](#):

1. A declared exact name/N operation qualifies the scope, except that a generated getter at arity zero must establish callable eligibility.
2. Otherwise, if the scope declares name/0, select its effective getter on the associated receiver. An eligible generated accessor qualifies the scope. At arity zero, an ordinary method overriding that getter also qualifies directly.
3. A miss continues outward; an eligibility error stops selection.
4. Once qualified, dispatch the original invocation uniformly on that receiver, retaining successful accessor evidence.
5. If all lexical scopes miss, dispatch on current `self` through its owned contribution, direct mixins left-to-right, then superclass chain.

A subclass name/N alone cannot make an ineligible declared getter qualify. Once eligible, that receiver's overrides apply normally. An operation added on a different inner receiver cannot capture an enclosing dependency.

```
{
  class Base {
    f = fun(x) { 7 };
    run { f(1) }
  }
  class Child < Base { f(x) { 42 } }
}.Child().run // 42: Base selects the receiver; Child overrides f/1
```

If `Base.f` instead holds a non-callable or wrong-arity value, lexical search continues before the final `self` invocation. Getter masking, failure handling and retained callable evidence are specified once in [Message Sends](#).

9.2.1. Capabilities and declaration scopes

The instantiating caller does not supply a class's lexical scope. Constructor parameters, member declarations and class expressions obey the [construction scope rules](#). Normal module entry and explicit tooling scopes are distinguished in [Program Structure](#).

9.3. `self` — Current Receiver

`self` denotes the current native receiver with fixed meaning. It parses as an identifier but is not an ordinary getter; native declarations cannot shadow it. It can be passed as a value and used in chains such as `self.x`. An explicit native receiver has no `self` selector. `alien.self` is instead an ordinary foreign selector with adapter-defined meaning.

9.3.1. Leading-Dot Shorthand for Self

`.m(args)` equals `self.m(args)`; `..m..n` equals `self..m..n`. Both bypass lexical receiver selection. See [cascades](#).

9.4. **outer** — Qualified Lexical Receiver

`outer` `ClassName` selects the ordinary receiver for the nearest matching named lexically enclosing declaration, including the immediately containing class. Subsequent messages dispatch normally on that receiver.

```
class Counter(start) {
  n = start;
  class Stepper {
    step { outer Counter.n!(outer Counter.n.plus(1)) }
    current { outer Stepper }
  }
}
```

`outer Stepper` selects the current `Stepper` instance. The qualifier is declaration metadata, not a variable, evaluated accessor or dynamic class name. Repeated class names choose the nearest matching declaration. An unrelated subclass or superclass name is not thereby an enclosing qualifier.

Lambdas retain their enclosing declaration context. Named class expressions introduce qualifiers for their bodies; anonymous class expressions and object literals introduce no invented name. They preserve access to enclosing named declarations. Captured parameters and locals remain internal dependencies, not activation objects exposed by `outer`.

Contributed methods preserve their definition and application origins; applying a mixin elsewhere cannot substitute the receiving class's outer scope. Member classes also retain their bound receiver and declaration origin. This holds at every nesting depth: a member selected from the second of two applications retains that application's farther enclosing objects, even when both applications share the same declaration and immediate receiver. The [repeated-parent example](#) therefore returns 42, preserving the selected `b.Family` ancestry. This is an intentional difference from Newspeak's deeper nearest-parent reselection rule.

`outer C` is a standalone receiver value: grouping, passing it as an argument and ordinary sends are allowed. It grants no public parent getter, activation reflection or additional access authority. Bare `outer`, unqualified `outer.message` and native `object.outer` are invalid. `alien.outer` is an ordinary foreign selector; repeated sends follow that adapter's protocol.

An unknown or non-enclosing qualifier is a semantic error. The bootstrap validates it when evaluated, before evaluating arguments of a send using that receiver. Static qualifier validation is deferred. Qualifying a normal module's own declaration can select its instance; it cannot expose the instantiation service, tooling capabilities or empty top activation.

9.5. **super** — Lookup Redirector

`super.m(args)` retains `self` and starts lookup immediately after the executing contribution's exact application occurrence. It continues through later mixins and the superclass chain, preserving the send mode and using fresh getter masking. Repeated applications

of one mixin remain distinct; lookup does not restart after the first occurrence of its definition.

`super` is not a value: standalone use, assignment and `super..` are invalid. Its native meaning cannot be overridden. The explicit selector in `alien.super` belongs to the foreign protocol.

9.6. Lexical, Self, and Outer Dispatch — Compared

Origin	Receiver/search
<code>m(args)</code>	Declaration-relative lexical selection, then self fallback.
<code>self.m(args)</code> / <code>.m(args)</code>	Current receiver's hierarchy only.
<code>outer C.m(args)</code>	Lexical receiver for <code>C</code> , then ordinary dispatch.
<code>super.m(args)</code>	Current receiver, after the executing occurrence.
<code>receiver.m(args)</code>	Evaluate receiver once; native hierarchy or Alien protocol.

These origins are language forms, not a universal protocol implemented by every value. Aliens acquire no native class, mixin or lexical outer.

9.7. Reserved Words

9.7.1. Grammar Keywords

Grammar keywords cannot be declaration identifiers. `outer` and `super` are also allowed as explicit foreign selector spellings.

Tokens	Purpose
<code>class</code> , <code>factory</code>	Class and factory declarations.
<code>var</code>	Local declaration.
<code>fun</code> , <code>λ</code>	Lambda literal.
<code>outer</code> , <code>super</code>	Native receiver forms.
<code><</code> , <code>extends</code>	Superclass clause.
<code><:</code> , <code>with</code>	Mixin clause.

9.7.2. Semantically Reserved Identifiers

Identifier	Restriction
<code>self</code>	Cannot name a native slot, parameter, local or method, or be sent as a native selector.

Identifier	Restriction
new	factory new is rejected because the primary source-class factory is reserved. Ordinary instance methods named new remain allowed.

These spellings parse as identifiers and are checked semantically. See [primary construction](#).

10. Recursion

Recursion uses ordinary late-bound messages and lexical captures; it requires no special recursive declaration form. It remains subject to [normal selection](#), including overrides and callable eligibility.

10.1. Named Method Recursion

A method can send its own selector or another method's selector. Declarations are available regardless of textual order, enabling mutual recursion. Use `self.m(...)` when current-receiver dispatch is intended; implicit `m(...)` still performs lexical receiver selection.

10.2. Slot-Bound Lambda Recursion

A stored lambda can refer to the accessor holding it:

```
{
  fact = fun(n) {
    n.eq(0).ifTrue(fun { 1 }, fun { n.times(fact(n.minus(1))) })
  };
}
```

Its body resolves `fact` when invoked, after the slot is initialized. Arithmetic and branching here assume suitable capabilities. Normal expression results return through recursive invocations. A `^` would target the creating initializer, normally already retired; see [return homes](#).

10.3. Local Lambda Recursion

A `var` local can similarly hold a recursive lambda. Its accessor belongs to the captured activation. A lambda's caller supplies no replacement lexical scope or implicit self-name.

10.4. Mutual Recursion

All locals in a source scope are reserved before initialization. Lambdas may therefore capture references to later local declarations, provided they run after those bindings are initialized. Reading a reserved but uninitialized local is an error, not an outer lookup. See [locals](#).

10.5. Passing Recursive Lambdas as Arguments

Passing or returning a recursive lambda preserves its captured accessors. The caller's parameter name does not become visible in the lambda body. Captured data may survive the defining method, but its return home does not: ordinary results remain valid, while ^ to a retired home fails.

For name-based recursion, place the lambda in a captured slot or local. An unbound anonymous lambda has no automatically provided name for itself.

10.6. Tail-Call Optimization

The prototype uses explicit continuations for native execution but does not implement tail-call elimination. This is not a bounded-memory guarantee. Foreign callback depth and other execution limits are separate; see [implementation](#) and [future TCO](#).

11. Descriptors

Descriptors attach optional metadata expressions to syntax for tools or separately specified extensions.

11.1. Design Constraint

Removing all descriptors must preserve raw execution, including results, effects and failures. The core interpreter does not evaluate descriptor expressions as program behavior. An annotation named `immutable`, `cached`, `public` or `module` alone grants no such runtime semantics.

Class, superclass and mixin clauses belong to the core grammar and affect execution independently of descriptors.

11.2. Syntax

```
element : descriptor
element : descriptor1 | descriptor2
element : descriptor1 : descriptor2
```

| separates expressions within one group; : chains groups. Descriptors use ordinary expression syntax, including message sends such as `constrained(0, 100)`. Their interpretation is supplied by the consuming tool, not by the name of the annotation.

11.3. Where Descriptors Apply

Attachment	Example
Slot or local	<code>x = 0 : tracked; / var x = 0 : tracked;</code>
Method	<code>move(dx, dy) { ... } : cached</code>
Class or object	<code>class { ... } : typed / { ... } : module</code>
Lambda	<code>fun(x) { x } : annotation</code>
Formal parameter	<code>(x : nonNeg, y : nonNeg)</code>
Expression	<code>(3 : immutable : tracked)</code>

11.3.1. Expression-Level Descriptors

Parenthesized expression descriptors distinguish the annotated expression from its surrounding declaration:

```
x = (3 : annotation); // describes the expression  
x = 3 : annotation;   // describes the slot
```

Groups may chain at every attachment point. When | would otherwise extend a descriptor list, terminate a described declaration with ; before a [final initializer body](#).

11.4. Semantics

Compilation hints, documentation, contracts and analysis constraints need explicit tooling or extension contracts. The syntax itself promises none of those features and cannot replace core construction, lookup or boundary rules. See [tooling architecture](#) for external annotations.

12. Foreign Semantic Values and the Alien/Expat Boundary

Foreign systems retain their semantics and execution mechanisms. An **Alien** makes a foreign value reachable inside VarioHyve; it supplies no native class, mixins or lexical outer. An **Expat** exposes native behavior to a foreign participant. Arguments, results, identity, failures and callbacks obey the same boundary contract in both directions, including language-visible VM services. Native lookup and receiver-origin semantics remain fixed.

The chapter follows values through selection, conversion and control transfer, then defines the VM-service and mirror capabilities. Operational rules are in [the formal appendix](#).

12.1. Aliens — Foreign Semantic Values Inside VarioHyve

An Alien may denote an object, function, pointer, struct, resource handle, simulator model or remote endpoint. It need not support direct operations. Storing it in a slot does not make that slot's owner its lexical outer.

12.1.1. Alien Dispatch

After receiver and argument evaluation, an Alien send selects the adapter's exact (name, arity) operation. Native class/mixin lookup does not continue through the Alien. Selection must distinguish absence from failure, perform no operation or callback, and retain the selected operation for execution. A resolution or execution failure never restarts lookup or replays effects.

A foreign getter is not a generated native accessor: `alien.f(args)` does not read `f/0` to discover a callable. Write `alien.f.apply(args)` for that behavior. A stored Alien can qualify for native callable-binding invocation when its adapter advertises exact `apply/N`; the eligibility check's selected operation is reused. See [Message sends](#).

Explicit Alien selectors `self`, `outer` and `super` use the foreign protocol. They do not navigate native scope. Native `self`, qualified `outer` `ClassName` and `super.message` keep their receiver-origin meanings; native declarations do not acquire those reserved selector names through this exception.

12.1.2. Arity Mismatch

An adapter defines how name/arity requests map to foreign behavior. Foreign methods, explicit capability operations and opaque handles need not share one object model. Overloads, defaults, ABI layout and lifetime are adapter concerns; automatic host reflection is not implied.

12.1.3. Alien Identity

Each adapter defines identity and lifetime for its foreign domain and preserves sharing on repeated compatible crossings. Numeric address equality alone is insufficient for pointer identity, provenance or reused allocations. Alienation does not synthesize an `eq` method. Concrete Java identity caching is an [implementation policy](#), not a universal foreign identity law or an implemented C FFI.

12.2. Expats — VarioHyve Objects Outside VarioHyve

An Expat reenters native semantics through a behavioral interface. Its public contract exposes no store, address, activation, private initializer or VM representation. Adapters may privately retain what execution requires. The current exact-send interface, `VHExpat.send`, includes zero-argument access; it does not apply source invocation's callable-binding fallback. To use a stored callable, read the binding and send `apply/N` to the result explicitly.

12.2.1. Expat Surface

Without language access control, an Expat exposes the same source-visible behavior available to an external native caller, including generated accessors. Backend-private construction routines are not selectors. Proposed [export control](#) must preserve equality of the native external interface and the foreign export interface.

12.2.2. Expat Identity

A native object has at most one Expat proxy per compatible foreign runtime. Exporting it repeatedly through different paths returns the same proxy.

12.3. The Symmetry

Direction	Arguments	Operation	Result
Native → Alien	Expatriate	Execute the selected foreign operation	Alienate
Foreign → Expat	Alienate	Exact native send	Expatriate

For compatible references, importing an owned Expat recovers the original native identity, and exporting an Alien to its originating adapter recovers its foreign identity. Cross-runtime references require an explicit bridge. Conversion by value instead follows a declared codec and may normalize host representations; it does not promise preservation of their object identity.

12.4. Operation Results

An Alien send returns the operation's ordinary result through the declared conversion protocol, just as a native send returns its method result. There is no automatic Alien-only

`ok(value) | AlienError(error)` wrapper and no required sum result. Such an outcome protocol is one optional contract an operation may explicitly promise, equally for native and foreign implementations. The boundary does not infer failure from an ordinary returned object's shape, class name or truth value. Defined exceptional completions remain diagnostics under [Error Propagation](#).

12.5. Primitive Marshalling

Numbers, strings, booleans and null may cross by value instead of through proxies. Each adapter must state its supported domains and reject unsupported conversions. A numeric encoding must not silently turn a pointer into an integer while claiming to preserve its provenance.

Canonical null and Booleans are ordinary native objects with language methods. Their Java boundary representations are exactly `null`, `Boolean.TRUE` and `Boolean.FALSE`, never Expats. Incoming scalars recover the corresponding canonical native identities, equally for arguments, results and callbacks. Conversion recognizes those identities; it never invokes `toString`, `isNull`, `not` or a truth-testing protocol to classify another native object. Similar behavior or a source name such as `null`, `true` or `false` does not make an object canonical. The internal core null constant and empty expressions select canonical null directly; those source names use ordinary message lookup. The current integer/string subset is recorded in [the implementation](#).

12.6. Explicit Wrappers

A native wrapper supplies its own identity, scope and behavior around foreign values. Multiple wrappers may share one Alien without sharing native identity. For example, a callable capability can operate on an opaque handle:

```
class Device(deviceHandle, reader) {
  handle = deviceHandle;
  readFn = reader;
  read(buffer) { readFn(handle, buffer) }
}
```

This is explicit adaptation, not a built-in calling convention. Persistent dependencies use slots under the ordinary constructor-scope rules.

12.7. Constructor Arguments and Optional Bundles

Aliens, native objects and bundles can be ordinary [module constructor inputs](#). The same conversion contract applies in richer [tooling contexts](#); it does not add capabilities to an isolated module root.

12.8. Control and Failure Agreements

12.8.1. Error Propagation

Selector absence is distinct from a selected operation's failure. Failures cross as defined diagnostics, never as retained host exception objects, classes or causes. The Java categories `FOREIGN_FAILURE`, `CONVERSION`, `OWNERSHIP` and `EXECUTION_POLICY` survive machine execution and callback propagation; native lookup/control errors use `LANGUAGE_FAILURE`.

Callbacks use ordinary native semantics and preserve state changes. A failed callback aborts its own native continuation, retires its invocation homes and reports a defined diagnostic to its foreign caller. It does not automatically fail the suspended native caller. Foreign code may handle the diagnostic, make further callbacks and return normally, or propagate a failure. The outer NF send observes the foreign operation's completion, subject to normal result conversion and execution limits. A propagated diagnostic preserves its kind; a later foreign failure is reported as that failure, not replaced by an earlier handled one.

Effects already performed are not rolled back. Handling a callback failure does not resume the aborted callback, revive its homes, replay the operation or grant NLR crossing. The suspended caller's homes remain live until its own completion or failure. Callbacks continue to share the active execution budget; handling an exhaustion diagnostic does not replenish it. There are no native resumable conditions in the current language. See the [accepted recovery agreement](#).

12.8.2. Non-local Returns Across the Boundary

The boundary is the agreement between native and foreign participants. That agreement owns whether a non-local return may cross a foreign invocation and how the crossing is handled. The native language cannot prescribe how arbitrary foreign execution unwinds or otherwise transfers control.

The default agreement forbids crossing. A callback may return to an accessible home created inside that callback; an attempt to reach a live home across an active foreign-call barrier fails with `LANGUAGE_FAILURE`. The failure is reported to the foreign caller under the recovery agreement above. This is the only crossing agreement implemented by the current Java boundary.

A boundary may explicitly support crossing under a future agreement. It is responsible for implementing that agreement, including its observable control flow and treatment of intervening foreign work; the foreign-side mechanism is not fixed by VarioHyve. Every intervening boundary must support the requested transfer. Such support does not change the lexical target of `^`, revive a retired home, or bypass initializer phase restrictions. Crossing support and its transfer protocol are deferred; the default barrier must not be disabled without implementing a supporting agreement. See the [accepted decision and examples](#).

12.8.3. Control Tokens and Execution Agreements

Ordinary native transitions require execution authority under an explicit execution agreement. **The current sequential agreement has one conceptual control token per live run-**

time. It governs advancement of ordinary native continuations and their NF/FN control transfers. A suspended continuation has no independent authority to advance. The token is neither a language value nor an additional capability that programs must pass; implementations need not reify it. A refinement argument must account for the authority using the implementation's actual synchronization and state.

The token may be idle at the boundary, assigned to a native continuation, or assigned to a foreign invocation. Independent FN entry acquires the existing idle token. NF transfers it to the selected foreign invocation; admitted callback entry transfers it to a new native continuation. Callback success or failure returns it to that invocation; foreign completion transfers it to the suspended native caller only after admitted descendants finish. Independent native completion returns it to the idle boundary. Nested calls retain suspended continuations and interaction state, not additional control tokens. Backend tooling may also yield after a requested step and later reacquire authority to advance its retained successor. Yielding is not native completion and does not retire homes; storing a configuration grants neither execution authority nor a snapshot of the mutable runtime.

This is an execution discipline, not exclusive physical access to all runtime memory. It permits three distinct forms of activity:

Activity	Authority and correctness obligation
Ordinary evaluation and callbacks	Execution authority under the active agreement; preserve continuations, admission and boundary transfers.
Representation maintenance and optimizations, including concurrent GC	Implementation refinement of the agreed semantics and observations; no second ordinary native continuation is implied by concurrent implementation work.
Explicit observation or intervention	A granted capability with a declared effect and coordination contract; it may intentionally change abstract program state without owning the ordinary control token.

An observation or intervention contract must specify its subjects and scope, permitted effects, consistency and coordination with execution, authority lifetime, and completion/failure behavior. Reading live state requires a defined consistency model. Changing a slot, pausing execution or replacing a continuation requires an explicit intervention contract; it cannot be justified as invisible maintenance. Such authority does not implicitly grant arbitrary evaluation, additional ordinary continuations, NLR crossing, dead-home revival or relaxed initializer rules. Language-visible VM services, debuggers and language monitors remain explicitly supplied Aliens using ordinary boundary sends. No general intervention API is implemented by this agreement. All agreements preserve fixed lookup, identity, return-home lifetime and initializer phase rules. NLR crossing still requires an explicitly supporting boundary agreement.

Implementations may use parallel work, concurrent collectors and boundary optimizations without a global representation lock. They must preserve logical identity, return-home liveness, roots and agreed observations, and coordinate their concrete data structures correctly. An optimization cannot silently replay foreign effects or change their

specified ordering. Boundary bookkeeping, such as recording a pending request or an arriving completion, does not itself advance a native continuation.

A richer execution agreement may explicitly authorize simultaneous native transitions, including a model checker's request to execute proven independent transitions on a parallel VM. It must specify execution authority, shared-state and observation semantics, and applicable independence or synchronization conditions. Token uniqueness is a property of the sequential agreement, not a universal serialization requirement. The accepted extension principle and the remaining implementation work are separated in [Concurrency and Parallelism](#).

12.8.4. Concurrency Boundary

The boundary supports synchronous same-thread callbacks and explicitly call-associated worker callbacks. Native execution remains serial over one runtime/store under the sequential agreement. Each NF invocation suspends and roots its native caller, transfers the conceptual control token, and records its call ancestry. An admitted FN callback acquires that authority, runs a separate native continuation, and shares the active budget. Nested NF calls repeat this protocol.

Foreign code captures a `CallbackContext` on its own active operation thread and may explicitly pass it to a worker. Its send requires an Expat from the same runtime; the context grants permission to request admission, not receiver authority or possession of the control token. Contexts may be copied among workers; competing requests negotiate access to the unique token. Expats obtained before the NF invocation remain valid targets. Unassociated entry on another thread during an active execution is rejected, as is callback entry during selection. Neither thread identity alone nor possession of an Expat grants admission to an outstanding foreign call.

Only callbacks associated with the innermost active foreign invocation may acquire native execution permission. Other associated requests wait for their turn without running native code. A descendant operation cannot synchronously use an ancestor context to wait on its own completion; that request is rejected. There is no FIFO or fairness guarantee. A future FIFO policy must respect call eligibility: a waiting ancestor request cannot block a needed descendant callback merely because it arrived first. Foreign completion closes admission, rejects queued or late requests and waits for already admitted descendants to finish before importing the result and resuming its native caller. A foreign result can arrive while a callback owns the token; arrival is recorded, and delivery waits for ownership transfer. Retained call contexts cannot attach to a later invocation. This preserves the existing NLR barriers and callback-local failure contract.

This protocol provides no preemption or termination guarantee: foreign work or an admitted descendant may never finish, and foreign dependencies may deadlock. Independent-entry scheduling, detached asynchronous native tasks and parallel native execution remain outside this contract. Execution limits belong to [the implementation policy](#).

12.8.5. Lifecycle and Garbage Collection

Ownership, resource expiry, callback lifetime and cross-boundary cycles belong to each adapter's contract. No universal reclamation protocol is defined. Public raw addresses

are not a substitute for that contract.

12.8.6. Foreign Kinds and Capability Contracts

An adapter may classify a value as callable, pointer, struct or endpoint; these are foreign contracts, not native classes. Analysis needs explicit assumptions about effects, callbacks, blocking, determinism and state changes. Unknown behavior stays opaque. General contract metadata, provenance registries and foreign reflection remain unimplemented; see the [boundary assessment](#).

12.9. VM Services and the Trusted Seed

The host boundary has a public foreign facet and a privileged VM-service facet over one private owner. The public facet exposes only the ordinary transport, explicit mirror grant and call-associated callback admission. Trusted seed provisioning supplies narrow VM service capabilities; public clients have no operation for obtaining the provisioning facet or raw runtime representations. Object's identity service is provisioned only to its definition scope. The optional public `IdentityMirror` grants its own limited observations.

Both facets share identity maps, conversion, execution admission, budgets and GC roots. Current services use the same serial admission protocol. Privilege changes authority, not lookup, return or failure semantics; privilege alone grants no additional ordinary native execution. A future independently operating service requires an explicit [execution or intervention agreement](#). The same capability view preserves identity across either route. Distinct restricted views have distinct identities even when they concern one resource. Deliberately exporting a privileged capability delegates that capability; a partition label does not silently attenuate it. No new privilege registry, selector allowlist or native invocation path is introduced.

Language-visible VM services use this same boundary; there is no privileged native-function invocation path. The trusted backend may privately allocate values, maintain stores and implement lookup/continuations. Those internal operations are not language services.

A service returning a native object must return its Expat, so import recovers the object. Returning its raw backend representation as a foreign value is invalid. Any future representation-sensitive service requires explicit authority and private unwrapping without adding raw-world access to public Expats. See [the VM boundary decision](#).

12.10. IdentityMirror

`IdentityMirror` is an explicitly supplied capability for observations that must not dispatch through the subject. A host obtains it with `runtime.boundary().identityMirror()` and can pass it as an ordinary module constructor argument. It is not installed in the kernel or exposed by Object. The Java public interface uses the same `ForeignObject` selector protocol as other services; it grants no store, address or runtime access.

Operation	Result
<code>same(a, b)</code>	Whether supported values have the same logical identity
<code>identityHash(a)</code>	Integer stable for that identity's lifetime
<code>kind(a, name)</code>	Membership in the semantic kind named by a string
<code>isAlien(a)</code>	<code>kind(a, "Alien")</code>
<code>isNative(a)</code>	<code>kind(a, "Object")</code>
<code>instanceOf(a, C)</code>	Whether the actual native class/superclass chain contains class C by identity
<code>applies(a, C)</code>	Whether the native contribution chain contains C's owned mixin by identity

These operations execute no subject or target method, foreign resolver, computed getter or member-class realization. Their arguments are first evaluated using ordinary message-send rules, which may themselves realize a member class. All explicit sends on an Alien retain their foreign meaning, even for these same selector names. Object's ordinary equality and hash defaults are normative for the current runtime seed and remain available without granting the mirror itself. Another seed may choose different root defaults.

12.10.1. Identity and kinds

Identity comparison is reflexive, symmetric and transitive on its supported domain. It observes native identity or adapter-preserved Alien identity, never semantic equality or remote resource equivalence. Compatible round trips preserve identity and hashes; same identities hash equally, but collisions are permitted. Hashes are neither addresses nor stable across sessions. A wrapper and its payload differ; differently restricted handles must not be merged merely because they refer to the same resource. Ownership failures require an explicit bridge.

The supported kind labels are exactly "Object" and "Alien", case sensitive. Object includes native instances, class objects, metaclasses, canonical null and Booleans, and lambdas. Alien includes opaque foreign references and VM services exposed through the adapter. It does not imply callability or trust. Classification is relative to the observing runtime; importing its owned Expat recovers a native object.

Current integer/string codec values belong to neither kind and have no native class or mixin membership. Identity operations on them, including mixed same queries, fail with `CONVERSION`; interning does not specify scalar identity. Future native or preserved foreign scalars require their own specified contracts. Thus `isNative` is not implemented as the negation of `isAlien`. Object's default `equals` with a codec scalar still returns false because its receiver is native. An unknown kind label fails with `LANGUAGE_FAILURE`, a non-string kind label with `CONVERSION`, and a missing selector/arity follows ordinary lookup failure.

12.10.2. Class and contribution references

The second argument of both membership queries is a native class reference, obtained through ordinary messages or explicit capability provision. For an ordinary class, it is

the same definition object usable in superclass and mixin applications. `instanceOf` uses that class's identity; `applies` selects that class's owned reified mixin, just as `<: C` does. It does not send an `ownedMixin` accessor or require a separately exposed mixin token. The query does not resolve a name or consult a class registry. Names and hashes, including old anonymous labels, are not targets.

`instanceOf` starts at the receiver's actual class and follows superclasses through root `Object`, inclusive. It returns at the first matching class identity. It does not treat a mixin application's source class as a superclass.

`applies` walks the same linear contribution order used for native dispatch: the class's owned contribution, its direct applications left to right, then its superclass's owned contribution and direct applications, continuing through `Object` inclusive. It returns true at the first match and false after the chain is exhausted. Matching compares the reified contribution's identity, not its syntax, name or semantic equality. An application contributes only the selected source's owned mixin; this query does not traverse that source's superclass or applications. Owned, inherited and repeated contributions are included without collapsing occurrence identities or executing construction routes.

Anonymous and named definitions follow identical identity rules. Distinct class evaluations and distinct per-enclosing-receiver member realizations remain distinct even when they share a declaration or name. Aliases to the same class select the same identity and owned mixin. No identity hash participates in membership, so hash collisions cannot change an answer.

For a class object, queries inspect its metaclass hierarchy and class-side contributions; they never switch to the represented class's instance hierarchy. The target rule remains the same: `C` denotes `C` itself or `C`'s owned instance-side mixin, not its metaclass's contribution. In particular, `instanceOf(C, C)` and `applies(C, C)` are normally false. If a metaclass reference is explicitly supplied, it can select that metaclass or its owned class-side contribution. This does not add a public class/metaclass getter.

Both arguments undergo ordinary boundary ownership validation. A non-class target, including a string, canonical null, ordinary instance or foreign object, fails with `CONVERSION`; an unowned class fails with `OWNERSHIP`. Invalid targets fail even when the subject is an Alien or codec value. With a valid target, Aliens and codec values return false because they have no native membership.

These are structural identity tests, not proofs that a selector is supported or that a contribution's behavior remains effective after overriding. They do not establish trust in a subclass or authorize its behavior. The [design note](#) records the routing and capability tradeoffs.

Part III.

Implementation

13. Runtime Object Representation

This implementation chapter describes `VisitorSemanticsVM`'s records and links. The language contracts are in [Objects and Classes](#), [Slots](#), [Name Resolution](#), and [Message Sends](#). These Java structures are backend-private; none is a required representation for foreign clients.

13.1. Core Structures

The following sketches abbreviate the current value types:

```
VMObject      = { ValueRef[] slots, slotLayout, classRef?,  
  ↪ lexicalParentRef?, memberCache }  
VMMixinClosure = { definitionScope, declarationName, mixinSyntax,  
  ↪ parameters, initializer }  
VMClass       = VMObject + { mixins, superclassRef, initializationEdges,  
  ↪ instanceLayout, initializer }  
VMMetaclass   = VMClass
```

`VMObject` has no per-instance method dictionary. Reified contributions retain method syntax and declarations; [ObjectProtocol](#) selects their operations. `VMClass.mixins[0]` is its owned mixin; later entries are direct applications. Class objects currently have empty value-slot arrays: instance declarations belong to their contributions, and instance values belong to allocated receivers.

`VMMixinClosure` and method closures remain dedicated `VMValue` types. `VMLambdaClosure` is a `VMObject` with the shared native `Lambda` class and private `function/captured-scope/receiver/origin/return-home` fields. Its ordinary `Object` methods use the closure as receiver; intrinsic `apply/N` uses its lexical captures. No captured slots, internal closures or activations become public. Activations reuse `VMObject` storage but have no class reference. A missing Java reference is distinct from the language's canonical null object. Alien and scalar nodes are described under [Java boundary representation](#).

Applying a reified contribution reuses its identity without importing the source class's construction or inheritance chain. [Mirror membership](#) selects the supplied class's owned contribution and compares that identity; it requires no naming metadata or reverse link to the owning class.

13.1.1. Store Entries

Evaluating a class expression creates a class/metaclass pair. A member accessor creates that pair on first successful realization. Construction creates its receiver; each object-literal evaluation realizes a fresh anonymous class/metaclass pair with its selected contributors

and sends primary `new/0` to create the receiver. These are object-graph counts, not total backend allocations: contributions, activations and continuations also occupy representation space.

`VMObject.MemberClassKey` contains applying class, contribution index and member declaration. The cache lives on the enclosing receiver, completing the semantic key. Each entry records a realized value, a retained failure, or an in-progress flag. `ClassTargetFrame` sequences target computations; `MemberClassReturnFrame` publishes a result. Failure and unwind clear the in-progress state and cache the failure, preventing retries and permanently busy entries.

13.2. Contribution Occurrences and Layouts

The backend identifies an occurrence by `(applyingClass, mixinIndex)` and a logical slot by adding its contribution-local position. Inherited occurrences retain their own applying-class identities. Direct applications hold the selected `VMMixinClosure`, without importing the source class's construction record.

`InstanceLayout` collects owned/direct/inherited contributions and interns physical positions by slot name. Its immutable mapping is cached on the realized class. Instances allocate fresh arrays from its physical declarations. Logical identities survive name sharing; physical index order is an implementation choice.

```
selected slot: (applyingClass, mixinIndex, localSlot)
physicalIndex = actualReceiverClass.instanceLayout.physicalIndex(selected
  ↪ slot)
```

Accessor mutability and eligibility come from the selected contribution, not from the declaration chosen to represent the physical cell. Initialization uses the same mapping. Ordinary source sends still pass through lookup; only an already selected accessor or private initializer write uses a direct array operation. See the [accepted layout decision](#).

13.3. Class Assembly

`ClassConstruction` resolves contributor targets, creates each distinct metaclass, installs owned factories and finalizes layouts and coordinators. `VisitorSemanticsVM` retains backend entry points that delegate trusted seeding and anonymous assembly to it. `seedClassGraph` installs the six root identities implementing the [flat graph](#), plus `Lambda` and its metaclass. `Lambda` extends `Object` and has no public factories. The metaclass has no additional constructor arity, argument routes or initializer fields. The [factory contracts](#) specify their public selectors.

13.3.1. Representing Top without Reification

The specification's `Top` is the empty constructor of the class algebra. `VisitorSemanticsVM` deliberately does not allocate a `VMClass`, metaclass, mixin or handle for it. The implementation refines the specification with this field-specific representation:

```
decodeSuperclass(Object, absent Java reference) = Top
decodeSuperclass(C, reference to S)             = S
```

Only `Object`'s superclass may use the absent case in a well-formed class graph. An absent lexical parent, receiver or class link has its own meaning; it does not denote `Top`. Neither Java absence nor `Top` is the canonical language null. The spec's `super(Object) = Top` and the VM's `Object.superclassRef() == null` therefore describe the same terminal structure at different representation levels.

The correspondence is local and concrete:

Semantic empty case	Current implementation
<code>lin(Top) = []</code> ; exact/invoke search over it misses	<code>ObjectProtocol</code> stops when the superclass reference is absent, after searching <code>Object</code> 's contribution. No extra operation is selected or executed.
<code>Top</code> has an empty layout and no contribution	<code>ClassConstruction.finish</code> adds no superclass layout when that reference is absent; <code>Object</code> retains its ordinary owned mixin.
No initialization dependency on <code>Top</code>	<code>Object</code> has no superclass initialization edge. No terminal initializer, activation, return home or argument evaluation is introduced.

No current source or boundary operation observes a `Top` object. Reification would extend the value contract and is justified only by an accepted feature requiring such a first-class reference. Its exposure, identity, class-of and construction rules would then need specification. The [Top decision](#) records that criterion and the rationale for the present representation.

[ClassConstructionChecks](#) asserts the absent root superclass and flat metaclass graph. [NativeSeedSourceTest](#) checks the corresponding source recipe. These are implementation evidence; the [general Java simulation proof](#) remains an obligation.

13.3.2. Private Construction Code

[ConstructionCode](#) generates `CoreUserFunction` bodies for ordinary primary `new`, default `apply`, owned initializers and class coordinators. Coordinators sequence dependency calls using `CoreLet`, then evaluate their owned body directly in the existing initializer home. The language schedule and argument binding are specified in [Construction Order](#).

Private operation	Required backend work
Allocate	Allocate one receiver using a bound class's cached layout.

Private operation	Required backend work
InvokeInitializer	Evaluate receiver and arguments through frames; enter a bound complete coordinator or owned contribution with its occurrence and fresh home.
WriteSlot	Resolve the active initializer's occurrence-local destination through the actual receiver layout before evaluating the value; retain the destination in a write frame.
SlotsComplete	Enable the post-slot phase after the final write has completed.

These operations have no selectors. `new` itself uses ordinary method lookup; no privileged construction lookup target is required. The [construction decision](#) records why the four operations are necessary.

13.4. Method Activations

`MethodActivation` records immutable parameter slots, the selected `VMethodClosure`, receiver, caller continuation and a fresh return-home reference. Its lexical parent is a `LexicalObjectScope`, pairing the receiver with its selected contribution and linking to that contribution's definition scope:

```
method activation
  → lexical receiver scope(receiver, applyingClass, contributionIndex,
↪  definition)
  → definition.definitionScope
```

`InitializerActivation` likewise has constructor parameter slots and a fresh home, plus slot/body phase state. Instances never acquire an automatic link to their own constructor activation. A lowered `CoreLetExpression` creates a separate activation, reserves all locals first, and inherits receiver and home metadata.

13.4.1. Lambda Activations

`VMLambdaClosure` retains its function, captured scope, receiver, applying class and return target. Invocation allocates parameter slots over the captured scope and restores the caller afterward, without a fresh home. `Let`/`method`/`initializer` activations can remain captured after their homes retire. Native tracing retains their reachable data without reviving return authority. The first collector conservatively also traces activation continuation links, which can retain old caller graphs; see [collection trade-offs](#).

13.5. Dispatch Origin Tracking

For [lexical lookup](#) and [super](#), `VMethodClosure` retains (`applyingClass`, `contributionIndex`) separately from definition scope. `MethodActivation.methodOrigin` and `LexicalObjectScope` preserve that selection. `Let`/`lambda` activations follow lexical links; initializers use their own occurrence. Origins are neither inferred from a mixin's source class nor copied to every activation.

14. Java Interpreter

VisitorSemanticsVM is the executable prototype. The older VM is not a semantic authority. This chapter records how Java realizes the language contracts and [formal reference machine](#), including implementation restrictions. It does not claim a completed refinement proof.

14.1. Machine Components

The CESK-inspired configuration is `Configuration(control, environmentRef, runtimeWorld, continuationRef)`. The scope reference identifies an activation or lexical receiver view; `RuntimeWorld` supplies the store, boundary and seeded identities. There is no separate environment namespace.

Reference component	Java representation
Value v , store σ	Typed <code>ValueRef</code> keys and mutable <code>VMValue</code> entries in <code>ConcreteStore</code> .
Scope ρ	<code>Activation</code> or <code>LexicalObjectScope</code> , with generated accessor storage and declaration/application metadata.
Continuation κ	Linked <code>ContinuationFrame</code> entries addressed by <code>ContinuationRef</code> .
Return homes H	<code>Activation</code> addresses also identify homes; <code>ReturnHomeActivation</code> stores liveness and <code>InitializerActivation</code> stores phase.
Boundary B	<code>DefaultJavaBoundary</code> identity maps and suspended synchronous foreign calls.
Sequential control authority	Conceptual ownership is reconstructed from boundary admission and suspended-call state; there is no reified control-token value.
Failure control	<code>Control.Error</code> terminates the current native continuation; callback failure is exported to its foreign caller. No execution-wide failure marker is retained.

`Control` distinguishes expression evaluation, exact host send, committed foreign call, returned value and error. [EvaluateStepVisitor](#) handles expressions; [ContinuationStepVisitor](#) handles completion; [ObjectProtocol](#) selects and invokes operations. Its ordered loops, `getterSeen`, `Selection` and `EligibleAccessor` retain lookup evidence without repeating reads or selection. The language algorithm is specified in [Message Sends](#).

The step API returns a set, but the concrete driver requires exactly one successor for each nonterminal native configuration. It stops at an error or a value under `HaltFrame`. Ob-

servable determinism additionally depends on supplied foreign behavior. A set-valued interface does not implement abstract execution. Retained or prepared configurations do not each hold execution authority. All ordinary entry and stepping paths for one runtime obey the same sequential [control agreement](#). `step` acquires admission for its selected configuration, advances one transition and yields authority back to the backend driver. A nonterminal successor retains its ordinary home state and needs admission again before `step` or `run` can advance it; yielding does not mean final delivery.

Public inject prepares an unexecuted tooling configuration under this implementation's execution guard, because allocation mutates the serial concrete store. Unassociated entry during an active execution fails before allocation. This guard is coordination for the current representation, not evidence that preparing a configuration is itself an ordinary native transition. `evaluate` keeps preparation, execution and export inside one guard and budget. Raw backend helpers remain subject to caller coordination; this is not a generally thread-safe backend API.

14.1.1. Addresses and Allocation

Store separates `Value(VMValue)` and `Continuation(ContinuationFrame)` entries. `ConcreteStore` uses packed entry storage, a logical-handle-to-position map and fresh increasing identifiers. Reads return one entry; concrete `join` rejects conflicting entries. Address reuse is not a supported abstract execution mode. Concrete addresses are internal and are never required by source programs or boundary clients.

The native collector traces at complete configuration boundaries when occupancy reaches 75% of an elastic entry budget (16,384 initially; backend-configurable threshold from 70% to 80%). It compacts live entry references while preserving logical handles and Java object identity. The `GarbageCollector` interface separates policy from VM reference enumeration. This is storage compaction, not a replacement for the Java collector that manages the underlying objects. The native collector currently runs serially at safepoints; the [execution agreement](#) permits other correctly coordinated refinements, including concurrent collection. See [native heap collection](#) for roots, boundary retention, measurements and limitations.

Backend-only root provenance and shortest retention paths share the collector's root enumerator and graph tracer. Reports are non-owning observations rejected by the public boundary; no language selector or activation API is added. Audited field signatures, randomized graph oracles and GC-on/off execution comparisons guard coverage. See [graph hardening](#) for guarantees and limits.

14.1.2. Values

[Runtime Object Representation](#) describes objects, classes, contributions, scopes, caches and occurrence layouts. `VMUninitialized` is an allocated backend sentinel, corresponding to the reference machine's non-value marker. Canonical null and Booleans are native objects; integer/string transport and Aliens use separate private entries.

14.1.3. Continuations

Frames retain their next reference and the scope/operands needed on resumption:

Frames	Pending work
ReceiverFrame, ArgFrame	Receiver and ordered argument evaluation.
LetFrame	Ordered local binding and sequencing.
CallReturnFrame, DoReturnFrame	Scope restoration, method completion or delivery to the exact captured home.
ClassTargetFrame, MemberClassReturnFrame, ApplyFrame	Contributor resolution, member-cache publication and deferred member invocation.
InitializerCallFrame, InitializationWriteFrame, InitializerReturnFrame	Private-call operands, resolved slot writes and initializer completion.
HaltFrame	Final delivery.

There is no SeqFrame: CoreLetExpression and LetFrame sequence code. CallReturnFrame also restores let/lambda scopes without introducing a home. Non-local return scans for its exact home before mutating liveness. Completion, failure and unwind retire homes and abandon pending member realization. Java callbacks start separate native continuation chains; their active foreign context provides the barrier required by the default [boundary agreement](#).

14.1.4. State Transitions

Class realization installs generated CoreUserFunction bodies. Primary new uses ordinary method dispatch; private allocation/calls/writes/phase transitions are implemented by ConstructionCode and the same visitors. CoreObjectLiteral retains a zero-formal, factory-free CoreClassLiteral, including its contributor targets and argument routes. Evaluation sends exact new/0 to that class expression, reusing ordinary realization, dispatch and generated construction. No object-specific construction operation or continuation is needed. Empty private-call argument lists still schedule machine steps. The representation and operation rationale are in [Private Construction Code](#).

14.2. Explicit Store: The Key Commitment

A VMObject contains a mutable ValueRef[]; a slot holds a reference rather than a separately allocated binding cell. Initialization, setters, caches and home retirement mutate backend objects. Configurations share RuntimeWorld: retaining an earlier configuration does not preserve an earlier store state. Only reachable native entries survive a collection. Active and synchronously suspended configurations, seed objects, boundary handles and explicit backend root leases define reachability. Backend tools retaining a configuration or raw address across other executions must use world.nativeHeap().retain(...) and close the lease when finished; a Java variable alone is not a native heap root. Root registration and lease release must themselves occur under the current guard or while the runtime is exclusively idle. These backend helpers do not acquire coordination internally; leases protect reachability rather than authorizing execution or concurrent store access. Public Expats and boundary references are pinned automatically for this increment. Alien entries remain boundary-owned and are retained without inspecting foreign payloads. Col-

lection preserves captured lexical data and retired return-home state, without restoring return authority or introducing activation reflection.

14.3. Module Entry

`BootstrapRuntime.instantiateModule` checks a class literal's declared arity and module restrictions, evaluates it in a fresh empty top activation, then uses an exact Expat new send. Definition, construction and synchronous callbacks share one transition budget. It returns an Expat; the host explicitly sends any entry message. Host sends contribute an empty caller scope.

`BootstrapRuntime.evaluate` is the distinct expression harness, using the assembled kernel as parent and receiver. Its supplied capability context may become part of returned closures/classes. The normative isolation contract is in [Program Structure](#); the richer contexts are described in [Tooling](#).

`MinimalRuntimeWorld` installs ordinary immutable bundle slots named `null`, `true`, `false` and `Object`, holding the corresponding seed identities. Additional supplied capabilities cannot replace those slots in this assembler. These are this tooling bundle's assembly rules, not reserved language names; nearer declarations can shadow its slots through ordinary lexical lookup. Normal modules do not receive these bindings implicitly.

14.4. Java Boundary

`ForeignBoundary.identityMirror()` returns a stable, boundary-owned capability. It is supplied explicitly to modules and observes identity and membership through the [ordinary mirror protocol](#), never a special evaluator dispatch branch. The narrow root Object service shares private identity helpers without exposing the mirror. Current identity hashes use the retained native/Alien representation's Java identity hash; that algorithm is a backend policy, not a portable identifier.

`DefaultJavaBoundary` owns the [Alien/Expat contract](#). `BootstrapRuntime.boundary()` returns a narrow `PublicFacet`; package-private `VmServices` provisions the seed identity service. Both delegate to the same private owner. It uses a Java identity cache for Aliens and a per-native-identity Expat cache, both retaining strong references, which are roots for native collection and implement the specified identity round trips.

Integer/string interning is a non-owning native cache: collection removes cache entries whose native transport values were reclaimed. An explicit public boundary reference still pins its value. Conversion by value does not promise host identity.

Exact native null/Boolean identities map to Java null/Boolean without Expats. Byte, Short, Integer and in-range BigInteger normalize to Long; Long and String use by-value transport. Other numeric forms and raw VM representation values are rejected. Arbitrary objects become opaque Aliens, not reflected Java method collections. Integers and strings currently have no native class dispatch.

For the specified [callback admission protocol](#), `DefaultJavaBoundary.Call` records the suspended configuration, parent call, originating thread, admission state and active callback count. `NativeHeap` transition leases root suspended configurations until their native thread resumes; closed calls clear their configuration and ancestry references.

`CallbackContext.send` uses a permit to serialize native execution and short representation-sensitive services. `invoke` releases permission around the selected foreign operation and reacquires it before result conversion. Selection retains native permission and prohibits callbacks. Worker callbacks run on their own host thread, so the blocked caller needs no callback pump. The coordinator's native owner, active call and idle state collectively realize conceptual token ownership; neither copied contexts nor nested permits are individual tokens.

The innermost call admits callbacks and completion waits for admitted descendants, as required by the contract. The implementation uses `wait/notifyAll`, with no FIFO or fairness guarantee. Waiting admission can be interrupted with `EXECUTION_POLICY`; required caller restoration waits without abandoning native state and preserves the thread's interrupt flag. No foreign-thread affinity or termination guarantee is added. The shared guard also protects this concrete store's representation-sensitive operations; it is an implementation constraint, not a universal physical-memory token rule.

The callback nesting limit is 64; pending requests do not consume nesting depth. The default [no-crossing NLR agreement](#) is implemented by checking home liveness and the callback continuation, then delegating crossing rejection to `DefaultJavaBoundary.nonLocalReturnFailure()`. `Control.Error` aborts the callback and retires its homes before the boundary exports the [specified diagnostic](#). The shared Execution retains only the step budget, not a sticky failure marker; foreign recovery does not replenish it. Exhaustion prevents further native transitions without vetoing a terminal foreign result that needs no further step. Host exception classes and message text are not language interfaces.

14.4.1. Stack Safety

The native driver loops over explicit frames, so language method/lambda calls and nested initializers do not recursively call the Java evaluator. Synchronous foreign calls and callbacks do use the host stack. A transition budget cannot preempt a blocking foreign operation; termination remains an adapter concern. The callback limit, retained allocations and possible resource exhaustion prevent any claim of unlimited execution.

14.5. Supported Subset and Remaining Work

Area	Current implementation status
Numbers and strings	Signed 64-bit integer literals and string transport. Decimal literals are rejected; native arithmetic/string protocols are absent. Broader numeric range, overflow and string contracts remain underdeveloped.

Area	Current implementation status
Qualified outer	Runtime name scan over lexical scopes; frontend binding to declaration identities remains unfinished. Exact captured application ancestry at every depth implements the accepted lexical-origin rule.
Holes	A reached hole is fatal (<code>UnresolvedHole</code>); no configurable concrete policy.
Composition	Whole-declaration member override and the specified shared-name state; no deep family merge or adaptation algebra.
Non-local returns across foreign execution	Boundary-owned agreement; only default no crossing is implemented. A supporting transfer protocol is deferred.
Tail calls and reclamation	Native tracing and entry compaction at occupancy safe-points; no TCO, foreign reclamation or hard memory bound. Expats and Alien entries remain pinned.
Execution agreements	Sequential ordinary execution with scoped worker callbacks. The conceptual token is not reified; parallel native execution, concurrent native GC and general monitor/intervention capabilities are permitted extension directions, not implemented APIs.
Analysis and persistence	No sound abstract interpreter, persistent snapshots, rollback or portable runtime persistence.

These limits are implementation restrictions or identified open work, not permission to replace accepted semantics. Future TCO must preserve captured homes and barriers; abstract execution needs sound domains, joins, transitions and foreign-effect models beyond an allocator change. See [Future Directions](#) and the [outer comparison](#).

14.6. Refinement of the Formal Machine

A refinement relation must decode addressed frames and suspended Java calls into the reference stack; map mutable entries to the current σ ; and preserve scope, occurrence, cache, H , B and active failure control. The allocated uninitialized sentinel maps to the private marker. Fresh identities and physical slot positions may be renamed while preserving identity, sharing and logical mappings.

It must reconstruct control ownership from the coordinator according to [runtime admission](#). Representation maintenance may stutter; declared interventions would need their specified effects in the target relation. The present refinement target includes neither a parallel execution agreement nor an independent intervention relation.

Object's absent superclass uses the field-specific [Top decoding](#).

Administrative steps may stutter, and one foreign Java call can contain many native call-back steps. Neither fact permits hiding effects, changing failure kinds, replaying selection or ignoring divergence. A comparison must include the prototype's scalar subset and execution limits, or explicitly exclude runs that hit them. No simulation proof is claimed; the formal appendix records the remaining obligations.

`bash scripts/check-bootstrap.sh` runs focused backend checks with JDK 17+ and Python 3. `./gradlew test` additionally exercises parsing and the complete project with its configured JDK 23 toolchain. Relevant witnesses include [UnifiedInvocationTest](#), [ClassCompositionTest](#), [InitializerReturnHomeTest](#), [NativeValuesTest](#) and [ModuleEntryTest](#). The admission regressions in [BoundaryReentryChecks](#) cover competing callbacks and pending completion, rejection of unassociated preparation before allocation, leased idle preparation followed by stepping, and concurrent foreign computation and consumption of previously published immutable diagnostics while native execution owns the guard.

15. Tooling Architecture

The interpreter executes without consulting analysis annotations. Tools may add naming, diagnostics, inferred types, contracts or analysis results around the [descriptor layer](#). This chapter specifies intended tooling interfaces and their current limits; it does not claim an implemented analyzer or debugger.

15.1. Evaluation Contexts

A tool can evaluate with explicitly supplied objects or select a debug activation. The context uses activation objects, ordinary lexical lookup and the same Alien/Expat and return rules. It introduces neither a separate Environment namespace nor a global service registry. Language-visible debugger and mirror services must be explicitly supplied boundary capabilities. Internal activation selection does not make activations public language values.

Operation	Context
Module instantiation	Empty top activation ; explicit constructor inputs
Tool expression evaluation	Explicitly supplied objects, such as sample data or a console
Proposed debugger evaluation	Selected activation's bindings plus explicitly supplied services

A tool must identify its context and additional capabilities. It cannot silently enrich normal module entry. Results retain actual lexical captures, including classes that resolve superclass/mixin targets there; export and persistence must preserve or explicitly account for those dependencies.

The [Java entry paths](#) implement module and supplied-expression evaluation, not a general selected-activation debugger API.

15.2. Execution, Observation and Intervention

The [execution agreement](#) distinguishes ordinary evaluation, representation maintenance and explicitly authorized observation/intervention. Tools use that contract rather than gaining execution rights from possession of a configuration. Backend preparation and retention follow the [Java coordination rules](#).

For example, an immutable published observation can be consumed while ordinary execution continues. Reading live slots needs a specified consistency model; changing one is an intervention whose effective ordering must be defined. Replacing or resuming a

continuation also needs an ownership-transfer protocol so its previous owner cannot continue. These examples do not imply a general monitor or selected-activation intervention API in the current prototype.

A model checker is another explicitly supplied tool: a supporting parallel VM could honor its request for independent simultaneous transitions under the [parallel-agreement requirements](#). The execution capability, proof evidence and concrete implementation must meet that agreement; a saved configuration alone supplies none of them.

15.3. Descriptors as the Naming Bridge

Intrinsic declaration names identify many syntax elements. A descriptor can name an otherwise anonymous expression, for example `(compute(x) : intermediate)`. It attaches information without changing execution. Name resolution for tool references is separate from language message lookup.

15.4. External Annotation Files

Each tool may keep a separate external file associating syntax identities with its own facts: a type, interval, units assumption, proof obligation or diagnostic. Formats and interpretations belong to the tool. Adding or changing annotations does not alter raw execution, supply runtime capabilities or establish that an asserted property holds. Different tool views need not use a shared format.

15.5. Qualified Naming

Paths such as `module.Class.method.local` are proposed tooling conventions, not language selectors. Tools must resolve collisions and preserve references when source changes. Descriptor-supplied names can identify subexpressions, but a stable AST/source-mapping scheme is still required; spelling a name alone does not solve identity across edits.

15.6. Connection to Abstract Interpretation

The explicit-state visitor machine provides a starting point for analysis. [AAM and ADI](#) are research approaches, not modes enabled by an allocator or an “abstract kernel.” The required derivation is described under [Persistence and Analysis](#).

Annotations may supply domains or assumptions to a particular analysis, which must state their meaning and justify its results. Descriptors alone perform no checking. Analysis, mirror tooling and persistence remain [future work](#).

Part IV.

Future

16. Future Directions

This chapter separates accepted extension directions from unresolved proposals; neither implies an implemented feature or promised release. Extensions preserve the accepted [capability inputs](#), [lookup](#), [construction](#) and [boundary](#) contracts unless a later decision explicitly changes them. Tool annotations alone cannot change raw execution. Any default handler, mirror or scheduling service must be supplied explicitly, not discovered through an ambient kernel.

16.1. Operators and Control Structures

Proposed surface extension. Binary operators, conventional conditionals, loops, pattern matching and library DSLs could lower to the core's sends, lambdas and objects. A monadic extensible parser inspired by Lean 4 is one candidate. Precedence, hygiene, phase separation and preservation of evaluation order need specification. The current syntax already expresses control through ordinary messages and thunks; no extensible parser is implemented.

16.2. Named and Optional Arguments

Proposed; dispatch unresolved. Named arguments, defaults and varargs must coexist with exact name/arity selection and generated setters. A candidate `name = expression` argument form would need a distinct grammar context from assignment. Decisions include parameter-name binding, default evaluation scope and timing, duplicate/unknown arguments, and how omitted or variable arguments map to selectors. The current language has positional arguments only.

16.3. String Interpolation

Proposed syntax. Interpolation could lower to explicit conversion and concatenation messages. Delimiters, conversion protocol and evaluation order remain unspecified. It also depends on native string operations, which the prototype does not yet implement; see the [scalar design note](#).

16.4. Collection Literals

Proposed syntax and libraries. Lists/maps could be constructed through ordinary supplied classes, with future literal sugar. Syntax must avoid conflicting with object literals. Collection classes, key equality and hashing, mutability and element evaluation order require contracts; example `List/Map` names do not denote ambient standard objects.

16.5. Mixin Contract Verification

Proposed analysis. A verifier could collect a contribution's super sends and check the required selectors at each actual application occurrence. The selected continuation of the dispatch chain, arity and invocation rules matter; a set of names alone is insufficient. Descriptors could state stronger contracts. Results belong to external tooling and do not replace runtime failure on an unsatisfied contract. See [object-model dispatch](#) and [tooling](#).

16.6. Deep Family and Mixin Composition

Accepted direction; deferred semantics. Deep composition with state in member classes needs rules for nested declarations, constructor signatures, sibling references, state and ordering. The current whole-declaration member override and ordered contributions remain the reference. Preserve declaration identities, definition scopes and occurrence identities so later composition can distinguish repeated applications.

Possible operations include aliasing, renaming, hiding, exclusion, precedence and explicit state sharing/mapping. They are distinct: an alias need not rewrite recursive sends; hiding need not remove internal access; selecting behavior does not settle storage collisions. Effectful initializer routes require an execution plan—registrations and callbacks cannot be assumed to commute or roll back. One-object construction and the foreign boundary must survive any extension. See the [accepted scope decisions](#) and [composition design space](#).

16.7. Trait-Style Conflict Resolution

Alternative under consideration. Detection of overlapping method selectors could require an explicit own override or contribution-specific delegation, instead of silently accepting declared precedence. That would change current ordered override semantics and is not accepted. Direct contribution delegation syntax and its receiver/origin rules are also unresolved. Reified definitions help detection, but future composition may require additional metadata.

16.7.1. `doesNotUnderstand` as a Message

Open design. Receiver interception through a `doesNotUnderstand` message could support proxies and delegation. Questions include recursive failure, typo masking, default behavior and analysis of dynamic selectors. Signaling a missing-message condition is another proposal. Neither is implemented: current missing dispatch is a fatal diagnostic and never invokes a DNU method.

16.8. Exception System

Proposed condition/restart system. Current [fatal diagnostics](#) are not catchable, resumable or retryable. The design goals are local recovery, escalation through callers, optional

resumption at the signal site with a supplied value, and an explicitly configured last-resort policy.

The Common Lisp-inspired proposal separates:

Role	Responsibility
Condition	Describe a problem at the signaling site.
Handler	Select recovery policy in an enclosing dynamic context.
Restart	Offer a named recovery operation near the component that can perform it.

One candidate scans active handler / restart frames while preserving the signaling continuation, then either resumes or explicitly unwinds. Direct frame mechanisms and a design built from delimited continuations / algebraic effects remain alternatives. Handler matching and ordering, restart extent and selection, resumption multiplicity, cleanup, home liveness and foreign-call barriers need precise rules. Two or three new frame classes would not by themselves specify this semantics or prove its analysis cost.

The proposed missing-message condition would replace fatal DNU only after an accepted change. Unhandled conditions could reach a deployment-supplied handler: a test runner may record failure, a simulator may choose a degraded value, and an analyzer may represent alternatives. These are distinct execution policies, not capabilities implicitly available to every module. Existing boundary failure kinds must survive propagation; changing resumability requires an explicit contract for external effects.

A later library could offer `try/catch`, `ensure` and assertion-like operations over the chosen mechanism. Cleanup on normal return, failure and non-local return must be defined before claiming that `ensure` is ordinary sugar. The investigation order is basic signaling / handlers, restarts and explicit abort, library forms, then analysis. No release numbers or implementation-size claims are committed.

16.8.1. AAM Compatibility

No condition-system abstraction has been derived. Finite source or frame forms do not imply finite execution state. An analysis must represent handler / restart instances, dynamic names, continuation alternatives, state updates and control outcomes, with sound matching and transfer rules. Joins combine alternatives; widening is a separate convergence technique when a domain needs it. See [analysis obligations](#).

16.9. Tail-Call Optimization

Proposed investigation; not implemented. The objective is bounded control space for eligible native tail-call chains, including mutual calls and delegation. Explicit continuations already avoid one Java evaluator frame per native call; that is distinct from bounded store use or proper tail recursion.

A final send is only a candidate. Its callee may invoke a captured lambda whose $\wedge$ still targets the caller's live home. For $\wedge$ `recurse()`, the operand executes before return delivery; collapsing frames afterward does not reduce peak recursive space. An optimization

must preserve home identity and retirement, initializer phases and remaining contributions, constructor results, pending member-cache completion, callback barriers, selected receiver/origin, evaluation order and exactly-once effects. Foreign calls need separate eligibility rules.

The proposed sequence is to measure the [recursion catalog](#), identify core tail contexts and completion obligations, prototype a conservative native optimization, and compare results, traces, identity, failures, continuation depth and allocation. Captured bindings cannot be reused if doing so changes closure observations. Reclamation and retained data/caches need a separate space account; a growing list of deferred homes does not establish bounded control space.

Inlining needs the actual selected behavior or justified guards, not special selector names such as `ifTrue`. Debug history also has a cost: bounded summaries, recording and replay provide different guarantees. Proper tail recursion remains a stronger uncommitted space property. The research basis is [Clinger, Proper tail recursion and space efficiency](#).

16.10. Mirror-Based Reflection API

Broader reflection remains proposed. Mirrors could offer controlled inspection or invocation on a target. Reflective operations belong on mirrors, not ambient methods of `Object`; the application need not itself implement reflection. Obtaining a mirror requires authority, and language-visible backend services still use the Alien/Expat boundary.

The API must decide which class, slot, method and origin information is exposed, which mutations are allowed, and how access restrictions, optimizations and lifetime are respected. Existing backend fields are implementation evidence, not a public representation contract or proof that no new metadata is needed. There is currently no public class getter or activation reification.

The implemented [IdentityMirror protocol](#) is the baseline. Further kinds, standalone mixin references, native scalar identity and broader reflection remain open. The [design note](#) records the current scope and limitations.

16.11. Access Control

Proposed policy; no language access control is enforced today. The candidate object-capability design treats an object's export surface as its external behavioral contract:

1. Private declarations by default, with explicit exports; getter and setter exposure can differ.
2. Inherited exports remain visible, while parent internals are sealed from subclasses. Whether a separate "heritable" visibility is useful remains open.
3. A mixin's exported behavior becomes internal to its applier unless re-exported; the mixin's own helpers remain available to that contribution but hidden from unrelated contributions.
4. Lexical nesting grants access to enclosing internals. The exact treatment of explicit sends to an outer `ClassName` receiver still needs specification.
5. Class-side `new`, `apply` and named factories follow the same export policy; external construction requires an exported path.

These are candidate changes to current lookup, not behavior enabled by existing annotations. Export syntax, especially for synthesized factories, is undecided. A tool-only descriptor could check conventions first; runtime enforcement would require an explicit semantic increment. Exports must then expose the same surface as external native callers. Origin metadata may assist enforcement, but sealing, virtual overrides, state access and composition require proofs and possibly new metadata. Export sets alone do not establish safe pruning in an analyzer.

The accepted outer operation still selects an ordinary declaration-relative receiver. This proposal creates neither a universal parent getter nor public activation reflection. [Related Works](#) places this proposal alongside Newspeak and other capability designs; no novelty or simplicity claim is assumed.

16.12. Method tear-offs

Proposed; neither syntax nor a method-reification API is implemented. Ordinary `obj.m` invokes `m/0`; it never implicitly returns a method. The current candidate `obj.m#N` would evaluate the receiver once, select an actual method `m/N`, and return a callable retaining that method, receiver and dispatch origin. Applying it would execute the selected method with its original `self` and exact `apply/N` arity. It would not select callable-slot fallback or member-class factory candidates.

Under that proposal, `obj.m#2(a,b)` obtains the method reference and applies it; a mismatched application arity fails. This requires no separate immediate-apply semantic operation. An earlier `$` suffix candidate omitted explicit arity; it is not accepted syntax either. Final grammar, bound versus unbound references, identity/equality of repeated references, interaction with overrides and `super`, and mirror integration remain open. The accepted distinction between access, invocation and callable values stays in [Message sends](#).

16.13. Concurrency and Parallelism

Accepted execution-agreement extension principle; concrete parallel agreements and the composition layer remain future work. No scheduler is implemented. The [current execution agreement](#) already permits maintenance refinements and declared interventions while serializing ordinary native control. This section concerns richer agreements authorizing simultaneous native transitions. The Java world's mutable store and effectful foreign operations supply neither snapshots nor a pure state transformer.

16.13.1. Independent Transitions and Parallel Execution

A model checker with an appropriate capability may ask a supporting parallel VM to execute two independent enabled transitions concurrently. The agreement must specify execution authority, shared-state semantics, observations and the independence evidence it accepts. It need not mandate a proof format: evidence may be supplied with the request or established by a trusted analysis, but it must apply to the actual configuration and assumptions used.

For transitions t_1, t_2 enabled in C , the independence obligation is that each preserves

the other's applicability and both orders yield equivalent configurations and observable effects under the agreement:

$$C \xrightarrow{t_1} C_1 \xrightarrow{t_2} C_{12}, \quad C \xrightarrow{t_2} C_2 \xrightarrow{t_1} C_{21}, \quad C_{12} \approx C_{21}.$$

Equivalence includes the specified boundary effects and their ordering, not just equal final slot values. Arbitrary foreign operations cannot be presumed independent; their declared contracts or an explicit effect model must supply the necessary justification. Speculation, cancellation and replay need their own effect agreements.

Semantic independence and concrete concurrency safety are separate obligations. A parallel implementation must correctly coordinate its allocator, store, roots, continuations, caches and collector; mathematical commutation does not make today's Java data structures thread-safe. An implementation parallelizing work that refines an allowed sequential trace may retain the sequential abstract agreement. Authorizing additional ordinary native control requires the richer agreement and its authority discipline. Neither case changes fixed lookup, identity, return-home lifetime, initializer phases or the boundary's NLR policy.

This extension principle adopts no parallel VM implementation, scheduler, snapshot representation, model-checking algorithm or public transition-proof API. Those remain separate increments with their own specifications and tests.

16.13.2. Boundary-supported Non-local Returns

Implementing an agreement beyond the [default no-crossing boundary](#) requires a transfer mechanism and specified treatment of intervening foreign work. This is separate from parallel execution or scheduling. The [NF/FN design note](#) compares immediate escape and deferred delivery without selecting either as a mandatory mechanism.

16.13.3. The Semantic Language Interface (SLI)

The proposed SLI would expose machine stepping, input/output interaction and possibly inspection or snapshots to an external composition runtime. Actors, CSP, dataflow and parallel simulation are candidate compositions, with explicit scheduling, synchronization, time, routing and failure policies. Those policies must preserve native lookup and the message-level Alien/Expat contract; swapping schedulers does not prove application behavior unchanged.

A future boundary suspension could expose an operation request, then resume with a reply. It must define callback/reentrancy, identity, ownership, cancellation and failure behavior before replacing today's synchronous calls. Snapshot/restore must account for the native store, live homes, continuations and boundary caches, and explicitly exclude, model or compensate external effects. Replay and speculation require recorded inputs and suitable foreign contracts; they are not free consequences of sequential stepping.

The [incremental composition proposal](#) starts with bounded native state copying/comparison, explicit admitted state, a small SLI adapter and observations before shared-state composition. Gamine's SLI, communicating vats/actors, DEVS and virtual-actor runtimes are inspirations, not implemented integrations. Progress and sound analysis across composed machines remain separate proof obligations.

16.14. Persistence and Analysis

Deferred. Portable platform persistence must preserve identities, captures, composition origins and explicitly reconnectable foreign bindings. It is not Java object serialization and must not discover new authority while loading. See [object-graph persistence](#).

An abstract execution requires domains, store/control abstractions, transfer rules and foreign-effect assumptions related to the reference semantics. A configurable allocator, supplied abstract object or descriptor does not provide that derivation. Native scalar protocols and foreign conversion must also have explicit contracts; current open choices are recorded in the [value/analysis note](#).

Part V.

Related Works

17. Connections and Comparisons

VarioHyve combines an object language with explicit boundaries for independently implemented behavior. These comparisons distinguish inherited ideas, alternative choices and possible verification techniques. Proposed integrations and proof directions are not implemented results.

17.1. Federation and Model Interoperability

Maier identifies operational and managerial independence as distinguishing systems-of-systems concerns. VarioHyve adopts this perspective when participants retain their semantics and authority. Federating engineering models nevertheless does not imply that their subject is a system-of-systems, or that the coordinator controls every participant. [Maier \(1998\)](#)

Openflexo's FML organizes virtual models, concepts, roles and behaviors, connected to resources through technology adapters. Its synchronization behaviors operate on models in their original technical spaces: both FML and VarioHyve can coordinate execution. FML supplies modeling abstractions; VarioHyve investigates an object-language boundary exposing selected operations as capabilities. An experiment should compare the same coordination in FML, including adapter and correspondence maintenance. [Openflexo Core, model-mapping tutorial](#)

Eclipse Epsilon supplies model querying, validation and transformation, with connectivity, Java embedding and workflow support. VarioHyve might combine an Epsilon validation with a simulator while retaining Epsilon's semantics. The experiment must establish whether explicit authority and interaction contracts improve that workflow over Epsilon-only or host-language coordination. [Epsilon documentation](#)

CorrLang and comprehensive systems specify relationships among heterogeneous endpoints, distinguishing identity from other commonalities. Their graph-based correspondences address entity and constraint alignment. An Alien's reference identity does not establish that two models describe the same physical entity; conversely, correspondence does not establish compatible callback or failure behavior. These agreements could complement VarioHyve's behavioral contracts. [CorrLang introduction and comprehensive-systems references](#)

17.2. Objects, Modules and Reified Composition

Smalltalk supplies the orientation toward communicating objects and minimal irreducible machinery. VarioHyve shares these concerns without inheriting a Smalltalk image or debugger through similar syntax. [Ingalls, *Design Principles Behind Smalltalk* \(1981\)](#)

Newspeak is the closer comparison: lexical nesting, late binding and modules without globals make dependencies construction inputs. VarioHyve likewise uses explicit mod-

ule inputs and preserves declaration origins in lexical selection and mixin application. It specifies its own callable eligibility, initialization and class-side construction. The [detailed comparison](#) records deliberate differences, including exact captured ancestry for deeper repeated parent applications, and remaining implementation limits; complete Newspeak conformance is not claimed. [Bracha et al., *Modules as Objects in Newspeak* \(2010\)](#)

Piumarta and Warth bootstrap an extensible object model from a small messaging seed. This informs VarioHyve’s private initialization machinery, with a deliberate difference: native lookup and invocation remain fixed. Reified contributions preserve semantic information rather than granting replacement dispatch policies. Language-visible VM services use the ordinary Alien/Expat agreement. [Piumarta and Warth, *Open, Extensible Object Models* \(2008\)](#)

17.3. Authority, Reflection and Foreign Boundaries

Miller’s *Robust Composition* connects object capabilities, cooperation and limiting interference. VarioHyve’s explicit inputs and restricted service views follow this concern: public and privileged VM-service facets share transport without sharing every grant. This does not provide E’s distributed execution, persistence or hostile-component security guarantees. [Miller \(2006\)](#)

Bracha and Ungar separate reflection from base behavior, encapsulate its implementation and align reflective concepts with the observed language. VarioHyve’s supplied IdentityMirror follows this separation: observations belong to the mirror, leaving Alien selectors to their foreign protocol. Implemented identity and membership observations are a limited facility, not a general activation-inspection API. [Bracha and Ungar, *Mirrors* \(2004\)](#)

17.4. Execution Monitoring and Controlled Intervention

Kishon, Hudak and Consel compose language semantics with monitor specifications. Their monitoring semantics separates the program’s answer from monitoring information, with preservation obligations; subsequent work develops profilers, tracers and interactive debuggers. [Kishon, Hudak and Consel \(1991\)](#), [Kishon and Hudak \(1995\)](#)

Drey and Teodorov distinguish observation from deliberate intervention, such as editing a variable during diagnosis. VarioHyve accordingly separates ordinary continuation authority, observation and intervention contracts. Its sequential control token does not universally lock representations. Observers need defined consistency; mutating monitors need specified additional effects. Neither implicitly changes lexical return-home rules. These are [tooling contracts](#), not an implemented debugger. [Drey and Teodorov \(2016\)](#)

Implementation concurrency remains separate: Dijkstra and colleagues demonstrate collection concurrent with computation under established invariants. VarioHyve permits such semantic-preserving maintenance, without claiming a concurrent collector implementation or proof. [Dijkstra et al. \(1978\)](#)

17.5. Analysis and Verification of Composed Behavior

Abstracting Abstract Machines derives sound analyses through systematic machine abstraction. VarioHyve’s explicit state is a starting point, not an analyzer: soundness must cover object scopes, contribution identities, return homes and foreign effects. Bounding addresses alone is insufficient. Foreign summaries must account for mutation, callbacks, failures and nontermination. [Van Horn and Might \(2010\)](#)

Abstracting Definitional Interpreters offers another derivation path: monadic interpreters can support collecting and abstract semantics while inheriting precise call/return matching from the defining language. This suggests an alternative analysis organization, not a property obtained automatically by VarioHyve’s Java interpreter. Either route needs a sound relationship to the specified object and boundary semantics. [Darais et al. \(2017\)](#)

Interaction trees model recursive computation and external events; VarioHyve crossings would need intermediate callbacks, not just atomic results. Omnisemantics supports reasoning over every permitted nondeterministic outcome. Neither establishes that a foreign provider meets its contract. [Xia et al. \(2020\)](#), [Charguéraud et al. \(2023\)](#)

DimSum composes independently defined language semantics through events and protocol translations. Melocoton verifies OCaml/C interoperability with related language-local state. Both suggest obligations for conversions, roots and callback control; neither verifies VarioHyve’s Java adapter. The [research audit](#) expands these comparisons, including alternative boundary calculi, while the [case-study catalog](#) defines integration experiments and baselines. [DimSum \(2023\)](#), [Melocoton \(2023\)](#)

Part VI.

Appendix

A. Formal Rules

This appendix gives the structural operational semantics (SOS) of the accepted core. Surface syntax and its explanatory examples are in **Specification**; Java representations and restrictions are in [Java Interpreter](#). Unsettled parameters are listed at the end. No correctness or refinement theorem is assumed.

A.1. Signature and notation

$$\begin{aligned}
 v, \rho \in A, \quad \sigma : A \rightarrow \text{Node}, \quad u \notin A, \quad s = (n, k), \quad o = (C, i, \mu), \\
 H : \text{Home} \rightarrow \{\text{method}, \text{slots}, \text{body}, \text{dead}\}, \\
 X = (\sigma, H, B), \\
 \kappa ::= \text{halt} \mid f :: \kappa, \quad K = \langle c, \rho, \kappa \rangle_X.
 \end{aligned}$$

A contains private runtime identities; u is uninitialized storage. B is the boundary state, including identity maps and canonical native null/Boolean identities. Failure is carried by the active control and is reported at the nearest callback boundary or independent entry. Fresh identities are always distinct from existing ones. An omitted configuration component is unchanged; $X[\sigma(v).p := w]$ denotes a field update, not a source assignment. $\cdot$ concatenates sequences/stacks. For context-preserving steps, $\langle c \rangle_X$ abbreviates $\langle c, \rho, \kappa \rangle_X$ with the same ρ, κ on both sides.

Node or record	Fields relevant to execution
$\text{Obj}(C, S, \rho_d, \Gamma)$	Class, physical slots, definition scope, member cache.
$\text{Act}(U, \rho_p, v, o, h)$	Generated local/parameter accessors, lexical parent, receiver, occurrence, return home.
$\text{View}(v, o, \rho_d)$	Declaration-relative receiver scope; no parameter bindings or return home.
$\Lambda(\bar{x}, e, \rho_d, v, o, h)$	Native object of class Lambda, with code and private lexical captures.
$\mu =$	Reified owned contribution: declaration, scope, formals,
$(D, \rho_d, \bar{x}, T, \bar{S}, \bar{D}_m, e_b)$	operations, slots, members, final initializer body.
$\text{Class}(\mu, \bar{o}, S, R, L, M)$	Owned contribution, direct applications, superclass, routes, complete layout, metaclass.
$\text{Meta}(\mu, \dots)$	Class-side record; its fixed structural fields are given below.
$\text{Alien}(\phi), \text{Scalar}(p)$	Not an eligible construction-clause target.
	Foreign identity or scalar payload; neither implies a native class.

Scopes use object accessors, not a separate binding environment. Every active scope carries receiver/origin/home metadata; a View has $h = \perp$. $\sigma(\rho).U$ is storage for generated accessors, not a source namespace. It retains declaration mutability: local bindings

have setters; parameters do not. The maps below abbreviate these tagged storage declarations.

A.1.1. Class algebra

Let $A_{\text{cls}} \subseteq A$ contain identities whose store records are **Class** or **Meta**. The superclass field ranges over $A_{\text{cls}} \cup \{\text{Top}\}$. The distinguished empty constructor $\text{Top} \notin A$ is not a store node, source value, lookup miss $\perp$, uninitialized marker u , or the canonical null identity.

The **class algebra** and its projection from realized classes are:

$$\begin{aligned} Q &::= \text{Top} \mid \text{Apply}(\mu, Q), \\ \text{shape}(\text{Top}) &= \text{Top}, \\ \text{shape}(C) &= \text{Apply}(\mu_C, \text{Apply}(\mu_{o_1}, \dots \text{Apply}(\mu_{o_m}, \text{shape}(S_C)) \dots)). \end{aligned}$$

For no direct applications the last equation is $\text{shape}(C) = \text{Apply}(\mu_C, \text{shape}(S_C))$; in particular, $\text{shape}(\text{Object}) = \text{Apply}(\mu_{\text{Object}}, \text{Top})$. This is a projection of instance-side composition, not an equality of runtime identities: occurrences, scopes, routes and metaclasses remain in their records. It introduces no intermediate classes. Every realized superclass chain is finite and ends at **Top**; only **Object** has **Top** as its direct superclass.

Top has no owned contribution, scope, class-of link or superclass projection. There is no value, allocation, factory or initializer-entry rule for it. Source construction-clause targets must be realized non-metaclass identities in A_{cls} ; the seed supplies **Object**'s terminal superclass.

A.1.2. Core and machine controls

$$\begin{aligned} e &::= l \mid \text{null} \mid ? \mid \text{self} \mid \text{outer}(D) \\ &\quad \mid q.n(\bar{e})_\iota \mid \lambda \bar{x}.e \mid \text{class}(d) \mid \text{object}(d) \\ &\quad \mid \text{let}(\bar{b}; e) \mid \text{ret}(e) \\ &\quad \mid \text{alloc}(C) \mid \text{init}(\tau; e_r, \bar{e}) \mid \text{write}(j, e) \mid \text{slotsDone}, \\ q &::= \text{implicit} \mid \text{explicit}(e) \mid \text{super}, \\ \iota &::= \text{exact} \mid \text{invoke}, \quad b ::= x \leftarrow e \mid _ \leftarrow e. \end{aligned}$$

The return form $\text{ret}(e)$ is $\text{source} \hat{=} e$. Bare sends use $\text{exact}/\emptyset$; parentheses use invoke/k . Leading-dot sends lower to an explicit **self** receiver. The final four forms are private generated construction code. A class descriptor d retains owned declarations, contributor-target expressions and delayed routes. For $\text{object}(d)$, the descriptor is anonymous, with no owned constructor formals or factories; it may retain the same optional contributor clauses as a class descriptor.

The core form **null** is an internal constant, not the source identifier **null**. Empty bodies and omitted initializers lower to this form; source **null**, **true** and **false** lower to ordinary implicit sends. Their results depend on lookup and the selected behavior, not on this constant rule or a reserved source spelling.

$$\begin{aligned}
c ::= & e \mid \text{val}(v) \mid \text{collect}(a; \bar{v}; \bar{e}) \mid a[\bar{v}] \\
& \mid \text{call}(p, \bar{v}) \mid \text{enter}(v, o, \bar{x}, \bar{v}, e, \chi) \\
& \mid \text{steps}(\bar{b}; e) \mid \text{return}(h, v) \\
& \mid \text{member}(g) \mid \text{foreign}(\omega) \mid \text{callback}(v, n, \bar{f}) \\
& \mid \text{error}(\epsilon) \mid \text{abort}(\epsilon), \\
\chi ::= & \text{method} \mid \text{initializer}.
\end{aligned}$$

a is a pending control with a value-list hole: a send, a private initializer entry, or class realization. Frames appearing below are exhaustive for these forms: Recv, Args, Bind, Restore, Done, Return, Write, Cache, Apply, Module, and Barrier. Their fields are given by their rules; the tail is κ .

A.1.3. Runtime admission and conceptual control

The following transition rules describe ordinary execution under the [sequential execution agreement](#). Their runtime-level admissibility condition is one conceptual control token τ_c per live runtime, with one owner:

$$\begin{aligned}
\text{owner}(\tau_c) \in & \{\text{idle}\} \\
& \cup \{\text{native}(\alpha) \mid \alpha \text{ admitted}\} \\
& \cup \{\text{foreign}(\iota) \mid \iota \text{ active}\}.
\end{aligned}$$

Here α ranges over native continuations and ι over foreign invocations. The condition ranges over one runtime's evolving state and all its configurations, not separate tokens per configuration, stored version or thread. Ordinary native rules require ownership by their continuation; modeled foreign actions require ownership by their invocation. Transfers below are abstractly atomic, with associations retained in B and barriers. τ_c is ghost state, not a required field or language value; initializer target τ is unrelated.

Abstract event	Required ownership transfer
Accepted independent entry or tooling readmission	idle to the selected new or prepared native continuation
Committed NF invocation	Native caller to its fresh foreign invocation
Admitted callback	Current foreign invocation to the fresh callback continuation
Callback result or failure delivered at its barrier	Callback continuation to the associated foreign invocation
Foreign done or fail delivered	Foreign invocation to its suspended native caller, after admitted descendants finish
Independent final result or failure delivered	Native continuation to idle
Backend driver yields after a requested step	Native continuation to idle, retaining the successor for later readmission

All other ordinary steps retain ownership. Pending/rejected requests and completion arrival are adapter bookkeeping; done/fail below denotes delivery after descendant com-

pletion. The **admission contract** supplies nesting eligibility and rules out confusing a copied context with control ownership.

Backend one-step yield may leave a nonterminal successor without retiring its homes or producing a final observation. Later advancement requires readmission. The source evaluator's driver instead retains authority between native steps until a boundary transfer or completion.

This layer models serialized control effects, not arbitrary foreign computation, host queues, wakeups or fairness. Such work can continue while a callback owns the token. Refinement must reconstruct ownership from the implementation; these conditions are not a completed proof of the Java coordinator.

The **execution agreement** also permits maintenance refinements and declared interventions. Maintenance may stutter; an intervention changing abstract state needs its own specified transition. The rules below define neither an intervention relation nor a parallel agreement. Proofs must state which extensions, if any, they include.

A.2. Evaluation

Literal interpretation $B, \sigma \vdash l \Downarrow (v, \sigma', B')$ is fixed by the selected scalar profile; conversion failures use error. The internal null form returns the canonical identity v_{null} .

$$\frac{B, \sigma \vdash l \Downarrow (v, \sigma', B')}{\langle l, \rho, \kappa \rangle_X \longrightarrow \langle \text{val}(v), \rho, \kappa \rangle_{X[\sigma := \sigma', B := B']}}$$

$$\begin{aligned} \langle \text{null}, \rho, \kappa \rangle_X &\longrightarrow \langle \text{val}(v_{\text{null}}), \rho, \kappa \rangle_X, \\ \langle ?, \rho, \kappa \rangle_X &\longrightarrow \langle \text{error}(\text{Hole}), \rho, \kappa \rangle_X, \\ \langle \text{self}, \rho, \kappa \rangle_X &\longrightarrow \langle \text{val}(\sigma(\rho).v), \rho, \kappa \rangle_X. \end{aligned}$$

The **self** rule requires a receiver; absence is an error. For **outer(D)**, let ρ_j be the first declaration-relative view for lexical declaration D in the retained lexical chain. No such view is **InvalidOuter**. At every depth, traversal follows the retained lexical parent of each activation or view. A view preserves its exact occurrence and captured definition parent; the enclosing receiver's contribution chain is never searched for a replacement application of the same declaration. Implicit lexical selection uses this same chain, followed by ordinary dispatch on the selected receiver.

$$\frac{\sigma(\rho_j) = \text{View}(v, o, \rho_d) \quad \mu_o.D = D}{\langle \text{outer}(D), \rho, \kappa \rangle_X \longrightarrow \langle \text{val}(v), \rho, \kappa \rangle_X}$$

$$\frac{w \text{ fresh} \quad \sigma' = \sigma[w \mapsto \Lambda(\bar{x}, e, \rho, \sigma(\rho).v, \sigma(\rho).o, \sigma(\rho).h)]}{\langle \lambda \bar{x}.e, \rho, \kappa \rangle_X \longrightarrow \langle \text{val}(w), \rho, \kappa \rangle_{X[\sigma := \sigma']}}$$

A.2.1. Receiver and arguments

send retains its mode and origin: $r = \text{lex}(\rho)$, $\text{recv}(v)$, or $\text{super}(v, o)$. In the following first rule, $q \in \{\text{implicit}, \text{super}\}$, and r is $\text{lex}(\rho)$ for implicit sends and $\text{super}(\sigma(\rho).v, \sigma(\rho).o)$ for **super**; an absent required receiver/origin is an error.

$$\begin{aligned}
\langle q.n(\bar{e})_\iota, \rho, \kappa \rangle_X &\longrightarrow \langle \text{collect}(\text{send}(r, n, \square, \iota); []; \bar{e}), \rho, \kappa \rangle_X, \\
\langle \text{explicit}(e).n(\bar{e})_\iota, \rho, \kappa \rangle_X &\longrightarrow \langle e, \rho, \text{Recv}(n, \bar{e}, \iota, \rho) :: \kappa \rangle_X. \\
\langle \text{val}(v), \rho', \text{Recv}(n, \bar{e}, \iota, \rho) :: \kappa \rangle_X &\longrightarrow \langle \text{collect}(\text{send}(\text{recv}(v), n, \square, \iota); []; \bar{e}), \rho, \kappa \rangle_X. \\
\langle \text{collect}(a; \bar{v}; []), \rho, \kappa \rangle_X &\longrightarrow \langle a[\bar{v}], \rho, \kappa \rangle_X, \\
\langle \text{collect}(a; \bar{v}; e :: \bar{e}), \rho, \kappa \rangle_X &\longrightarrow \langle e, \rho, \text{Args}(a, \bar{v}, \bar{e}, \rho) :: \kappa \rangle_X, \\
\langle \text{val}(v), \rho', \text{Args}(a, \bar{v}, \bar{e}, \rho) :: \kappa \rangle_X &\longrightarrow \langle \text{collect}(a; \bar{v} \cdot [v]; \bar{e}), \rho, \kappa \rangle_X.
\end{aligned}$$

A class-target Args frame rejects each nonclass or metaclass result before advancing to the next target. Other argument lists retain values without executing their contents. These rules evaluate receivers/arguments once, left-to-right.

A.2.2. Local scope and sequencing

For $\text{let}(\bar{b}; e)$, allocate fresh a and $\sigma' = \sigma[a \mapsto \text{Act}(U, \rho, v, o, h)]$, where (v, o, h) are copied from ρ and $U = \{x \mapsto u \mid (x \leftarrow e_x) \in \bar{b}\}$. All local names are reserved before the first initializer; duplicate names fail.

$$\begin{aligned}
\langle \text{let}(\bar{b}; e), \rho, \kappa \rangle_X &\longrightarrow \langle \text{steps}(\bar{b}; e), a, \text{Restore}(\rho) :: \kappa \rangle_{X[\sigma := \sigma']}, \\
\langle \text{steps}([]; e), \rho, \kappa \rangle_X &\longrightarrow \langle e, \rho, \kappa \rangle_X, \\
\langle \text{steps}((x \leftarrow e_0) :: \bar{b}; e), \rho, \kappa \rangle_X &\longrightarrow \langle e_0, \rho, \text{Bind}(x, \bar{b}, e, \rho) :: \kappa \rangle_X, \\
\langle \text{val}(v), \rho', \text{Bind}(x, \bar{b}, e, \rho) :: \kappa \rangle_X &\longrightarrow \langle \text{steps}(\bar{b}; e), \rho, \kappa \rangle_{X[\sigma(\rho).U(x) := v]}, \\
\langle \text{val}(v), \rho', \text{Restore}(\rho) :: \kappa \rangle_X &\longrightarrow \langle \text{val}(v), \rho, \kappa \rangle_X.
\end{aligned}$$

For $x = _$ the Bind rule discards the value and leaves storage unchanged. Source assignment remains a setter send. Empty bodies and missing initializers lower to the internal null form. Sequencing is a let with discard steps, not an additional binding discipline.

A.3. Selection

This section is the formal counterpart of [message selection](#) and [lexical lookup](#).

$$\begin{aligned}
\text{lin}(\text{Top}) &= [], \quad L_{\text{Top}} = \emptyset, \\
\text{lin}(C) &= [(C, 0, \mu_C)] \cdot \bar{o}_C \cdot \text{lin}(S_C), \\
\mathcal{R} &= \{\perp\} \cup \{!\epsilon \mid \epsilon \in \text{Error}\} \cup \text{Plan}, \\
p &::= t \mid \text{memberApply}(g, k), \\
t &::= \text{get}(v, p_s) \mid \text{set}(v, p_s) \\
&\quad \mid \text{method}(v, o, \bar{x}, e) \mid \text{lambda}(w) \\
&\quad \mid \text{memberGet}(v, o, d) \mid \text{foreignOp}(\phi, op).
\end{aligned}$$

$\perp$ is a miss and $!\epsilon$ is an error. A plan is committed behavior. $T_{v,o}(s)$ is the instantiated declaration table at occurrence o : explicit methods override generated accessors at the

same selector. Slot targets contain $p_s = L_{\text{class}(v)}(o, j)$; activation targets contain their local slot. Generated getters are `get` and `memberGet`. A lambda has intrinsic `apply/k` at its declared arity; other selectors use its native Lambda/Object hierarchy. Scalar tables are parameter **S**.

The recursive equation for $\text{lin}(C)$ applies only to realized class records. The empty base contributes no occurrence or slot mapping. Reaching it therefore uses the empty-list miss rules below for both exact and invocation search, including an exhausted super suffix; Top itself is never a receiver.

A.3.1. Exact and invocation lookup

Exact search over an ordered contribution list is:

$$\begin{aligned} E(v, [], s) &= \perp, \\ E(v, o :: L, s) &= \begin{cases} T_{v,o}(s) & T_{v,o}(s) \neq \perp, \\ E(v, L, s) & T_{v,o}(s) = \perp. \end{cases} \end{aligned}$$

For an Alien, $E(v, s)$ instead uses effect-free adapter selection $B \vdash \phi.s \Downarrow R$, translating a selected operation to `foreignOp( $\phi$ , op)` and retaining miss/error. No foreign getter is speculatively invoked. For native v , $E(v, s)$ starts at its complete hierarchy; an activation uses only its own accessor table. Write L_v for the receiver's search list: $\text{lin}(\text{class}(v))$ for native objects, including lambdas for non-apply selectors, and one accessor table for an activation. Lambda `apply/k` selects its intrinsic operation only at the declared arity; invocation retains the captures in the lambda rule below. Intrinsic `apply` has no invented method/contribution origin; inherited Object methods use their normal origin and the lambda object as receiver.

Exact callable eligibility excludes generated getters. Compute $E(v, (\text{apply}, k))$ once and match its retained outcome against these cases:

$$P(v, k) = \begin{cases} t & E(v, (\text{apply}, k)) = t \text{ and } t \text{ is not a generated getter,} \\ !\epsilon & E(v, (\text{apply}, k)) = !\epsilon, \\ \perp & \text{otherwise.} \end{cases}$$

Let η retain successful accessor evidence for this invocation. The following ordered equations define generated-accessor eligibility A ; in the member row, $g = \text{memberGet}(v, o, d)$:

$$\begin{aligned} A(g, k, \eta) &= \eta(g, k) && \text{if defined,} \\ A(\text{get}(v, p_s), k, \eta) &= \begin{cases} !\text{Uninitialized} & \sigma(v).S[p_s] = u, \\ P(w, k) & \sigma(v).S[p_s] = w, \end{cases} \\ A(g, k, \eta) &= \text{memberApply}(g, k) && g \text{ a member, } k \in \text{arities}(d), \\ A(g, k, \eta) &= \perp && \text{otherwise.} \end{aligned}$$

Here storage notation includes activation slots. $\text{arities}(d)$ contains the selected member declaration's constructor arity and owned `apply` factory arities; it neither consults the realization cache nor imports contributor factories.

Invocation search $I(v, L, n, k, b, \eta)$ carries the getter-masking bit b . In these rules set $t = T_{v,o}(n, k)$, $g = T_{v,o}(n, 0)$:

$$\begin{array}{c}
 I(v, [], n, k, b, \eta) = \perp, \\
 \frac{t \neq \perp \quad t \text{ not a generated getter}}{I(v, o :: L, n, k, b, \eta) = t}, \\
 \frac{t = \perp \text{ or generated} \quad \neg b \quad g \neq \perp \quad A(g, k, \eta) = R \neq \perp}{I(v, o :: L, n, k, b, \eta) = R}, \\
 \frac{t = \perp \text{ or generated} \quad b \vee g = \perp \vee A(g, k, \eta) = \perp}{I(v, o :: L, n, k, b, \eta) = I(v, L, n, k, b \vee (g \neq \perp), \eta)}.
 \end{array}$$

For each occurrence, compute the unmasked $A(g, k, \eta)$ at most once and match its retained outcome across the alternatives. Premises short-circuit left-to-right: never read a masked getter. All searches start with $b = \text{false}$. An ordinary `n/0` method masks older getters without being executed to discover `apply/k`. A nearer eligible accessor can precede a farther exact method. Errors terminate selection.

A.3.2. Lexical receiver selection

For each scope ρ_i , let D_i be its own declaration table and v_i its associated receiver: the activation itself or the receiver of a View. Define the eligibility judgment $\rho_i \vdash (n, k, \iota) \Downarrow R_i$ by this ordered table. $\checkmark(v_i, \eta)$ selects a receiver and evidence.

Condition	Eligibility result
exact, $D_i(n, k) \neq \perp$	$\checkmark(v_i, \emptyset)$
invoke, $D_i(n, k)$ exists and is not a generated getter	$\checkmark(v_i, \emptyset)$
invoke, $D_i(n, 0) \neq \perp$, $g = E(v_i, (n, 0))$ is an ordinary method, $k = 0$	$\checkmark(v_i, \emptyset)$
invoke, $D_i(n, 0) \neq \perp$, $g = E(v_i, (n, 0))$, $A(g, k, \emptyset) = p$	$\checkmark(v_i, \{(g, k) \mapsto p\})$
An evaluated selection premise yields $!\epsilon$	$!\epsilon$
Otherwise	$\perp$

Walk lexical parents until the first nonmiss. On $\checkmark(v_i, \eta)$, dispatch the **original** selector/mode on v_i ; do not execute the declaring operation directly. Invocation uses $I(v_i, L_{v_i}, n, k, \text{false}, \eta)$. Exhausting the lexical chain starts the same search on current `self`, or misses if no receiver exists. A final dispatch error/miss never resumes lexical search. Eligibility is thus established before an override can replace the eligible accessor route.

Explicit native sends start at the full receiver hierarchy. `super(v, o)` starts strictly after the **executing occurrence** o , with fresh getter masking. The suffix is determined by occurrence identity, not by contribution equality. Explicit Aliens use adapter selection in either mode. Invalid native origins fail; foreign spellings `self`, `outer`, and `super` remain foreign selectors. Write $r \vdash (n, k, \iota) \Downarrow R$ for this complete selection judgment.

$$\frac{r \vdash (n, |\bar{v}|, \iota) \Downarrow p}{\langle \text{send}(r, n, \bar{v}, \iota), \rho, \kappa \rangle_X \longrightarrow \langle \text{call}(p, \bar{v}), \rho, \kappa \rangle_X},$$

$$\frac{r \vdash (n, |\bar{v}|, \iota) \Downarrow \perp}{\langle \text{send}(r, n, \bar{v}, \iota), \rho, \kappa \rangle_X \longrightarrow \langle \text{error}(\text{MissingSelector}), \rho, \kappa \rangle_X}.$$

A selected $!e$ similarly enters $\text{error}(\epsilon)$. Eligibility evidence retains the callable target itself, including a selected foreign operation; call never rereads its getter or repeats adapter selection.

A.4. Calls and generated accessors

$$\begin{aligned} \langle \text{call}(\text{get}(v, p_s), []), \rho, \kappa \rangle_X &\longrightarrow \langle \text{val}(\sigma(v).S[p_s]), \rho, \kappa \rangle_X, \\ \langle \text{call}(\text{set}(v, p_s), [w]), \rho, \kappa \rangle_X &\longrightarrow \langle \text{val}(w), \rho, \kappa \rangle_{X[\sigma(v).S[p_s] := w]}, \\ \langle \text{call}(\text{method}(v, o, \bar{x}, e), \bar{v}), \rho, \kappa \rangle_X &\longrightarrow \langle \text{enter}(v, o, \bar{x}, \bar{v}, e, \text{method}), \rho, \kappa \rangle_X. \end{aligned}$$

The getter requires a value other than u ; otherwise it enters $\text{error}(\text{Uninitialized})$. Setters exist only for writable declarations. For enter , arity must match. Allocate fresh a, ℓ, h :

$$\begin{aligned} \sigma' &= \sigma[\ell \mapsto \text{View}(v, o, \mu_o.\rho_d), a \mapsto \text{Act}(\bar{x} \mapsto \bar{v}, \ell, v, o, h)], \\ H' &= H[h \mapsto \begin{cases} \text{method} & \chi = \text{method}, \\ \text{slots} & \chi = \text{initializer}. \end{cases}] \\ \langle \text{enter}(v, o, \bar{x}, \bar{v}, e, \chi), \rho, \kappa \rangle_X &\longrightarrow \langle e, a, \text{Done}(h, v, \chi, \rho) :: \kappa \rangle_{X[\sigma := \sigma', H := H']}. \end{aligned}$$

A method's definition scope is the selected contribution's scope, never its receiver's own constructor activation. For a lambda, no fresh home is created:

$$\frac{\sigma(w) = \Lambda(\bar{x}, e, \rho_d, v, o, h) \quad |\bar{x}| = |\bar{v}| \quad a \text{ fresh} \quad \sigma' = \sigma[a \mapsto \text{Act}(\bar{x} \mapsto \bar{v}, \rho_d, v, o, h)]}{\langle \text{call}(\text{lambda}(w), \bar{v}), \rho, \kappa \rangle_X \longrightarrow \langle e, a, \text{Restore}(\rho) :: \kappa \rangle_{X[\sigma := \sigma']}}$$

Arity errors in a committed call are failures, not new lookup misses.

A.5. Class realization and construction

A.5.1. Definition, occurrences and layout

A descriptor's target list is $\bar{e}_d = [e_{A_1}, \dots, e_{A_m}, e_S]$: direct mixins left-to-right, then an explicit superclass target. Omit e_S for implicit Object . Terminal constructor arguments remain in $d.R$.

$$\langle \text{class}(d), \rho, \kappa \rangle_X \longrightarrow \langle \text{collect}(\text{realize}(d, \rho, \square); []; \bar{e}_d), \rho, \kappa \rangle_X.$$

Given validated target classes $A_1, \dots, A_m, S$, allocate fresh C, M . Let μ_C be d 's owned instance contribution capturing $\rho_d, o_i = (C, i, \mu_{A_i})$, and $o_0 = (C, 0, \mu_C)$. The store extension is:

$$\begin{aligned}\sigma(C) &= \text{Class}(\mu_C, [o_1, \dots, o_m], S, R_C, L_C, M), \\ \sigma(M) &= \text{Meta}(\mu_C^{\text{class}}, [], \text{Class}, [], L_M, \text{Metaclass}), \\ L_C(o, j) &= L_C(o', j') \iff \text{name}(o, j) = \text{name}(o', j').\end{aligned}$$

L_C numbers distinct slot names in first-occurrence order through $\text{lin}(C)$, retaining a mapping for every logical slot. All inherited occurrences keep their original applying class. The class-side contribution contains only owned factories and generated new/default apply. With this extension σ' :

$$\langle \text{realize}(d, \rho_d, [A_1, \dots, A_m, S]), \rho, \kappa \rangle_X \longrightarrow \langle \text{val}(C), \rho, \kappa \rangle_{X[\sigma := \sigma']}.$$

For implicit `Object`, insert that structural root without a source lookup. Declaration validity, reserved new, flat root seeding and factory signatures are the static constraints of [Objects and Classes](#). For realized ordinary classes C , including `Object`, `Class`, `Metaclass` and the shared `Lambda` class (not the semantic terminal `Top`):

$$\begin{aligned}\text{super}(\text{Object}) &= \text{Top}, & \text{super}(\text{Class}) &= \text{Object}, \\ \text{super}(\text{Metaclass}) &= \text{Class}, & \text{super}(\text{Lambda}) &= \text{Object}, \\ \text{class}(C) &= M_C, & \text{super}(M_C) &= \text{Class}, & \text{class}(M_C) &= \text{Metaclass}.\end{aligned}$$

`Lambda` values have class `Lambda` while retaining the record's lexical captures. `Lambda`'s class has no public factories. Applications reuse the selected owned contribution's identity; membership observations compare that identity with the supplied class's owned contribution. `IdentityMirror` is an ordinary foreign capability governed by the [observation contract](#); it adds no privileged machine transition.

A.5.2. Member-class cache

For $g = \text{memberGet}(v, o, d)$, the cache key is $k_g = (v, o, d.D)$, with $\Gamma(k_g) \in \{\perp, \text{busy}, \text{ready}(C), \text{failed}(\epsilon)\}$. Γ abbreviates the enclosing object's private cache in σ .

$$\begin{aligned}\langle \text{call}(g, []), \rho, \kappa \rangle_X &\longrightarrow \langle \text{member}(g), \rho, \kappa \rangle_X, \\ \langle \text{call}(\text{memberApply}(g, k), \bar{v}), \rho, \kappa \rangle_X &\longrightarrow \langle \text{member}(g), \rho, \text{Apply}(\bar{v}, \rho) :: \kappa \rangle_X.\end{aligned}$$

$$\frac{\Gamma(k_g) = \text{ready}(C)}{\langle \text{member}(g) \rangle_X \longrightarrow \langle \text{val}(C) \rangle_X}.$$

For an absent entry, allocate fresh ℓ with $\sigma(\ell) = \text{View}(v, o, \mu_o \cdot \rho_d)$, and set $\Gamma(k_g) = \text{busy}$:

$$\langle \text{member}(g), \rho, \kappa \rangle_X \longrightarrow \langle \text{class}(d), \ell, \text{Cache}(k_g, \rho) :: \kappa \rangle_{X'}.$$

$$\begin{aligned}
\langle \text{val}(C), \rho', \text{Cache}(k_g, \rho) :: \kappa \rangle_X &\longrightarrow \langle \text{val}(C), \rho, \kappa \rangle_{X[\Gamma(k_g) := \text{ready}(C)]}, \\
\langle \text{val}(C), \rho', \text{Apply}(\bar{v}, \rho) :: \kappa \rangle_X &\longrightarrow \langle \text{call}(t, \bar{v}), \rho, \kappa \rangle_X \quad P(C, |\bar{v}|) = t.
\end{aligned}$$

busy raises *CyclicRealization*; failed(ϵ) raises that error without retry. Apply commits to the realized class's exact callable operation: miss/error fails, never resumes outer lookup. A member that loses virtual dispatch or fails arity eligibility never enters these cache rules.

A.5.3. Generated constructor code

Let $\tau = \text{whole}(C)$ select the complete coordinator and $\tau = \text{owned}(o)$ select one owned contribution. With $;$ denoting the already-defined discard sequencing:

$$\begin{aligned}
I_\mu &= \text{write}(0, e_0); \dots; \text{write}(r-1, e_{r-1}); \text{slotsDone}; e_b, \\
\text{superRoute}(\text{Top}, []) &= [], \\
\text{superRoute}(S, \bar{a}_S) &= [(\text{whole}(S), \bar{a}_S)] \quad (S \in A_{\text{cls}}), \\
R_C &= \text{superRoute}(S, \bar{a}_S) \cdot [(\text{owned}(o_m), \bar{a}_m), \dots, (\text{owned}(o_1), \bar{a}_1)], \\
R_C &= [(\tau_1, \bar{\beta}_1), \dots, (\tau_q, \bar{\beta}_q)], \\
I_C &= \text{init}(\tau_1; \text{self}, \bar{\beta}_1); \dots; \text{init}(\tau_q; \text{self}, \bar{\beta}_q); I_{\mu_C}, \\
\text{new}_C(\bar{x}) &= \text{let}(z \leftarrow \text{alloc}(C), _ \leftarrow \text{init}(\text{whole}(C); z, \bar{x}); z), \\
\text{apply}_C(\bar{x}) &= \text{explicit}(\text{self}).\text{new}(\bar{x})_{\text{exact}}.
\end{aligned}$$

Names $z, \bar{x}$ in generated code denote exact accessor sends; z is fresh. An owned apply/ k replaces the generated default at that arity. Object has no direct applications and its superclass is Top, so its dependency list is empty by superRoute. Its owned initializer is also empty; an empty implicit Object call may be omitted. No route targets Top and no initializer activation, return home or effects are created for it. The base equation admits no arguments; there is no whole(Top) routine. A direct mixin imports neither its source class's routes nor its other contributors. Source factories otherwise use ordinary method calls.

$$\begin{aligned}
\langle \text{alloc}(C), \rho, \kappa \rangle_X &\longrightarrow \langle \text{val}(v), \rho, \kappa \rangle_{X[\sigma(v) := \text{Obj}(C, u^{\lim L_C}, \mu_C \cdot \rho_d, \emptyset)]}, \\
\langle \text{init}(\tau; e_r, \bar{e}), \rho, \kappa \rangle_X &\longrightarrow \langle \text{collect}(\text{initEntry}(\tau, \square); []; e_r :: \bar{e}), \rho, \kappa \rangle_X, \\
\langle \text{initEntry}(\tau, v :: \bar{v}), \rho, \kappa \rangle_X &\longrightarrow \langle \text{enter}(v, o, \mu_o \cdot \bar{x}, \bar{v}, I_\tau, \text{initializer}), \rho, \kappa \rangle_X.
\end{aligned}$$

Allocation requires a realized constructible C and fresh v . For whole(C), $o = o_0$, $I_\tau = I_C$; for owned(o), $I_\tau = I_{\mu_o}$. The coordinator's route expressions and owned body share this single home; each nested dependency call gets its own. An object literal realizes its anonymous class and sends ordinary exact new/ $\emptyset$:

$$\langle \text{object}(d), \rho, \kappa \rangle_X \longrightarrow \langle \text{explicit}(\text{class}(d)).\text{new}([])_{\text{exact}}, \rho, \kappa \rangle_X.$$

The ordinary receiver rule evaluates the class expression exactly once before dispatch. Its target expressions run in ρ ; routed arguments run in the fresh declaring initializer

home after allocation. The resulting class and receiver are fresh on every evaluation. This introduces no additional private operation or object-specific continuation, and does not call `apply` or any contributor factory.

For a live current initializer home h with $H(h) = \text{slots}$, set $v = \sigma(\rho).v$, $o = \sigma(\rho).o$, and $p_s = L_{\text{class}(v)}(o, j)$ **before** evaluating the value expression:

$$\begin{aligned} \langle \text{write}(j, e), \rho, \kappa \rangle_X &\longrightarrow \langle e, \rho, \text{Write}(v, p_s, \rho) :: \kappa \rangle_X, \\ \langle \text{val}(w), \rho', \text{Write}(v, p_s, \rho) :: \kappa \rangle_X &\longrightarrow \langle \text{val}(w), \rho, \kappa \rangle_{X[\sigma(v).S[p_s] := w]}, \\ \langle \text{slotsDone}, \rho, \kappa \rangle_X &\longrightarrow \langle \text{val}(v), \rho, \kappa \rangle_{X[H(h) := \text{body}]}. \end{aligned}$$

Invalid private targets, arities or phases raise errors. No selector or Expat operation can name these controls.

A.6. Completion, return and failure

The rules below model the default boundary agreement, which prohibits non-local returns across foreign execution. Whether to support crossing belongs to the [boundary agreement](#), not a universal native-language prohibition. A supporting agreement requires additional transfer rules; none are defined or implemented here. Lexical return targets, home liveness and initializer phase restrictions remain native rules.

$$\frac{(\chi, H(h), v') \in \{(\text{method}, \text{method}, w), (\text{initializer}, \text{body}, v)\}}{\langle \text{val}(w), \rho', \text{Done}(h, v, \chi, \rho) :: \kappa \rangle_X \longrightarrow \langle \text{val}(v'), \rho, \kappa \rangle_{X[H(h) := \text{dead}]}.$$

An initializer finishing in `slots` raises `PrematureCompletion`. A source return first evaluates its operand, capturing $h = \sigma(\rho).h$:

$$\begin{aligned} \langle \text{ret}(e), \rho, \kappa \rangle_X &\longrightarrow \langle e, \rho, \text{Return}(h) :: \kappa \rangle_X, \\ \langle \text{val}(v), \rho, \text{Return}(h) :: \kappa \rangle_X &\longrightarrow \langle \text{return}(h, v), \rho, \kappa \rangle_X. \end{aligned}$$

Let $\kappa = P \cdot [\text{Done}(h, w, \chi, \rho_c)] \cdot \kappa_c$, with no `Barrier` in P . Successful delivery requires $H(h) = \text{method}$ or $H(h) = \text{body}$, according to χ . Let X' retire all homes in that prefix through the target and mark its pending Cache frames failed with `AbandonedRealization`:

$$\frac{\kappa = P \cdot [\text{Done}(h, w, \chi, \rho_c)] \cdot \kappa_c \quad v' = \begin{cases} v & \chi = \text{method}, \\ w & \chi = \text{initializer} \end{cases}}{\langle \text{return}(h, v), \rho, \kappa \rangle_X \longrightarrow \langle \text{val}(v'), \rho_c, \kappa_c \rangle_{X'}}.$$

Failure cases for this default agreement, checked before any successful-unwind mutation, are:

Condition	Error
Missing or dead captured home	<code>DeadContext</code>
Live target lies below the first barrier (default no-crossing agreement)	<code>ForeignReturn</code>

Condition	Error
No matching completion frame	DeadContext
Reachable target still has $H(h) = \text{slots}$	PrematureCompletion

Only completion of the target contribution is skipped; its caller's subsequent contributions continue. A lambda's captured home is never dynamically rebound.

$$\langle \text{error}(\epsilon), \rho, \kappa \rangle_X \longrightarrow \langle \text{abort}(\epsilon), \rho, \kappa \rangle_X.$$

For an ordinary frame f (not `Barrier`), obtain X_f by retiring its home if it is `Done`, or caching `failed`(ϵ) if it is `Cache`; otherwise $X_f = \bar{X}$:

$$\langle \text{abort}(\epsilon), \rho, f :: \kappa \rangle_X \longrightarrow \langle \text{abort}(\epsilon), \rho, \kappa \rangle_{X_f}.$$

There is no rollback, lookup retry, or revival of a retired home. Aborting a callback retires only frames above its barrier; the suspended caller remains live. Cache failure caused by a successful return does not abort that return.

A.7. Alien/Expat transitions

The adapter state **B** includes call association and admission lifetime. The Java realization may obtain a callback from the operation thread or from a worker holding an explicit call context; admission serializes their native transitions. Each admitted callback belongs to the current foreign invocation, retains its suspended caller and budget, and creates the barrier below. Closing a foreign invocation disallows further callback actions for it and joins admitted descendants before delivering `done` or `fail`. Host requests rejected before admission do not create a native callback continuation. These rules describe the serialized native interaction; they do not formalize arbitrary parallel foreign actions, host waiting queues or a general scheduler.

These transitions use the default no-crossing agreement: callback entry installs `Barrier`, and the foreign action relation has no non-local-return transfer action. A future supporting boundary must define that transfer and its observable interaction with foreign execution; merely removing `Barrier` is insufficient.

The adapter provides stateful, identity-preserving conversions $B, \sigma \vdash \bar{v} \uparrow (\bar{f}, B')$ and $B, \sigma \vdash \bar{f} \downarrow (\bar{v}, \sigma', B')$, or failure with the state reached before failure. Lists convert left-to-right. Exact canonical null/Booleans convert by identity; scalars follow **S**. Compatible identity round trips satisfy $\downarrow \uparrow v = v$ and $\uparrow \downarrow \phi = \phi$. These are boundary obligations, not privileged native service operations.

$$\frac{B, \sigma \vdash \bar{v} \uparrow (\bar{f}, B')}{\langle \text{call}(\text{foreignOp}(\phi, op), \bar{v}), \rho, \kappa \rangle_X \longrightarrow \langle \text{foreign}(op(\phi, \bar{f})), \rho, \kappa \rangle_{X[B:=B']}}.$$

The foreign interaction-state relation $B \vdash \omega \rightsquigarrow (a, B')$ has actions $a ::= \text{done}(f) \mid \text{fail}(\epsilon) \mid \text{next}(\omega') \mid \text{send}(v, n, \bar{f}, \omega')$. It may block or diverge; it need not be deterministic. The state ω records foreign behavior and resumption; it is not the unique control token. Several suspended barriers can retain distinct foreign interaction states. Actions `done` and

`fail` below mean completion delivery after the admission condition above is satisfied, not the physical arrival of an answer from a foreign worker. Its completion rules are:

$$\frac{B \vdash \omega \rightsquigarrow (\text{next}(\omega'), B')}{\langle \text{foreign}(\omega), \rho, \kappa \rangle_X \longrightarrow \langle \text{foreign}(\omega'), \rho, \kappa \rangle_{X[B:=B']}},$$

$$\frac{B \vdash \omega \rightsquigarrow (\text{done}(f), B_1) \quad B_1, \sigma \vdash f \Downarrow (v, \sigma', B_2)}{\langle \text{foreign}(\omega), \rho, \kappa \rangle_X \longrightarrow \langle \text{val}(v), \rho, \kappa \rangle_{X[\sigma:=\sigma', B:=B_2]}},$$

$$\frac{B \vdash \omega \rightsquigarrow (\text{fail}(\epsilon), B')}{\langle \text{foreign}(\omega), \rho, \kappa \rangle_X \longrightarrow \langle \text{error}(\epsilon), \rho, \kappa \rangle_{X[B:=B']}}.$$

For callback action $\text{send}(v, n, fs, \omega')$, allocate an empty activation a with no parent, receiver or home:

$$\frac{\langle \text{foreign}(\omega), \rho, \kappa \rangle_X \longrightarrow \langle \text{callback}(v, n, \bar{f}), a, \text{Barrier}(\omega', \rho) :: \kappa \rangle_{X'}, \quad B, \sigma \vdash \bar{f} \Downarrow (\bar{v}, \sigma', B')}{\langle \text{callback}(v, n, \bar{f}), a, \kappa \rangle_X \longrightarrow \langle \text{send}(\text{rcv}(v), n, \bar{v}, \text{exact}), a, \kappa \rangle_{X[\sigma:=\sigma', B:=B']}}.$$

Here X' includes the adapter step and fresh activation. Installing the barrier before import gives conversion failure the same failure path as the callback body. A previously handled failure does not prevent a new callback.

$$\frac{B, \sigma \vdash v \Uparrow (f, B')}{\langle \text{val}(v), \rho', \text{Barrier}(\omega, \rho) :: \kappa \rangle_X \longrightarrow \langle \text{foreign}(\omega[\text{result}(f)]), \rho, \kappa \rangle_{X[B:=B']}},$$

$$\langle \text{abort}(\epsilon), \rho', \text{Barrier}(\omega, \rho) :: \kappa \rangle_X \longrightarrow \langle \text{foreign}(\omega[\text{failure}(\epsilon)]), \rho, \kappa \rangle_X.$$

Export failure enters error with the barrier still present. The failed callback reports its diagnostic to the foreign continuation. Foreign code can handle it, make another callback and complete normally, or propagate a failure. The outer native caller observes that foreign completion after conversion; no shared fatal marker overrides it. Native mutations and callback-home retirement survive reentry, while suspended caller homes remain live until their own completion or failure. This does not resume the aborted callback or permit NLR crossing.

A.7.1. Conversion failures

Import failure has form $!(\epsilon, \sigma', B')$; export failure has form $!(\epsilon, B')$, with unchanged native store. At each site the reached state is retained:

$$\begin{array}{c}
\frac{B, \sigma \vdash l \Downarrow!(\epsilon, \sigma', B')}{\langle l \rangle_X \longrightarrow \langle \text{error}(\epsilon) \rangle_{X[\sigma:=\sigma', B:=B']}}, \\
\frac{B, \sigma \vdash \bar{v} \Uparrow!(\epsilon, B')}{\langle \text{call}(\text{foreignOp}(\phi, op), \bar{v}) \rangle_X \longrightarrow \langle \text{error}(\epsilon) \rangle_{X[B:=B']}}, \\
\frac{B, \sigma \vdash \bar{f} \Downarrow!(\epsilon, \sigma', B')}{\langle \text{callback}(v, n, \bar{f}) \rangle_X \longrightarrow \langle \text{error}(\epsilon) \rangle_{X[\sigma:=\sigma', B:=B']}}, \\
\frac{B \vdash \omega \rightsquigarrow (\text{done}(f), B_1) \quad B_1, \sigma \vdash f \Downarrow!(\epsilon, \sigma', B_2)}{\langle \text{foreign}(\omega) \rangle_X \longrightarrow \langle \text{error}(\epsilon) \rangle_{X[\sigma:=\sigma', B:=B_2]}}. \\
\frac{B, \sigma \vdash v \Uparrow!(\epsilon, B')}{\langle \text{val}(v), \rho', \text{Barrier}(\omega, \rho) :: \kappa \rangle_X} \\
\longrightarrow \langle \text{error}(\epsilon), \rho', \text{Barrier}(\omega, \rho) :: \kappa \rangle_{X[B:=B']}.
\end{array}$$

A.8. Entry, observations and remaining parameters

Normal module definition starts at an empty top activation, with structural superclass `Object` and no mixins; forbidden top-level contributor clauses fail before evaluation. Instantiation supplies existing argument values to exact `new/k`, without capturing the service's scope. Tools may explicitly supply a different starting activation. See [module entry](#). Independent entry requires successful runtime admission from `idle` under the control agreement above. Construction of an entry configuration does not itself grant execution authority. For a valid module descriptor d , d 's arity must equal $|\bar{v}|$. Allocate fresh a with $\sigma' = \sigma[a \mapsto \text{Act}(\emptyset, \perp, \perp, \perp, \perp)]$:

$$\begin{aligned}
& \text{module}(d, \bar{v}; X) \rightsquigarrow \langle \text{class}(d), a, \text{Module}(\bar{v}) :: \text{halt} \rangle_{X[\sigma:=\sigma']}, \\
& \langle \text{val}(C), a, \text{Module}(\bar{v}) :: \text{halt} \rangle_X \longrightarrow \langle \text{send}(\text{recv}(C), \text{new}, \bar{v}, \text{exact}), a, \text{halt} \rangle_X, \\
& \text{tool}(e, \rho; X) \rightsquigarrow \langle e, \rho, \text{halt} \rangle_X.
\end{aligned}$$

These are admitted independent entry points, not source operations. The entry arrow acquires the existing idle token for the new continuation. The same admission premise applies to independent exact `Expat` sends; callbacks instead use the foreign invocation's admission path. A rejected module descriptor has no definition transition; it reports its validation error. Delivery of a `Final` observation returns control to `idle`; retaining the final configuration does not retain execution authority.

$$\text{Final}(K) = \begin{cases} \text{success}(v) & K = \langle \text{val}(v), \rho, \text{halt} \rangle_X, \\ \text{failure}(\epsilon) & K = \langle \text{abort}(\epsilon), \rho, \text{halt} \rangle_X. \end{cases}$$

Parameter / obligation	Boundary of this formalization
S — scalar profile	Numeric domains, overflow and native string/number methods are underdeveloped. The prototype supplies signed-64-bit/string transport, not the full intended scalar protocol.
B — adapter relation	Each adapter must specify effect-free selection, conversion, foreign actions and failure kinds satisfying the boundary contract.
Execution authority	The global sequential admission condition must be refined by every ordinary entry, callback and completion path. Host queues, fairness, parallel execution and intervention relations require additional contracts; token uniqueness does not prohibit concurrent implementation maintenance.
Static validity	Complete surface-to-core elaboration and declaration-validity judgments remain to be mechanized; invalid/unsupported forms must fail, not acquire substitute semantics.
Proofs	Preservation/progress, determinism modulo fresh identities and fixed foreign choices, descriptor erasure, capability confinement, and Java simulation remain obligations.

The intended implementation relation $R(J, K)$ reads the current Java store, decodes addressed frames and suspended callbacks, and preserves origins, homes, caches and active failure controls. It also reconstructs global control ownership from the Java coordinator and suspended calls; a permit object or copied callback context is not individually a control token. In the superclass field of root Object, it decodes Java's absent reference as semantic Top, with no corresponding store identity. Other absent links retain their field-specific meanings. The [terminal representation](#) preserves the empty lookup, layout and construction cases. The relation is restricted to the supported scalar and sequential execution profile, with no unspecified interventions:

$$R(J, K) \wedge J \rightarrow_J J' \implies \exists K'. K \rightarrow^* K' \wedge R(J', K').$$

Administrative stuttering must preserve result/error and boundary traces and must not hide divergence. The concrete choices and limitations are recorded once in [implementation refinement](#).