客户--客户

包类型:需要的信息(挑战者:A;被挑战者:B)

挑战请求(A挑战B):【A->S】【S->B】

```
[opcode=0P_CHALLENGE_RQT]
[flags=0]
[opr_cnt=4]
[id = A-ID]
[id = B-ID]
[name = A-username]
[name = B-username]
```

【A】: "您向B发起了挑战, 等待B响应..."

【S】: "A向B发起了挑战"

【B】: "A向您发起了挑战,是否接受?"

挑战回应(B拒绝A的挑战):【B->S】【S->A】

```
[opcode=0P_CHALLENGE_RPL]
[flags=FLAG_REJECT]
[opr_cnt=2]
[id = A-ID]
[id = B-ID]
```

【A】: "B拒绝了您的挑战"

【S】: "B拒绝了A的挑战"

【B】: "您拒绝了A的挑战"

挑战回应(B接受A的挑战): 【B->S】【S->A】

```
[opcode=0P_CHALLENGE_RPL]
[flags=FLAG_ACCEPT]
[opr_cnt=2]
[id = A-ID]
[id = A-ID]
```

【A】:"B接受了您的挑战,战斗开始"

【S】:"B接受了A的挑战,AB对战开始"

【B】: "您接受了B的挑战,战斗开始"

战斗输入1(A挑战B, B接受挑战):【A->S】

```
[opcode=0P_BATTLE_INPUT]
[flags=0]
[opr_cnt=2]
[A-ID]
[A-input]
```

【A】: "您输入XXX,等待B的输入"

战斗输入2(A挑战B, B接受挑战): 【B->S】

```
[opcode=OP_BATTLE_INPUT]
[flags=0]
[opr_cnt=2]
[B-ID]
[B-input]
```

【S】: "A输入XXX, B输入XXX, 战斗开始"

战斗开始(A挑战B, B接受挑战): 【S->A】【S->B】

```
[opcode= OP_BATTLE_MSG ]
[flags= FLAG_BATTLE_INTRO]
[opr_cnt=4]
[A-ID]
[A-input]
[B-ID]
[B-input]
```

【S】: "A输入XXX, B输入XXX, 战斗开始"

【A】:"您输入XXX, B输入XXX, 战斗开始"

【B】: "A输入XXX, 您输入XXX, 战斗开始"

战斗过程(A挑战B):

```
[opcode= OP_BATTLE_MSG]
[flags= FLAG_BATTLE_EACH]
[opr_cnt=5]
[userid]
[move_name]
[userid]
[move_name]
[userid]
```

winner-id:0-前者贏, 1-平手, 2-后者贏

【S】: "A出XX, B出XX, 结果XX"

【A】:"本局您出XXX,B出XXX,结果XX"

【B】:"本局A出XXX,您出XXX,结果XX"

战斗结束:A的ID&结果、B的ID&结果

[opcode=0P_BATTLE_RESULT]

```
[flags=0]
[opr_cnt=8]
[user_id]
[win]
[lose]
[draw]
[user_id]
[win]
[lose]
```

【S】: "A对战B, A胜X局, B胜Y局, 平Z局, A/B获胜"

【A】:"您挑战B,胜X局,负Y局,平Z局,您赢/输了"

【B】: "A挑战您,胜X局,负Y局,平Z局,您赢/输了"

客户--服务器

包类型:需要的信息(客户:C;服务器:S)

查看当前在线列表:

request

```
[opcode=OP_CURR_USRLST_RQT]
[flags=0]
[opr_cnt=0]
```

reply

查看排行榜

request

```
[opcode=OP_RANKING_RQT]
[flags=0]
[opr_cnt=0]
```

reply

```
[opcode=OP_RANKING_RPL]
[flags=0]
[opr_cnt=number_of_returned_entries]
[[id][username][score][ranking]] <- packed into a struct
    ^ multiple times</pre>
```

注册

request

```
[opcode=OP_REGISTER_RQT]
[flags=0]
[opr_cnt=3]
[C-ID:length = 32]
[C-PWD:len=32]
[C-EM:len=64]
```

reply

success

```
[opcode=0P_REGISTER_RPL]
[flags=FLAG_ACCEPT]
[opr_cnt=1]
[0]
```

failure

```
[opcode=OP_REGISTER_RPL]
[flags=FLAG_REJECT]
[opr_cnt=1]
[ERROR-CODE,refer to error number]
```

登录

request

```
[opcode=0P_LOGIN_RQT]
[flags=0]
[opr_cnt=2]
[C-ID:len=32]
[C-PWD:len=32]
```

reply

success

```
[opcode=0P_L0GIN_RPL]
[flags=FLAG_ACCEPT]
[opr_cnt=1]
[userinfo]
```

failure

```
[opcode=0P_LOGIN_RPL]
[flags=FLAG_REJECT]
[opr_cnt=1]
[ERROR-CODE, refer to error number]
```