

# IMEI Validation V2

---

## CONTENTS

1 Overview .....	3
2 API Contracts.....	3
2.1 IMEI Validation.....	3
2.1.1 Environment .....	3
2.1.2 Request .....	3
2.1.3 Response.....	6
2.1.4 Response codes.....	8

## 1 Overview

This document outlines the IMEI validation API and its parameters. Merchant can integrate this API and real time response from the OEM will be shared back.

## 2 API Contracts

### 2.1 IMEI Validation

#### 2.1.1 Environment

Environment Name	URL	Content-Type
Sandbox	https://uat.pinepg.in:8059/api/v2IMEIValidation/DoIMEIOperation	application/json
Live	https://pinepg.in:8098/api/v2IMEIValidation/DoIMEIOperation	application/json

#### 2.1.2 Request

##### 2.1.2.1 Body Params

Parameter Name	Type	Description	Mandatory(M)/Optional
merchant_data	object	It contains information about merchant.	M
txn_data	object	It contains information about transaction data.	M

product_imei_details	Array of objects	It contains information about products wise imei number.	M
imei_request_type	string	It describe the imei action type. Following are the valid values: BLOCKING UNBLOCKED	M

#### merchant\_data

Parameter Name	Type	Description	Mandatory(M)/Optional
merchant_id	int	Merchant id provided by pine labs	M
merchant_access_code	string	Merchant access code provided by pine labs	M

#### txn\_data

Parameter Name	Type	Description	Mandatory(M)/Optional
pine_pg_txn_id	long	Purchase Pine PG transaction id on which multi-cart EMI transaction had done.	M

#### product\_imei\_details

Parameter Name	Type	Description	Mandatory(M)/Optional
----------------	------	-------------	-----------------------

product_code	string	Product code present at merchant end. It should be one of the product code on which multi-cart EMI transaction had done.	M
imei_no	string	Imei No to be validated	M
state_code	string	Pass the state code provided by OEM	O / M (OPPO/VIVO)
dealer_code	string	Pass the dealer code provided by OEM	O / M (OPPO/VIVO/Motorola/Nothing)
model_number	string	Pass the model number provided by OEM	O / M (OPPO/VIVO/Motorola/Nothing)

- State\_code, dealer\_code, model\_number is MANDATORY for OPPO / VIVO OEM's to perform IMEI validation as well as UNBLOCKING.
- For other OEM's these 3 parameters will be optional.

#### 2.1.2.2 Sample Request

```
{
  "merchant_data": {
    "merchant_id": 3413,
    "merchant_access_code": "1c295f88-4477-4cd3-b5ac-e76148545a3e"
  },
  "txn_data": {
    "pine_pg_txn_id": 360285
  },
  "imei_request_type": "BLOCKING",
  "product_imei_details": [
    {
      "product_code": "786",
      "imei_no": "9090999933332251"
    },
    {
      "product_code": "40",
      "imei_no": "9090999933332252",
      "state_code": "Jammu Kashmir"
    }
  ]
}
```

```

    }
  ]
}

```

### 2.1.3 Response

#### 2.1.3.1 Body Params

Parameter Name	Type	Description	Mandatory(M)/Optional
product_imei_details	Array of objects	It contains the information about each product code wise imei no.	O
response_code	int	It notifies the result of api processing. Value 0 denotes success.	M
response_message	string	It denotes the message corresponding to above code.	M

#### product\_imei\_details

Parameter Name	Type	Description	Mandatory(M)/Optional
product_code	string	Product code passed in request..	O
imei_no	string	Imei No passed in request.	O
state_code	string	State code passed in request.	O
imei_processing_status	object	Processing status .	O

### imei\_processing\_status

Parameter Name	Type	Description	Mandatory(M)/Optional
response_code	int	Response code received from OEM.	M
response_message	string	It denotes the message corresponding to above code	M

#### 2.1.3.2 Sample Response

##### Success Response:

```
{
  "product_imei_details": [
    {
      "product_code": "786",
      "imei_no": "9090999933332251",
      "imei_processing_status": {
        "response_code": 0,
        "response_message": "SUCCESS"
      }
    },
    {
      "product_code": "40",
      "imei_no": "9090999933332252",
      "imei_processing_status": {
        "response_code": 0,
        "response_message": "SUCCESS"
      }
    }
  ]
}
```

```
],  
"response_code": 0,  
"response_message": "SUCCESS"  
}
```

**Failure Response:**

```
{  
"response_code": 107,  
"response_message": "MERCHANT DATA IS NOT VALID"  
}
```

**2.1.4 Response codes**

It contains the list of all response code .

Response Code	Response Message
0	SUCCESS
-1	FAILURE
107	MERCHANT DATA IS NOT VALID
108	IMEI OPERATION IS NOT REQUIRED FOR OEM
109	ONLINE VALIDATION IS NOT ENABLE FOR OEM_GROUP_CODE
110	TRANSACTION IS NOT REFUNDED
111	TRANSACTION IS IN CAPTURED STATE.IT SHOULD BE IN REFUNDED STATE FOR UNBLOCKING
-99	IMEI VALIDATION IN PROGRESS
-100	IMEI IS NOT BLOCKED



-115	ON SOME PRODUCT IMEI OPERATION IS SUCESSFUL
-116	EITHER NO_PRODUCT IS ELEGIBLE FOR IMEI OPERATION OR IMEI OPERATION IS NOT SUCESSFULL FOR ANY PRODUCT
-117	IMEI IS ALREADY BLOCKED ON PRODUCT
-118	IMEI OPERATION REQUEST IN IS NOT VALID
-119	IMEI IS NOT IN BLOCKED STATE.UNABLE TO DO BLOCKING
-120	IMEI OPERATION FAILED BY OEM
-121	PRODUCT NOT ELEGIBLE FOR IMEI OPERATION
-1	INVALID SERIAL NUMBER
-1	SERIAL NUMBER ALREADY VALIDATED
-1	MISMATCH IN MODEL AND SERIAL NUMBER
-1	IMEI DOES NOT EXIST WITH GIVEN DISTRIBUTOR
-1	INVALID DISTRIBUTOR CODE
-1	INVALID SKUCODE