

My Emacs 配置手册（快捷键对齐版）

基于 .emacs.d 源码自动对账（含 init-mini.el / custom.el / init.el / lisp/init-*.el）。

目录

- 全局自定义快捷键
- 模式与插件专属快捷键
- Hydra 入口与内部键
- 常用 Emacs 默认快捷键
- 冲突与覆盖说明
- 源码权威索引（全部自定义键位）

全局自定义快捷键

快捷键	命令	来源
<C-return>	rectangle-mark-mode	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:160
<f12>	agent-shell	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-ai.el:124
<f13>	agent-shell	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-ai.el:125
<f2>	open-dashboard	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dashboard
<f5>	dape	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dap.el:38
<f5>	revert-current-buffer	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:169
<f6>	toggles-hydra/body	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-hydra.el:1
<f7>	olivetti-mode	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-utils.el:1
[(super a)]	mark-whole-buffer	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:151
[(super c)]	kill-ring-save	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:153
[(super l)]	goto-line	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:155
[(super s)]	save-buffer	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:154
[(super v)]	yank	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:152
[(super w)]	delete-frame	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:156
[(super z)]	undo	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:157
[remap describe-bindings]	embark-bindings	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
[remap describe-command]	helpful-command	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-elisp.el:1
[remap describe-function]	helpful-callable	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-elisp.el:1
[remap describe-key]	helpful-key	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-elisp.el:1
[remap describe-symbol]	helpful-symbol	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-elisp.el:1
[remap describe-variable]	helpful-variable	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-elisp.el:1
[remap Info-search]	consult-info	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
[remap isearch-forward]	consult-line	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
[remap kill-ring-save]	easy-kill	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-kill-ring
[remap mark-sexp]	easy-mark	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-kill-ring

快捷键	命令	来源
[remap move-beginning-of-line]	mwim-beginning	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:3:
[remap move-end-of-line]	mwim-end	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:3:
[remap other-window]	ace-window	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-window.el
[remap query-replace-regexp]	anzu-query-replace-regexp	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:1:
[remap query-replace]	anzu-query-replace	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:1:
[remap recentf-open-files]	consult-recent-file	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
C-'	avy-goto-char-2	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:1:
C-,	goto-last-change	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:3:
C-.	consult-imenu	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
C-:	avy-goto-char	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:1:
C-;	iedit-mode	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2:
C-<	mc/mark-previous-like-this	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2:
C-<f12>	gptel	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-ai.el:68
C-<f5>	quickrun	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-prog.el:1:
C-<f8>	bongo	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-player.el
C-=	er/expand-region	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2:
C->	mc/mark-next-like-this	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2:
C-c /	webjump	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-utils.el::
C-c 1	my-maximize-buffer	/Users/bytedance/Desktop/dotfiles/.emacs.d/custom.el:144
C-c a	agent-shell	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-ai.el:126
C-c A	agent-shell-new-shell	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-ai.el:127
C-c a	org-agenda	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:78
C-c b	org-switchb	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:79
C-c c e	consult-colors-emacs	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
C-c c f	describe-face	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
C-c c g	git-link-dispatch	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-vcs.el:22:
C-c c i	file-info-show	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-utils.el::
C-c c l	find-library	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
C-c c t	consult-theme	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
C-c c w	consult-colors-web	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
C-c C-<	mc/mark-all-like-this	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2:
C-c C-z .	browse-url-at-point	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:8:
C-c C-z b	browse-url-of-buffer	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:9:
C-c C-z e	browse-url-emacs	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:9:
C-c C-z r	browse-url-of-region	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:9:
C-c C-z u	browse-url	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:9:
C-c C-z v	browse-url-of-file	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:9:

快捷键	命令	来源
C-c C-z w	xwidget-webkit-browse-url	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-web.el:47
C-c D	docker	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-docker.el
C-c d d	fanyi-dwim2	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:39
C-c d f	fanyi-dwim	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:39
C-c d g	gt-translate	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:40
C-c d G	gt-translate-prompt	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:41
C-c d h	fanyi-from-history	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:40
C-c d i	osx-dictionary-search-input	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:11
C-c d p	gt-speak	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:40
C-c d s	gt-setup	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:40
C-c d u	gt-use-text-utility	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:50
C-c d x	osx-dictionary-search-pointer	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:11
C-c f	flymake-show-buffer-diagnostics	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-check.el:1
C-c g	gt-translate	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:40
C-c G	gt-translate-prompt	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:40
C-c h	consult-history	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
C-c i	consult-info	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
C-c k	browse-kill-ring	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-kill-ring
C-c k	consult-kmacro	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
C-c l c	link-hint-copy-link	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:11
C-c l o	link-hint-open-link	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:11
C-c m	multiple-cursors-hydra/body	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:20
C-c M-x	consult-mode-command	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
C-c n c	org-roam-capture	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:29
C-c n f	org-roam-node-find	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:29
C-c n g	org-roam-graph	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:29
C-c n i	org-roam-node-insert	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:29
C-c n j	org-roam-dailies-capture-today	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:30
C-c n l	org-roam-buffer-toggle	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:29
C-c n u	org-roam-ui-mode	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:31
C-c r	consult-ripgrep	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
C-c T	consult-theme	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion
C-c u	gt-use-text-utility	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:40
C-c u	lsp-ui-imenu	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-lsp.el:22
C-c w	ace-window-hydra/body	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-window.el
C-c x	org-capture	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:80
C-c X	quickrun	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-prog.el:10

快捷键	命令	来源
C-h M-m	which-key-show-major-mode	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-utils.el:2
C-M-#	consult-register	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-M-7	transwin-toggle	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-base.el:2
C-M-8	transwin-dec	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-base.el:2
C-M-9	transwin-inc	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-base.el:2
C-M-<	mc/skip-to-previous-like-this	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2
C-M-<f12>	gptel-menu	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-ai.el:69
C-M->	mc/skip-to-next-like-this	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2
C-s-.	embark-act	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-S-<mouse-1>	mc/add-cursor-on-click	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2
C-S-c C-S-c	mc/edit-lines	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2
C-s-f	toggle-frame-fullscreen	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-base.el:2
C-x 4 b	consult-buffer-other-window	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-x 5 b	consult-buffer-other-frame	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-x _	split-window-vertically-instead	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-window.el:1
C-x b	consult-buffer	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-x C-b	ibuffer	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-ibuffer.el:1
C-x C-d	consult-dir	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-x C-r	fido-recentf-open	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:121
C-x C-r	ido-recentf-open	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:137
C-x C-r	recentf-open-files	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-base.el:1
C-x j	elfeed	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-reader.el:1
C-x J	newsticker-show-news	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-reader.el:1
C-x M-:	consult-complex-command	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-x p b	consult-project-buffer	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-x r b	consult-bookmark	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
C-x r RET	iedit-rectangle-mode	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2
C-x t 1	treemacs-delete-other-windows	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-treemacs.el:1
C-x t b	treemacs-bookmark	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-treemacs.el:1
C-x t C-t	treemacs-find-file	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-treemacs.el:1
C-x t M-t	treemacs-find-tag	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-treemacs.el:1
C-x t t	treemacs	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-treemacs.el:1
C-x u	vundo	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:3
`C-x	`	split-window-horizontally-instead
M-#	consult-register-load	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
M-'	consult-register-store	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1
M-.	embark-dwim	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:1

快捷键	命令	来源
M-/	completion-at-point	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-0	treemacs-select-window	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-treemacs.el
M-<f5>	dape-hydra/body	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dape.el:39
M-<f7>	my-read-mode	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-reader.el
M-<f8>	mingus	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-player.el
M-C	symbol-overlay-remove-all	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-highlight.el
M-g ,	xref-go-back	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-prog.el:84
M-g .	xref-find-definitions	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-prog.el:84
M-g e	avy-goto-word-0	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:11
M-g e	consult-compile-error	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g f	consult-flymake	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g g	consult-goto-line	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g i	consult-imenu	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g I	consult-imenu-multi	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g k	consult-global-mark	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g l	avy-goto-line	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:11
M-g m	consult-mark	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g M-g	consult-goto-line	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g o	consult-outline	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g s	consult-flyspell	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-g w	avy-goto-word-1	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:11
M-g y	consult-yasnipet	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-i	symbol-overlay-put	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-highlight.el
M-n	symbol-overlay-jump-next	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-highlight.el
M-N	symbol-overlay-switch-forward	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-highlight.el
M-o	link-hint-open-link	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:11
M-p	symbol-overlay-jump-prev	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-highlight.el
M-P	symbol-overlay-switch-backward	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-highlight.el
M-s d	consult-find	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-s D	consult-locate	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-s e	consult-isearch-history	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-s G	consult-git-grep	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-s g	consult-grep	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-s k	consult-keep-lines	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-s l	consult-line	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-s L	consult-line-multi	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el
M-s r	consult-ripgrep	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el

快捷键	命令	来源
M-s s	symbol-overlay-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-highlight
M-s u	consult-focus-lines	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completi
M-y	consult-yank-pop	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completi
M-z	avy-zap-to-char-dwim	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:1
M-Z	avy-zap-up-to-char-dwim	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:1
s-.	embark-act	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completi
s-<f12>	pomidor	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-utils.el:1
S-<f8>	mpc	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-player.el
s-<f8>	simple-mpc+	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-player.el
s-<mouse-1>	mc/add-cursor-on-click	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit.el:2
S-s-<return>	toggle-frame-fullscreen	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-base.el:2

模式与插件专属快捷键

作用域(map/mode)	快捷键	命令	
agent-shell-mode-map	C-<return>	agent-shell-help-menu	/L
agent-shell-mode-map	C-h ?	agent-shell-help-menu	/L
compilation-mode-map	o	link-hint-open-link	/L
copilot-completion-map	<tab>	copilot-accept-completion	/L
copilot-completion-map	C-<tab>	copilot-accept-completion-by-word	/L
copilot-completion-map	C-TAB	copilot-accept-completion-by-word	/L
copilot-completion-map	M-[	copilot-previous-completion	/L
copilot-completion-map	M-]	copilot-next-completion	/L
copilot-completion-map	TAB	copilot-accept-completion	/L
corfu-map	M-m	corfu-move-to-minibuffer	/L
custom-mode-map	o	link-hint-open-link	/L
dashboard-mode-map	H	browse-homepage	/L
dashboard-mode-map	q	quit-dashboard	/L
dashboard-mode-map	R	restore-session	/L
dashboard-mode-map	S	find-custom-file	/L
dashboard-mode-map	U	update-config-and-packages	/L
default-text-scale-mode-map	C-s--	default-text-scale-decrease	/L
default-text-scale-mode-map	C-s-0	default-text-scale-reset	/L
default-text-scale-mode-map	C-s==	default-text-scale-increase	/L
default-text-scale-mode-map	s--	default-text-scale-decrease	/L
default-text-scale-mode-map	s-0	default-text-scale-reset	/L
default-text-scale-mode-map	s==	default-text-scale-increase	/L

作用域(map/mode)	快捷键	命令	
devdocs-mode-map	o	link-hint-open-link	/L
diff-hl-command-map	SPC	diff-hl-mark-hunk	/L
dired-mode-map	)	dired-git-info-mode	/L
dired-mode-map	b	bongo-add-dired-files	/L
dired-mode-map	C-c C-p	wdired-change-to-wdired-mode	/L
dired-mode-map	C-c C-r	dired-rsync	/L
dired-mode-map	C-c C-z f	browse-url-of-file	/L
dired-mode-map	S	hydra-dired-quick-sort/body	/L
doom-modeline-mode-map	C-<f6>	doom-modeline-hydra/body	/L
eglot-mode-map	C-M-.	consult-eglot-symbols	/L
elfeed-search-mode-map	?	elfeed-hydra/body	/L
elfeed-search-mode-map	h	elfeed-hydra/body	/L
elfeed-show-mode-map	%	elfeed-webkit-toggle	/L
elfeed-show-mode-map	o	link-hint-open-link	/L
emacs-lisp-mode-map	C-c C-d	helpful-at-point	/L
emacs-lisp-mode-map	C-c e	macrostep-expand	/L
esc-map	C-;	iedit-execute-last-modification	/L
eshell-mode-map	[remap recenter-top-bottom]	eshell/clear	/L
eww-mode-map	o	link-hint-open-link	/L
flyspell-mode-map	C-,	nil	/L
flyspell-mode-map	C-.	nil	/L
flyspell-mode-map	C-;	nil	/L
git-messenger-map	m	git-messenger:copy-message	/L
go-keymap	C-c t b	go-test-current-benchmark	/L
go-keymap	C-c t c	go-test-current-coverage	/L
go-keymap	C-c t f	go-test-current-file	/L
go-keymap	C-c t g	go-gen-test-dwim	/L
go-keymap	C-c t j	go-test-current-project	/L
go-keymap	C-c t t	go-test-current-test	/L
go-keymap	C-c t x	go-run	/L
go-mode-map	<f1>	godoc	/L
go-mode-map	C-c t a	go-tag-add	/L
go-mode-map	C-c t r	go-tag-remove	/L
help-map	C-;	iedit-mode-toggle-on-function	/L
help-mode-map	o	link-hint-open-link	/L
help-mode-map	r	remove-hook-at-point	/L
helpful-mode-map	C-x K	helpful-kill-buffers	/L

作用域(map/mode)	快捷键	命令	
helpful-mode-map	o	link-hint-open-link	/L
helpful-mode-map	r	remove-hook-at-point	/L
hl-todo-mode-map	C-c t i	hl-todo-insert	/L
hl-todo-mode-map	C-c t n	hl-todo-next	/L
hl-todo-mode-map	C-c t o	hl-todo-occur	/L
hl-todo-mode-map	C-c t p	hl-todo-previous	/L
hl-todo-mode-map	C-c t R	hl-todo-rg	/L
hl-todo-mode-map	C-c t r	hl-todo-rg-project	/L
hs-minor-mode-map	C-S-<escape>	hideshow-hydra/body	/L
hs-minor-mode-map	C-~	hideshow-hydra/body	/L
Info-mode-map	o	link-hint-open-link	/L
isearch-mode-map	[remap isearch-query-replace-regexp]	anzu-isearch-query-replace-regexp	/L
isearch-mode-map	[remap isearch-query-replace]	anzu-isearch-query-replace	/L
isearch-mode-map	C-;	iedit-mode-from-isearch	/L
isearch-mode-map	M-e	consult-isearch-history	/L
isearch-mode-map	M-s e	consult-isearch-history	/L
isearch-mode-map	M-s l	consult-line	/L
isearch-mode-map	M-s L	consult-line-multi	/L
lisp-interaction-mode-map	C-c C-d	helpful-at-point	/L
lisp-interaction-mode-map	C-c e	macrostep-expand	/L
local	C-c C-b	eval-buffer	/L
local	C-c C-c	eval-defun	/L
local	C-c C-x	ielm	/L
lsp-mode-map	[remap xref-find-definitions]	lsp-find-definition	/L
lsp-mode-map	[remap xref-find-references]	lsp-find-references	/L
lsp-mode-map	C-<f8>	lsp-treemacs-errors-list	/L
lsp-mode-map	C-c C-d	lsp-describe-thing-at-point	/L
lsp-mode-map	C-M-.	consult-lsp-symbols	/L
lsp-mode-map	M-<f8>	lsp-treemacs-symbols	/L
lsp-mode-map	s-<f8>	lsp-treemacs-java-deps-list	/L
lsp-ui-mode-map	[remap xref-find-definitions]	lsp-ui-peek-find-definitions	/L
lsp-ui-mode-map	[remap xref-find-references]	lsp-ui-peek-find-references	/L
lsp-ui-mode-map	M-<f6>	lsp-ui-hydra/body	/L
lsp-ui-mode-map	s-<return>	lsp-ui-sideline-apply-code-actions	/L
magit-mode-map	C-c C-g	my/agent-shell-magit-generate-commit	/L
magit-mode-map	C-c C-r	my/agent-shell-review-magit-commit	/L
markdown-mode-command-map	g	grip-mode	/L

作用域(map/mode)	快捷键	命令	
markdown-mode-command-map	r	markdown-toc-generate-or-refresh-toc	/L
mc/keymap	`C-	`	mc
minibuffer-local-completion-map	C-x C-d	consult-dir	/L
minibuffer-local-completion-map	C-x C-j	consult-dir-jump-file	/L
minibuffer-local-map	M-.	my/embark-preview	/L
minibuffer-local-map	M-r	consult-history	/L
minibuffer-local-map	M-s	consult-history	/L
minibuffer-mode-map	C-c C-o	embark-export	/L
nov-mode-map	o	link-hint-open-link	/L
org-mode-map	<	(lambda	/L
org-mode-map	<s-return>	rect-hydra/body	/L
org-mode-map	C-c C-g	grip-mode	/L
org-mode-map	C-c C-h	org-preview-html-mode	/L
org-mode-map	C-c C-x m	org-pomodoro	/L
org-mode-map	C-M-y	org-rich-yank	/L
org-mode-map	s-<f7>	dslide-deck-start	/L
org-mode-map	s-<f7>	org-tree-slide-mode	/L
org-tree-slide-mode-map	<left>	org-tree-slide-move-previous-tree	/L
org-tree-slide-mode-map	<right>	org-tree-slide-move-next-tree	/L
org-tree-slide-mode-map	S-SPC	org-tree-slide-move-previous-tree	/L
org-tree-slide-mode-map	SPC	org-tree-slide-move-next-tree	/L
pdf-view-mode-map	C-s	isearch-forward	/L
persistent-scratch-mode-map	[remap kill-buffer]	(lambda	/L
persistent-scratch-mode-map	[remap revert-buffer-quick]	persistent-scratch-restore	/L
persistent-scratch-mode-map	[remap revert-buffer]	persistent-scratch-restore	/L
popper-mode-map	C-<tab>	popper-cycle	/L
popper-mode-map	C-h z	popper-toggle	/L
popper-mode-map	C-M-<tab>	popper-toggle-type	/L
prog-mode-map	<C-return>	rect-hydra/body	/L
prog-mode-map	C-h D	devdocs-dwim	/L
prog-mode-map	M-<f1>	devdocs-dwim	/L
region-occurrences-highlighter-nav-mode-map	M-n	region-occurrences-highlighter-next	/L
region-occurrences-highlighter-nav-mode-map	M-p	region-occurrences-highlighter-prev	/L
rg-global-map	c	rg-dwim-current-dir	/L
rg-global-map	f	rg-dwim-current-file	/L
rg-global-map	m	rg-menu	/L
simple-mpc-mode-map	0	simple-mpc-stop	/L

作用域(map/mode)	快捷键	命令	
simple-mpc-mode-map	P	simple-mpc-play	/L
simple-mpc-mode-map	u	simple-mpc-update	/L
smerge-mode-map	C-c m	smerge-mode-hydra/body	/L
tabspace-command-map	C-r	tabspace-restore-session	/L
tabspace-command-map	C-s	tabspace-save-session	/L
tabspace-command-map	C-S-r	tabspace-restore-session-alt	/L
tabspace-command-map	C-w	tabspace-save-current-project-session	/L
text-mode-map	<C-return>	rect-hydra/body	/L
vc-prefix-map	B	browse-at-remote	/L
vc-prefix-map	p	git-messenger:popup-message	/L
vc-prefix-map	t	git-timemachine	/L
vertico-map	DEL	vertico-directory-delete-char	/L
vertico-map	M-DEL	vertico-directory-delete-word	/L
vertico-map	RET	vertico-directory-enter	/L
wdired-mode-map	<C-return>	rect-hydra/body	/L
wgrep-mode-map	<C-return>	rect-hydra/body	/L
woman-mode-map	o	link-hint-open-link	/L
xref--xref-buffer-mode-map	o	link-hint-open-link	/L
xwidget-webkit-mode-map	h	xwidget-hydra/body	/L
ztreediff-mode-map	C-<f5>	ztree-hydra/body	/L

Hydra 入口与内部键

Hydra 入口（触发键）

快捷键	Hydra	作用域	来源
<C-return>	rect-hydra/body	prog-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit
<C-return>	rect-hydra/body	text-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit
<C-return>	rect-hydra/body	wdired-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit
<C-return>	rect-hydra/body	wgrep-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit
<f6>	toggles-hydra/body	global	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-hydr
<s-return>	rect-hydra/body	org-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit
?	elfeed-hydra/body	elfeed-search-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-reac
C-<f5>	ztree-hydra/body	ztreediff-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-util
C-<f6>	doom-modeline-hydra/body	doom-modeline-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-ui.e
C-S-<escape>	hideshow-hydra/body	hs-minor-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit
C-c m	multiple-cursors-hydra/body	global	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit
C-c m	smerge-mode-hydra/body	smerge-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-vcs.

快捷键	Hydra	作用域	来源
C-c w	ace-window-hydra/body	global	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-winc
C-~	hideshow-hydra/body	hs-minor-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-edit
M-<f5>	dape-hydra/body	global	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dap.
M-<f6>	lsp-ui-hydra/body	lsp-ui-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-lsp.
h	elfeed-hydra/body	elfeed-search-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-reac
h	xwidget-hydra/body	xwidget-webkit-mode-map	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-web.

Hydra 内部键（请以对应 mode/hydra 打开后使用）

- Window: TAB/x/X/s/a/m/u/h/j/k/l/n/r/R/v/V/t/+/-/0/o/f/d/<left>/<right> (init-window.el)
- Rectangle: h/j/k/l/w/y/t/d/c/o/N/e/u/r (init-edit.el)
- LSP UI: d e/s/t/b/p/h/f/w , s e/h/d/s/c/i , h/j/k/l/c (init-lsp.el)
- DAP: n/s/o/c/p/k/r/D/m/t/w/S/i/R/b/l/e/B/d/Q (init-dap.el)
- Org Template: a/c/C/x/E/h/l/n/o/v/i/A/I/H/L/s/e/y/p/w/r/S/g/m/u/Y/P/< (init-org.el)
- Smerge: n/p/b/u/l/a/RET/C-m/<=/>/R/E/C/r/k/ZZ (init-vcs.el)
- Elfeed: c/g/G/y/+/-/</>/l/s/*a/t/b/n/p/u/r/RET (init-reader.el)
- Ztree: C/h/H/D/v/d/r/R/RET/SPC/TAB/g/x/<backspace> (init-utils.el)
- Toggles: n/a/d/e/c/s/l/b/i/m/h */f/0/u/W/E/Q/v/V/M/D/t * /p * (init-hydra.el)

常用 Emacs 默认快捷键

快捷键	默认命令	说明
C-x C-f	find-file	打开文件
C-x C-s	save-buffer	保存
C-x C-w	write-file	另存为
C-x k	kill-buffer	关闭当前 buffer
C-x C-c	save-buffers-kill-terminal	退出 Emacs
C-g	keyboard-quit	取消当前操作
C-/	undo	撤销
C-SPC	set-mark-command	设置标记
C-w	kill-region	剪切区域
M-w	kill-ring-save	复制区域
C-y	yank	粘贴
M-y	yank-pop	轮换粘贴历史
C-a	move-beginning-of-line	行首
C-e	move-end-of-line	行尾
M-f	forward-word	前进一个词
M-b	backward-word	后退一个词
M-<	beginning-of-buffer	文件开头
M->	end-of-buffer	文件结尾
C-v	scroll-up-command	下翻页
M-v	scroll-down-command	上翻页

快捷键	默认命令	说明
C-s	isearch-forward	向前搜索
C-r	isearch-backward	向后搜索
M-%	query-replace	查询替换
C-M-%	query-replace-regexp	正则替换
M-g g	goto-line	跳到行
C-x 0	delete-window	关闭当前窗口
C-x 1	delete-other-windows	仅保留当前窗口
C-x 2	split-window-below	上下分屏
C-x 3	split-window-right	左右分屏
C-x o	other-window	切换窗口
C-x b	switch-to-buffer	切换 buffer
C-x C-b	list-buffers	buffer 列表
C-h k	describe-key	查看按键绑定
C-h f	describe-function	查看函数文档
C-h v	describe-variable	查看变量文档

冲突与覆盖说明

快捷键	说明	证据
C-x C-r	init-mini 中条件绑定 fido/ido recentf, init-base 绑定 recentf-open-files；且 consult remap recentf -> consult-recent-file	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:121,137; /Users/bytedance/Desktop/dotfiles
C-c a	org-agenda 与 agent-shell 冲突（后加载的 init-ai 覆盖全局）	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:78; /Users/bytedance/Desktop/dotfiles/
C-c k	consult-kmacro 与 browse-kill-ring 冲突（后者覆盖）	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:102; /Users/bytedance/Desktop/d
C-c u	gt-use-text-utility 与 lsp-ui-imenu 冲突（后加载 init-lsp 覆盖）	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-dict.el:45; /Users/bytedance/Desktop/dotfiles
<f5>	init-mini 绑定 revert-current-buffer；init-dap 绑定 dape（后者覆盖）	/Users/bytedance/Desktop/dotfiles/.emacs.d/init-mini.el:169; /Users/bytedance/Desktop/dotfiles/.em
M-g e	consult-compile-error 与 avy-goto-word-0 冲突（后加载 init-prog 仍可能被 map/remap 影响）	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-completion.el:132; /Users/bytedance/Desktop/d

快捷键	说明	证据
C-M-.	eglot/lsp-mode 下分别绑定 consult- eglot-symbols / consult-lsp-symbols (按客户端条件生效)	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-lsp.el:54,112
s-<f7>	dslide 与 org-tree- slide 二选一（由 Emacs 版本条件决定）	/Users/bytedance/Desktop/dotfiles/.emacs.d/lisp/init-org.el:260,266

源码权威索引（全部自定义键位）

下表是基于源码抽取的完整清单（含 remap 、map 专属、条件加载项）。

快捷键	命令	作用域	
o	link-hint-open-link	Info-mode-map	/l
C-<return>	agent-shell-help-menu	agent-shell-mode-map	/l
C-h ?	agent-shell-help-menu	agent-shell-mode-map	/l
o	link-hint-open-link	compilation-mode-map	/l
<tab>	copilot-accept-completion	copilot-completion-map	/l
C-<tab>	copilot-accept-completion-by-word	copilot-completion-map	/l
C-TAB	copilot-accept-completion-by-word	copilot-completion-map	/l
M-[	copilot-previous-completion	copilot-completion-map	/l
M-]	copilot-next-completion	copilot-completion-map	/l
TAB	copilot-accept-completion	copilot-completion-map	/l
M-m	corfu-move-to-minibuffer	corfu-map	/l
o	link-hint-open-link	custom-mode-map	/l
H	browse-homepage	dashboard-mode-map	/l
R	restore-session	dashboard-mode-map	/l
S	find-custom-file	dashboard-mode-map	/l
U	update-config-and-packages	dashboard-mode-map	/l
q	quit-dashboard	dashboard-mode-map	/l
C-s--	default-text-scale-decrease	default-text-scale-mode-map	/l
C-s-0	default-text-scale-reset	default-text-scale-mode-map	/l
C-s-=	default-text-scale-increase	default-text-scale-mode-map	/l
s--	default-text-scale-decrease	default-text-scale-mode-map	/l
s-0	default-text-scale-reset	default-text-scale-mode-map	/l
s-=	default-text-scale-increase	default-text-scale-mode-map	/l
o	link-hint-open-link	devdocs-mode-map	/l
SPC	diff-hl-mark-hunk	diff-hl-command-map	/l
)	dired-git-info-mode	dired-mode-map	/l

快捷键	命令	作用域	
C-c C-p	wdired-change-to-wdired-mode	dired-mode-map	/L
C-c C-r	dired-rsync	dired-mode-map	/L
C-c C-z f	browse-url-of-file	dired-mode-map	/L
S	hydra-dired-quick-sort/body	dired-mode-map	/L
b	bongo-add-dired-files	dired-mode-map	/L
C-<f6>	doom-modeline-hydra/body	doom-modeline-mode-map	/L
C-M-.	consult-eglot-symbols	eglot-mode-map	/L
?	elfeed-hydra/body	elfeed-search-mode-map	/L
h	elfeed-hydra/body	elfeed-search-mode-map	/L
%	elfeed-webkit-toggle	elfeed-show-mode-map	/L
o	link-hint-open-link	elfeed-show-mode-map	/L
C-c C-d	helpful-at-point	emacs-lisp-mode-map	/L
C-c e	macrostep-expand	emacs-lisp-mode-map	/L
C-;	iedit-execute-last-modification	esc-map	/L
[remap recenter-top-bottom]	eshell/clear	eshell-mode-map	/L
o	link-hint-open-link	eww-mode-map	/L
C-,	nil	flyspell-mode-map	/L
C-.	nil	flyspell-mode-map	/L
C-;	nil	flyspell-mode-map	/L
m	git-messenger:copy-message	git-messenger-map	/L
<C-return>	rectangle-mark-mode	global	/L
<f12>	agent-shell	global	/L
<f13>	agent-shell	global	/L
<f2>	open-dashboard	global	/L
<f5>	dape	global	/L
<f5>	revert-current-buffer	global	/L
<f6>	toggles-hydra/body	global	/L
<f7>	olivetti-mode	global	/L
C-'	avy-goto-char-2	global	/L
C-,	goto-last-change	global	/L
C-.	consult-imenu	global	/L
C-:	avy-goto-char	global	/L
C-<	mc/mark-previous-like-this	global	/L
C-<f12>	gptel	global	/L
C-<f5>	quickrun	global	/L
C-<f8>	bongo	global	/L
C-=	er/expand-region	global	/L

快捷键	命令	作用域	
C->	mc/mark-next-like-this	global	/L
C-M-#	consult-register	global	/L
C-M-7	transwin-toggle	global	/L
C-M-8	transwin-dec	global	/L
C-M-9	transwin-inc	global	/L
C-M-<	mc/skip-to-previous-like-this	global	/L
C-M-<f12>	gptel-menu	global	/L
C-M->	mc/skip-to-next-like-this	global	/L
C-S-<mouse-1>	mc/add-cursor-on-click	global	/L
C-S-c C-S-c	mc/edit-lines	global	/L
C-c /	webjump	global	/L
C-c 1	my-maximize-buffer	global	/L
C-c A	agent-shell-new-shell	global	/L
C-c C-<	mc/mark-all-like-this	global	/L
C-c C-z .	browse-url-at-point	global	/L
C-c C-z b	browse-url-of-buffer	global	/L
C-c C-z e	browse-url-emacs	global	/L
C-c C-z r	browse-url-of-region	global	/L
C-c C-z u	browse-url	global	/L
C-c C-z v	browse-url-of-file	global	/L
C-c C-z w	xwidget-webkit-browse-url	global	/L
C-c D	docker	global	/L
C-c G	gt-translate-prompt	global	/L
C-c M-x	consult-mode-command	global	/L
C-c T	consult-theme	global	/L
C-c X	quickrun	global	/L
C-c a	agent-shell	global	/L
C-c a	org-agenda	global	/L
C-c b	org-switchb	global	/L
C-c c e	consult-colors-emacs	global	/L
C-c c f	describe-face	global	/L
C-c c g	git-link-dispatch	global	/L
C-c c i	file-info-show	global	/L
C-c c l	find-library	global	/L
C-c c t	consult-theme	global	/L
C-c c w	consult-colors-web	global	/L
C-c d G	gt-translate-prompt	global	/L

快捷键	命令	作用域	
C-c d d	fanyi-dwim2	global	/L
C-c d f	fanyi-dwim	global	/L
C-c d g	gt-translate	global	/L
C-c d h	fanyi-from-history	global	/L
C-c d i	osx-dictionary-search-input	global	/L
C-c d p	gt-speak	global	/L
C-c d s	gt-setup	global	/L
C-c d u	gt-use-text-utility	global	/L
C-c d x	osx-dictionary-search-pointer	global	/L
C-c f	flymake-show-buffer-diagnostics	global	/L
C-c g	gt-translate	global	/L
C-c h	consult-history	global	/L
C-c i	consult-info	global	/L
C-c k	browse-kill-ring	global	/L
C-c k	consult-kmacro	global	/L
C-c l c	link-hint-copy-link	global	/L
C-c l o	link-hint-open-link	global	/L
C-c m	multiple-cursors-hydra/body	global	/L
C-c n c	org-roam-capture	global	/L
C-c n f	org-roam-node-find	global	/L
C-c n g	org-roam-graph	global	/L
C-c n i	org-roam-node-insert	global	/L
C-c n j	org-roam-dailies-capture-today	global	/L
C-c n l	org-roam-buffer-toggle	global	/L
C-c n u	org-roam-ui-mode	global	/L
C-c r	consult-ripgrep	global	/L
C-c u	gt-use-text-utility	global	/L
C-c u	lsp-ui-imenu	global	/L
C-c w	ace-window-hydra/body	global	/L
C-c x	org-capture	global	/L
C-h M-m	which-key-show-major-mode	global	/L
C-s-.	embark-act	global	/L
C-s-f	toggle-frame-fullscreen	global	/L
C-x 4 b	consult-buffer-other-window	global	/L
C-x 5 b	consult-buffer-other-frame	global	/L
C-x C-b	ibuffer	global	/L
C-x C-d	consult-dir	global	/L

快捷键	命令	作用域	
C-x C-r	fido-recentf-open	global	/L
C-x C-r	ido-recentf-open	global	/L
C-x C-r	recentf-open-files	global	/L
C-x J	newsticker-show-news	global	/L
C-x M-:	consult-complex-command	global	/L
C-x _	split-window-vertically-instead	global	/L
C-x b	consult-buffer	global	/L
C-x j	elfeed	global	/L
C-x p b	consult-project-buffer	global	/L
C-x r b	consult-bookmark	global	/L
C-x t 1	treemacs-delete-other-windows	global	/L
C-x t C-t	treemacs-find-file	global	/L
C-x t M-t	treemacs-find-tag	global	/L
C-x t b	treemacs-bookmark	global	/L
C-x t t	treemacs	global	/L
C-x u	vundo	global	/L
`C-x	`	split-window-horizontally-instead	gl
M-#	consult-register-load	global	/L
M-'	consult-register-store	global	/L
M-.	embark-dwim	global	/L
M-/	completion-at-point	global	/L
M-0	treemacs-select-window	global	/L
M-<f5>	dape-hydra/body	global	/L
M-<f7>	my-read-mode	global	/L
M-<f8>	mingus	global	/L
M-C	symbol-overlay-remove-all	global	/L
M-N	symbol-overlay-switch-forward	global	/L
M-P	symbol-overlay-switch-backward	global	/L
M-Z	avy-zap-up-to-char-dwim	global	/L
M-g ,	xref-go-back	global	/L
M-g .	xref-find-definitions	global	/L
M-g I	consult-imenu-multi	global	/L
M-g M-g	consult-goto-line	global	/L
M-g e	avy-goto-word-0	global	/L
M-g e	consult-compile-error	global	/L
M-g f	consult-flymake	global	/L
M-g g	consult-goto-line	global	/L

快捷键	命令	作用域	
M-g i	consult-imenu	global	/L
M-g k	consult-global-mark	global	/L
M-g l	avy-goto-line	global	/L
M-g m	consult-mark	global	/L
M-g o	consult-outline	global	/L
M-g s	consult-flyspell	global	/L
M-g w	avy-goto-word-1	global	/L
M-g y	consult-yasnippet	global	/L
M-i	symbol-overlay-put	global	/L
M-n	symbol-overlay-jump-next	global	/L
M-o	link-hint-open-link	global	/L
M-p	symbol-overlay-jump-prev	global	/L
M-s D	consult-locate	global	/L
M-s G	consult-git-grep	global	/L
M-s L	consult-line-multi	global	/L
M-s d	consult-find	global	/L
M-s e	consult-isearch-history	global	/L
M-s g	consult-grep	global	/L
M-s k	consult-keep-lines	global	/L
M-s l	consult-line	global	/L
M-s r	consult-ripgrep	global	/L
M-s s	symbol-overlay-map	global	/L
M-s u	consult-focus-lines	global	/L
M-y	consult-yank-pop	global	/L
M-z	avy-zap-to-char-dwim	global	/L
S-<f8>	mpc	global	/L
S-s-<return>	toggle-frame-fullscreen	global	/L
[(super a)]	mark-whole-buffer	global	/L
[(super c)]	kill-ring-save	global	/L
[(super l)]	goto-line	global	/L
[(super s)]	save-buffer	global	/L
[(super v)]	yank	global	/L
[(super w)]	delete-frame	global	/L
[(super z)]	undo	global	/L
[remap Info-search]	consult-info	global	/L
[remap describe-bindings]	embark-bindings	global	/L
[remap describe-command]	helpful-command	global	/L

快捷键	命令	作用域	
[remap describe-function]	helpful-callable	global	/L
[remap describe-key]	helpful-key	global	/L
[remap describe-symbol]	helpful-symbol	global	/L
[remap describe-variable]	helpful-variable	global	/L
[remap isearch-forward]	consult-line	global	/L
[remap kill-ring-save]	easy-kill	global	/L
[remap mark-sexp]	easy-mark	global	/L
[remap move-beginning-of-line]	mwim-beginning	global	/L
[remap move-end-of-line]	mwim-end	global	/L
[remap other-window]	ace-window	global	/L
[remap query-replace-regexp]	anzu-query-replace-regexp	global	/L
[remap query-replace]	anzu-query-replace	global	/L
[remap recentf-open-files]	consult-recent-file	global	/L
s-.	embark-act	global	/L
s-<f12>	pomidor	global	/L
s-<f8>	simple-mpc+	global	/L
s-<mouse-1>	mc/add-cursor-on-click	global	/L
C-;	iedit-mode	global-map	/L
C-x r RET	iedit-rectangle-mode	global-map	/L
C-c t b	go-test-current-benchmark	go-keymap	/L
C-c t c	go-test-current-coverage	go-keymap	/L
C-c t f	go-test-current-file	go-keymap	/L
C-c t g	go-gen-test-dwim	go-keymap	/L
C-c t j	go-test-current-project	go-keymap	/L
C-c t t	go-test-current-test	go-keymap	/L
C-c t x	go-run	go-keymap	/L
<f1>	godoc	go-mode-map	/L
C-c t a	go-tag-add	go-mode-map	/L
C-c t r	go-tag-remove	go-mode-map	/L
C-;	iedit-mode-toggle-on-function	help-map	/L
o	link-hint-open-link	help-mode-map	/L
r	remove-hook-at-point	help-mode-map	/L
C-x K	helpful-kill-buffers	helpful-mode-map	/L
o	link-hint-open-link	helpful-mode-map	/L
r	remove-hook-at-point	helpful-mode-map	/L
C-c t R	hl-todo-rg	hl-todo-mode-map	/L
C-c t i	hl-todo-insert	hl-todo-mode-map	/L

快捷键	命令	作用域	
C-c t n	hl-todo-next	hl-todo-mode-map	/L
C-c t o	hl-todo-occur	hl-todo-mode-map	/L
C-c t p	hl-todo-previous	hl-todo-mode-map	/L
C-c t r	hl-todo-rg-project	hl-todo-mode-map	/L
C-S-<escape>	hideshow-hydra/body	hs-minor-mode-map	/L
C-~	hideshow-hydra/body	hs-minor-mode-map	/L
C-;	iedit-mode-from-isearch	isearch-mode-map	/L
M-e	consult-isearch-history	isearch-mode-map	/L
M-s L	consult-line-multi	isearch-mode-map	/L
M-s e	consult-isearch-history	isearch-mode-map	/L
M-s l	consult-line	isearch-mode-map	/L
[remap isearch-query-replace-regexp]	anzu-isearch-query-replace-regexp	isearch-mode-map	/L
[remap isearch-query-replace]	anzu-isearch-query-replace	isearch-mode-map	/L
C-c C-d	helpful-at-point	lisp-interaction-mode-map	/L
C-c e	macrostep-expand	lisp-interaction-mode-map	/L
C-c C-b	eval-buffer	local	/L
C-c C-c	eval-defun	local	/L
C-c C-x	ielm	local	/L
C-<f8>	lsp-treemacs-errors-list	lsp-mode-map	/L
C-M-.	consult-lsp-symbols	lsp-mode-map	/L
C-c C-d	lsp-describe-thing-at-point	lsp-mode-map	/L
M-<f8>	lsp-treemacs-symbols	lsp-mode-map	/L
[remap xref-find-definitions]	lsp-find-definition	lsp-mode-map	/L
[remap xref-find-references]	lsp-find-references	lsp-mode-map	/L
s-<f8>	lsp-treemacs-java-deps-list	lsp-mode-map	/L
M-<f6>	lsp-ui-hydra/body	lsp-ui-mode-map	/L
[remap xref-find-definitions]	lsp-ui-peek-find-definitions	lsp-ui-mode-map	/L
[remap xref-find-references]	lsp-ui-peek-find-references	lsp-ui-mode-map	/L
s-<return>	lsp-ui-sideline-apply-code-actions	lsp-ui-mode-map	/L
C-c C-g	my/agent-shell-magit-generate-commit	magit-mode-map	/L
C-c C-r	my/agent-shell-review-magit-commit	magit-mode-map	/L
g	grip-mode	markdown-mode-command-map	/L
r	markdown-toc-generate-or-refresh-toc	markdown-mode-command-map	/L
`C-	`	mc/vertical-align-with-space	mc
C-x C-d	consult-dir	minibuffer-local-completion-map	/L
C-x C-j	consult-dir-jump-file	minibuffer-local-completion-map	/L
M-.	my/embark-preview	minibuffer-local-map	/L

快捷键	命令	作用域	
M-r	consult-history	minibuffer-local-map	/L
M-s	consult-history	minibuffer-local-map	/L
C-c C-o	embark-export	minibuffer-mode-map	/L
o	link-hint-open-link	nov-mode-map	/L
<	(lambda	org-mode-map	/L
<s-return>	rect-hydra/body	org-mode-map	/L
C-M-y	org-rich-yank	org-mode-map	/L
C-c C-g	grip-mode	org-mode-map	/L
C-c C-h	org-preview-html-mode	org-mode-map	/L
C-c C-x m	org-pomodoro	org-mode-map	/L
s-<f7>	dslide-deck-start	org-mode-map	/L
s-<f7>	org-tree-slide-mode	org-mode-map	/L
<left>	org-tree-slide-move-previous-tree	org-tree-slide-mode-map	/L
<right>	org-tree-slide-move-next-tree	org-tree-slide-mode-map	/L
S-SPC	org-tree-slide-move-previous-tree	org-tree-slide-mode-map	/L
SPC	org-tree-slide-move-next-tree	org-tree-slide-mode-map	/L
C-s	isearch-forward	pdf-view-mode-map	/L
[remap kill-buffer]	(lambda	persistent-scratch-mode-map	/L
[remap revert-buffer-quick]	persistent-scratch-restore	persistent-scratch-mode-map	/L
[remap revert-buffer]	persistent-scratch-restore	persistent-scratch-mode-map	/L
C-<tab>	popper-cycle	popper-mode-map	/L
C-M-<tab>	popper-toggle-type	popper-mode-map	/L
C-h z	popper-toggle	popper-mode-map	/L
<C-return>	rect-hydra/body	prog-mode-map	/L
C-h D	devdocs-dwim	prog-mode-map	/L
M-<f1>	devdocs-dwim	prog-mode-map	/L
M-n	region-occurrences-highlighter-next	region-occurrences-highlighter-nav-mode-map	/L
M-p	region-occurrences-highlighter-prev	region-occurrences-highlighter-nav-mode-map	/L
c	rg-dwim-current-dir	rg-global-map	/L
f	rg-dwim-current-file	rg-global-map	/L
m	rg-menu	rg-global-map	/L
O	simple-mpc-stop	simple-mpc-mode-map	/L
P	simple-mpc-play	simple-mpc-mode-map	/L
u	simple-mpc-update	simple-mpc-mode-map	/L
C-c m	smerge-mode-hydra/body	smerge-mode-map	/L
C-S-r	tabspace-restore-session-alt	tabspace-command-map	/L
C-r	tabspace-restore-session	tabspace-command-map	/L

快捷键	命令	作用域	
C-s	tabspaces-save-session	tabspaces-command-map	/L
C-w	tabspaces-save-current-project-session	tabspaces-command-map	/L
<C-return>	rect-hydra/body	text-mode-map	/L
B	browse-at-remote	vc-prefix-map	/L
p	git-messenger:popup-message	vc-prefix-map	/L
t	git-timemachine	vc-prefix-map	/L
DEL	vertico-directory-delete-char	vertico-map	/L
M-DEL	vertico-directory-delete-word	vertico-map	/L
RET	vertico-directory-enter	vertico-map	/L
<C-return>	rect-hydra/body	wdired-mode-map	/L
<C-return>	rect-hydra/body	wgrep-mode-map	/L
o	link-hint-open-link	woman-mode-map	/L
o	link-hint-open-link	xref--xref-buffer-mode-map	/L
h	xwidget-hydra/body	xwidget-webkit-mode-map	/L
C-<f5>	ztree-hydra/body	ztreediff-mode-map	/L

最后更新: 2026-03-19