



MetaboCensoR Tutorial

2026-08-23

Tutorial Edition 1.4

Software Release 1.4.x



Contents

General Information.....	3
Running & Installation.....	4
Input Requirements	4
Overview of Interface	5
Implementation Details.....	6
Quick Start	6
Tab “Upload Data”: Control Panel	7
Tab “Upload Data”: Display Area	8
Tab “Blank Filters”: Control Panel	9
Tab “Blank Filters”: Display Area	10
Tab “MS Filters”: Control Panel.....	11
Tab “MS Filters”: Display Area.....	12
Tab “QC Filters”: Control Panel.....	13
Tab “QC Filters”: Display Area	14
Tab “Peak Filters”: Control Panel.....	15
Tab “Peak Filters”: Display Area.....	16
Tab “Final Summary”: Control Panel.....	17
Tab “Final Summary”: Display Area.....	18
Tab “About” Overview	19



General Information


This tutorial aims at guiding the user to process data LC-MS data through Shiny GUI interface of MetaboCensoR. MetaboCensoR is an input-versatile Shiny application and local R package for analyte-centric peak table filtering. The workflow integrates four complementary modules for blank filtering, redundant ion-species filtering, quality-control filtering, and peak-based filtering. MetaboCensoR also provides interactive threshold optimization, exportable annotation tables, and synchronized filtering of associated .mgf files.

An overview of MetaboCensoR is presented below. The workflow is organized into six functional tabs that collectively support peak table curation, parameter optimization, and export of filtered results. The output of the app is a filtered peak table and, optionally, an MGF spectra file. Only the peak table upload is required for full workflow execution and final output generation. All other tabs are optional.

License: GPL-3.0

Contact: plyushchenko.ivan@gmail.com

Project Repository: github.com/plyush1993/MetaboCensoR





Running & Installation

Shiny Web Deployment is available by the link:

plyush1993.shinyapps.io/metabocensor/

Local installation of R package:

```
if (!require("BiocManager", quietly = TRUE)) {  
  install.packages("BiocManager")  
}  
if (!require("remotes", quietly = TRUE)) {  
  install.packages("remotes")  
}  
remotes::install_github("plyush1993/MetaboCensor", INSTALL_opts = "--no-multiarch")
```

or

```
if (!requireNamespace("pak", quietly = TRUE)) install.packages("pak")  
pak::pak("plyush1993/MetaboCensor")
```

Run Locally:

```
MetaboCensor::run_metabocensor()
```

Input Requirements

The application accepts peak tables in **.csv** format and MS1/MS2 mass spectral data in **.mgf** format, both of which can be directly exported from dedicated metabolomics processing software (xcms, MZmine, MS-DIAL). Make sure that your input peak table is aligned with data formats. Examples of acceptable formats are available here: [Input Examples](#).

Important note

The Shiny server has limited memory capacity (**1 GB**). Computationally intensive steps (like MS filters) or large MGF files may cause the app to stack or disconnect. For large datasets or memory-intensive analyses, we recommend activating the “**Limit table previews**” option and running *MetaboCensor* locally



Overview of Interface

The screenshot shows the interface with three main panels highlighted by red boxes and numbers:

- 1. The Sidebar Panel (Control Panel):** Contains the 'Upload' section with a 'Data table type' dropdown (set to 'mzMine'), an 'Upload Peak Table (*.csv)' section with a 'Browse...' button, and 'Global parsing settings' including 'Feature ID (auto-generated)', 'm/z column', 'rt column', and 'How to define sample columns?' options.
- 2. The Main Panel (Display Area):** Displays 'TOTAL SAMPLES DETECTED' (9) and 'TOTAL FEATURES (PEAKS)' (6,167). It shows a 'Dataset: Example' table with columns: row ID, row m/z, row retention time, row ion mobility, row ion mobility unit, row CCS, correlation group ID, annotation network number, best ion, auto MS2 verify, identified by n, partners, and neutral M mass. The table shows 6 entries.
- 3. The Navigation Bar (Tab Menu):** Located at the top, it contains tabs: 'Upload Data', 'Blank Filters', 'MS Filters', 'QC Filters', 'Peak Filters', 'Final Summary', and 'About'.

GUI is organized into 3 main panels:

1. The Sidebar Panel (Control Panel)

- This is the primary area for user interaction. It houses the input controls where users upload data, configure global settings, define parameters, and execute filtering steps.

2. The Main Panel (Display Area)

- This is where the application renders the output and displays interactive data tables, statistical plots, and provides summary metrics.

3. The Navigation Bar (Tab Menu)

- This allows users to navigate linearly through the sequential steps of the data processing pipeline, from data upload to final summary and export.

Contextual assistance is embedded throughout the interface. Users can access detailed parameter descriptions and recommendations by interacting with the tooltip icons.

On the following pages, yellow numbered circles indicate the recommended operational order within each interface tab in *Control Panel*.

Red numbered squares describe widgets in *Display Area*.



Implementation Details

All filter groups are applied sequentially in the order shown in the tab panel: Blank Filters → MS Filters → QC Filters → Peak Filters. Changes made on later tabs do not affect the results of previous tabs. To change the order of applied filters (e.g., 'Peak Filters' before 'Blank Filters'), run the application sequentially several times, using the output peak table from one run as the input for the next.

Quick Start

Press button  in “Upload data” tab to upload attached example dataset and get access to the MetaboCensoR functionality. If you use this example, run the Blank filter first to save memory for further steps. You can keep all parameters by default.

Briefly, it is the LC-MS plant profiling dataset, which is described in [Houriet et al.](#) Briefly, methanol extracts from the plant ashwagandha [*Withania somnifera* (L.) Dunal] together with blanks were analyzed on RP column in DDA positive mode on Thermo Q-Exactive Plus Orbitrap. Raw mzML files were then processed in mzMine in default pre-settings for UPLC-DDA to obtain resulted peak table.



Tab “Upload Data”: Control Panel



Upload Data

Blank Filters

MS Filters

QC Filters

Peak Filters

Final Summary

About

Upload

Data table type: ?
mzMine

Upload Peak Table (*.csv)
Browse... No file selected

Global parsing settings

Feature ID (auto-generated):
feature_id

m/z column:
row m/z

rt column:
row retention time

How to define sample columns?
☐ Auto-detect numeric sample columns
☒ By keyword match
☐ Pick columns manually

Sample column keywords (pick/add multiple):
.mzML .mzXML

Limit table previews ☐

Clear dataset

Example dataset ?

TOTAL SAMPLES DETECTED
9

TOTAL FEATURES (PEAKS)
6,167

LARGE DATASETS / MEMORY LIMITS

Dataset: Example

1. Pick the right table type and upload

MetaboCensoR supports mzMine, xcms, MS-DIAL, and Default input tables. If the type is wrong, the app throws a parsing error.

2. Specify peak characteristic columns

Use the selectors to check/select 3 columns:

- Feature ID (by default: auto-generates numeric vector)
- m/z
- rt

We recommend to start with default column names.

3. Specify sample intensity columns

Use auto-detect, keyword matching, or manual column selection. Keyword matching is the most transparent because you can inspect the exact suffixes/prefixes used in your export.

4. Limit table previews

For large datasets we recommend activating the “**Limit table previews**” option

5. Clear dataset

Reset all calculations.

6. Example dataset shortcut

The Example dataset button loads the built-in example.

by Plyushchenko I.V. | GPLv3 | v. 1.3.4 | Publication



Tab “Upload Data”: Display Area



[Upload Data](#)[Blank Filters](#)[MS Filters](#)[QC Filters](#)[Peak Filters](#)[Final Summary](#)[About](#)

Upload

Data table type: ?

mzMine

Upload Peak Table (*.csv)

Browse...

 No file selected

Global parsing settings

Feature ID (auto-generated):

feature_id

m/z column:

row m/z

rt column:

row retention time

How to define sample columns?

☐ Auto-detect numeric sample columns

☒ By keyword match

☐ Pick columns manually

Sample column keywords (pick/add multiple):

.mzML .mzXML

Limit table previews ☐

Clear dataset

Example dataset

?

TOTAL SAMPLES: 9

1 Statistics of uploaded dataset

Dataset: Example

Show 6 entries

Search:

row ID	row m/z	row retention time	row ion mobility	row ion mobility unit	row CCS	correlation group ID	annotation network number	best ion
1	108	148.0277472	0.3691534			31	0	[M+H] ⁺
2	181	169.0462455	0.3699988			31		
3	175	128.0197664	0.37076914			31	20	[M+NH ₄] ⁺
4	231	216.95						
5	43	234.9						[2M+Na] ⁺
6	145	244.9475245	0.37269926			31		

Showing 1 to 6 of 6,167 entries

Previous

1

2

3

4

5

...

1,028

Next

by Plyushchenko I.V. | GPLv3 | v. 1.3.4 | Publication



Tab “Blank Filters”: Control Panel

Sample Label

Label source: 1

- ☒ From sample names (by token)
- ☐ From metadata CSV
- ☐ From custom CSV (one column, no header)
- ☐ Manual editable table

Token index: 2

Token separator: -

☒ Show labels table

Blank / Media Removal

Enable Blank filter: ☒

Choose blank/media group(s): Blank

Filtering mode:

- ☒ Blank < Cutoff * Sample Max
- ☐ Drop any feature detected in Blank

Cutoff (fraction of max experimental mean): 0.1

Plot values distribution

☒ Show Blank plot panel

Apply

Clear

Input table

Show 5 entries

row	ID	m/z
1	108	148.02774
2	181	169.04624
3	175	128.01976
4	231	216.95126
5	43	234.96133
6	145	244.94752

Output table — a

Show 5 entries

row	ID	m/z
1	108	148.02774
2	181	169.04624
3	175	128.01976
4	231	216.95126
5	43	234.96133
6	145	244.94752

Showing 1 to 5 of 2,597 entries

Previous 1 2 3 4 5 ... 520 Next

Filtering results — Step 1 (Blank Filters)

Metric	Value
Features before	6167
Removed by Blank Filters	3570
Features after	2597

1. Sample Labels — how to specify groups

Choose a label source:

- From sample name:

Define token and index for extracting labels from sample names.

Example — parse from sample names

Sample name: Sample_WT_1_R-C1_1_5037.mzML Peak area

Separator: _

Token index: 2

Resulting label: WT

- From metadata CSV:

Upload a metadata table with column names, choose the sample-name column and the column to use as Label. Rows are matched by sample name. You can also clean sample name to remove file extension, suffixes, etc.

- From custom CSV:

Upload a one-column CSV without header. Label order must match sample column order.

- Manual editable table:

The editable label table is filled from the current token-based labels. Double-click cells in the Label column to manually correct group names.

2. Show resulted Labels in Display Area

3. Set Up Blank Filters

Enable filter.

Specify blank groups.

Choose between filtering modes:

- Blank < Cutoff * Sample Max

- Drop any feature detected in Blank

4. Plot distribution of filtered peaks

5. Apply or Discard Filtering Step



Tab “Blank Filters”: Display Area

MetaboCampor

Upload Data

Blank Filters

MS Filters

QC Filters

Peak Filters

Final Summary

About

Sample Label

Label source:

From sample names (by token)

From metadata CSV

From custom CSV (one column, no header)

Manual editable table

Token index:

2

Token separator:

-

Show labels table

Blank / Media Removal

Enable Blank filter

Choose blank/media group(s):

Blank

Filtering mode:

Blank < Cutoff * Sample Max

Drop any feature detected in Blank

Cutoff (fraction of max experimental mean):

0.1

Plot values distribution

Show Blank plot panel

Apply

Clear

Input table

Show

5

 entries

Search:

row ID	mz	rt	row ion mobility	row ion mobility unit	row CCS	correlation group ID	annotat network number
1	108	148.0277472	0.3691534			31	0
2	181	169.0462455	0.3699988			31	
3	175	128.0197664	0.37076914			31	20
4	231	216.9512638				31	
5	43	234.961351	0.3725			31	14

Showing 1 to 5 of 6,167 entries

Previous

1

2

3

4

5

...

1,234

Next

Check matching Sample Names and Group Labels:

Show

6

 entries

Sample	Label
Orbi_Blank_A.mzML Peak area	Blank
Orbi_Blank_B.mzML Peak area	Blank
Orbi_Blank_C.mzML Peak area	Blank
Orbi_Sample_A.mzML Peak area	Sample
Orbi_Sample_B.mzML Peak area	Sample
Orbi_Sample_C.mzML Peak area	Sample

Showing 1 to 6 of 9 entries

Previous

1

2

Next

Check Blank Ratio Distribution:

Blank to Sample Ratio Distribution

Count

Ratio: Mean(Blank) / Max(Mean(Sample)) (log10 scale)

Filtered: 57.9%

Output table — after Blank Filters

Show

5

 entries

Search:

row ID	mz	rt	row ion mobility	row ion mobility unit	row CCS	correlation group ID	annotat network number
1	108	148.0277472	0.3691534			31	0
2	181	169.0462455	0.3699988			31	
4	231	216.9512638	0.371403			31	
5	43	234.961351	0.3725			31	14
6	145	244.9475245	0.37269			31	

Showing 1 to 5 of 2,597 entries

Previous

1

2

3

4

5

...

520

Next

Filtering results — Step 1 (Blank Filters)

Metric	Value
Features before	6167
Removed by Blank Filters	3570
Features after	2597

10



Tab “MS Filters”: Control Panel

The screenshot shows the 'MS Filters' tab in a software interface. The top navigation bar includes 'Upload Data', 'Blank Filters', 'MS Filters' (selected), 'QC Filters', 'Peak Filters', 'Final Summary', and 'About'. The left sidebar contains six filter sections: A) Isotopes & Dimers, B) Adduct Families, C) Neutral Losses, D) In-Source Fragments, E) Mispicked Ions, and F) Saturated Ions. Each section has a 'Show' button and a 'Collapse' toggle. The main area displays the 'Input table' and 'Output table' with columns for row ID, m/z, rt, ion mobility, CCS, correlation group ID, and annotation number. A 'Download CSV' button is visible below the output table. Numbered callouts 1 through 8 point to specific features: 1. Enable & Set Up Isotopes Filtering (Isotopes & Dimers section), 2. Enable & Set Up Adducts Filtering (Adduct Families section), 3. Enable & Set Up Neutral Losses Filtering (Neutral Losses section), 4. Enable & Set Up In-Source Fragments Filtering (In-Source Fragments section), 5. Enable & Set Up Mispicked Ions Filtering (Mispicked Ions section), 6. Enable & Set Up Saturated Ions Filtering (Saturated Ions section), 7. Print & Download annotation tables (Download CSV button), and 8. Apply or Discard Filtering Step (Apply and Clear buttons).

1. Enable & Set Up Isotopes Filtering

Need parameter help? Click the tooltips or read the [About](#) tab for details. **Pro-Tip:** Start with the default settings.

2. Enable & Set Up Adducts Filtering

Need parameter help? Click the tooltips or read the [About](#) tab for details. **Pro-Tip:** Start with the default settings and check your polarity.

3. Enable & Set Up Neutral Losses Filtering

Need parameter help? Click the tooltips or read the [About](#) tab for details. **Pro-Tip:** Start with the default settings and check your polarity.

4. Enable & Set Up In-Source Fragments Filtering

Need parameter help? Click the tooltips or read the [About](#) tab for details. **Pro-Tip:** Start with the default settings.

4. Enable & Set Up Mispicked Ions Filtering

Need parameter help? Click the tooltips or read the [About](#) tab for details.

6. Enable & Set Up Saturated Ions Filtering

Need parameter help? Click the tooltips or read the [About](#) tab for details.

7. Print & Download annotation tables

8. Apply or Discard Filtering Step



rt	row mobility	row ion mobility	row CCS	row g
0.3691534				3
0.0000000				0

Input table

Output table

SV	Search:			
	mz	rt	iso_group	status
55	981.5019	5.962	9	keep_rep
75	982.5019			filtered
93	977.9383			keep_rep
99	977.4369	9.749	295.6	filtered
				filtered
				keep_rep
1	895.9259	4.402	1.189.1	filtered
2	896.4304	4.404	1.256.7	keep_rep

4 Summary



Tab “QC Filters”: Control Panel

The screenshot shows the QC Filters control panel with the following components:

- 1. Sample Labels**: A section for specifying label sources. Options include: Use labels from Blank Tab (selected), From sample names (by token), From metadata CSV, From custom CSV (one column, no header), and Manual editable table. A checkbox for "Show labels table" is checked.
- 2. QC value filters**: A section for enabling filters. Buttons for Zeros, Mean, RSD, and Min are visible. The evaluation mode is set to "Groupwise (ANY selected group passes)".
- 3. Evaluation mode**: A section for choosing between filtering modes: Groupwise (ANY selected group passes) (selected), Groupwise (EVERY selected group passes), and POOLED across selected groups.
- 4. Zeros metric**: A section for specifying the Zeros metric (Count or Percent) and the Zeros ≤ threshold (count or %).
- 5. Mean/RSD/Min values**: A section for specifying the Mean ≥ threshold, RSD ≤ threshold, and Min ≥ threshold.
- 6. Plot values distribution**: A section for plotting the distribution of selected values. A checkbox for "Show QC plot panel" is checked.
- 7. Apply or Discard Filtering Step**: Buttons for "Apply" and "Clear".

The output table shows the results of the filtering process. The table has columns for row ID, mz, and other metrics. The table is filtered to show 1 to 5 of 1,112 entries.

row ID	mz	rt	row ion mobility	row ion mobility unit	row CCS	correlation group ID	annotated network number
1	108	148.0277472	0.3691534			31	0
2	181	169.0462455	0.3699988			31	
4	231	216.9512638	0.371403			31	
5	43	234.961351	0.3725722			31	14
6	145	244.9475245	0.37269926			31	

Showing 1 to 5 of 1,112 entries

Filtering results — Step 3 (QC Filters)

Metric	Value
Features before	2597
Removed by Zeros	5
Removed by Mean	1453
Removed by RSD	110
Removed by Min	595
Total removed	1485
Features after	1112

Note: a feature may be counted in multiple filter categories.

1. Sample Labels — how to specify groups

Choose a label source: from *Blank Filters* tab, sample names, metadata CSV, custom CSV (one column, no header), or by manual editing.

See details for extracting Labels on the Page **Tab “Blank Filters”: Control Panel**.

2. Show resulted Labels in Display Area

3. Set Up QC Values Filters

Select desired values for filtering: Zeros, Mean, RSD, or Min.

Choose between filtering modes:

- Groupwise (ANY selected group passes)
- Groupwise (EVERY selected group passes)
- POOLED across selected groups

Specify groups used for evaluation.

4. Set Up Zero Values Filters

Specify Zero metric (counts or %) and threshold.

5. Set Up Mean/RSD/Min Values Filters

Specify thresholds for corresponding value.

6. Plot distribution of selected values

7. Apply or Discard Filtering Step



Tab “QC Filters”: Display Area

Upload DataBlank FiltersMS FiltersQC FiltersPeak FiltersFinal SummaryAbout

Sample Label

Label source:

- Use labels from Blank Tab
- From sample names (by token)
- From metadata CSV
- From custom CSV (one column, no header)
- Manual editable table

☒ Show labels table

QC value filters

Enable filters:

ZerosMeanRSDMin

Evaluation mode:

- Groupwise (ANY selected group passes)
- Groupwise (EVERY selected group passes)
- POOLED across selected groups

Group(s) to evaluate:

Empty = all groups

Zeros metric

- Count
- Percent

Zeros $\leq$ threshold (count or %)

0

Mean $\geq$ threshold

5000

RSD $\leq$ threshold

30

Min $\geq$ threshold

1000

Plot values distribution

☒ Show QC plot panel

Apply

Clear

Input table

Show 5 entriesSearch:

row ID	mz	rt	row ion mobility unit	row CCS	correlation group ID	annotat network number
1	108	148.0277472	0.3691534		31	0
2	181	169.0462455	0.3699988		31	
4	231	216.951			31	
5	43	234.961351	0.3725722		31	14
6	145	244.9475245	0.37269926		31	

Showing 1 to 5 of 2597 entriesPrevious12345...520Next

Check matching Sample Names and Group Labels:

Show 6 entries

Sample	Label
Orbi_Blank_A.mzML Peak area	Blank
Orbi_Blank_B.mzML Peak area	Blank
Orbi_Blank_C.mzML Peak area	Blank
Orbi_Sample_A.mzML Peak area	Sample
Orbi_Sample_B.mzML Peak area	Sample
Orbi_Sample_C.mzML Peak area	Sample

Showing 1 to 6 of 9 entriesPrevious12Next

Check Values Distribution:

ZEROS [Zero values (count)] - Groupwise (ANY) | Filtered: 5 of 2597 (0.2%)

MEAN [Mean intensity (log10)] - Groupwise (ANY) | Filtered: 1453 of 2597 (55.9%)

MIN [Minimum intensity (log10)] - Groupwise (ANY) | Filtered: 595 of 2597 (22.9%)

RSD [RSD (%)] - Groupwise (ANY) | Filtered: 366 of 2597 (14.1%)

Output table — after QC Filters

Show 5 entriesSearch:

row ID	mz	rt	row ion mobility unit	row CCS	correlation group ID	annotat network number
1	108	148.0277472	0.3691534		31	0
2	181	169.0462455	0.3699988		31	
4	231	216.951			31	
5	43	234.961351	0.3725722		31	14
6	145	244.9475245	0.37269926		31	

Showing 1 to 5 of 1112 entriesPrevious12345...223Next

Filtering results — Step 3 (QC Filters)

Metric	Value
Features before	2597
Removed by Zeros	5
Removed by Mean	1453
Removed by RSD	
Removed by Min	
Total removed	5
Features after	1112

Note: a feature may be counted in multiple filter categories.

14



Tab “Peak Filters”: Control Panel

Upload Data | Blank Filters | MS Filters | QC Filters | **Peak Filters** | Final Summary | About

Peak Filters

Enable filters: ☒ m/z ☒ rt ☐ RMD ☐ AMD

Target peak list

☒ m/z ≥ ☐ m/z ≤
200

☒ rt ≥ (min) ☐ rt ≤ (min)
1

Action for matched target peaks:
☒ Remove matched peaks
☐ Keep only matched peaks

m/z tolerance type:
☒ Da ☐ ppm

m/z tolerance (Da)
0.005

rt tolerance (min)
0.05

Type target peaks:
506.528, 11.6
970.611, 9.7

Or upload target list (.csv)
Browse... No file selected

CSV should contain mz and rt columns. If column names are not detected, the first two columns are treated as mz and rt.

Plot values distribution
☒ Show Peak plot panel

Apply

Clear

Input table

Show 5 entries

	rt	row ion mobility	row ion mobility unit	row CCS	correlation group ID	annotat number
1	172	0.3691534			31	0
2	181	0.3699988			31	
4	198	0.371403			31	
5	211	0.3725722			31	14
6	245	0.37269926			31	

Showing 1 to 5 of 2,597 entries

Matched Peaks

Show 5 entries

target_id	target_mz	target_rt	Feature	mz	rt	delta_mz	delta_mz_ppm
typed_1	506.5280	11.600	24617	506.5288	11.598	0.0008	1.5
typed_2	970.6110	9.700	21209	970.6115	9.678	0.0005	0.4

Showing 1 to 2 of 2 entries

Plot values distribution

Filtered m/z: 252

RT (min)

Output table – after Peak Filters

Show 5 entries

row ID	mz	rt	row ion mobility
818	2815	336.074296	1.0103563
819	2820	314.0921816	1.0123757
820	2814	284.1344503	1.0150422
821	2819	289.091359	1.0168543
822	2824	352.0481904	1.0176588

Showing 1 to 5 of 1,941 entries

Filtering results – Step 4 (Peak Filters)

Metric	Value
Features before	2597
Removed by m/z	252
Removed by rt	555
Removed by RMD	0
Removed by AMD	0
Matched target peaks	2
Removed by target m/z + rt	2
Total removed	656
Features after	1941

Note: a feature may be counted in multiple filter categories.

1. Set Up Peak Values Filters

Select desired values for filtering:

m/z, rt, mass defect (RMD, or AMD), or a list of target peaks to remove.

2. Set Up m/z/rt/AMD/RMD Values Filters

Specify threshold ranges for corresponding value.

3. Set Up Peaks to Remove/Keep

Specify action as keep or remove; provide target m/z and RT pairs. Enter comma-separated values manually, one pair per line, or upload a CSV file. Specify m/z and RT tolerances for matching.

4. Plot distribution of selected values

5. Apply or Discard Filtering Step



Tab “Peak Filters”: Display Area

MC

ADDITIONAL

Upload Data

Blank Filters

MS Filters

QC Filters

Peak Filters

Final Summary

About

Peak Filters

Enable filters:

m/z

rt

RMD

AMD

Target peak list

☒ m/z ≥

☐ m/z ≤

200

☒ rt ≥ (min)

☐ rt ≤ (min)

1

Action for matched target peaks:

☒ Remove matched peaks

☐ Keep only matched peaks

m/z tolerance type:

☒ Da

☐ ppm

m/z tolerance (Da)

0.005

rt tolerance (min)

0.05

Type target peaks:

506.528, 11.6

970.611, 9.7

Or upload target list (.csv)

Browse...

No file selected

CSV should contain mz and rt columns. If column names are not detected, the first two columns are treated as mz and rt.

Plot values distribution

☒ Show Peak plot panel

Apply

Clear

Input table

Show 5 entries

Search:

row ID	mz	rt	row ID	row ion mobility	row CCS	correlation group ID	annotation number
1	108	148.0277472	0.3691534			31	0
2	181	169.0462455	0.3699988			31	
4	231	216.951263				31	
5	43	234.96135				31	14
6	145	244.9475245	0.37269926			31	

Showing 1 to 5 of 2,597 entries

Previous

1

2

3

4

5

...

520

Next

Matched Peaks

Show 5 entries

Search:

target_id	target_mz	target_rt	mz	rt	delta_mz	delta_mz_ppm	
typed_1	506.5280	11.600	24	506.5288	11.598	0.0008	1.5
ty							0.4
1.4							1.2

Showing 1 to 5 of 2,597 entries

Previous

1

2

3

4

5

...

520

Next

Check values map:

m/z vs RT

1500

1000

500

0

3

6

9

12

RT (min)

Filtered m/z: 252

Filtered rt: 555

Total Filtered: 654

Output table — after Peak Filters

Show 5 entries

Search:

row ID	mz	rt	row ID	row ion mobility	row CCS	correlation group ID	annotation number
818	2815	336.074296	1.0103563			58	489
819	2820	314.0921816	1.0123757			58	489
820	2814	284.134450					490
821	2819	289.09139					490
822	2824	352.0481904					489

Showing 1 to 5 of 1,941 entries

Previous

1

2

3

4

5

...

389

Next

Filtering results — Step 4 (Peak Filters)

Metric	Value
Features before	2597
Removed by m/z	252
Removed by rt	555
Removed by RMD	0
Removed by AMD	0
Matched target peaks	2
Removed by target m/z + rt	2
Total removed	656
Features after	1941



Tab “Final Summary”: Control Panel



Upload Data

Blank Filters

MS Filters

QC Filters

Peak Filters

Final Summary

About

Compile final output

Compile output ?

Final peak table (.csv)

MGF Filtering

Filter MGF ☒ ?

Upload MGF file

Browse...

orbi_jimn_gms.mgf

Upload complete

Select ID column in Table:

row ID

MGF Feature ID field:

acquisitionNum

Filter MGF

Clear MGF

Success! Matched 321 spectra from your filtered table.

Download Filtered MGF

1

2

3

4

5

6

Filtering summary

- Dataset: Example
- Step 1 Blank Filters: APPLIED
- Step 2 MS Filters: APPLIED

1. Compile final filtered table

Clicking this button enables the table download and MGF filtering.

2. Download final table

3. Enable MGF filtering & upload .mgf file

4. Match peak ID between table and .mgf file

The feature identifier in the final peak table must correspond to the chosen spectrum identifier field inside the uploaded MGF. We recommend using the default columns unless you have specific requirements.

5. Filter or clear uploaded .mgf file

6. Download filtered .mgf file

819		489
821		490
822		489
829		495
830		495

Showing 1 to 5 of 1,083 entries

Previous

1

2

3

4

5

...

217

Next



Tab “Final Summary”: Display Area

[Upload Data](#)[Blank Filters](#)[MS Filters](#)[QC Filters](#)[Peak Filters](#)[Final Summary](#)[About](#)

Compile final output

[Compile output](#) ?[Final peak table \(.csv\)](#)

MGF Filtering

Filter MGF ☒ ?

Upload MGF file

[Browse...](#)

orbi_iimn_gnps.mgf

Upload complete

Select ID column in Table:

row ID

MGF Feature ID field:

acquisitionNum

[Filter MGF](#)[Clear MGF](#)

Filtering summary

- Dataset: Example
- Step 1 Blank Filters: APPLIED
- Step 2 MS Filters: APPLIED
- Step 3 QC Filters: not applied
- Step 4 Peak Filters: APPLIED
- Raw features: 6167
- Filtered features: 5084 (82.44%)
- Final features: 1083

1
Final Summary

Final table

Show entriesSearch:

	row ID	row m/z	row retention time	row ion mobility	row ion mobility unit	row CCS	correlation group ID	annotation network number
819	2820	314.0921816	1.0127777				58	489
821	2819	289.091359	1.016				58	490
822	2824	352.0481904	1.0176588				58	489
829	2893	275.1104506	1.0585195				60	495
830	2862	253.1291676	1.0596385				60	495

2
Final output table

Showing 1 to 5 of 1,083 entries

[Previous](#)[1](#)[2](#)[3](#)[4](#)[5](#)[...](#)[217](#)[Next](#)

Success! Matched 321 spectra from your filtered table.

3 **Matches in filtered .mgf**[Download Filtered MGF](#)



Tab “About” Overview

How to:

Select a section:

- Quick Start
- Upload Data
- Blank Filters
- MS Filters
- QC Filters
- Peak Filters
- Final Summary
- Troubleshooting
- Project Details

Troubleshooting

- **No sample columns:** your sample keywords don't match sample column names.
- **Parsing error:** check selected Data table type and compatibility with examples of accessible Peak Table data formats in the [GitHub](#) repository.
- **Disconnected from the server:** could be caused by memory limit, try to compile and run it locally. Instructions in the [GitHub](#) repository.

Navigate through the sections to get more information

by Plyushchenko I.V. | 2026 | [GitHub](#) | [Cite](#)