



About

HELLO!

HELLO MY NAME IS
PREMCHAND MAURYA IN THIS
PROJECT I HAVE UTILIZED SQL
QUARY TO SOLVE QUESTION
THAT REALATED TO PIZZA SELL





RETRIEVE THE TOTAL NUMBER OF ORDERS PLACED.

[Home](#)[About](#)[Contact](#)

```
SELECT
    COUNT(order_id) AS total_orders
FROM
    orders;
```

	total_orders
	21350



CALCULATED THE TOTAL REVENUE GENERATED PIZZA SALES.

[Home](#)[About](#)[Contact](#)

SELECT

```
ROUND(SUM(order_details.quantity * pizzas.price),  
      2) AS total_sales
```

FROM

```
order_details
```

JOIN

```
pizzas ON pizzas.pizza_id = order_details.pizza_id;
```

Result Grid

	total_sales
▶	817860.05



HIGHHEST PRICE OF PIZZA

[Home](#)[About](#)[Contact](#)

```
SELECT
    pizza_types.name, pizzas.price
FROM
    pizza_types
    JOIN
        pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
ORDER BY pizzas.price DESC
LIMIT 1;
```

	name	price
▶	The Greek Pizza	35.95



IDENTIFY THE MOST COMMON PIZZA SIZE ORDERS

[Home](#)[About](#)[Contact](#)

```
SELECT
    pizzas.size,
    COUNT(order_details.order_details_id) AS order_count
FROM
    pizzas
    JOIN
    order_details ON pizzas.pizza_id = order_details.pizza_id
GROUP BY pizzas.size
ORDER BY order_count DESC;
```

Result Grid				
	size	order_count		
▶	L	18526		
	M	15385		
	S	14137		
	XL	544		
	XXL	28		



LIST THE TOP 5 MOST ORDERED PIZZA TYPES ALONG WITH THEIR QUANTITIES.

[Home](#)[About](#)[Contact](#)

```
SELECT
    pizza_types.name, SUM(order_details.quantity) AS quantity
FROM
    pizza_types
    JOIN
    pizzas ON pizza_types.pizza_type_id = pizzas.pizza_type_id
    JOIN
    order_details ON order_details.pizza_id = pizzas.pizza_id
GROUP BY pizza_types.name
ORDER BY quantity DESC
LIMIT 5;
```

[Result Grid](#)

Filter Rows:

	name	quantity
▶	The Classic Deluxe Pizza	2453
	The Barbecue Chicken Pizza	2432
	The Hawaiian Pizza	2422
	The Pepperoni Pizza	2418
	The Thai Chicken Pizza	2371