Отчет по лабораторной работе №5 по курсу Разработка интернет приложений

| ИСПОЛНИТЕЛЬ: | | |
|-----------------------|----------|------------|
| студент группы ИУ5-52 | | |
| | (подпись | b) |
| Матвеева П.Р. | " " | 2016 г |

Оглавление

| 1. Описание задания лабораторной работы | 3 |
|---|---|
| 2. Модули | 3 |
| | |
| 3. Результаты работы. | 9 |

1. Описание задания лабораторной работы.

В этой ЛР вы создадите Django-проект, покажете пользователю статичную страницу, познакомитесь с конструкциями шаблонизаторов: переменные, теги, наследование шаблонов.

- Создать проект
- Реализовать view, в которых генерируются html-страницы
- В шаблонах должны быть использованы рассмотренные конструкции: переменные, вложенные значения, циклы, условия
- Все шаблоны должны расширять базовый шаблон
- Для элементов списка использовать тег include
- По нажатии на элемент списка должна открываться страница информации об элементе
- Для верстки необходимо использовать Bootstrap

'id': '123521',

2. Модули.

```
shop/views.py
from django.shortcuts import render
def index(request):
    return render (request, 'index.html', {'var name': "Полина"})
def shopping(request):
    data = [
        {
            'name': 'New collection',
            'description': 'Check our new models!'
        },
            'name': "Basics",
            'description': 'Models that are always relevant.'
        },
            'name': 'Sales',
            'description': "The best promotions and the biggest discounts.",
    return render(request, 'product.html', context={'menu':data})
def search new(request):
    data_search_n = [
            'name': 'Product 1',
            'id': '123321',
            'description': 'text about 1',
            'image': 'https://img.corsocomo.com/image/cache/data/w/19-422-1602-12/19-
422-1602-12-630x630.jpg'
        },
            'name': 'Product 2',
            'id': '122321',
            'description': 'text about product 2',
            'image': 'https://img.corsocomo.com/image/cache/data/w/05-0002-16/05-0002-
16-1000x1000.jpg'
        },
            'name': 'Product 3',
```

```
'description': 'text about product 3',
            'image': 'https://img.corsocomo.com/image/cache/data/w/17-669-02-57-35/17-
669-02-57-35-630x630.jpg'
       }
    if len(data search n) == 0:
        return render(request, 'search-empty.html')
        return render(request, 'search.html', context={'search':data search n})
def search basic(request):
    data_search_b = [
            'name': 'Product 1',
            'id': '127621',
            'description': 'text about 1',
            'image':'http://vsezapolceny.ru/sites/default/files/zhenskaya-domashnyaya-
obuv/funny-mens-plush-slippers-2015-indoor-shoes-house-cute-women-slippers-emoji-shoes-
warm-house-slipper.jpg'
        }
    if len(data search b) == 0:
        return render(request, 'search-empty.html')
    else:
        return render(request, 'search.html', context={'search':data_search_b})
def search sale(request):
    data s=[]
    if len(data s) == 0:
        return render(request, 'search-empty.html')
        return render(request, 'search.html', context={'search':data s})
shop/urls.py
from django.conf.urls import url
from . import views
urlpatterns = [
    url(r'^$', views.index, name='index'),
    url(r'^shop/', views.shopping, name='shopping'),
    url(r'^search-new/', views.search_new, name='search_new'),
    url(r'^search-basic/', views.search_basic, name='search_basic'),
    url(r'^search-sale/', views.search sale, name='search sale')
1
urls.py
"""mysite URL Configuration
The `urlpatterns` list routes URLs to views. For more information please see:
   https://docs.djangoproject.com/en/1.10/topics/http/urls/
Examples:
Function views
    1. Add an import: from my app import views
    2. Add a URL to urlpatterns: url(r'\$', views.home, name='home')
Class-based views
    1. Add an import: from other_app.views import Home
    2. Add a URL to urlpatterns: url(r'^$', Home.as view(), name='home')
Including another URLconf
    1. Import the include() function: from django.conf.urls import url, include
    2. Add a URL to urlpatterns: url(r'^blog/', include('blog.urls'))
```

```
from django.conf.urls import include, url
from django.conf.urls.static import static
from django.conf import settings
from django.contrib import admin
urlpatterns = [
    url(r'^admin/', admin.site.urls),
    url(r'', include('shop.urls')),
    url(r'^shop/', include('shop.urls')),
    url(r'^search-new/', include('shop.urls')),
    url(r'^search-basic/', include('shop.urls')),
url(r'^search-sale/', include('shop.urls')),
] + static(settings.STATIC_URL, document_root=settings.STATIC_ROOT)
Шаблоны
base.html
{% load staticfiles %}
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <title>{% block title %}{% endblock %}</title>
    <link rel="stylesheet" type="text/css" href="/static/css/bootstrap.css">
    <link href="/static/css/jumbotron-narrow.css" rel="stylesheet">
    <link href="https://fonts.googleapis.com/css?family=Lobster" rel="stylesheet">
    <style>
    body {
        background: url(/static/3.jpg) no-repeat center center fixed;
        -webkit-background-size: cover;
        -moz-background-size: cover;
        -o-background-size: cover;
        background-size: cover;
   }
        h3 {
            font-family: 'Lobster';
            font-size: xx-large;
  </style>
</head>
<body>
    <div class="container-fluid">
        <style>
             .link1 {
                font-size: 40px;
                 color: black;
        </style>
        <div class="text-center">
            <h3><a href="/" class="link1"> Fashion is our profession </a></h3>
        </div>
    </div>
{% block content %}{% endblock %}
</body>
</html>
index.html
{% extends 'base.html' %}
{% block title %} Welcome to our shop! {% endblock %}
{% block content %}
    <div class="jumbotron">
```

```
Dear {{ var name }}! We are glad to see you in our store. Have
a good shopping! Click on the link below to begin. 
        <a href="/shop" class="btn btn-primary" role="button" >Go shopping</a>
    </div>
{% endblock %}
product.html
{% extends 'base.html' %}
{% block title %}Our products{% endblock %}
{% block content %}
    <div class="row marketing">
        {% for category in menu %}
            <div class="col-lg-4" >
                    <div class="panel panel-default">
                         <div class="panel-body bg-info">
                    {% if category.name == 'Sales' %}
                       <style>
                            .s1 {
                               color: #c12e2a;
                                text-align: center;
                                font-weight: 700;
                        </style>
                        <h4>{{ category.name }}</h4>
                            <div class="caption">
                                {{ category.description }}
                                <div class="s2">
                                <a href="/search-sale" class="btn btn-primary"
role="button">{% include 'search f.html' with field=category.name %}</a>
                                \overline{<}/div>
                            </div>
                    {% elif category.name != 'Sales' %}
                    <style>
                            .s2 {
                                text-align: center;
                                font-weight: 700;
                        </style>
                    <h4> {{ category.name }}</h4>
                            <div class="caption">
                                {{ category.description }}
                                <div class="s2">
                                    {% if category.name == 'New collection' %}
                                        <a href="/search-new" class="btn btn-primary"</pre>
role="button">{% include 'search f.html' with field=category.name %}</a>
                                    {% elif category.name != 'New Collection' %}
                                        <a href="/search-basic" class="btn btn-primary"</pre>
role="button">{% include 'search f.html' with field=category.name %}</a>
                                    {% endif %}
                                </div>
                            </div>
                    {% endif %}
                    </div>
                    </div>
            </div>
        {% endfor %}
    </div>
{% endblock %}
```

```
{% extends 'base.html' %}
{% block title %}Search{% endblock %}
{% block content %}
    <div class="container-fluid">
        <div class="blog-header">
            <h1 class="blog-title col-lg-offset-3"><b>Search results</b></h1>
        </div>
        <div class="row">
            <div class="col-lg-8 blog-main">
                {% for item in search %}
                    <section class="panel panel-search">
                    <div class="panel-heading bg-info">
                        <div class="panel-title">
                            <h4> {{ item.name}}<small> item no:{{ item.id}}</small>
</h4>
                        </div>
                    </div>
                    <div class="panel-body ">
                        <div class="row">
                            <div class="col-lg-4">
                                <img src="{{ item.image }}" width="100%"/>
                            </div>
                            <div class="col-lg-4">
                                {{ item.description }}
                            </div>
                        </div>
                    </div>
                </section>
                {% endfor %}
           </div>
            <div class="col-lg-3 blog-sidebar">
                <section class="panel panel-search">
                    <div class="panel-heading bg-info">
                       <div class="panel-title">
                            <h3>Search</h3>
                        </div>
                    </div>
                    <h4><div class="col-lg-offset-1">Filters</div></h4>
                    <a href="#">Price low to high</a>
                        <a href="#">Price high to low</a>
                        <a href="#">Popularity</a>
                    <div class="panel-body bg-info">
                        <div class="input-group">
                            <form data-key="2af70d95e12e1e4e9344fa7468f8213d00434d93"</pre>
action="search" method="get" style="margin-bottom:10px;">
                            <span class="input-group-btn">
                                    <input type="text" class="form-control"</pre>
name="query" placeholder="Enter here" value="" />
                                   <button type="submit" class="btn btn-</pre>
default">Find</button>
                                </span>
                                </form>
                            </div>
                        </div>
                </section>
            </div>
        </div>
    </div>
{% endblock %}
```

```
{% extends 'base.html' %}
{% block title %}Search{% endblock %}
{% block content %}
    <div class="container-fluid">
       <div class="blog-header">
            <h1 class="blog-title col-lg-offset-3"><b>Search results</b></h1>
       <div class="row">
           <div class="col-lq-8 blog-main">
               <h1 class="blog-title col-lg-offset-4">There are no items:(</h1>
           </div>
           <div class="col-lg-3 blog-sidebar">
               <section class="panel panel-search">
                   <div class="panel-heading bg-info">
                       <div class="panel-title">
                           <h3>Search</h3>
                       </div>
                   </div>
                   <h4><div class="col-lg-offset-1">Filters</div></h4>
                   <a href="#">Price low to high</a>
                       <a href="#">Price high to low</a>
                       <a href="#">Popularity</a>
                   <div class="panel-body bg-info">
                       <div class="input-group">
                           <form data-key="2af70d95e12e1e4e9344fa7468f8213d00434d93"</pre>
action="search" method="get" style="margin-bottom:10px;">
                           <span class="input-group-btn">
                                   <input type="text" class="form-control"</pre>
name="query" placeholder="Enter here" value="" />
                                   <button type="submit" class="btn btn-</pre>
default">Find</button>
                               </span>
                               </form>
                           </div>
                       </div>
               </section>
           </div>
       </div>
   </div>
{% endblock %}
search-f.html
Find yours in {{ field }}!
```

3. Результаты.





