

Modular Adaptive Data Node for Dynamic Value Systems

Chapter 2

Literature Review

2.1 Introduction

The theoretical and technological foundations of the Modular Adaptive Data Node (MADN) are rooted in the shift away from centralized computing architectures toward localized, decentralized models [24, 26]. This chapter explores the theoretical background of edge computing, distributed networks, precision agriculture, embedded computer vision, and resilient commerce [24, 26]. In doing so, it situates MADN within a broader effort to design intelligent systems that remain functional, adaptive, and context-aware in environments with limited infrastructure [34]. It also establishes the conceptual basis for understanding why locally coordinated computing can offer a more resilient alternative to cloud-dependent service delivery in underserved settings [35]. More specifically, the chapter evaluates the literature through the interconnected lenses of latency, resilience, scalability, affordability, and contextual suitability, since these criteria determine whether advanced computational systems remain practically usable in resource-constrained environments [26, 34, 35, 37]. It critically reviews existing technologies that attempt to address data-driven challenges in agriculture, public security, and commerce, and explicitly identifies the technological gaps that the MADN framework aims to fill [25, 27].

2.2 Theoretical Background

The conceptualization of the MADN framework relies on several key technological paradigms:

- **Edge Computing and the Internet of Things (IoT):** Edge computing and IoT offer a pathway to bring data processing closer to the source of data generation [8, 31]. By shifting the computational burden from fragile external cloud networks to a resilient, community-driven

edge ecosystem, systems can dynamically process complex data locally [1, 2, 18].

- **Distributed and Latent Computing:** The proliferation of personal computing devices, such as smartphones, tablets, and laptops, has transformed the digital landscape [28]. For most of the day, the processors inside these personal devices sit idle, representing a latent, decentralized computing capacity that is currently wasted [3, 29]. By creating a collaborative network where idle consumer devices can temporarily lend their processing power, communities can essentially build their own localized micro-clouds [9, 32].
- **Embedded Machine Learning:** The deployment of lightweight machine learning models at the edge, such as TensorFlow Lite for agricultural yield prediction and OpenCV for object recognition, forms the basis for extracting actionable intelligence without cloud dependency [19, 20, 21].

Although these paradigms are closely related, the literature distinguishes them in analytically important ways. Edge computing emphasizes placing computation near data sources to reduce latency and improve responsiveness; distributed computing concerns the coordination of multiple computational nodes; latent computing focuses on mobilizing otherwise idle devices; and hybrid edge–cloud models address how these resources can be orchestrated across different infrastructure layers [8, 9, 16, 31, 32]. Recognizing these distinctions is important for MADN because the framework does not depend on a single paradigm in isolation. Rather, it combines locality of processing, cooperation among heterogeneous devices, opportunistic use of idle resources, and selective access to cloud services into a unified architectural logic [16, 31, 33].

From this perspective, MADN should be understood not as an edge-only architecture, but as a hybrid edge–cloud system operating across a broader computing continuum. Its primary logic remains local and edge-oriented so that latency-sensitive, connectivity-critical, and context-dependent functions can continue operating close to users and data sources. However, whenever network conditions, bandwidth, and service availability permit, the framework can also leverage cloud infrastructure for computationally intensive analytics, long-term data retention, cross-node synchronization, model training, and elastic scaling of services beyond the limitations of local hardware. This hybrid orientation is important because cloud platforms provide rapid elasticity, resource pooling, and on-demand access to high-capacity compute and storage resources, while edge layers provide responsiveness, locality, and operational resilience under constrained conditions [31, 33, 36, 37]. In practical terms, this means that tasks such as immediate sensing, local inference, temporary data buffering, and continuity of transactions are better retained near the edge, whereas aggregated analytics, historical archiving, multi-node synchronization, and computationally intensive model refinement may be shifted to cloud infrastructure when connectivity conditions are favorable [6, 12, 19, 31, 36, 37]. Accordingly, the architectural value of MADN lies not in rejecting cloud computing, but in selectively integrating cloud capabilities when they enhance flexibility, coordination, and overall system capability without undermining offline resilience [31, 33, 37].

In innovation studies, a technological paradigm refers to a shared model of problem framing and

solution search that channels technical development along particular trajectories, while ecosystem scholarship emphasizes the interdependent constellation of actors, artifacts, and complementarities through which value is created and captured [38, 39]. Read together, these perspectives suggest that a technological ecosystem can be understood as the organizational and material instantiation of a paradigm, because the rules, interfaces, and complementarities of an ecosystem shape what kinds of innovation become visible, feasible, and scalable [38, 39, 45]. Mature platform ecosystems illustrate this dynamic clearly: ecosystems such as Apple’s App Store and Android provide not only distribution channels but also development rules, governance mechanisms, and technical dependencies that condition how developers search for solutions and bring them to market [39, 40, 41].

In the case of edge computing, the search space is similarly conditioned by the infrastructural logic of locality, latency sensitivity, and constrained device resources [31, 33, 37]. Developers working in edge-oriented environments therefore tend to prioritize model compression, energy-aware execution, and hardware-constrained deployment over default reliance on centralized offloading, especially when targeting devices such as Raspberry Pi Pico W-class hardware or GPU-oriented environments such as CUDA-enabled systems [19, 20, 42, 43]. In this sense, ecosystems do not merely host innovation; they delimit and enable it by defining the boundary conditions within which optimization and interoperability must occur [38, 39, 45].

MADN can therefore be conceptualized as an architectural bridge across heterogeneous and partially closed digital ecosystems whose governance structures channel innovation through platform-specific rules, interfaces, and boundary resources [39, 45, 46]. Rather than assuming that openness already exists, the framework can leverage APIs and SDKs as practical mechanisms for negotiated interoperability, because these interfaces increasingly structure how external actors access platform capabilities, coordinate services, and extend existing functionality [43, 44, 46]. Official development environments such as NVIDIA CUDA and Samsung Knox exemplify how contemporary interfaces have evolved beyond simple data exchange toward deeper forms of controlled integration with hardware, security, and management layers [43, 44]. For MADN, this means interoperability should be pursued not as abstraction detached from existing platforms, but as modular integration that can operate within platform logics while preserving local autonomy and cross-ecosystem coordination [33, 37, 46].

At the same time, platform and ecosystem research consistently shows that digital systems are socio-technical arrangements whose technical architectures are inseparable from governance, incentives, and patterns of human coordination [39, 45]. Improvements in sensing, data collection, APIs, and computational methods can feed back into subsequent rounds of redesign, making system evolution increasingly iterative and path-dependent rather than purely linear [19, 21, 46]. Accordingly, MADN should be viewed not only as a technical interoperability mechanism but also as a socio-technical intervention aimed at navigating fragmentation, improving local adaptability, and aligning digital infrastructure with contextual social and economic realities [34, 35, 45].

2.3 Review of Existing Systems and Technologies

Current technological interventions designed to solve localized challenges predominantly utilize centralized models:

- **Cloud-Reliant Precision Agriculture:** Traditional agricultural optimization platforms process generalized regional data on remote servers [22]. While these models are technically robust, they require constant internet connectivity to transmit raw environmental metrics and receive actionable planting or irrigation insights back from the cloud [4].
- **Centralized Public Security Surveillance:** Existing security and perimeter defense technologies heavily rely on traditional CCTV systems [23]. These architectures transmit continuous, high-bandwidth video feeds to central servers for storage and processing, relying on constant internet uplinks to function effectively [6, 23].
- **Cloud-Dependent Point-of-Sale (POS) Systems:** Modern commercial trade and digital inventory tools are engineered to synchronize with remote databases. Informal and small-scale vendors currently utilize POS systems that demand stable internet connections to validate transactions and update stock [7, 12].

Taken together, these systems demonstrate that contemporary digital interventions are often technically sophisticated yet operationally dependent on assumptions of stable connectivity, persistent cloud access, and adequate financial capacity for data-intensive services [4, 7, 22, 23]. This creates a tension between what such systems can achieve under ideal conditions and what communities can sustainably use under infrastructural constraint. The literature therefore suggests that the core limitation is not the absence of advanced digital tools themselves, but the persistence of architectural models whose success depends on infrastructural conditions that cannot be assumed in the target setting [14, 30, 33, 35].

2.4 Contextual Challenges

For MADN, the literature is most meaningful when interpreted against the realities of the environments in which the framework is intended to operate. In contexts such as Bulawayo and Tsholotsho, unreliable connectivity, intermittent power, constrained bandwidth, and the high relative cost of cloud-reliant services shape not only technical performance but also whether a digital system can be trusted, sustained, and routinely adopted [14, 30]. These conditions make it insufficient to evaluate intelligent systems only in terms of algorithmic capability or centralized processing efficiency. Instead, suitability depends on whether computation can degrade gracefully, preserve core functionality during outages, and exploit local resources before resorting to external infrastructure [33, 34, 35].

A further challenge is that resource-constrained environments are not merely low-capacity versions of well-connected settings; they often require different architectural priorities altogether. Systems designed primarily for remote processing may optimize for scale and centralized coordination, yet communities facing unstable connectivity require architectures that prioritize locality, resilience, recoverability, and selective synchronization [16, 35, 37]. This distinction is important because it shifts the design question from how to maximize cloud dependence to how to balance local autonomy with opportunistic access to wider computational resources when conditions allow [31, 36, 37]. It also suggests that success should be measured not only by processing throughput or model sophistication, but by whether a system remains affordable, maintainable, trustworthy, and functionally useful under ordinary infrastructural stress [13, 14, 30, 35].

2.5 Gaps in Existing Solutions

A critical review of the existing technological landscape reveals significant shortcomings when applied to resource-constrained environments:

- **Vulnerability to Infrastructure Realities:** Existing technological interventions rely heavily on expensive, centralized cloud computing architectures [13]. These traditional systems are ill-suited for local socio-economic and infrastructure realities, often failing due to intermittent internet access and high data costs [14]. Cloud-dependent paradigms often falter in regions like Bulawayo and Tsholotsho due to latency issues and connectivity blackouts [4, 30].
- **Wasted Local Compute Resources:** Despite the high penetration of smartphones, laptops, and other personal computing devices in Bulawayo and Tsholotsho, a vast reservoir of local computational power remains idle and unutilized for most of the day [10]. Currently, there is no viable, localized framework designed to seamlessly aggregate and orchestrate the latent processing capacity of ubiquitous personal devices to solve regional issues [15].
- **Lack of Microclimate Specificity:** In agriculture, existing solutions suffer from a lack of localized, microclimate-specific data processing for yield optimization [11]. Farmers require precise, microclimate-specific insights to enhance crop yields, rather than generalized regional data [5, 22].
- **Absence of Offline Operational Resilience:** Public security lacks intelligent, real-time edge processing for perimeter surveillance that does not rely on constant internet uplinks [6, 12]. Furthermore, commercial vendors struggle with transaction inefficiencies and inventory management due to unreliable connectivity and the absence of resilient POS systems that maintain transaction integrity during blackouts [7, 12].

2.6 Implications for MADN Design

The reviewed literature does more than identify a technological gap; it clarifies the architectural principles that MADN must embody. First, the framework must preserve *local operational continuity*, ensuring that essential sensing, inference, coordination, and transaction functions remain available even when internet access is unstable or absent [6, 12, 35]. Second, it must support *hybrid edge–cloud adaptability*, allowing tasks to be retained locally when latency, privacy, or connectivity constraints dominate, while still offloading appropriate workloads to cloud infrastructure when elasticity, storage, or large-scale coordination become advantageous [31, 33, 36, 37]. Third, it must enable *distributed utilization of latent resources*, so that idle consumer devices can contribute meaningful computational value within a localized network rather than leaving communities wholly dependent on external infrastructure [3, 15, 32].

In design terms, these implications suggest that MADN should not be framed merely as a software platform, but as a resilient orchestration layer across heterogeneous devices, services, and connectivity states. Its novelty lies in combining edge intelligence, decentralized participation, and selective cloud augmentation into a system that is responsive to local conditions while still capable of scaling outward when infrastructure permits [16, 17, 33, 37]. This interpretation positions MADN as a practical response to the central limitation identified across the literature: the mismatch between advanced digital systems and the environments in which they are expected to operate. It further implies that orchestration is not a secondary implementation concern, but a core design principle through which MADN can decide what should execute locally, what should be shared across nearby devices, and what should be escalated to cloud infrastructure under favorable conditions [16, 31, 33, 37].

2.7 Summary of Literature Review

The literature demonstrates that while complex data-driven solutions exist for agriculture, security, and commerce, their reliance on centralized cloud infrastructures renders them largely ineffective for regions experiencing intermittent connectivity and high bandwidth costs [4, 30]. At the same time, the reviewed studies show that edge intelligence, distributed computing, embedded machine learning, and cloud elasticity are not competing paradigms, but complementary components of a more adaptive computational architecture [26, 31, 33, 37]. Without a modular system capable of coordinating these components while utilizing decentralized local power, communities in Bulawayo and Tsholotsho remain dependent on fragile external infrastructure [16]. This underscores the critical necessity for a localized yet hybrid edge–cloud network—specifically, the Modular Adaptive Data Node (MADN)—to bridge the gap between idle local hardware, constrained infrastructure, and the pressing computational demands of the region [17, 32, 33]. In this sense, the chapter establishes not only the relevance of MADN, but also the design logic that should guide the chapters

that follow: computation must be local when necessary, collaborative where possible, and cloud-augmented when advantageous [16, 31, 33, 37].

Bibliography

- [1] E. Ahmed, A. Ahmed, I. Yaqoob, J. Shuja, A. Gani, M. Imran, and M. Shoaib, “Bringing Computation Closer toward the User Network: Is Edge Computing the Solution?,” *IEEE Communications Magazine*, vol. 55, no. 11, pp. 138–144, Nov. 2017, doi: 10.1109/MCOM.2017.1700120.
- [2] T. Taleb, K. Samdanis, B. Mada, H. Flinck, S. Dutta, and D. Sabella, “On Multi-Access Edge Computing: A Survey of the Emerging 5G Network Edge Cloud Architecture and Orchestration,” *IEEE Communications Surveys & Tutorials*, vol. 19, no. 3, pp. 1657–1681, 3rd Quart., 2017, doi: 10.1109/COMST.2017.2705720.
- [3] M. Y. Arslan, I. Singh, S. Singh, H. V. Madhyastha, K. Sundaresan, and S. V. Krishnamurthy, “Computing while Charging: Building a Distributed Computing Infrastructure Using Smartphones,” in *Proc. 8th Int. Conf. Emerging Netw. Experiments Technol. (CoNEXT)*, Nice, France, Dec. 2012, pp. 193–204, doi: 10.1145/2413176.2413199.
- [4] L. Tan, “Cloud-based Decision Support and Automation for Precision Agriculture in Orchards,” *IFAC-PapersOnLine*, vol. 49, no. 16, pp. 330–335, 2016, doi: 10.1016/j.ifacol.2016.10.061.
- [5] S. R. Schultze, M. N. Campbell, S. Walley, K. Pfeiffer, and B. Wilkins, “Exploration of Sub-Field Microclimates and Winter Temperatures: Implications for Precision Agriculture,” *International Journal of Biometeorology*, vol. 65, no. 7, pp. 1043–1052, Jul. 2021, doi: 10.1007/s00484-021-02086-0.
- [6] A. C. Cob-Parro, C. Losada-Gutiérrez, M. Marrón-Romera, A. Gardel-Vicente, and I. Bravo-Muñoz, “Smart Video Surveillance System Based on Edge Computing,” *Sensors*, vol. 21, no. 9, Art. no. 2958, Apr. 2021, doi: 10.3390/s21092958.
- [7] G. T. Li and L. K. Lau, “Mobile Point of Sales System with Cloud-Based Inventory Management for Micro and Small Enterprises,” in *Proc. World Congr. Eng. Comput. Sci. (WCECS)*, San Francisco, CA, USA, Oct. 2015, pp. 664–669.
- [8] K.-D. Kang, D. S. Menascé, G. Küçük, T. Zhu, and P. Yi, “Edge Computing in the Internet of Things,” *International Journal of Distributed Sensor Networks*, vol. 13, no. 11, Nov. 2017, Art. no. 1550147717732446, doi: 10.1177/1550147717732446.

- [9] M. Satyanarayanan, P. Bahl, R. Cáceres, and N. Davies, “The Case for VM-Based Cloudlets in Mobile Computing,” *IEEE Pervasive Computing*, vol. 8, no. 4, pp. 14–23, Oct.–Dec. 2009, doi: 10.1109/MPRV.2009.82.
- [10] S. Hove, “Zimbabwe’s Mobile Penetration Rate Surges to 116.37% as Active Mobile Subscriptions Rise to 18.91 Million,” *TechZim*, Sept. 30, 2024.
- [11] J. Everingham, J. Sexton, D. Skocaj, and H. Inman-Bamber, “Accurate Prediction of Sugarcane Yield Using a Random Forest Algorithm,” *Agronomy for Sustainable Development*, vol. 36, no. 2, Art. no. 27, May 2016, doi: 10.1007/s13593-016-0364-z.
- [12] S. Kochar, H. Nikam, R. Tripathi, and A. Vidhate, “Offline Transaction System,” *ITM Web of Conferences*, vol. 44, Art. no. 03072, 2022, doi: 10.1051/itmconf/20224403072.
- [13] K. M. Khan, J. Han, and H. K. Zhang, “Hidden Costs in Cloud Computing,” in *Proc. IEEE 6th Int. Conf. Cloud Comput.*, Santa Clara, CA, USA, June–July 2013, pp. 652–659, doi: 10.1109/CLOUD.2013.97.
- [14] Freedom House, “Freedom on the Net 2024: Zimbabwe,” Washington, DC, USA, 2024.
- [15] S. M. Otero Corrales and K. Fach Gomez, “Volunteer Computing for Scalability in Fog-Computing Systems: A Systematic Review,” *PeerJ Computer Science*, vol. 10, Art. no. e2542, 2024, doi: 10.7717/peerj-cs.2542.
- [16] A. Al-Hawawreh, M. C. Yuen, A. Shahabi, Y. Ma, M. Moh, and T.-S. Moh, “A Decentralized Collaborative Framework for Scalable Edge AI: A Systematic Approach,” *Sensors*, vol. 24, no. 1, Art. no. 236, Jan. 2024, doi: 10.3390/s24010236.
- [17] J. Chen and X. Ran, “Deep Learning with Edge Computing: A Review,” *Proceedings of the IEEE*, vol. 107, no. 8, pp. 1655–1674, Aug. 2019, doi: 10.1109/JPROC.2019.2921977.
- [18] G. Rjoub, O. A. Wahab, J. Bentahar, and A. A. Bataineh, “Distributed Data Stream Processing and Edge Computing: A Survey on Resource Elasticity and Future Directions,” *Sensors*, vol. 21, no. 16, Art. no. 5348, Aug. 2021, doi: 10.3390/s21165348.
- [19] E. E. Ogiemwonyi, M. Bodunde, O. O. Obe, and V. O. Matthews, “On-Device AI for Climate-Resilient Farming: Lightweight Models on Smart Agricultural Devices,” *Scientific Reports*, vol. 15, Art. no. 18745, 2025, doi: 10.1038/s41598-025-03389-z.
- [20] M. Singha and S. K. Das, “Real-Time and Accurate Object Detection on Edge Device with TensorFlow Lite,” *Journal of Physics: Conference Series*, vol. 1651, no. 1, Art. no. 012114, Oct. 2020, doi: 10.1088/1742-6596/1651/1/012114.
- [21] S. Kumar, A. A. Khan, K. P. Singh, and T. Shankar, “Advancing Smart Systems with TinyML: A Review of Applications, Challenges, and Future Prospects,” *IEEE Access*, vol. 13, pp. 1924–1954, 2025, doi: 10.1109/ACCESS.2024.3525393.

- [22] P. K. Sethy, A. Kumar Barik, and S. K. Rath, “A Cloud Enabled Crop Recommendation Platform for Machine Learning Driven Precision Farming,” *Computers and Electronics in Agriculture*, vol. 216, Art. no. 108527, Jan. 2024, doi: 10.1016/j.compag.2023.108527.
- [23] H. Xu, L. Wang, Z. Liu, and Y. Li, “A Privacy-Preserving Video Surveillance System Based on Edge Computing,” *IEEE Access*, vol. 9, pp. 112055–112067, 2021, doi: 10.1109/ACCESS.2021.3103010.
- [24] S. S. Gill, M. Xu, P. Garraghan, R. Bahsoon, A. K. Kar, S. Kaddoum, T. Baker, and O. Rana, “Edge Computing for Smart Agriculture: Opportunities, Challenges, and Future Directions,” *IEEE/CAA Journal of Automatica Sinica*, vol. 9, no. 5, pp. 908–929, May 2022, doi: 10.1109/JAS.2022.105690.
- [25] B. Ahmed, H. Shabbir, S. R. Naqvi, and L. Peng, “Smart Agriculture: Current State, Opportunities and Challenges,” *IEEE Access*, vol. 12, pp. 140762–140802, 2024, doi: 10.1109/ACCESS.2024.3471647.
- [26] G. S. Aujla, A. Singh, S. K. Garg, K. K. R. Choo, and R. Buyya, “Distributed Intelligence for Edge-to-Cloud Computing: A Systematic Review,” *ACM Computing Surveys*, vol. 56, no. 10, Art. no. 253, 2024, doi: 10.1145/3649449.
- [27] A. R. Matin, S. Kamal, M. M. U. Rathore, T. Amgoth, and G. Srivastava, “A Review of Smart Agriculture Using Internet of Things, Artificial Intelligence, and Computer Vision,” *Sensors*, vol. 22, no. 23, Art. no. 9309, Dec. 2022, doi: 10.3390/s22239309.
- [28] J. C. West, “Why Your Company Needs More Mobile Apps,” *Engineering Management Review*, vol. 43, no. 2, pp. 12–15, June 2015, doi: 10.1109/EMR.2015.2437354.
- [29] H. Cui and A. R. Butt, “The Challenge of Exploiting Idle System Resources in a Virtually Integrated End-to-End Computing Environment,” in *Proc. USENIX Conf. File Storage Technol. (FAST)*, San Jose, CA, USA, Feb. 2007, pp. 33–48.
- [30] Postal and Telecommunications Regulatory Authority of Zimbabwe (POTRAZ), “Third Quarter 2024 Abridged Sector Performance Report,” Harare, Zimbabwe, 2025.
- [31] F. C. Andriulo, M. Fiore, M. Mongiello, E. Traversa, and V. Zizzo, “Edge Computing and Cloud Computing for Internet of Things: A Review,” *Informatics*, vol. 11, no. 4, Art. no. 71, Sept. 2024, doi: 10.3390/informatics11040071.
- [32] M. E. Hirsch, C. Mateos, and A. Zunino, “Augmenting Computing Capabilities at the Edge by Jointly Exploiting Mobile Devices: A Survey,” *Future Generation Computer Systems*, vol. 88, pp. 644–662, Nov. 2018, doi: 10.1016/j.future.2018.06.005.
- [33] D. Rosendo, A. Costan, P. Valduriez, and G. Antoniu, “Distributed Intelligence on the Edge-to-Cloud Continuum: A Systematic Literature Review,” *Journal of Parallel and Distributed Computing*, vol. 166, pp. 71–94, Aug. 2022, doi: 10.1016/j.jpdc.2022.04.004.

- [34] H.-L. Truong, T. Truong-Huu, and T.-D. Cao, “Making Distributed Edge Machine Learning for Resource-Constrained Communities and Environments Smarter: Contexts and Challenges,” *Journal of Reliable Intelligent Environments*, vol. 9, pp. 119–134, June 2023, doi: 10.1007/s40860-022-00176-3.
- [35] S. Bagchi, M.-B. Siddiqui, P. Wood, and H. Zhang, “Dependability in Edge Computing,” *Communications of the ACM*, vol. 63, no. 1, pp. 58–66, Jan. 2020, doi: 10.1145/3364118.
- [36] P. Mell and T. Grance, “The NIST Definition of Cloud Computing,” NIST Special Publication 800-145, Gaithersburg, MD, USA, Sept. 2011, doi: 10.6028/NIST.SP.800-145.
- [37] D. Balouek-Thomert, E. G. Renart, A. R. Zamani, A. Simonet, and M. Parashar, “Towards a Computing Continuum: Enabling Edge-to-Cloud Integration for Data-Driven Workflows,” *The Journal of Supercomputing*, vol. 76, pp. 9020–9044, Nov. 2020, doi: 10.1007/s11227-019-03102-3.
- [38] G. Dosi, “Technological Paradigms and Technological Trajectories: A Suggested Interpretation of the Determinants and Directions of Technical Change,” *Research Policy*, vol. 11, no. 3, pp. 147–162, June 1982, doi: 10.1016/0048-7333(82)90016-6.
- [39] M. de Reuver, C. Sørensen, and R. C. Basole, “The Digital Platform: A Research Agenda,” *Journal of Information Technology*, vol. 33, no. 2, pp. 124–135, June 2018, doi: 10.1057/s41265-016-0033-3.
- [40] Apple Developer, “App Store Features,” Apple Inc., Cupertino, CA, USA, 2026.
- [41] Android Developers, “Android Platform,” Google LLC, Mountain View, CA, USA, 2026.
- [42] Raspberry Pi Ltd, “Pico-Series Microcontrollers,” Raspberry Pi Documentation, Cambridge, U.K., 2026.
- [43] NVIDIA, “CUDA Programming Guide,” NVIDIA Documentation, Santa Clara, CA, USA, 2026.
- [44] Samsung Knox, “About the Knox SDK,” Samsung Electronics Co., Ltd., Suwon, Republic of Korea, 2026.
- [45] K. Kapoor, A. Z. Bigdeli, Y. K. Dwivedi, A. Schroeder, A. Beltagui, and T. Baines, “A Socio-Technical View of Platform Ecosystems: Systematic Review and Research Agenda,” *Journal of Business Research*, vol. 128, pp. 94–108, May 2021, doi: 10.1016/j.jbusres.2021.01.060.
- [46] M. G. Jacobides, A. Cennamo, and A. Gawer, “The Value and Structuring Role of Web APIs in Digital Innovation Ecosystems: The Case of the Online Travel Ecosystem,” *Research Policy*, vol. 53, no. 1, Art. no. 104931, Jan. 2024, doi: 10.1016/j.respol.2023.104931.