

Retrieving data from multiple tables

Displaying Data from Multiple Tables




Cartesian product

- In Mathematics, given two sets A and B, the Cartesian product of $A \times B$ is the set of all ordered pair (a,b), which a belongs to A and b belongs to B.
 - To create a Cartesian product of tables, you use the CROSS JOIN clause. The following illustrates the syntax of the CROSS JOIN clause:

```
SELECT * FROM P1 CROSS JOIN P2;
```
 - When you perform a cross join of two tables, which have no relationship, we will get a Cartesian product of rows and columns of both tables.


`SELECT * FROM table1 CROSS JOIN table2;`



In CROSS JOIN, each row from 1st table joins with all the rows of another table.
If 1st table contain x rows and y rows in 2nd one the result set will be $x * y$ rows.

Cartesian product

- A Cartesian product occurs when data is selected from two or more tables and no common relationship is specified in the WHERE clause.
 - If you do not specify a join condition for the tables listed in the FROM clause, database joins each row from the first table to every row in the second table.
 - If the first table has 3 rows and the second table has 4 rows, the result will have 12 rows.
 - If you add another table with 2 rows without specifying a join condition, the result will have 24 rows.
 - For the most part, Cartesian joins happen when there are many tables in the FROM clause and developers forget to include the join condition or they specify a wrong join condition.
- You should, therefore, avoid them. To avoid a Cartesian join, there should be at least $n-1$ join conditions when joining n tables. Sometimes you intentionally use Cartesian joins to generate large amounts of data, especially when testing applications



Matching using Equijoin

- Equi join returns the matching column values of the associated tables. It uses a comparison operator in the WHERE clause to refer equality.
 - Equijoin also can be performed by using JOIN keyword followed by ON keyword and then specifying names of the columns along with their associated tables to check equality.
 - An **equijoin** returns only the rows that have equivalent values for the specified columns.
 - An inner join is a join of two or more tables that returns only those rows (compared using a comparison operator) that satisfy the join condition.
- **What is the difference between Equi Join and Inner Join in SQL?**
 - An equijoin is a join with a join condition containing an equality operator. An equijoin returns only the rows that have equivalent values for the specified columns.
 - An inner join is a join of two or more tables that returns only those rows (compared using a comparison operator) that satisfy the join condition.

EQUI JOIN

table_a

ID	COL1
2	A2
5	A5
3	A3
1	-
4	A4

no equality
in table_b

table_b

ID	COL2
5	B5
1	B1
3	-
6	B6
2	B2
5	C5

no equality
in table_a

VS.

INNER JOIN

table_a

ID	COL1
2	A2
5	A5
3	A3
1	-
4	A4

no matches
in table_b

table_b

ID	COL2
5	B5
1	B1
3	-
6	B6
2	B2
5	C5

no matches
in table_a

```
SQL> SELECT * FROM TABLE_A
2 JOIN TABLE_B
3 ON TABLE_A.ID=TABLE_B.ID;
```

ID	COL1	ID	COL2
5	A5	5	B5
1	-	1	B1
3	A3	3	-
2	A2	2	B2
5	A5	5	C5

```
SQL> SELECT * FROM TABLE_A
2 JOIN TABLE_B
3 ON TABLE_A.ID=TABLE_B.ID;
```

ID	COL1	ID	COL2
5	A5	5	B5
1	-	1	B1
3	A3	3	-
2	A2	2	B2
5	A5	5	C5

Matching using Equijoin


ID	COL1
2	A2
5	A5
3	A3
1	-
4	A4

new1

ID	COL2
5	B5
1	B1
3	-
6	B6
2	B2
5	C5

new2

```
SELECT * FROM new1  
JOIN new2  
ON new1.id = new2.id;
```



SQL JOINS – Non Equi JOIN

- Non Equi Join is a join condition containing something other than equality operator.
 - For example: sometimes you would like to join two tables that do not have a shared column, and seemingly have no join condition
 - Non-equi joins don't have a specific keyword
 - They are defined by the type of operator in the join condition:
 - Anything but an equals sign means a non-equi join.
 - Below, we have some non-equi join operators and their meanings:

Operator	Meaning
">"	Greater than
">="	Greater than or equal to
"<"	Less than
"<="	Less than or equal to
"<>"	Not equal to
"<>"	Not equal to (ANSI Standard)

Matching using the EXISTS criteria

- EXISTS is only used to test if a subquery returns results. JOIN is used to extend a result set by combining it with additional fields from another table to which there is a relation.
 - EXISTS is used to return a boolean value, JOIN returns a whole other table.
- use EXISTS when:
 - You don't need to return data from the related table
 - You have duplicate in the related table (JOIN can cause duplicate rows if values are repeated)
 - You want to check existence (use instead of LEFT OUTER JOIN)

```
-- EXISTS
SELECT *
FROM tableA
WHERE EXISTS (SELECT 1 FROM tableB WHERE title = 'Analyst' AND tableA.id = tableB.id);
```

```
-- JOIN (INNER is the default when only JOIN is specified)
SELECT *
FROM tableA
JOIN tableB
  ON tableA.id = tableB.id
WHERE tableB.title = 'Analyst';
```

Retrieving data from multiple tables

- Questions