

```
-----  
-----  
-----  
-----  
# Do Not start the logrotate.service  
sudo dnf install rsyslog-logrotate logrotate
```

```
sudo systemctl start logrotate.timer  
sudo logrotate -f /etc/logrotate.conf
```

The logrotate.timer will trigger logrotate.service and rsyslog-logrotate.service to run.

```
-----  
-----  
# Need update every maitnenance?  
sudo cp 50-coredump.conf /usr/lib/sysctl.d/ && sudo sysctl --system  
sudo cp 10-default-yama-scope.conf /usr/lib/sysctl.d/ && sudo sysctl --system  
sudo chmod 640 /root/.bash_logout && sudo chmod 640 /root/.bash_profile  
sudo chmod 750 /opt/splunkforwarder/  
sudo cp 50-default.conf /usr/lib/sysctl.d/ && sudo sysctl --system  
-----  
-----
```

Add the folowing lines at the end of /etc/vimrc

```
syntax off  
set nohlsearch  
set t_Co=0  
-----  
-----
```

```
sudo cat /etc/audit/auditd.conf | grep max_log_file  
sudo cat /etc/audit/auditd.conf | grep IGNORE  
max_log_file_action = ROTATE  
sudo sed -i s/ROTATE/IGNORE/g /etc/audit/auditd.conf  
sudo sed -i s/keep_logs/IGNORE/g /etc/audit/auditd.conf
```

```
sudo cat /etc/audit/auditd.conf | grep num_logs  
num_logs = 5  
sudo sed -i s/'num_logs = 5'/'num_logs = 99'/g /etc/audit/auditd.conf  
num_logs = 99
```

```
sudo systemctl status auditd.service
```

```
sudo cat /etc/logrotate.d/aide | grep log_dir  
sudo cat /etc/logrotate.d/aide | grep weekly (or daily)  
sudo cat /etc/logrotate.d/syslog | grep log_dir  
sudo cat /etc/logrotate.d/syslog | grep weekly (or daily)
```

```
sudo cp ~/rhel_disa/Peter/Logrotate/etc/cron.daily/logrotate  
/etc/cron.daily/logrotate
```

```
sudo cp ~/rhel_disa/Peter/Logrotate/etc/logrotate.d/syslog /etc/logrotate.d/
```

```
-----  
-----  
cd rhel_disa/Peter/RAY_Logrotate/RHEL9
```

```
sudo rpm --import RPM-GPG-KEY-sdirpmbuilder-public
```

```
sudo dnf localinstall RAY-SetLogRotate-el9-2024.1.0-1.noarch.rpm
```

```
sudo dnf localinstall RAY-SetLogRotate-el9-2024.1.0-1.noarch.rpm --nogpgcheck
```

```
sudo ls -al /root/RAY/LogRotate/files
```

```
-rw-r--r--. 1 root root 155 Nov 17 21:02 aide_backup-2025-11-17  
-rw-r-----. 1 root root 911 Nov 17 21:02 auditd.conf_backup-2025-11-17  
-rw-r-x---. 1 root root 1353 May 21 2023 logrotate_aide  
-rw-r-x---. 1 root root 3960 Jul 22 2024 logrotate_syslog  
-rw-r--r--. 1 root root 226 Nov 17 21:02 syslog_backup-2025-11-17
```

```
sudo cp /etc/audit/auditd.conf /etc/audit/auditd.conf.orig
```

To Restore log files:

```
sudo ls -al /root/RAY/LogRotate/scripts/install_logrotate.sh
```

```
-----  
-----  
sudo mv /etc/rsyslog.conf /etc/rsyslog.conf.orig && sudo cp  
rhel_disa/Peter/rSyslog/Configs/Client/rsyslog.conf /etc/rsyslog.conf
```

Ansible-Playbook (error if trying to use)

```
sudo setsebool -P use_nfs_home_dirs=true
```

```
-----  
-----  
cd
```

```
~/rhel_disa/Peter/RAY-Splunk/1.0.1/Install_Script_Splunk_Ray_1.0.1_Release/Forwarder  
_Files
```

```
sudo rpm -ivh splunkforwarder-9.3.1-0b8d769cb912.x86_64.rpm
```

```
sudo chown -R root: /opt/splunkforwarder/
```

```
sudo /opt/splunkforwarder/bin/splunk enable boot-start -systemd-managed 1 -user root  
-group root --accept-license --gen-and-print-passwd
```

```
Randomly generated admin password:
```

```
*J$.UP8R
```

```
# Enable again due to bug
```

```
sudo /opt/splunkforwarder/bin/splunk enable boot-start -systemd-managed 1 -user root  
-group root
```

```
sudo vi /etc/systemd/system/SplunkForwarder.service
```

```
# Add this to file and add after LimitNOFILE=65536
```

```
uMask=0022
```

```
sudo systemctl daemon-reload
```

```
sudo /opt/splunkforwarder/bin/splunk set deploy-poll splunk:8089
```

```
sudo /opt/splunkforwarder/bin/splunk list deploy-poll
```

```
sudo /opt/splunkforwarder/bin/splunk start
```

```
# If there are permission denied errors or doesn't run then
"/opt/splunkforwarder/bin/splunk disable boot-start"
# and then run "sudo /opt/splunkforwarder/bin/splunk enable boot-start
-systemd-managed 1 -user root -group root"
```

```
sudo systemctl enable --now SplunkForwarder
```

```
# Add cron entry
```

```
crontab -e
```

```
# Doesn't work according to TIG
```

```
*/10 * * * * find /opt/splunkforwarder/etc/apps \(-name *.sh -o -type d\) ! -perm
-u=rwx,g=rwx,o=rx -exec chmod 755 {} \;
```

```
# Modified Cron Job
```

```
#Splunk Forwarder
```

```
*/10 * * * * sudo find /opt/splunkforwarder/etc/apps -name *.sh -o -type d ! -perm
-u=rwx,g=rwx,o=rx -exec chmod 755 {} \;
```

```
-----
sudo cp /etc/fapolicyd/compiled.rules /etc/fapolicyd/compiled.rules.orig
sudo cp ~/rhel_disa/Peter/Fapolicy/etc/fapolicyd/rules.d/80-scc-scap.rules
/etc/fapolicyd/rules.d/
sudo fagenrules --load
sudo cat /etc/fapolicyd/compiled.rules
sudo systemctl restart fapolicyd.service
```

```
sudo cat /etc/fapolicyd/fapolicyd.conf | grep permissive
sudo systemctl stop fapolicyd.service
```

```
#Start the daemon manually
```

```
sudo fapolicyd --debug-deny 2> fapolicy.out
```

```
sudo fapolicyd --permissive --debug 2> fapolicy.out
```

```
Look for a decision to deny:
```

```
"dec=deny"
```

```
sudo cat /etc/fapolicyd/fapolicyd.trust
sudo fapolicyd-cli --file add /opt/scc-remote/lib64/csc64
sudo fapolicyd-cli --file add /opt/scc-remote/csc64-remote
```

```
sudo fapolicyd-cli --file add /opt/scc-remote/lib64/csc64 && sudo fapolicyd-cli
--file add /opt/scc-remote/csc64-remote
```

```
sudo fapolicyd-cli --update
```

```
sudo cat /etc/fapolicyd/fapolicyd.trust
-----
```

```
sudo dnf install clevis clevis-luks clevis-dracut
```

```
sudo grubby --update-kernel=ALL --args="rd.neednet=1"
```

```
sudo dracut -fv --regenerate-all
```

```
# Okra = Tang Server
```

```
sudo clevis luks bind -d /dev/mapper/rhel-root tang
```

```
'{"url":"http://192.168.12.69:7500"}'
```

```
sudo clevis luks bind -d /dev/mapper/rhel-swap tang
```

```
'{"url":"http://192.168.12.69:7500"}'
```

```
sudo clevis luks bind -d /dev/mapper/rhel-home tang
```

```
'{"url":"http://192.168.12.69:7500"}'
```

```
sudo clevis luks bind -d /dev/mapper/rhel-tmp tang
```

```
'{"url":"http://192.168.12.69:7500"}'
```

```
sudo clevis luks bind -d /dev/mapper/rhel-var_log_audit tang
```

```
'{"url":"http://192.168.12.69:7500"}'
```

```
sudo clevis luks bind -d /dev/mapper/rhel-var tang
```

```
'{"url":"http://192.168.12.69:7500"}'
```

```
sudo clevis luks bind -d /dev/mapper/rhel-var_log tang
```

```
'{"url":"http://192.168.12.69:7500"}'
```

```
sudo clevis luks bind -d /dev/mapper/rhel-var_tmp tang
```

```
'{"url":"http://192.168.12.69:7500"}'
```

```
sudo vi /etc/chrony.conf
```

```
#pool 2.rhel.pool.ntp.org iburst maxpoll 16
```

```
server mainswitch.opir.local iburst maxpoll 16
```

```
server 192.168.2.254 iburst maxpoll 16
```

```
sudo sed -i 's/root/superuser/g' /etc/grub.d/01_users
```

```
sudo cat /etc/grub.d/01_users
```

```
[sudo] password for pmeigs-da:
```

```
#!/bin/sh -e
```

```
cat << EOF
```

```
if [ -f \${prefix}/user.cfg ]; then
```

```
    source \${prefix}/user.cfg
```

```
    if [ -n "\${GRUB2_PASSWORD}" ]; then
```

```
        set superusers="superuser"
```

```
        export superusers
```

```
        password_pbkdf2 superuser \${GRUB2_PASSWORD}
```

```
    fi
```

```
fi
```

```
EOF
```

RHEL9:

```
sudo grub2-setpassword superuser
```

```
sudo grub2-mkconfig -o /boot/grub2/grub.cfg
```

RHEL8:

```
sudo grub2-mkpasswd-pbkdf2
```

```
sudo grub2-mkconfig -o /boot/efi/EFI/redhat/grub.cfg
```

```
sudo grub2-mkconfig -o /boot/efi/EFI/redhat/grubx64.cfg
```

```
/etc/yum.repos.d/oracle.repo
```

```
[BaseOS]
```

```
name = BaseOS RHEL 9
```

```
baseurl = http://oracle.opir.local/RHN/rhel-9-for-x86_64-baseos-rpms/
```

```
enabled = 1
```

```
gpgcheck = 1
```

```
gpgkey =
```

```
http://oracle.opir.local/RHN/rhel-9-for-x86_64-baseos-rpms/RPM-GPG-KEY-redhat-release
```

```
[AppStream]
```

```
name = Appstream RHEL 9
```

```
baseurl = http://oracle.opir.local/RHN/rhel-9-for-x86_64-appstream-rpms/
```

```
enabled = 1
```

```
gpgcheck = 1
```

```
gpgkey =
```

```
http://oracle.opir.local/RHN/rhel-9-for-x86_64-appstream-rpms/RPM-GPG-KEY-redhat-release
```

```
[RIS$releasever]
```

```
baseurl = http://oracle.opir.local/RIS/RHEL9
```

```
enabled = 1
```

```
gpgcheck = 1
```

```
gpgkey = http://oracle.opir.local/RIS/RHEL9/RIS_DTCS_GPG_KEY
```

```
name = RIS $releasever
```

```
#[Extras]
```

```
#name = Extra Packages
```

```
#baseurl = http://oracle.opir.local/EXTRAS
```

```
#enabled = 1
```

```
#gpgcheck = 1
```

```
#gpgkey = http://oracle.opir.local/etc/pki/rpm-gpg/RPM-GPG-KEY-redhat-release
```

```
/etc/sudoers
```

```

sudo visudo
Defaults    secure_path = /sbin:/bin:/usr/sbin:/usr/bin:/usr/local/bin/
## Allows people in group wheel to run all commands
%wheel  ALL=(ALL)        ALL
%domain\ admins ALL=(ALL)    ALL
-----
-----
sudo visudo

Defaults    secure_path = /sbin:/bin:/usr/sbin:/usr/bin:/usr/local/bin

## Allows people in group wheel to run all commands
%wheel  ALL=(ALL)        ALL
%domain\ users  ALL=(ALL)    ALL
-----
-----
# Not used any more
sudo vi /etc/auto.direct
#/var/lib/clamav -ro,nosuid,noexec,nodev oracle.opir.local:/var/lib/clamav
sudo systemctl restart autofs
-----
-----
sudo dnf remove clam*

sudo dnf install clamav --nogpgcheck
=====
Package Architecture Version      Repository Size
=====
clamav   x86_64      1.5.0_beta-1  Extras    40 M

sudo mkdir -p /var/log/ClamAV/VIRUS
sudo mkdir -p /var/clamav/quarantine

sudo useradd clamav -s /sbin/nologin -d /home/clamav -c "clamav user" && sudo mkdir
-p /var/lib/clamav && sudo chown -R clamav: /var/lib/clamav/

sudo cp freshclam.conf /usr/local/etc/ && sudo ln -s /usr/local/etc/freshclam.conf
/etc/freshclam.conf

sudo touch /var/log/freshclam.log && sudo chown clamav: /var/log/freshclam.log

# sudo vi /usr/local/etc/freshclam.conf
DatabaseMirror http://clamav.opir.local
#Feshclam's Default location: /usr/local/share/clamav/
DatabaseDirectory /var/lib/clamav
UpdateLogFile /var/log/freshclam.log
-----
-----
# If ClamAV does not start in the cron job then reset the root passwd. It may have
expired.

```

```
sudo crontab -e
```

```
#Ansible: Weekly Virus Scan
```

```
#15 1 * * 0 /usr/bin/virus_scan.sh
```

```
#TSPS Checks
```

```
00 4 * * * /usr/local/TSPS_Nix_Package/audit/bin/logcollect -a
```

```
30 4 * * * /usr/local/TSPS_Nix_Package/audit/bin/logcollect -r
```

```
45 * * * * chmod -R 755 /opt/splunkforwarder/etc/apps/*/bin/*
```

```
# AIDE specific checks.
```

```
01 3 * * 6 /usr/sbin/aide --init
```

```
30 3 * * 6 /bin/cp /var/lib/aide/aide.db.new.gz /var/lib/aide/aide.db.gz
```

```
45 3 * * * /usr/sbin/aide --check
```

```
# Splunk Forwarder
```

```
*/10 * * * * sudo find /opt/splunkforwarder/etc/apps -name *.sh -o -type d ! -perm  
-u=rwx,g=rwx,o=rx -exec chmod 755 {} \;
```

```
# Weekly Virus Scan
```

```
0 4 * * 6 /usr/bin/virus_scan.sh
```

```
#Freshclam Update
```

```
0 4 * * 1,3,5 freshclam
```

```
-----  
-----  
sudo dnf install autofs
```

```
sudo systemctl enable --now autofs
```

```
sudo cp auto.* /etc  
-----  
-----
```

```
sudo dnf install samba-common-tools realmd oddjob oddjob-mkhomedir sssd adcli  
krb5-workstation
```

```
cd /etc/crypto-policies/back-ends
```

```
sudo mv nss.config nss.config.orig
```

```
sudo ln -s /usr/share/crypto-policies/FIPS/nss.txt nss.config
```

```
cd /usr/share/crypto-policies/FIPS/
```

```
sudo mv krb5.txt krb5.txt.FIPS
```

```
sudo cp ../DEFAULT/krb5.txt .
```

```
sudo realm join opir.local -U pmeigs-da
```

```
/etc/krb5.conf
```

```
# To opt out of the system crypto-policies configuration of krb5, remove the  
# symlink at /etc/krb5.conf.d/crypto-policies which will not be recreated.
```



```
includedir /etc/krb5.conf.d/
```

```
[logging]
```

```
default = FILE:/var/log/krb5libs.log  
kdc = FILE:/var/log/krb5kdc.log  
admin_server = FILE:/var/log/kadmind.log
```

```
[libdefaults]
```

```
dns_lookup_realm = false  
ticket_lifetime = 24h  
renew_lifetime = 7d  
forwardable = true  
rdns = false  
pkinit_anchors = FILE:/etc/pki/tls/certs/ca-bundle.crt  
spake_preauth_groups = edwards25519  
dns_canonicalize_hostname = fallback  
qualify_shortname = ""  
default_realm = OPIR.LOCAL  
default_ccache_name = KEYRING:persistent:%{uid}  
udp_preference_limit = 0
```

```
[realms]
```

```
OPIR.LOCAL = {  
    kdc = dc01.opir.local  
    admin_server = dc01.opir.local  
}
```

```
[domain_realm]
```

```
.opir.local = OPIR.LOCAL  
opir.local = OPIR.LOCAL
```

```
-----  
/etc/sss/sss/conf
```

```
[pam]
```

```
pam_cert_auth=True  
offline_credentials_expiration=1
```

```
[sss]
```

```
domains = opir.local  
config_file_version = 2  
services = nss, pam
```

```
[domain/opir.local]
```

```
default_shell = /bin/bash  
krb5_store_password_if_offline = True  
cache_credentials = False  
krb5_realm = OPIR.LOCAL  
realmd_tags = manages-system joined-with-adcli  
id_provider = ad  
ldap_sasl_authid = OPIR-RHEL9-TEST$
```



```
fallback_homedir = /home/%u@%d
#override_homedir = /home/%u
ad_domain = opir.local
use_fully_qualified_names = False
ldap_id_mapping = True
access_provider = ad
```

```
-----
sudo dnf install nfs-utils
sudo mkdir -p /gswshare
-----
```

```
-----
sudo cat /etc/auto.master
/home    /etc/auto.home
/- /etc/auto.direct
-----
```

```
-----
sudo cat /etc/auto.direct
[sudo] password for pmeigs-da:
#/var/lib/clamav -ro,nosuid,noexec,nodev oracle.opir.local:/var/lib/clamav
/gswshare -rw,nosuid,noexec,nodev cheeto.opir.local:/array/gswshare
-----
```

```
-----
sudo cat /etc/auto.home
*        -rw,noexec,nosuid,nodev      lindows.opir.local:/home/&
-----
```

```
-----
Vul ID: V-258131
```

```
$ sudo openssl x509 -text -in /etc/sssdpki/sssdpki_auth_ca_db.pem

/etc/sssdpki/sssdpki_auth_ca_db.pem
-----
```

```
-----
sudo cat /etc/chrony.conf
```

```
server mainswitch.opir.local iburst maxpoll 16
server 192.168.2.254 iburst maxpoll 16
```

```
mainswitch.opir.local [192.168.0.254]
-----
-----
-----
-----
-----
-----
-----
-----
-----
```