

Polarization transfer matrix

Gate: 52–70 ns · 8/8 settings · completed · H/R/V/L names provisional

Detected rate (counts/s)

Input state / Alice EOM target	H (S0) Alice -155.146 V	253.0	53.3	168.5	141.8
	V (S2) Alice +45.302 V	27.6	329.4	136.4	207.0
	R (S1) Alice -54.922 V	110.3	232.3	261.8	48.4
	L (S3) Alice +145.526 V	146.6	163.8	27.2	325.6
		H (S0) · HV/CH2 Bob +38.712 V	V (S2) · HV/CH1 Bob +38.712 V	R (S1) · RL/CH2 Bob -58.54 V	L (S3) · RL/CH1 Bob -58.54 V

Output channel / Bob EOM target

Conditional detection probability

Input state / Alice EOM target	H (S0) Alice -155.146 V	0.826	0.174	0.543	0.457
	V (S2) Alice +45.302 V	0.077	0.923	0.397	0.603
	R (S1) Alice -54.922 V	0.322	0.678	0.844	0.156
	L (S3) Alice +145.526 V	0.472	0.528	0.077	0.923
		H (S0) · HV/CH2 Bob +38.712 V	V (S2) · HV/CH1 Bob +38.712 V	R (S1) · RL/CH2 Bob -58.54 V	L (S3) · RL/CH1 Bob -58.54 V

Output channel / Bob EOM target

Color identifies output channel; shade and numbers show measured values. Outlines mark expected unity outcomes.

Probabilities are normalized within each Bob basis. No background subtraction or detector-efficiency correction.

EOM targets: Alice/AO0, Bob/AO1. Plot order is saved in analysis.json; raw data and CSV matrix order are unchanged.