

Polarization transfer matrix

Gate: 52–60 ns · 8/8 settings · completed · H/R/V/L names provisional

Detected rate (counts/s)

Conditional detection probability

Input state / Alice EOM target

H (S0)
Alice -155.146 V

150.4	36.8	100.8	95.5
14.6	227.0	80.5	144.1
66.2	162.1	156.1	34.5
86.5	113.5	15.4	225.8

V (S2)
Alice +45.302 V

H (S0)
Alice -155.146 V

0.804	0.196	0.513	0.487
0.060	0.940	0.358	0.642
0.290	0.710	0.819	0.181
0.433	0.567	0.064	0.936

V (S2)
Alice +45.302 V

R (S1)
Alice -54.922 V

L (S3)
Alice +145.526 V

H (S0) · HV/CH2
Bob +38.712 V

V (S2) · HV/CH1
Bob +38.712 V

R (S1) · RL/CH2
Bob -58.54 V

L (S3) · RL/CH1
Bob -58.54 V

H (S0) · HV/CH2
Bob +38.712 V

V (S2) · HV/CH1
Bob +38.712 V

R (S1) · RL/CH2
Bob -58.54 V

L (S3) · RL/CH1
Bob -58.54 V

Output channel / Bob EOM target

Output channel / Bob EOM target

Color identifies output channel; shade and numbers show measured values. Outlines mark expected unity outcomes.

Probabilities are normalized within each Bob basis. No background subtraction or detector-efficiency correction.

EOM targets: Alice/AO0, Bob/AO1. Plot order is saved in analysis.json; raw data and CSV matrix order are unchanged.