

Polarization transfer matrix

Ungated · 8/8 settings · completed · H/R/V/L names provisional

Detected rate (counts/s)

Input state / Alice EOM target	H (S0) Alice -159.184 V	414.2	119.0	320.6	204.1
	V (S2) Alice +36.7347 V	132.2	441.8	275.2	299.1
	R (S1) Alice -69.3878 V	254.7	312.7	425.4	104.8
	L (S3) Alice +151.02 V	304.3	236.1	133.3	449.6
		H (S0) · HV/CH2 Bob +44.898 V	V (S2) · HV/CH1 Bob +44.898 V	R (S1) · RL/CH2 Bob -53.0612 V	L (S3) · RL/CH1 Bob -53.0612 V

Output channel / Bob EOM target

Conditional detection probability

Input state / Alice EOM target	H (S0) Alice -159.184 V	0.777	0.223	0.611	0.389
	V (S2) Alice +36.7347 V	0.230	0.770	0.479	0.521
	R (S1) Alice -69.3878 V	0.449	0.551	0.802	0.198
	L (S3) Alice +151.02 V	0.563	0.437	0.229	0.771
		H (S0) · HV/CH2 Bob +44.898 V	V (S2) · HV/CH1 Bob +44.898 V	R (S1) · RL/CH2 Bob -53.0612 V	L (S3) · RL/CH1 Bob -53.0612 V

Output channel / Bob EOM target

Color identifies output channel; shade and numbers show measured values. Outlines mark expected unity outcomes.

Probabilities are normalized within each Bob basis. No background subtraction or detector-efficiency correction.

EOM targets: Alice/AO0, Bob/AO1. Plot order is saved in analysis.json; raw data and CSV matrix order are unchanged.