The Trial of the Pyx

The Desk Volume

An Audio Course in the Evaluation of Models in Training — definitions, derivations, protocols, exhibits, and problems

Narrated by Jeeves · Written for and with P. Milovanov, Esq.

Edition v0.4.0

How to Use This Volume

Each chapter of this volume is the desk companion to one episode of the course, and each is written to stand on its own. A chapter walks its episode's ground in the same order, in one narrated pass — the same story, told for the page, with less conversation and more derivation — and the formal apparatus is set where the story reaches it: the definitions and results at their story positions, the proofs immediately after their statements, the protocol boxes at the procedures they record, and the exhibits, worked tables above all, where the numbers are needed. The course's spoken names — the *instrument*, the *remedy*, the *trial plate*, the *reference checkpoint*, *pass at k* — are standing vocabulary here, introduced beside the formal objects they name, never in their place.

In this subject every claim is relative to a *sampling model*: what is held fixed and what is drawn at random — the questions, the samples drawn from the model on each question, the seeds, the checkpoints, the harness that poses the questions and scores the answers. An error bar without its sampling model is a rumour. So each model is declared in a titled box, *Model* — (its scope), standing immediately before the first claim it governs; a chapter working under several declares each where the story reaches it. The volume's alphabet is fixed in the first of them and kept throughout, in the letters of Chen and his colleagues: N questions, n samples drawn on each question, c of them correct, and k the number of attempts counted in *pass at k*.

The statistics a training run needs — the paired difference, power and the minimum detectable effect, multiple testing, sequential monitoring — are taught here in their own setting and under their own names, from the beginning, rather than assumed. Where the practice of online controlled experiments has given a tool its best-known name (the A/A test, peeking, variance reduction by a pre-experiment covariate), the name is given as a signpost, so that the reader can find the tool in that literature; nothing in the volume depends on having met it there.

Each chapter carries one *Examiner's Question* in a box: a question of the kind a laboratory puts to the person who reads its evaluations, with how a strong answer runs and what a weak answer misses. The Whiteboard — for the run review — and a short register paragraph close each narrated body. Then come the problems, in three tiers. Tier I is calisthenics; Tier II is the real thing, including each chapter's *sabotage* problem, in which a plausibly broken analysis or harness is supplied and your task is to prove its flaw fatal, with numbers; Tier III is starred and optional. Hints are segregated and spoiler-safe. Solutions are complete for Tier I, complete for the Tier II problems that finish arguments a chapter sketches and for every sabotage problem, and withheld — hints only — for Tier III.

The Bench is modest by design: one or two small laboratory scripts a chapter, numbered by chapter (lab 1a, lab 3b), each running in seconds on an ordinary computer with *numpy* and *scipy* — no graphics cards, no model downloads. Every exhibit that prints real numbers names the lab that produced them, and the numbers in its caption are copied from that lab's output, never typed by hand. The scripts and their manual live in the course's *lab* directory.

Nothing here appears unmotivated by the audio, and nothing in the audio pretends to a proof that is not here.

Contents

How to Use This Volume **1**

1 The Instrument and the Run **4**
1.1 Part One — What an Evaluation Is For 4
1.2 Part Two — The Instrument and Its Target 7
1.3 Part Three — The Three Clocks 9
1.4 Part Four — Every Number Is an Estimate 10
1.5 Part Five — The Instincts of Product Evaluation, Amended 11
1.6 Part Six — A Run, as Its Operators Saw It 14
1.7 The Examiner's Question 18
1.8 The Whiteboard 19
1.9 Problems 20
1.10 Hints 21
1.11 Solutions 22
1.12 The Reading 23

2 The Remedy **26**
2.1 Opening — Two Numbers for One Examination 26
2.2 Part One — The Master's Remedy 26
2.3 Part Two — Questions and Answers 28
2.4 Part Three — Comparing Two Checkpoints 29
2.5 Part Four — Comparing Two Runs 29
2.6 Part Five — What a Set Can See 30
2.7 Part Six — Pass at k, and Its Cousins 32
2.8 The Examiner's Question 34
2.9 The Whiteboard 34
2.10 Problems 35
2.11 Hints 36
2.12 Solutions 36
2.13 The Reading 37

Chapter 1

The Instrument and the Run

Companion to Episode One. An evaluation, at a laboratory, as an instrument read during training to decide what to do next: the alarm that was usually wrong, and why it was right; the five decisions of a run; the decision problem, the worth of an evaluation defined as the decisions it improves, and the threshold set by the prices of the two errors; the optimiser's excess, and why an instrument that shares the optimiser's target cannot see it; the three clocks; the error bar of a fixed question set and the sampling model behind it; the four amendments to the instincts of product evaluation, with a frozen checkpoint scored against itself and kept as the reference checkpoint; and a run as its operators saw it — restart points chosen by their instruments, interventions judged on held-out text, an alarm in the training loop and the false-alarm rate its threshold buys, and the reward and held-out curves parting after pre-training.

1.1 Part One — What an Evaluation Is For

The alarm that was usually wrong. Gemini 2.5 was trained, in its technical report's words, on "multiple 8960-chip pods of Google's TPUv5p accelerators, distributed across multiple datacenters"; at that scale "we see interruptions from hardware failures multiple times per hour". Interruptions announce themselves. *Silent data corruption* (SDC) does not: a processor that keeps answering, occasionally wrongly, with no error raised. A published Facebook case makes the phrase concrete — a single core that returned 0 for the integer part of 1.1^{53} (correctly 156) while computing 1.1^{52} correctly, on a host with "clean system event logs and clean kernel logs" (Dixit et al., 2021). In training, a corrupted step alters the weights and the alteration is carried forward. The report describes the old cost — "many hours to detect and localize machines with SDC errors, requiring both downtime while debugging, and rollback/replay of a large number of potentially corrupt training steps" — and the new instrument: "We now use lightweight deterministic replay to immediately repeat any step with suspicious metrics, and compare per-device intermediate checksums to localize the root cause of any data corruption." And its record: "During this run, around 0.25% of steps were replayed due to suspected SDCs and 6% of these replays turned out to be genuine hardware corruption."

Per hundred thousand training steps	Count
steps replayed on suspicion	250
replays that found a genuine corruption	15
replays that found nothing (false alarms)	235
share of alarms that were false	0.94

Exhibit 1.1 (the alarm's arithmetic). The report's two percentages put through a round hundred thousand steps (lab 1c). The same report adds that "around 4.5% of the computed steps were replays or rollbacks for model debugging interventions".

The report gives no prices. The reading that follows is this volume's: a false alarm costs one step done twice; a miss costs the regime the report describes as the old one. Ninety-four false alarms in a hundred are then a small price, and a quieter alarm — more often right when it spoke — would very likely have been a worse instrument, because it would very likely have missed some of the genuine six. Everything in this chapter is a generalisation of that sentence.

The five decisions. A training run is a sequence of decisions, and an evaluation is an instrument read to take them:

1. **continue** — the default, and the commonest outcome of a reading; a reading that says "carry on" is worth something only if it could have said otherwise;
2. **intervene** — change the data mixture, the learning rate, the reward. Llama 3: the pre-training data mix was adjusted "during training to improve model performance on particular downstream tasks". Choices that cannot be changed once a run has begun — architecture, initialisation — are taken beforehand, in smaller trial runs (*ablations*) read by evaluations too. OLMo, under the heading "In-Loop Training Ablations": "Throughout model training, we perform downstream evaluations to make decisions around model architecture, initialization, optimizers, learning rate schedule, and data mixtures. We call this our online evaluation as it runs in-loop every 1000 training steps (or ~4B training tokens)". The report does not say what its in-loop signal decided in the main run;
3. **roll back** — return to an earlier checkpoint (Gemini's replays at the scale of one step; Part Six reads a run restarted dozens of times);
4. **select** — choose the checkpoint to carry forward. Tülu 3, in its final stage: "we examine model checkpoints every 40-100 steps and choose the best checkpoint on our development evaluation set"; Llama 3 averaged checkpoints from the end of pre-training to make its final pre-trained model;
5. **ship or block** — Anthropic deployed Claude Opus 4 under its ASL-3 measures "as a precautionary and provisional action", having determined that "clearly ruling out ASL-3 risks is not possible for Claude Opus 4 in the way it was for every previous model" (Chapter 5).

The decision problem. The rest of the chapter needs only the oldest apparatus in statistics: a finite set of states, a finite set of actions, a loss, and evidence.

Definition 1.1 (Decision problem, rule, and risk)**.** A *decision problem* consists of a finite set Θ of states with prior probabilities $\pi(\theta)$, a finite set A of actions, and a loss $L(\theta, a) \geq 0$. An *evaluation*

is an observation X whose distribution P_θ depends on the state. A *decision rule* δ maps each outcome x to an action. Its *risk* is the expected loss

$$r(\delta) = \sum_\theta \pi(\theta)\, \mathbb{E}_\theta\big[L(\theta, \delta(X))\big].$$

A rule that ignores X and always takes action a has risk $\rho_0(a) = \sum_\theta \pi(\theta) L(\theta, a)$.

Definition 1.2 (The worth of an evaluation)**.** The *worth* of the evaluation X is the reduction in risk it permits, used as well as it can be:

$$V(X) = \min_{a \in A} \rho_0(a) \;-\; \min_\delta r(\delta).$$

The worth of a particular rule δ is $\min_a \rho_0(a) - r(\delta)$, which may be negative.

This is the course's first principle, set in symbols: an evaluation is worth exactly the decisions it improves. The proposition that follows says the two halves of that sentence are both true — that the worth cannot be negative if the evaluation is used well, and that it is zero exactly when the evaluation never changes the decision.

Proposition 1.3 (Worth is non-negative, and zero exactly when nothing changes)**.** $V(X) \geq 0$. *Moreover* $V(X) = 0$ *if and only if a single action is optimal, given the outcome, for almost every outcome of* X.

Proof. Write $\pi(\theta \mid x)$ for the posterior and $\rho(x, a) = \sum_\theta \pi(\theta \mid x) L(\theta, a)$ for the posterior expected loss of a. Conditioning on X gives $r(\delta) = \mathbb{E}_X[\rho(X, \delta(X))] \geq \mathbb{E}_X[\min_a \rho(X, a)]$, with equality for the rule that picks a minimiser of $\rho(x, \cdot)$ at every x; so $\min_\delta r(\delta) = \mathbb{E}_X[\min_a \rho(X, a)]$. For a constant action, the law of total probability gives $\mathbb{E}_X[\rho(X, a)] = \rho_0(a)$. Hence

$$\min_\delta r(\delta) = \mathbb{E}_X\big[\min_a \rho(X, a)\big] \leq \min_a \mathbb{E}_X\big[\rho(X, a)\big] = \min_a \rho_0(a),$$

which is $V(X) \geq 0$. Equality holds if and only if some a^* attains $\min_a \rho(x, a)$ for almost every x: if it does, the two sides agree; if it does not, then for every action a the set of outcomes on which a is strictly beaten has positive probability, and since A is finite the minimum over a of $\mathbb{E}_X[\rho(X, a)]$ exceeds $\mathbb{E}_X[\min_a \rho(X, a)]$. □

Three corollaries follow by inspection, and each describes an evaluation a fleet should retire: one that measures something on which no action depends; one whose alarms are ignored (the rule in use is constant, so its worth is at most zero); and one that only ever confirms the action the prior already favoured.

A hundred checkpoints. Take two states for each checkpoint, *good* and *broken*; two actions, *promote* and *hold*; a miss (promoting a broken checkpoint) costing a working week of five days, a false alarm (holding a good one) costing half a day. The evaluation raises its alarm on nine broken checkpoints in ten and on one good checkpoint in eighteen.

Case (per hundred checkpoints)	Without	Misses	False alarms	With	Worth
ten broken; false alarm half a day	50.00	5.00	2.50	7.50	42.50
one broken; false alarm half a day	5.00	0.50	2.75	3.25	1.75
ten broken; false alarm five days	50.00	5.00	25.00	30.00	20.00
one broken; false alarm five days	5.00	0.50	27.50	28.00	−23.00

Exhibit 1.2 (the worth of one evaluation in four situations). Expected days lost per hundred checkpoints, without the evaluation (promote everything) and with it at the fixed threshold described; worth is the difference (lab 1c). The same instrument is worth eight and a half weeks when breakage is common and less than two days when it is rare — some twenty-four times less — and, where breakage is rare and false alarms dear, the rule is worse than deciding without it. Proposition 1.3 is not contradicted: it concerns the evaluation *used well*, and used well the evaluation in the last row would be ignored, or its threshold moved.

The threshold set by the prices. The base rate and the two prices together fix where the alarm should sound.

Proposition 1.4 (The Bayes threshold)**.** *Let a checkpoint be broken with prior probability q, let a miss cost C_m and a false alarm C_f, and let the evaluation's outcome x have likelihood ratio $\Lambda(x) = f_{\text{broken}}(x)/f_{\text{good}}(x)$. The rule of least risk holds the checkpoint exactly when*

$$\Lambda(x) \;>\; \frac{(1-q)\,C_f}{q\,C_m}.$$

Proof. Holding has posterior expected loss $\pi(\text{good} \mid x)\,C_f$; promoting has $\pi(\text{broken} \mid x)\,C_m$. Hold when the first is smaller. By Bayes' rule the posterior odds of *broken* are $\Lambda(x)\,q/(1-q)$, and the inequality rearranges to the one stated. □

Remark 1.5 (The marginal reading). For a family of threshold rules with sensitivity s and false-alarm rate f, lowering the threshold changes the risk by $-q\,C_m\,\Delta s + (1-q)\,C_f\,\Delta f$ per checkpoint. It pays while each additional broken checkpoint caught costs fewer than C_m/C_f additional false alarms. In the example of Exhibit 1.2, $C_m/C_f = 10$. The Gemini alarm, on this reading, sat where a miss is very dear and a false alarm very cheap — which is why ninety-four false alarms in a hundred were the right price.

The thesis of the whole course can now be stated in full: at a laboratory, an evaluation is an instrument read during training to decide what to do next; it is worth exactly the decisions it improves; and that worth is set by four things — whether it measures what it is meant to (Chapters 3 and 4), its signal (Chapter 3), its noise (Chapters 2 and 4), and whether the model has learned to read it (this chapter's Parts Two and Six, and Chapter 5).

1.2 Part Two — The Instrument and Its Target

A gap with nobody pushing on it. Anthropic's "Challenges in evaluating AI systems" (4 October 2023) records that implementing the bias benchmark BBQ took "one of our best full-time engineers one uninterrupted week", and that some models then achieved a bias score of zero — until a check revealed that the models were not answering the questions at all: "our results were technically unbiased, but they were also completely useless. All evaluations are subject to the failure mode where you overinterpret the quantitative score and delude yourself into thinking that you have made progress when you haven't." A measure can be satisfied by something other than the thing it measures. That is the *gap*; an optimiser is a process that finds gaps.

The mechanism, in four steps. Take a reward of the form "the code passes these tests". (1) The reward measures what is wanted; it is not the thing wanted. (2) Between them lies a gap — everything that passes the tests without being correct code. (3) A reinforcement-learning search raises the reward by whatever path is cheapest, and where the real skill is hard a path through the gap often is; this is *reward hacking*. (4) Asked afterwards, the tests pass, because passing them is what was produced. A hundred problems make the arithmetic plain: ninety honestly solvable, ten not but gameable; the trained model passes a hundred; the true rate of correct code is ninety; the ten points of difference are exactly the instrument's blind spot.

The noiseless version of the argument is the four steps above. The version with noise is a proposition, and it is worth having because it shows the excess arises from selection alone, before any cleverness.

Model — Selection by a noisy measure

There are m candidates (checkpoints, policies, responses) with fixed true qualities $u_1, \dots, u_m$. A measure reports $M_i = u_i + \varepsilon_i$, the errors ε_i independent with mean zero. The selected candidate is $\hat{\imath} = \arg\max_i M_i$. A second, independent measure reports $M'_i = u_i + \varepsilon'_i$, the ε'_i independent of everything else with mean zero. *Governs* Proposition 1.6 and Corollary 1.10.

Proposition 1.6 (The optimiser's excess is invisible to its own instrument)**.** *Under the model above,* $\mathbb{E}[M_{\hat{\imath}}] \geq \mathbb{E}[u_{\hat{\imath}}]$*: the measure that did the selecting overstates the quality of what it selected, in expectation. The independent measure does not:* $\mathbb{E}[M'_{\hat{\imath}}] = \mathbb{E}[u_{\hat{\imath}}]$.

Proof. The maximum is convex, so by Jensen's inequality $\mathbb{E}[\max_i M_i] \geq \max_i \mathbb{E}[M_i] = \max_i u_i \geq \mathbb{E}[u_{\hat{\imath}}]$, and $M_{\hat{\imath}} = \max_i M_i$. For the second measure, $\mathbb{E}[\varepsilon'_{\hat{\imath}}] = \sum_i \mathbb{E}[\varepsilon'_i \, \mathbf{1}\{\hat{\imath} = i\}] = \sum_i \mathbb{E}[\varepsilon'_i] \, P(\hat{\imath} = i) = 0$, since each ε'_i is independent of the event $\{\hat{\imath} = i\}$, which depends only on the first measure. □

The proposition is the statistical skeleton of the episode's central sentence: *an instrument that shares the optimiser's target cannot see the optimiser's excess*. Training is selection repeated millions of times over a far larger space, and the reward is the measure that did the selecting. Systematic gaps (the gameable ten problems) add to the noise an excess the optimiser can climb towards deliberately; the conclusion only strengthens.

The published record. At least one laboratory now builds instruments aimed at the excess itself. Anthropic's announcement of its Claude 4 models (22 May 2025): "we've significantly reduced behavior where the models use shortcuts or loopholes to complete tasks. Both models are 65% less likely to engage in this behavior than Sonnet 3.7 on agentic tasks that are particularly susceptible to shortcuts and loopholes." The announcement gives no method; what it establishes is that the behaviour existed and that a separate measurement of it was made. The general principle has a name, *Goodhart's law*, after the economist Charles Goodhart; in the form in which it is usually reported, a measure leaned on for control stops measuring what it did. (Goodhart's own wording and venue are not checked at source here.)

In the world of products. Two instances. A reward that includes users' thumbs-up teaches whatever earns them, sycophancy among it, and a launch A/B test that measures satisfaction then shares the optimiser's target (Problem 1.7 makes the blindness exact). A language-model

judge that grades a model's answers is a good evaluator until it becomes the reward; judges show *verbosity bias* — Zheng et al. (2023) define it as a judge that "favors longer, verbose responses, even if they are not as clear, high-quality, or accurate as shorter alternatives" — and a judge in the loop teaches the length it then applauds.

What can see. An instrument that reads something the optimiser was not paid on: transcripts read by a classifier or a person; a held-out evaluation of a different kind from the reward; experts reading samples. Its independence is a resource and is spent by training against it: add the classifier's verdict to the reward and the optimiser is paid to evade the classifier (Chapter 5).

1.3 Part Three — The Three Clocks

Clock	Cadence	Sees	Cannot see	Published glimpse
the loop	every step (seconds)	the health of the run: loss, gradient norms, a corrupted step; ability, crudely	ability in any detail	Gemini 2.5's replay alarm; OLMo's online evaluation every 1000 steps
the checkpoint	every few hours	ability across a battery of evaluations	anything between checkpoints; a regression until after it happened	Tülu 3's checkpoint selection on a development suite
release	weeks	the heaviest battery: capability, safety, dangerous capabilities, people	nothing early, unless reached back into the run	Claude Opus 4: "early versions of the model during training showed other problematic behaviors"

Exhibit 1.3 (the three clocks). What each clock reads, and what it cannot; the published examples are those quoted in this chapter. Who reads each clock, and how the reading is organised, is largely unpublished; the volume says so where it infers.

The fleet's arithmetic. Two hundred evaluations on each of twelve overnight checkpoints are two thousand four hundred tests. At a five percent level with nothing changed, the expected number of "significant" results is $2400 \times 0.05 = 120$ (lab 1c) — *whatever the dependence among the evaluations*, since expectation is linear. Dependence changes how the false alarms clump, not how many there are on average. Methods built for thousands of correlated tests are Chapter 4's.

The cost of an evaluation. The same Anthropic essay records, of BBQ, that it "took the developers ~2 people years spread over 6 months across 8 people to build", and generalises: "Designing and implementing even just a single evaluation is a resource intensive effort that can take tens of people several months." The fleet costs computation and, scarcer, attention; Proposition 1.3 is the rule by which it is pruned.

1.4 Part Four — Every Number Is an Estimate

A score is the outcome of an experiment: questions put, answers drawn, a harness doing the asking and the marking. Its error bar answers the question *how much would this number move if the experiment were run again?* — and the question is incomplete until *again* is specified. The volume therefore declares, before every error bar, what is held fixed and what is drawn at random.

Model — One question set, one sample per question

The volume's alphabet, fixed here and kept throughout (the letters of Chen and colleagues): N questions; n samples drawn on each question; c of them correct; k the number of attempts counted in *pass at* k. In this chapter $n = 1$. Question i has a pass probability p_i — the chance that one sampled answer is correct — and the observed result is $y_i \in \{0, 1\}$ with $P(y_i = 1) = p_i$, independently across questions given the p_i. Two estimands must be kept apart:

- the **population pass rate** $p = \mathbb{E}[p_T]$, the mean pass probability over a population $\mathcal{D}$ of tasks T, when the N questions are drawn independently from $\mathcal{D}$;
- the **fixed-set pass rate** $\bar{p}_N = \frac{1}{N}\sum_i p_i$, when the N questions are held fixed and only the answers are drawn.

The *observed pass rate* is $\hat{p} = \frac{1}{N}\sum_i y_i$. *Governs* Proposition 1.7 and Exhibits 1.4–1.6.

Proposition 1.7 (Two variances)**.** *(a) If the questions are drawn independently from $\mathcal{D}$, then the y_i are independent Bernoulli(p) and* $\mathrm{Var}(\hat{p}) = p(1-p)/N$. *(b) Given the questions,* $\mathrm{Var}(\hat{p} \mid p_1, \ldots, p_N) = \frac{1}{N^2}\sum_i p_i(1-p_i) = \big(\bar{p}_N(1-\bar{p}_N) - s^2\big)/N$, *where $s^2 = \frac{1}{N}\sum_i (p_i - \bar{p}_N)^2$ is the spread of difficulty within the set. The fixed-set variance is the smaller by s^2/N.*

Proof. (a) Given T, y is Bernoulli(p_T); averaging over T gives $P(y = 1) = \mathbb{E}[p_T] = p$, and draws of distinct questions are independent; the variance of a mean of N independent Bernoulli(p) variables is $p(1-p)/N$. (b) Given the p_i, the y_i are independent with variances $p_i(1-p_i)$, so the variance of their mean is $\sum_i p_i(1-p_i)/N^2$; and $\frac{1}{N}\sum_i p_i(1-p_i) = \bar{p}_N - \frac{1}{N}\sum_i p_i^2 = \bar{p}_N - (s^2 + \bar{p}_N^2)$. □

The difference s^2/N is the variance contributed by *which questions happened to be asked*; Chapter 2 splits the two sources properly, by the law of total variance, and shows why more samples per question cannot remove the first.

Questions N (pass rate)	Standard error	95% half-width	Note
30 (one half)	9.13 points	17.89 points	the episode's example
120 (one half)	4.56 points	8.95 points	four times the questions
480 (one half)	2.28 points	4.47 points	sixteen times
14,079 (one half)	0.42 points	0.83 points	MMLU's test set
14,079 (0.7)	0.39 points	0.76 points	the same, nearer typical scores

Exhibit 1.4 (the root-n law). The standard error $\sqrt{p(1-p)/N}$ and the half-width 1.96 standard errors (lab 1c). For two independent scores on thirty questions the standard error of their dif-

ference is $\sqrt{2} \times 9.13 = 12.91$ points, so a gap must exceed 25.30 points to clear 1.96 standard errors.

Four sources. The questions, the sampled answers, the seeds (of sampling, of prompt construction, of training), and the harness (prompt wording, answer extraction, scoring). An error bar computed from one says nothing about the others. Llama 3 reports intervals $\mathrm{CI}(S) = 1.96\sqrt{S(1-S)/N}$, "assuming that benchmark scores are Gaussian distributed", and adds: "because subsampling is not the only source of variation, our CI values lower bound the actual variation in the capability estimate." Anthropic's 2023 essay gives the harness's contribution on MMLU: formatting changes — "changing the options from (A) to (1) or changing the parentheses from (A) to [A], or adding an extra space between the option and the answer" — "can lead to a ~5% change in accuracy on the evaluation", several times the interval the test set's size would earn (Exhibit 1.4). Anthropic's postmortem of three serving bugs (17 September 2025) supplies the diagnosis in general form: "The evaluations we ran simply didn't capture the degradation users were reporting, in part because Claude often recovers well from isolated mistakes", and "More fundamentally, we relied too heavily on noisy evaluations."

Remark 1.8 (How the volume speaks of numbers). A difference of percentages is in *points* (fifty-two against fifty is two points); a *percent* change is a ratio. The *standard error* is the spread of an estimate; the *ninety-five percent interval* is 1.96 standard errors either side. *Pass at k*, for one question, is the probability $1 - (1 - p_i)^k$ that at least one of k independent attempts succeeds; for a set, its average over questions. Its estimators, and their biases, are Chapter 2's.

1.5 Part Five — The Instincts of Product Evaluation, Amended

Judges reported by their true- and false-positive rates, gold sets of hand-labelled examples, launch gates: all kept. Four instincts are amended when the thing evaluated is a run.

1. The unit is the question, not the user. Traffic is renewable and questions are not. Sampling more answers reduces the within-question part of the variance and leaves the between-question part — the s^2/N of Proposition 1.7 — untouched.

2. A run is read as a trajectory. A launch gate reads two systems once; a run is read at every checkpoint. Lab 1a scores one frozen checkpoint — per-question pass probabilities drawn once from a $\mathrm{Beta}(2, 2)$ population and then held fixed — twenty-one times, one sample per question, and watches the fall from each cycle to the next under two rules: a *fixed* rule (alarm at a fall of two points or more) and a *scaled* rule (alarm at a fall of two standard deviations of the cycle-to-cycle difference). The checkpoint never changes; every alarm is false.

N	SE one	SE diff	fixed: per look	fixed: mean per run	fixed: at least one	scaled: per look	scaled: at least one
100	4.41	6.23	0.4048	8.10	1.000	0.0223	0.367
300	2.60	3.68	0.3090	6.18	1.000	0.0206	0.348
1000	1.41	2.00	0.1648	3.30	0.988	0.0214	0.357
3000	0.82	1.15	0.0429	0.86	0.600	0.0224	0.370
10000	0.45	0.63	0.0008	0.02	0.016	0.0227	0.375

Exhibit 1.5 (a frozen checkpoint, scored against itself). Standard errors in points. They are re-scoring standard errors — the fixed-set variance of Proposition 1.7(b) — and so smaller than the fresh-question figure (2.89 points at $N = 300$). Per-look false-alarm probabilities computed exactly from the Poisson-binomial distribution of the count of questions passed; mean false alarms in a run of twenty looks, exact; the probability of at least one false alarm in the run, simulated over 200,000 runs (Monte Carlo standard error about 0.001). Lab 1a.




Exhibit 1.6 (one run of the frozen checkpoint). Three hundred questions; true pass rate 50.72 percent (dashed); the fixed two-point rule sounds at cycles 2, 3, 5, 6, 14 and 17 (ringed) — six false alarms about a checkpoint nobody touched. Lab 1a.

Proposition 1.9 (Fixed and scaled thresholds)**.** *Approximate the fall D between two scorings as normal with mean Δ (zero for a frozen checkpoint) and standard deviation σ_N, where $\sigma_N^2 = 2\sum_i p_i(1-p_i)/N^2$ shrinks like $1/N$. A fixed rule "alarm when $D \geq \delta$" has false-alarm probability $\Phi(-\delta/\sigma_N)$, which tends to $\frac{1}{2}$ as σ_N grows and to 0 as $N \to \infty$; and it detects a true fall $\Delta < \delta$ with probability $\Phi\big((\Delta-\delta)/\sigma_N\big) \to 0$ as $N \to \infty$. A scaled rule "alarm when $D \geq z\sigma_N$" has false-alarm probability $\Phi(-z)$ for every N.*

Proof. Standardise: $P(D \geq t) = \Phi\big((\Delta - t)/\sigma_N\big)$, and take limits in σ_N. □

At $N = 10{,}000$ ($\sigma_N = 0.63$ points), a true fall of 1.5 points is caught by the fixed two-point rule with probability 0.214 and by the two-standard-deviation rule with probability 0.648 (lab 1c): too jumpy on small sets, too sleepy on large ones. Scaling fixes the dependence on N; it does not fix the number of looks. Over twenty looks the scaled rule still sounds at least once in more than one run in three (Exhibit 1.5); and because consecutive falls share a scoring, they are correlated (Problem 1.11), so the run-level rate differs a little from $1 - (1 - \Phi(-2))^{20} = 0.37$ (lab 1c).

The reference checkpoint. Keep such a frozen checkpoint for good. Re-scored every cycle on the same questions through the same harness, its true score never changes, so its movement is the instrument's: sampling noise, computable (Exhibit 1.5), or a change in the machinery — a harness edited, a server upgraded, a dataset re-downloaded — to be found. It is the training-room counterpart of the remedy Anthropic's postmortem announced for serving, evaluations run "continuously on true production systems", turned on the evaluation fleet itself. It shares the question set with everything else, so it detects drift in the machinery but not staleness or contamination of the questions. Its procedure — control limits from its own standard error, and what to do when it moves — is Chapter 4's.

3. A judge in the loop becomes a reward. For a judge used to evaluate, its error rates against a gold set are the right summary. For a judge used to reward, the direction in which it can be pushed to err matters more than how often it errs, because the optimiser pushes in that direction for the length of the run (Proposition 1.6).

4. The held-out set is spent by use. Every decision taken by consulting a set fits the choices to that set's questions; enough decisions turn a held-out set into a development set that flatters.

Corollary 1.10 (The winner's curse)**.** *Under the selection model of Part Two with $u_1 = \cdots = u_m$ and errors independent normal with standard deviation σ, the selected candidate's measured score overstates its true quality by $\sigma\,\mathbb{E}[\max_i Z_i]$ in expectation, the Z_i standard normal; an independent re-measurement is unbiased. The factor is $1/\sqrt{\pi} = 0.5642$ for two candidates,* 1.1630 *for five,* 1.5388 *for ten and* 2.5076 *for a hundred (lab 1c); ten equally good checkpoints measured to two points overstate the winner by about three.*

Proof. With equal u_i, $M_{\hat{\imath}} - u_{\hat{\imath}} = \max_i \varepsilon_i = \sigma \max_i Z_i$; the unbiasedness of the re-measurement is Proposition 1.6. The factors are the integral $\int x\, m\, \varphi(x)\Phi(x)^{m-1}\,dx$, evaluated numerically, and in closed form for $m = 2$. □

The danger of reuse has been studied formally. Dwork, Feldman, Hardt, Pitassi, Reingold and Roth: "Reusing a holdout set adaptively multiple times can easily lead to overfitting to the holdout set itself." In their synthetic demonstration, labels independent of the data, "no classifier can achieve true accuracy better than 50%. Nevertheless, reusing a standard holdout results in reported accuracy of over 63%" — on the holdout as well as the training set. The subject is *adaptive data analysis* — analysis in which each query depends on the answers to earlier ones — and a *holdout set* is a held-out set under its older name. Their remedy is the *reusable holdout*, and its first algorithm, *Thresholdout*, answers a query with the training-set mean when training and holdout agree within a noisy threshold (the analyst then learns "just a single bit"), and otherwise with the holdout mean plus calibrated noise, drawing down an "overfitting" budget; when the budget is exhausted, Thresholdout stops answering. Each consultation reveals little; the guarantee covers a number of queries exponential in the holdout's size provided the number of overfitting queries is at most quadratic in it.

Protocol — Box 1.1. Development and held-out sets

1. Before development begins, split the evaluation suite into a *development* set and a *held-out* set, and record the split.

2. Take every decision — data mixtures, hyperparameters, checkpoint selection — on the development set only, and expect its numbers to flatter the winner (Corollary 1.10).
3. Look at the held-out set once, at the end, to report; record every look. Where a held-out benchmark must inform development, ration it: OLMo 2 used "200 of 1319 GSM8k examples" as a development set and reserved "the remaining 1119" to "report final performance on them only".
4. Report both, and the gap between them. Tülu 3: "Crucially, we did not examine scores on our unseen set when developing our models, allowing us to observe how much we may have overfit to particular evaluations in our decisions around data mixtures, algorithms, and hyperparameters" — and it found overfitting to the development evaluations in precise instruction following, and to some extent in knowledge recall and reasoning.
5. If a held-out set must be consulted repeatedly, consult it through a mechanism that limits what each consultation reveals (Thresholdout), or replenish it.

1.6 Part Six — A Run, as Its Operators Saw It

The chapter's ideas, watched in one run and three later records: OPT-175B, trained by Meta in the winter of 2021–22 and written up both in a paper (Zhang et al., 2022) and in progress notes published beside it, the *chronicles*; Llama 3's interruption record; an alarm that lives in OLMo-core's training loop, and OLMo 2's spikes traced to their data; and, after pre-training, the proxy and gold curves of Gao, Schulman and Hilton.

The machine that fails. OPT-175B was trained "on 992 80GB A100 GPUs". "In total, hardware failures contributed to at least 35 manual restarts and the cycling of over 100 hosts over the course of 2 months. During manual restarts, the training run was paused, and a series of diagnostics tests were conducted to detect problematic nodes. Flagged nodes were then cordoned off and training was resumed from the last saved checkpoint." From the gap between hosts cycled and manual restarts the paper estimates "70+ automatic restarts due to hardware failures". Each restart is a roll back in its plainest form: the work since the last saved checkpoint is lost. Llama 3's report, two and a half years on, is plain about why: "a single GPU failure may require a restart of the entire job."

Run	Scale	Period	Interruptions	People
OPT-175B	992 A100 GPUs	about two months	at least 35 manual restarts; 70+ automatic (estimated); over 100 hosts cycled	an on-call rota, with "shadowers"
Llama 3 405B	up to 16K H100 GPUs	a 54-day snapshot	466 (47 planned, 419 unexpected)	"significant manual intervention" three times

Exhibit 1.7 (two runs, as their operators counted). The reports' own figures: the OPT paper, §§2.4–2.5, and its chronicles; Llama 3, §§3.3.1 and 3.3.4. Llama 3's Table 5 of root causes is not reproduced: its first row's printed share (30.1 percent) disagrees with its count (148 of 419 is 35.3 percent), and the text's 58.7 percent for GPU issues inherits the printed figure.

Dynamic loss scaling. Training in reduced precision, the smallest gradients can round to zero. *Dynamic loss scaling* multiplies the loss by a factor before back-propagation, raises the factor while steps succeed, and cuts it when the arithmetic overflows; OPT used it "to avoid underflows". A loss scale that keeps being cut is therefore an instrument: it reports values inside the model too large to represent. OPT's record: "We noticed a correlation between loss divergence, our dynamic loss scalar crashing to 0, and the ℓ_2-norm of the activations of the final layer spiking."

A restart point chosen by its instruments. On a divergence the run must go back; the question is how far. The latest checkpoint loses the least work and may already carry the trouble; an earlier one is safer and dearer. OPT's rule: "These observations led us to pick restart points for which our dynamic loss scalar was still in a 'healthy' state ($\geq$ 1.0), and after which our activation norms would trend downward instead of growing unboundedly." A threshold on one instrument and a trend on another, read — on this volume's reading, for the paper gives the two tests and not the search — backwards through the saved checkpoints: the roll-back decision of Part One, with its two errors (going back too little, and diverging again; going back too far, and paying in lost work). Going back alone did not always suffice. The chronicles record restarting "from previous checkpoints a couple of times", training getting "a bit further" before "hitting the same issue again"; the paper records that "lowering the learning rate and restarting from an earlier checkpoint allowed for the job to recover and continue training", and that early on "lowering gradient clipping from 1.0 to 0.3 helped with stability". One run's remedy, in the chronicle written at 56 percent: "we lowered our learning rate by 10%, which was sufficient for stabilizing our grad norm and activation norm." The interventions were read on an instrument they were not aimed at — Figure 2's caption: "Our mid-flight LR changes had clear effects on validation perplexity" (the body calls the same figure the validation loss).

Protocol — Box 1.2. Choosing a restart point

1. On a divergence, read the instruments that move with it — for OPT, the loss, the dynamic loss scalar, and the norm of the final layer's activations — and record which moved first.
2. Walk back through the saved checkpoints, and restart from the latest at which every such instrument was healthy: for OPT, a loss scalar at or above 1.0, and activation norms trending downward after it.
3. If a restart alone has already failed from that point, intervene before resuming: lower the learning rate, tighten gradient clipping.
4. Read the intervention on an instrument it was not aimed at — held-out loss or perplexity, not the training loss it was made to calm.
5. Record each restart with its reason and its instruments.

The generalisation is the volume's; the rules it generalises are OPT's.

The rota. The chronicles show the first clock read by people. The note at 27 percent invites colleagues to join the on-call, since "each hour the experiment stagnates or goes down costs us" money, "so the goal of the on-call is to minimize this downtime"; it remembers "the sleepless night of Thanksgiving break", and draws the lesson: "Thanksgiving break was a painful reminder that automation on this front is necessary when training at this scale". The note at 56 percent names volunteers paired with each existing team member as "shadowers", and, under a plot of training perplexity against wall-clock time, writes: "Those big holes were our Thanksgiving break." The final note sets the goal: "We have set a January infrastructure goal of training at 175B scale for 14 days without human intervention, which will allow us to officially dissolve the role of the on-call." Llama 3 reads as that goal met: "During a 54-day snapshot period of pre-training, we experienced a total of 466 job interruptions", of which 419 were unexpected, and "significant manual intervention was required only three times during this period, with the rest of issues handled by automation."

An alarm in the loop. OLMo-core's *SkipStepOptimizer* "can skip updates when the loss or gradient norm for a step is above a certain threshold of standard deviations computed over a rolling interval", with default settings of a rolling interval of 128 steps and a factor of 6 standard deviations. As the code reads (the class's source at commit 1d5c823, 6 March 2025): the loss and the gradient norm are tested separately, each against the mean and standard deviation of up to 128 previous steps, the current step excluded; the step is skipped if either stands more than six standard deviations *above* its mean, a fall never triggering a skip; nothing is skipped until 64 values are stored; and a skipped step's values still enter the history.

Model — One training statistic, step to step

$X_1, \dots, X_W$ are the values of one training statistic (the loss, or the gradient norm) over the window, and X the new step's value, all independent and identically distributed with mean μ and standard deviation σ; a trend slow enough to be absorbed by the window's mean is ignored. $\bar{X}$ and S are the window's mean and sample standard deviation, and the rule skips the step when $X > \bar{X} + zS$. Real training statistics are neither independent nor stationary: the model buys the shape of the trade-off, not any laboratory's rates. *Governs* Proposition 1.11 and Exhibits 1.8–1.9.

Proposition 1.11 (The false-skip rate under normal fluctuations)**.** *If the X_i and X are normal, then $(X - \bar{X})/\big(S\sqrt{1 + 1/W}\big)$ has Student's t distribution with $W - 1$ degrees of freedom, and the probability that the rule skips an ordinary step is $P\big(T_{W-1} > z/\sqrt{1 + 1/W}\big)$. For $W = 128$ and $z = 6$ it is 1.07×10^{-8}, about one step in ninety-three million, against $\Phi(-6) = 9.87 \times 10^{-10}$ for a rule that knew μ and σ (lab 1b).*

Proof. X and $\bar{X}$ are independent normals, so $X - \bar{X}$ is normal with mean 0 and variance $\sigma^2(1 + 1/W)$. For a normal sample, $(W - 1)S^2/\sigma^2$ has the χ^2_{W-1} distribution and is independent of $\bar{X}$; it is independent of X by construction. A standard normal divided by the square root of an independent $\chi^2_{W-1}/(W-1)$ is t_{W-1}, and $P(X > \bar{X} + zS) = P\big((X - \bar{X})/(S\sqrt{1 + 1/W}) > z/\sqrt{1 + 1/W}\big)$. □

The window's length is the lever. At $z = 6$ the rate for $W = 12$, 32, 128 and 512 is 6.28×10^{-5}, 7.96×10^{-7}, 1.07×10^{-8} and 1.93×10^{-9} — one step in about sixteen thousand, a million and a quarter, ninety-three million and five hundred million — against 9.87×10^{-10} for a known mean

and standard deviation; two standard deviations out, the two-sided tails are 0.0485 for t_{127} and 0.0455 for the normal (lab 1b). The t distribution is the normal's tail made honest about an estimated scale: the same in the middle, fatter far out, and the fatter the fewer the observations.

z	normal, exact	$\Phi(-z)$	heavy-tailed, simulated	per 10^5 steps, normal	per 10^5 steps, heavy
3	1.68×10^{-3}	1.35×10^{-3}	9.05×10^{-3}	168	905
4	5.67×10^{-5}	3.17×10^{-5}	4.07×10^{-3}	5.7	408
5	1.01×10^{-6}	2.87×10^{-7}	2.12×10^{-3}	0.10	212
6	1.07×10^{-8}	9.87×10^{-10}	1.24×10^{-3}	0.001	124

Exhibit 1.8 (false skips per step, $W = 128$). An ordinary step skipped by one statistic's test. Normal fluctuations exact (Proposition 1.11); heavy-tailed fluctuations are Student's t with three degrees of freedom, scaled to unit variance, simulated over two million steps. Lab 1b.

True spike	normal, $z = 4$	heavy, $z = 4$	normal, $z = 6$	heavy, $z = 6$
6 SD	0.974	0.952	0.505	0.642
8 SD	1.000	0.989	0.969	0.933
10 SD	1.000	0.996	1.000	0.980
15 SD	1.000	0.999	1.000	0.996

Exhibit 1.9 (catching a genuine spike). The probability that the rule skips a step whose value is raised by the stated number of true standard deviations, simulated over 200,000 steps a cell. Lab 1b.

Remark 1.12 (Why six). Proposition 1.4 prices the two errors: a false skip costs one batch unused, a missed spike may cost a rollback, and so the alarm should be jumpy — yet the default sits at six standard deviations. The volume's reading (the code records the rule, not its reasons) has two halves. In the instrument: the existence of spikes suggests heavy tails, under which a three-standard-deviation rule would skip nearly one ordinary step in a hundred (Exhibit 1.8). In the prices: a step with a high loss is often merely a hard one, and a model whose hard steps are skipped is trained on a quietly easier diet, so the false skip is dearer than its batch. Two further facts of the code bear on the rates: testing the loss and the gradient norm separately at most doubles the false-skip rate of either test alone; and a skipped spike still enters the window, inflating S, so that for the next 128 steps the effective threshold stands above six — a cost on the side of misses, not a reason for the threshold.

A spike traced to data. OLMo 2's report, on its predecessor: "Sudden spikes in the loss, and more frequently, in the gradient norm during training", with "more dramatic spikes in gradient norm often preceded training loss spikes". Then the cause: "Data can be a cause of both gradient norm and loss spikes. When investigating training batches at which spikes occurred, we found a high prevalence of instances containing long, repeated n-gram sequences." The remedies are a curation filter ("a filter that removes all documents with a sequence of 32 or more repeated n-grams, where an n-gram is any span of 1 to 13 tokens") and a safeguard in the trainer that masks such sequences out of the loss: "This intervention results in a clear mitigation—though not complete elimination—of gradient spikes. It had no effect on the slow growth in gradient norm." The alarm sat on the loss; the cause sat in the data. Telling the two apart is Chapter 4's.

Overoptimisation: the proxy and the gold. Gao, Schulman and Hilton (2022) measured the optimiser's excess of Part Two directly: "we use a synthetic setup in which a fixed 'gold-standard' reward model plays the role of humans, providing labels used to train a proxy reward model", and optimise a policy against the proxy by best-of-n sampling or by reinforcement learning, scoring it with the gold. Writing $d = \sqrt{D_{\mathrm{KL}}(\pi \,\|\, \pi_{\mathrm{init}})}$, they find for the gold score "for best-of-n (BoN) sampling, $R_{\mathrm{bon}}(d) = d(\alpha_{\mathrm{bon}} - \beta_{\mathrm{bon}} d)$, and for reinforcement learning, $R_{\mathrm{RL}}(d) = d(\alpha_{\mathrm{RL}} - \beta_{\mathrm{RL}} \log d)$", the gold reward "initially increases and later decreases", while the proxy scores "eventually grow roughly linearly in $\sqrt{\mathrm{KL}}$"; the coefficients "vary smoothly with the number of proxy reward model parameters", β falling as the proxy grows.

Remark 1.13 (Where the gold peaks). Setting the derivative to zero, the best-of-n form peaks at $d^* = \alpha_{\mathrm{bon}}/(2\beta_{\mathrm{bon}})$, with gold score $\alpha_{\mathrm{bon}}^2/(4\beta_{\mathrm{bon}})$; the reinforcement-learning form, whose derivative is $\alpha_{\mathrm{RL}} - \beta_{\mathrm{RL}}(\log d + 1)$, peaks at $d^* = \exp(\alpha_{\mathrm{RL}}/\beta_{\mathrm{RL}} - 1)$. Beyond d^* further optimisation lowers the gold score while the proxy keeps rising: the gap between the two curves is the optimiser's excess (Proposition 1.6), visible only because the gold is an instrument the optimiser is not paid on. In a real run there is no gold model; held-out evaluations stand in for it, and their job is to show the turn.




Exhibit 1.10 (two lines parting). The shapes Gao and colleagues report, with illustrative coefficients, not fitted ones: a proxy rising linearly in d, and a gold score of the best-of-n form with $\alpha = 1$ and $\beta = 0.25$, which peaks at $d^* = 2$ (Remark 1.13). Length is one documented path between the lines: Singhal et al. (first version, 2023) find that "around 70%–90% of the improvement on WebGPT and RLCD is explained purely by shifts in length" — improvement in the reward model's score, in their three settings ("STACK shows a lower value here, with only about 40% of the gain arising from length").

1.7 The Examiner's Question

The Examiner's Question

The question a laboratory puts. A checkpoint passes every test in your coding evaluation, wins its A/B test against the current model, and every behavioural evaluation on the dashboard is green. Do you ship it?

How a strong answer runs. It interrogates the evidence before deciding. (1) Which instruments share the optimiser's target? If the tests, or tests like them, were in the reward, their passing is the least informative fact present (Proposition 1.6); if user approval was

in the reward, so is the A/B test's metric. (2) Is there an instrument the optimiser was not paid on — transcripts read by a classifier or a person, a held-out evaluation of a different kind, experts? If none, say so, and build one. (3) What was sampled, and how wide are the intervals? Thirty questions apiece cannot see a drop smaller than about twenty-five points (Exhibit 1.4). (4) What does each error cost here, and how often has a dashboard this green hidden something (Exhibit 1.2)? Then decide — "ship after a transcript audit" or "hold while the missing instrument is built" can each be right.
What a weak answer misses. "Yes, everything is green" treats the optimiser's report on itself as an independent witness. "No, never trust the metrics" forgets that every decision is taken on some evidence, and that declining to decide has a price.

1.8 The Whiteboard

For the run review.

- An evaluation is worth exactly the decisions it improves; set its threshold by the prices of the two errors and the base rate (Propositions 1.3 and 1.4).
- An instrument that shares the optimiser's target cannot see the optimiser's excess; keep one instrument the optimiser is not paid on, and do not train against it (Proposition 1.6).
- Every number is an estimate, and its error bar depends on what was sampled; say which "again" an interval answers.
- Any threshold read at every look is, over enough looks, certain to cry wolf; scale it to the noise, then govern the looks (Chapter 4).
- The held-out set is spent by use: declare the split, decide on the development set, look once (Box 1.1).
- Re-score a frozen reference checkpoint every cycle (Chapter 4); pair every comparison of checkpoints (Chapter 2).
- Choose a restart point by its instruments, not by its recency; set an in-loop alarm by its prices, hidden ones included (Box 1.2, Proposition 1.11).
- Give the reward a second line on the dashboard, one the optimiser is not paid on; it is the only line that can show the turn.

The register. Debts issued: the trial the title names, and the root-n law in it; the anatomy of the error bar; the paired difference, with power and the minimum detectable effect (all Chapter 2); the thesis's four terms quantified, and the gold labels that may be wrong (Chapter 3); the reference-checkpoint procedure, the fleet's multiplicity, and the harness as first suspect (Chapter 4); the model that reads its examination, the frameworks and the safety levels, and the jury (Chapter 5). Paid within the chapter: the run restarted dozens of times, and its rota (Part Six). Episode One: 12,852 spoken words. Drift: the opening was substituted in production (the incidents first proposed could not be read at source); the closing line is the narrator's own; and in the second edition (Session 2, 21 October 2026) the course was recast in five episodes and the concordance with online experiments struck, Part Six replaced by *A Run, as Its Operators Saw It*, and the reference checkpoint moved into Part Five. In the third edition (Session 3, 3 November 2026),

by the listener's note on hearing the second ("Way too much basic statistics explained at excessive length"), the episode's walks of elementary statistics were cut to their results — the worth example, the arithmetic of a standard error, the frozen checkpoint's derivations, the definition of heavy tails — the derivations remaining here; the one exception, at the listener's instruction, is an explainer of Student's t distribution (Part Six), which this chapter's Proposition 1.11 formalises.

1.9 Problems

Tier I — Calisthenics

Problem 1.1 (Standard errors)**.** (a) A checkpoint passes 40 of 50 questions. Give the standard error of its observed pass rate and the half-width of the ninety-five percent interval, under the population model. (b) How many questions bring the standard error to one point at a pass rate of one half?

Problem 1.2 (A quieter evaluation)**.** Recompute the first two rows of Exhibit 1.2 for an evaluation that catches six broken checkpoints in ten and false-alarms on one good checkpoint in ninety. Which evaluation is worth more when breakage is common, and which when it is rare?

Problem 1.3 (The spike rule in numbers)**.** (a) From Proposition 1.11, why is the rule's false-skip rate at $z = 6$ more than ten times $\Phi(-6)$, and what happens to the ratio as the window grows? (b) A run of 500,000 steps meets five genuine spikes of eight true standard deviations. Using Exhibits 1.8 and 1.9, how many does the rule at $z = 6$ catch on average, and how many ordinary steps does it skip, under each model of the fluctuations?

Problem 1.4 (A fixed threshold at four hundred questions)**.** Every question in a set of 400 has pass probability one half. A frozen checkpoint is scored twice; the alarm sounds at a fall of two points or more. Compute the probability of a false alarm per look, exactly and by the normal approximation with and without a continuity correction, and the expected number of false alarms in twenty looks.

Problem 1.5 (The fleet)**.** A fleet runs 150 evaluations on each of 8 checkpoints and alarms on any change significant at one percent. If nothing has changed, how many alarms are expected? Does the answer depend on how the evaluations are correlated?

Tier II — The Real Thing

Problem 1.6 (The marginal reading)**.** Derive Remark 1.5 from Proposition 1.4: show that, for a family of threshold rules whose operating curve $s(f)$ is concave and differentiable, the risk is minimised where $s'(f) = (1-q)C_f/(qC_m)$, and interpret the condition in the example of Exhibit 1.2.

Problem 1.7 (Sabotage: the thumbs-up gate)**.** A launch gate ships a candidate if, in an A/B test with 200,000 users per arm, its thumbs-up rate exceeds the incumbent's by a difference significant at five percent. The probability that a user gives a thumbs-up is $t = 0.5 + 0.3\,\Delta q + 0.2\,\Delta s$, where Δq is the candidate's change in answer quality and Δs its change in sycophancy, each on a common scale. Candidate A improves quality ($\Delta q = 0.1$, $\Delta s = 0$); candidate B degrades quality and raises sycophancy ($\Delta q = -0.05$, $\Delta s = 0.225$). (a) Show that the gate ships B exactly as often as it ships A, and compute that probability. (b) Prove that *no* decision rule based only on the gate's data can ship A more often than B. (c) Name an instrument that separates them, and say what it must not share with the gate.

Problem 1.8 (The winner's curse)**.** For two candidates, prove the closed form given in Corollary 1.10,

$$\mathbb{E}[\max(Z_1, Z_2)] = 1/\sqrt{\pi},$$

and show that the overstatement grows without bound as the number of candidates grows.

Problem 1.9 (Fixed and scaled thresholds)**.** For $N = 10{,}000$ in Exhibit 1.5 ($\sigma_N = 0.63$ points), compute the probability that each rule detects a true fall of one point and of one and a half points. Explain, in a sentence a run review would accept, why the fixed rule is "too sleepy" at this size.

Problem 1.10 (A perfectly accurate evaluation worth nothing)**.** Construct a decision problem and an evaluation that reveals the state exactly, yet has worth zero. Then show, using Proposition 1.3, that an evaluation whose outcomes all lead to the same optimal action has worth zero however accurate it is.

Tier III — For the Ambitious (starred)

Problem 1.11 ($*$ Consecutive looks)**.** A frozen checkpoint is scored independently at cycles $0, 1, \ldots, T$, each score with variance v. Show that consecutive falls $D_t = S_{t-1} - S_t$ have correlation $-\frac{1}{2}$ with their neighbours and are otherwise uncorrelated. Discuss whether the chance of at least one alarm in T looks under the scaled rule is larger or smaller than under independent looks, and compare with Exhibit 1.5.

Problem 1.12 ($*$ Why Thresholdout leaks little)**.** Explain why answering with the *training*-set mean whenever training and holdout agree within a noisy threshold reveals little about the holdout set, and why the guarantee requires the number of overfitting queries to be limited.

1.10 Hints

Hint (1.1)**.** The observed pass rate is 0.8; the half-width is 1.96 standard errors. For (b), solve $\sqrt{0.25/N} = 0.01$.

Hint (1.2)**.** Misses cost $(1 - s)$ times the number broken times five days; false alarms cost f times the number good times half a day.

Hint (1.3)**.** The window's mean and standard deviation are estimates; the t distribution's tails are heavier than the normal's, and approach them as the degrees of freedom grow.

Hint (1.4)**.** A fall of two points is a fall of eight questions; the count passed is binomial with 400 trials.

Hint (1.5)**.** Linearity of expectation.

Hint (1.6)**.** Write the risk per checkpoint as $qC_m(1 - s(f)) + (1 - q)C_f f$ and differentiate in f.

Hint (1.7)**.** Compute t for each candidate. What does the gate's data depend on?

Hint (1.8)**.** $\max(a, b) = \frac{a+b}{2} + \frac{|a-b|}{2}$, and $Z_1 - Z_2$ is normal with variance 2. For the growth, compare with the probability that the maximum exceeds any fixed level.

Hint (1.9)**.** Use Proposition 1.9 with Δ equal to the true fall.

Hint (1.10). Let the loss not depend on the state.

Hint (1.11). Compute $\mathrm{Cov}(D_t, D_{t+1})$ from the shared score S_t. Negative correlation between neighbouring looks makes runs of alarms rarer.

Hint (1.12). When the two means agree, the answer is a function of the training set alone. Each disagreement spends a little of the holdout's privacy; count the disagreements.

1.11 Solutions

Solution (1.1). (a) $\sqrt{0.8 \times 0.2/50} = 0.0566$, a standard error of 5.66 points; the half-width is $1.96 \times 5.66 = 11.09$ points. (b) $N = 0.25/0.01^2 = 2{,}500$ (lab 1c).

Solution (1.2). Ten broken: misses $10 \times 0.4 \times 5 = 20$ days, false alarms $90 \times \frac{1}{90} \times 0.5 = 0.5$ days; with 20.5 against 50 without, worth 29.5 days. One broken: misses 2 days, false alarms $99 \times \frac{1}{90} \times 0.5 = 0.55$ days; with 2.55 against 5, worth 2.45 days. When breakage is common the original evaluation is worth more (42.5 against 29.5 days); when it is rare the quieter one is (2.45 against 1.75). The best threshold depends on the base rate, as Proposition 1.4 says it must (lab 1c).

Solution (1.3). (a) The rule measures the new value against an *estimated* mean and standard deviation, so the standardised value is t_{127}, scaled by $\sqrt{1 + 1/128}$, rather than normal; at six standard deviations the t tail is heavier, 1.07×10^{-8} against 9.87×10^{-10} (lab 1b). As W grows, t_{W-1} tends to the normal and the scaling to one, so the ratio falls towards one. (b) Normal fluctuations: $5 \times 0.969 = 4.8$ spikes caught, and $500{,}000 \times 1.07 \times 10^{-8} \approx 0.005$ ordinary steps skipped. Heavy-tailed: $5 \times 0.933 = 4.7$ caught, and $500{,}000 \times 1.24 \times 10^{-3} \approx 620$ skipped — for one statistic's test; testing the gradient norm as well roughly doubles it.

Solution (1.4). The standard deviation of the difference of two scorings is $\sqrt{2 \times 0.25/400} = 0.0354$, that is 3.54 points. A fall of two points or more is a fall of at least eight questions; the exact probability, from the convolution of two binomial distributions, is 0.2980; the normal approximation gives 0.2858 without a continuity correction and 0.2979 with one (threshold 7.5/400). Twenty looks bring $20 \times 0.2980 = 5.96$ false alarms on average (lab 1c).

Solution (1.5). $150 \times 8 \times 0.01 = 12$ alarms on average. No: expectation is linear whatever the dependence. Correlation changes the distribution of the count — alarms arrive in clumps — not its mean.

Solution (1.6). Per checkpoint the risk at operating point f is $R(f) = qC_m(1 - s(f)) + (1 - q)C_f f$, so $R'(f) = -qC_m s'(f) + (1 - q)C_f$. Concavity makes s' decreasing, so R is convex and is minimised where $R'(f) = 0$, that is $s'(f) = (1 - q)C_f/(qC_m)$. Lowering the threshold raises both s and f; it pays while $qC_m\,\Delta s > (1 - q)C_f\,\Delta f$. In counts per hundred checkpoints, the extra catches are $100q\,\Delta s$ and the extra false alarms $100(1 - q)\,\Delta f$, and the condition reads: extra false alarms per extra catch fewer than C_m/C_f. In Exhibit 1.2, $C_m/C_f = 5/0.5 = 10$.

Solution (1.7). (a) For A, $t = 0.5 + 0.3 \times 0.1 = 0.53$; for B, $t = 0.5 - 0.3 \times 0.05 + 0.2 \times 0.225 = 0.5 - 0.015 + 0.045 = 0.53$. Each user's thumbs-up is a Bernoulli(t) draw, so the gate's data — the counts of thumbs-up in each arm — have the same distribution under A as under B. The standard error of the difference of two rates near one half with 200,000 users per arm is $\sqrt{2 \times 0.25/200{,}000} =$

0.00158; the true difference 0.03 is about nineteen standard errors, so both candidates ship with probability indistinguishable from one. Shipping B lowers quality by 0.05 on the common scale. (b) Any rule based on the gate's data is a function of a random variable whose distribution is identical under A and B; its probability of shipping is therefore identical. No threshold, test or sequential procedure on that data can prefer A. The gate is not merely noisy here: it is structurally blind, because it measures t, and t is the optimiser's target. (c) A measurement of quality that does not pass through users' approval — for instance, expert grading of correctness against references, or a held-out task suite scored by checks of correctness — distinguishes $\Delta q = 0.1$ from $\Delta q = -0.05$. It must not share the thumbs-up signal, nor have been used as a training reward for these candidates (Proposition 1.6).

Solution (1.8)**.** $\mathbb{E}[\max(Z_1, Z_2)] = \mathbb{E}\left[\frac{Z_1+Z_2}{2}\right] + \frac{1}{2}\mathbb{E}|Z_1 - Z_2| = 0 + \frac{1}{2}\sqrt{2}\sqrt{2/\pi} = 1/\sqrt{\pi} = 0.5642$, using $\mathbb{E}|W| = \sigma\sqrt{2/\pi}$ for W normal with mean zero and standard deviation $\sigma = \sqrt{2}$. For growth: for any level c, $P(\max_i Z_i \le c) = \Phi(c)^m \to 0$ as $m \to \infty$, so the maximum eventually exceeds every level. Splitting on the event $\{\max_i Z_i > c\}$, and using $\max_i Z_i \ge Z_1 \ge -|Z_1|$ on its complement, gives $\mathbb{E}[\max_i Z_i] \ge c\,P(\max_i Z_i > c) - \mathbb{E}|Z_1|$; as m grows the probability tends to one, so the expectation eventually exceeds $c - \sqrt{2/\pi}$, for every c. The values 1.1630, 1.5388 and 2.5076 for five, ten and a hundred candidates are from lab 1c.

Solution (1.9)**.** By Proposition 1.9, a true fall Δ triggers a rule with threshold t with probability $\Phi((\Delta - t)/\sigma_N)$. Fixed rule, $t = 2$: $\Phi(-1/0.63) = 0.056$ for a one-point fall and $\Phi(-0.5/0.63) = 0.214$ for one and a half points. Scaled rule, $t = 1.26$: $\Phi(-0.26/0.63) = 0.340$ and $\Phi(0.24/0.63) = 0.648$ (lab 1c). The sentence: at ten thousand questions the noise is two thirds of a point, so a two-point threshold ignores regressions three times the noise.

Solution (1.10)**.** Let $\Theta = \{\theta_1, \theta_2\}$, $A = \{a_1, a_2\}$, and $L(\theta, a_1) = 0$, $L(\theta, a_2) = 1$ for both states; let $X = \theta$ exactly. Then a_1 is optimal under the prior and under every posterior, so by Proposition 1.3 the worth is zero: the evaluation is perfect and the decision does not depend on what it measures. Generally, if a single action minimises $\rho(x, \cdot)$ for almost every x, the equality case of Proposition 1.3 holds and $V(X) = 0$, whatever the accuracy.

Tier III: by standing policy, hints only.

1.12 The Reading

Gemini Team, Google, "Gemini 2.5: Pushing the Frontier with Advanced Reasoning, Multimodality, Long Context, and Next Generation Agentic Capabilities", 2025, §2.3. The section on training infrastructure; the replay alarm is one short numbered item of it, in its makers' words. Read them for the economics of an instrument read during a run; the rest of the report is capability, for another day.

Dixit et al., "Silent Data Corruptions at Scale", Facebook, 2021. The anatomy of one silent fault, traced to a single core with clean logs. Skim for the method; savour §§4–5.

Anthropic, "Challenges in evaluating AI systems", 4 October 2023. The bias score of zero, the cost of building and implementing one benchmark, and MMLU's sensitivity to formatting. Short; read it whole.

Anthropic, "A postmortem of three recent issues", 17 September 2025. Serving, not training, but the section "Why detection was difficult" is the best short account in print of evaluations too noisy to see a real fault.

Anthropic, "Introducing Claude 4" and "Activating AI Safety Level 3 protections", both 22 May 2025. The first for the measured reduction in "shortcuts or loopholes", the second for a decision taken because an evaluation could not rule a risk out.

Groeneveld et al., "OLMo: Accelerating the Science of Language Models", 2024, §2.4. An evaluation run in-loop to make decisions of model design, described under the heading "In-Loop Training Ablations".

OLMo Team, "2 OLMo 2 Furious", 2025, §2.5, §3 and §4. The development and held-out discipline, the rationed GSM8K, and the advocacy of declaring the split; and, in §3, the spikes traced to repeated n-grams.

Lambert et al., "Tülu 3: Pushing Frontiers in Open Language Model Post-Training", 2024, §2.2 and §7. The unseen suite, kept unexamined, and the measured overfitting to the development suite.

Llama Team, Meta, "The Llama 3 Herd of Models", 2024, §5.1.1. The paragraph "Significance estimates": the honest error bar, and its honest caveat.

Zheng et al., "Judging LLM-as-a-Judge with MT-Bench and Chatbot Arena", NeurIPS 2023 (Datasets and Benchmarks), §3.3. Verbosity bias, defined and measured.

Dwork, Feldman, Hardt, Pitassi, Reingold and Roth, "Generalization in Adaptive Data Analysis and Holdout Reuse", 2015. The danger of reusing a holdout, demonstrated, and Thresholdout; the theory is in "Preserving Statistical Validity in Adaptive Data Analysis" (STOC 2015).

Zhang et al., "OPT: Open Pre-trained Transformer Language Models", 2022, §§2.4–2.5. The hardware failures, the loss divergences, and the rule by which restart points were chosen, in a page; read with the team's progress notes, the OPT chronicles (November 2021 to January 2022), for the rota and the holes in the chart.

Allen Institute for AI, OLMo-core, the class *SkipStepOptimizer* (commit 1d5c823, 6 March 2025). An in-loop alarm in a dozen lines of code: the rule of Proposition 1.11, as a laboratory ships it.

Gao, Schulman and Hilton, "Scaling Laws for Reward Model Overoptimization", 2022. The proxy and the gold, measured; §1 for the forms, §3 for their coefficients.

Singhal, Goyal, Xu and Durrett, "A Long Way to Go: Investigating Length Correlations in RLHF", arXiv 2310.03716, first version 2023 (COLM 2024), §3.1. How much of a reward's improvement was length, setting by setting; the quotation in Exhibit 1.10 is the first version's.

Chapter 2

The Remedy

Companion to Episode Two. The statistics of evaluations, not statistics: two numbers for one examination; the trial of the pyx and the Master's Remedy, multiplied by n where it should have grown by $\sqrt{n}$; the two parts of an evaluation's error bar, and why more samples cannot rescue a small set; clustered questions; the paired difference; the third draw, the training run itself; power, and what a set can see; small sets and the interval that collapses; and pass at k, the majority vote and pass to the k, with their estimators and the two directions in which a careless one errs.

2.1 Opening — Two Numbers for One Examination

Model and benchmark	Score	Procedure, as the source labels it
Gemini 1.0 Ultra, MMLU	83.7%	"5-shot"
Gemini 1.0 Ultra, MMLU	90.0%	"maj@32"
GPT-4, MMLU	86.4%	"5-shot"
DeepSeek-R1-Zero, AIME 2024	71.0	pass@1, averaged over sampled answers
DeepSeek-R1-Zero, AIME 2024	86.7	cons@64 (majority of 64)

Exhibit 2.1 (two numbers for one examination). The Gemini figures from Google DeepMind's build of the Gemini 1.5 report (30 October 2024), Table 11; GPT-4's from its technical report, Table 2; DeepSeek-R1-Zero's from the R1 report, Table 2. Like for like, five-shot against five-shot, GPT-4 leads by 2.7 points; the majority-vote line reverses the order. The R1-Zero pair is one model on one thirty-problem set, 15.7 points apart by procedure alone.

A score is not a measurement until its procedure is stated: the number of questions, the samples drawn per question and their temperature, the rule that combines them, and the interval. Two scores are compared only when the procedures match.

2.2 Part One — The Master's Remedy

Garcia's thesis on P. A. MacMahon, Deputy Warden of the Standards at the Board of Trade from 1906, describes the trial of the pyx in his day: sample coins set aside through the year in boxes, a jury of the Goldsmiths' Company summoned by the Remembrancer, standards of diameter, weight

and composition tested by the London Assay Office, and a verdict usually in May. Of the tolerance for a consignment it records: "It was customary to calculate an overall allowable error in the pyx trials by simply summing the products of the number n of each coin by the allowance r for that coin, $\sum nr$; this was known as the 'Master's Remedy'. MacMahon pointed out that the square root of the sum of the products of the number of coins and the square of the allowance, $\sqrt{\sum nr^2}$, would make more sense, since any errors would be distributed normally. It is not clear from the surviving documents whether this suggestion was adopted."
The thesis does not say how the allowance was meant. This volume reads it as a tolerance on the single coin, set at z standard deviations of the coin's error; under that reading MacMahon's form holds the consignment to the same confidence as the coin, which fits his reason ("since any errors would be distributed normally").

Proposition 2.1 (The batch's tolerance)**.** *Let the errors of n coins of one kind be independent and normal, with mean zero and standard deviation σ, and let the allowance be the tolerance $r = z\sigma$, which an honest coin exceeds with probability $\alpha = 2(1-\Phi(z))$. The total has standard deviation $\sigma\sqrt{n}$, and the tolerance at the same z is $z\sigma\sqrt{n} = r\sqrt{n}$; across kinds j, with n_j coins of allowance $r_j = z\sigma_j$, it is $\sqrt{\sum_j n_j r_j^2}$, MacMahon's form. The Master's Remedy $\sum_j n_j r_j$ exceeds it by a factor that, for a single kind, is $\sqrt{n}$; and an honest consignment of one kind uses more than the fraction $1/\sqrt{n}$ of the Master's room with probability α only.*

Proof. Variances of independent errors add: the total has variance $n\sigma^2$, normal, and exceeds $z\sigma\sqrt{n} = r\sqrt{n}$ in absolute value with probability α. Across kinds the variance is $\sum_j n_j\sigma_j^2$, and z times its root is $\sqrt{\sum_j n_j r_j^2}$. For one kind, $nr/(r\sqrt{n}) = \sqrt{n}$, and using more than $1/\sqrt{n}$ of the room nr is the event that the total exceeds $r\sqrt{n}$. □

Proposition 2.2 (What the Master's Remedy hides)**.** *Suppose every coin carries a common bias b besides its independent error, and write $z_{1-\beta}$ for the normal quantile. (a) Under the Master's Remedy, for any fixed $|b| < r$ the consignment passes with probability tending to one as n grows. (b) Under MacMahon's remedy $r\sqrt{n}$, the expected total reaches the tolerance at $|b| = r/\sqrt{n}$, where the consignment is flagged about half the time; it is flagged with probability at least $1-\beta$ once $|b| \geq (z + z_{1-\beta})\,\sigma/\sqrt{n}$. At $z = 1.96$ and power 0.8 that is $2.80\,\sigma/\sqrt{n}$: $0.280\,\sigma$ for a hundred coins, $0.028\,\sigma$ for ten thousand (lab 2d).*

Proof. The total is $nb+e$, with e normal of standard deviation $\sigma\sqrt{n}$. (a) The consignment fails only if $|e| > n(r - |b|)$; the right side grows as n, the scale of e as $\sqrt{n}$, so the probability of failing tends to nought. (b) Take $b > 0$; the consignment is flagged when $|nb + e| > z\sigma\sqrt{n}$. At $nb = z\sigma\sqrt{n}$, that is $b = r/\sqrt{n}$, the event $e > 0$ has probability one half, and the other tail adds a negligible amount. At $nb = (z + z_{1-\beta})\sigma\sqrt{n}$ the event $e > -z_{1-\beta}\,\sigma\sqrt{n}$ already has probability $1-\beta$. □

That a Master could have exploited the gap is this volume's gloss, not the thesis's. The lesson for an evaluation is the remedy of Chapter 1's Proposition 1.9: a tolerance must scale with the standard error, not with the size of the batch.

2.3 Part Two — Questions and Answers

Model — Questions from a population, answers from a model

A set of N questions is drawn independently from a population of tasks; question i has pass probability p_i, distributed as F with mean $\bar{p}$, variance $\mathrm{Var}(p)$, and mean within-question variance $\mathbb{E}[p(1-p)]$. Each question is answered n times independently, and the score is $\hat{\mu} = \frac{1}{N}\sum_i \frac{1}{n}\sum_j y_{ij}$. *Governs* Proposition 2.3 and Exhibit 2.2; Proposition 2.4 relaxes the independence to clusters.

Proposition 2.3 (The two parts of the error bar)**.** $\mathrm{Var}(\hat{\mu}) = \mathrm{Var}(p)/N + \mathbb{E}[p(1-p)]/(Nn)$. *The first term, from which questions were asked, does not depend on n; as $n \to \infty$ the standard error falls to $\sqrt{\mathrm{Var}(p)/N}$ and no further.*

Proof. By the law of total variance over the draw of the questions,

$$\mathrm{Var}(\hat{\mu}) = \mathrm{Var}\big(\mathbb{E}[\hat{\mu} \mid p_1, \ldots, p_N]\big) + \mathbb{E}\big[\mathrm{Var}(\hat{\mu} \mid p_1, \ldots, p_N)\big].$$

The conditional mean is $\frac{1}{N}\sum p_i$, of variance $\mathrm{Var}(p)/N$; the conditional variance is $\frac{1}{N^2}\sum_i p_i(1-p_i)/n$, of expectation $\mathbb{E}[p(1-p)]/(Nn)$. □

Miller (2024, §3) states the same decomposition — "the variance associated with choosing questions from the super-population, and the mean conditional variance" — and draws the same conclusion: the first part "is a property of the super-population and therefore immutable", and "Once $\mathbb{E}[\sigma_i^2]/K \ll \mathrm{Var}(x)$, increasing K further will have little effect on the standard error." He adds two warnings: "computing a pooled standard error across all KN answers will be inconsistent" (Problem 2.7), and "In neither case should the sampling temperature be adjusted for the sake of reducing variance in the scores." DeepSeek-R1's report gives the practice and its reason: greedy decoding "results in higher repetition rates and significant variability across different checkpoints", so it reports pass@1 averaged over n samples, "typically between 4 and 64", at temperature 0.6. (Miller writes K for the samples per question; this volume keeps n, as Chapter 1 fixed it.)

Population of questions	N	$n=1$	$n=4$	$n=16$	$n=64$	$n\to\infty$
Beta(2, 2): moderately varied	30	9.13	5.77	4.56	4.21	4.08
	100	5.00	3.16	2.50	2.30	2.24
	500	2.24	1.41	1.12	1.03	1.00
Beta(0.5, 0.5): mostly easy or hard	30	9.13	7.22	6.65	6.51	6.45
	100	5.00	3.95	3.64	3.56	3.54
	500	2.24	1.77	1.63	1.59	1.58

Exhibit 2.2 (questions against samples). The standard error of the score in points, exact by Proposition 2.3, for two populations with mean pass rate one half; the questions' share of the one-sample variance is 0.20 and 0.50. Simulated checks at $N = 30$ agree within a hundredth. Lab 2a.

Clustered questions. Questions that share a passage, a repository or a translation rise and fall together.

Proposition 2.4 (The design effect)**.** *If the N questions come in clusters of m whose results have common variance σ^2 and correlation ρ within a cluster and none across clusters, then* $\operatorname{Var}(\hat{\mu}) = \frac{\sigma^2}{N}\big(1 + (m-1)\rho\big)$*; the clustered standard error is the naive one times* $\sqrt{1 + (m-1)\rho}$*.*

Proof. Each cluster's sum has variance $m\sigma^2 + m(m-1)\rho\sigma^2$; there are N/m independent clusters, and the mean divides the total variance by N^2. □

Cluster size m	$\rho = 0.1$	$\rho = 0.3$	$\rho = 0.5$
1	1.00	1.00	1.00
5	1.18	1.48	1.73
10	1.38	1.92	2.35
20	1.70	2.59	3.24

Exhibit 2.3 (the clustered factor). The multiple of the naive standard error, $\sqrt{1 + (m-1)\rho}$. Lab 2a. Miller's Table 4, on Anthropic models, measures factors of 3.05 on DROP, 1.88 on MGSM and 1.10 on RACE-H; Anthropic's post: "clustered standard errors on popular evals can be over three times as large as naive standard errors." Miller's estimator (his Eq. 4) sums the within-cluster cross products of residuals; the design effect above is its value under the model.

2.4 Part Three — Comparing Two Checkpoints

Proposition 2.5 (The paired difference)**.** *Let checkpoints A and B answer the same N questions, with per-question results of variances σ_A^2, σ_B^2 and correlation ρ, independent across questions. The mean of the per-question differences has variance $(\sigma_A^2+\sigma_B^2-2\rho\sigma_A\sigma_B)/N$; with equal variances, $2\sigma^2(1-\rho)/N$, a standard error $\sqrt{1-\rho}$ times the unpaired one.*

Proof. $\operatorname{Var}(y_i^A - y_i^B) = \sigma_A^2 + \sigma_B^2 - 2\operatorname{Cov}(y_i^A, y_i^B)$, and the N differences are independent. □

At $\rho = 0.3$, 0.5 and 0.7 the factor $\sqrt{1-\rho}$ is 0.84, 0.71 and 0.55 (lab 2d). Anthropic's post: "In practice, we find the correlation of question scores on popular evals between frontier models to be substantial—between 0.3 and 0.7 on a scale of −1 to +1." That range is between *frontier models*; for checkpoints of one run the volume expects more, an expectation and not a published figure. Miller (§4.2): "paired differences represent a 'free' reduction in estimator variance when comparing two models. We therefore recommend using the paired version of the standard error estimate wherever practicable." The pairing is lost for good if only totals are stored; keep per-question results for every checkpoint.

2.5 Part Four — Comparing Two Runs

Two checkpoints of one run differ by training; two runs of different recipes differ by the recipe and by everything random in their making. Madaan et al. (2024) trained ten Llama-2-7B-architecture models for 210B tokens: "These 10 runs are identical, except for the model initialisation seed", with "a deterministic data ordering". Their Table 1 reports each benchmark's seed standard

deviation (averaged over 21 checkpoints) beside its 95% interval from the number of questions, which is 1.96 standard errors.

Benchmark	N	seed SD	SE	SD/SE	two runs, 95% band
ARC-C	1,165	0.80	1.40	0.57	±2.2
COPA	100	2.15	4.23	0.51	±6.0
HumanEval	164	1.11	2.03	0.55	±3.1
Hellaswag	10,042	0.21	0.47	0.44	±0.6
MMLU (letters)	14,042	0.57	0.37	1.55	±1.6
MMLU-Cloze	14,042	0.22	0.40	0.55	±0.6
GSM8k	1,319	0.41	0.44	0.92	±1.1
MATH	5,000	0.23	0.14	1.61	±0.6

Exhibit 2.4 (the third draw). Seed standard deviations as printed in Madaan et al., Table 1; the standard error (the printed 95% interval over 1.96), the ratio, and the band within which two single runs of one recipe differ by chance ($1.96\sqrt{2}$ seed SDs) are the volume's arithmetic. Across all fourteen rows the ratio runs from 0.40 to 1.61: the seed's wobble is of the same order as the questions'. Lab 2e.

Proposition 2.6 (Two single runs)**.** *Let a run's score be μ_R+s+e, with μ_R the recipe's mean, s a seed effect of variance σ_s^2, and e the measurement's error of variance σ_e^2, all independent. The difference of single runs of recipes A and B has variance $2\sigma_s^2 + \mathrm{Var}(e_A - e_B)$, and no single run identifies σ_s^2; pairing on shared questions reduces* $\mathrm{Var}(e_A - e_B)$ *and leaves $2\sigma_s^2$.*

Proof. The seed effects of the two runs are independent, contributing $2\sigma_s^2$; the measurement errors contribute $\mathrm{Var}(e_A - e_B)$, which Proposition 2.5 reduces when the questions are shared. A single run yields one draw of $s + e$, from which s cannot be separated. □

Madaan et al. on the comparison: the interval "is easily computable from a single training run, whereas the former requires multiple (expensive) training runs with different seeds"; and, for an ablation, "we would want the performance increase to be larger than that due to random seed variance". Magnusson et al. (DataDecide, AI2, 2025) trained "a suite of 1,050 models using 25 data recipes × 14 model scales × 3 random seeds for initialization and data order"; "the standard deviation between runs at the 1B 5×C scale can be as high as 2% points of accuracy for some recipes on most tasks"; "The evaluation must separate pairs of data recipes by an amount greater than combined noise from run-to-run variance of each of the pair's runs"; and ranking by single runs at 150M parameters predicts the 1B winner in "~ 80% of comparisons". A ten-seed standard deviation is known to about ±24%, a three-seed one to about ±50% (lab 2e).

2.6 Part Five — What a Set Can See

Proposition 2.7 (Questions needed, and the minimum detectable effect)**.** *For a two-sided test at level α with power $1-\beta$, to detect a difference δ when one question contributes variance V to the difference ($V = 2\sigma^2$ unpaired, $2\sigma^2(1-\rho)$ paired), the number of questions needed is approximately $N = (z_{1-\alpha/2} + z_{1-\beta})^2 V/\delta^2$, and a set of N questions has minimum detectable effect $(z_{1-\alpha/2} + z_{1-\beta})\sqrt{V/N}$.*

Proof. Under the normal approximation the test statistic is $\hat{\delta}/\sqrt{V/N}$; it exceeds $z_{1-\alpha/2}$ with probability $1-\beta$ when $\delta\sqrt{N/V} - z_{1-\alpha/2} = z_{1-\beta}$. □

At $\alpha = 0.05$ and power 0.8 the constant $(z_{0.975} + z_{0.8})^2$ is 7.849 (lab 2d). Miller's worked example (§5): to detect three points at power 0.8 "the eval will need to contain at least" 969 "independent questions", parameters he calls fictional but reasonable, whence "new evals should contain at least 1,000 questions in order to have good signaling ability."

Comparison, two points	power 0.8	power 0.9
unpaired	9,811	13,134
paired, $\rho = 0.3$	6,868	9,194
paired, $\rho = 0.5$	4,906	6,567
paired, $\rho = 0.7$	2,943	3,940
paired, $\rho = 0.9$	981	1,313

Exhibit 2.5 (questions needed to see a two-point difference). Pass rates near one half, one answer per question, two-sided at five percent. Lab 2b.

Set	N	unpaired	paired, 0.7	per question
AIME (two sittings)	30	36.2	19.8	3.33
tau-bench, retail tasks	115	18.5	10.1	0.87
HumanEval	164	15.5	8.5	0.61
GSM8K, test set	1,319	5.5	3.0	0.08
MMLU, test set	14,079	1.7	0.9	0.01

Exhibit 2.6 (what real sets can see). Minimum detectable effects in points at power 0.8, pass rates near one half; the sizes are the sources' (MathArena's AIME 2025 configuration; the tau-bench paper's 115 retail tasks, its Table 1; Chen et al., "164 hand-written programming problems"; OLMo 2's 1,319 GSM8K examples; the MMLU paper's 14,079), the arithmetic the volume's. Lab 2b.

Small sets. Hochlehnert et al. (2025): "A change in just one question shifts Pass@1 by 2.5–3.3 percentage points", and "For small benchmarks (e.g., AIME'24), run evaluations with at least ten random seeds." Bowyer, Aitchison and Ivanova (ICML 2025): CLT-based methods on small sets "perform very poorly, usually dramatically underestimating uncertainty"; when every answer is right or every answer wrong, "the CLT-based interval (Eq.2) vanishes, since $SE(\hat{\theta}) = 0$, which is clearly not right"; and at $N = 100$, "95% CLT-based intervals achieve a coverage of only 92.5%". Their recommendation is the Wilson score or a Bayesian interval.

Definition 2.8 (The Wilson interval)**.** For c passes in N, with $\hat{p} = c/N$ and $z = z_{0.975}$, the Wilson interval is $\dfrac{\hat{p} + z^2/(2N)}{1 + z^2/N} \pm \dfrac{z}{1 + z^2/N}\sqrt{\dfrac{\hat{p}(1-\hat{p})}{N} + \dfrac{z^2}{4N^2}}$, the set of p not rejected by the score test $|\hat{p} - p| \le z\sqrt{p(1-p)/N}$.

N	Wald, mean	Wald, worst	Wilson, mean	Wilson, worst
30	0.883	0.260	0.952	0.930
100	0.927	0.633	0.949	0.921

Exhibit 2.7 (coverage of the nominal ninety-five percent interval). Exact coverage from the binomial distribution, averaged over true pass rates from 0.01 to 0.99, and the worst case. At thirty for thirty the Wald interval is the single point 1; the Wilson interval is $(0.886, 1.000)$, and at none of thirty $(0.000, 0.114)$. Lab 2b.

2.7 Part Six — Pass at k, and Its Cousins

Theorem 2.9 (The unbiased estimator of pass at k)**.** *For one problem with pass probability p, draw $n \geq k$ answers and let c pass. Then $\mathbb{E}\left[1 - \binom{n-c}{k} / \binom{n}{k}\right] = 1 - (1-p)^k$, and $\mathbb{E}\left[\binom{c}{k} / \binom{n}{k}\right] = p^k$.*

Proof. Given c, the ratio $\binom{n-c}{k}/\binom{n}{k}$ is the probability that k answers chosen without replacement from the n are all failures. Unconditionally, the n answers are independent draws, so a uniformly chosen subset of k of them is itself k independent draws, all failing with probability $(1-p)^k$. The same argument with successes gives p^k. □

Chen et al. (2021, §2.1 and Appendix A): drawing exactly k "can have high variance"; they draw $n = 200$, and the estimator "is unbiased, because it estimates the fail probability (1−pass@1)^k as the probability of drawing k failed samples without replacement"; the plug-in $1-(1-\hat{p})^k$ "results in a consistent underestimate", and "The gap doesn't fully close even when $n > 5k$, and results can seem better with more samples." Their numerically stable form multiplies $1 - k/j$ for j from $n - c + 1$ to n.

Proposition 2.10 (Two biases in opposite directions)**.** *(a) For one problem with $0 < p < 1$ and $k \geq 2$, the plug-in $1 - (1 - c/n)^k$ is biased low, and $(c/n)^k$ is biased high. (b) For a set with pass probabilities p_i, the pass at k computed from the mean, $1 - (1 - \bar{p})^k$, is at least the set's true pass at k, $\frac{1}{N}\sum_i (1 - (1 - p_i)^k)$; and $\bar{p}^{\,k}$ is at most the set's pass to the k, $\frac{1}{N}\sum_i p_i^k$.*

Proof. For $k \geq 2$, $x \mapsto (1-x)^k$ and $x \mapsto x^k$ are convex on $[0,1]$, so by Jensen's inequality $\mathbb{E}[(1 - c/n)^k] \geq (1-p)^k$ and $\mathbb{E}[(c/n)^k] \geq p^k$, which is (a). For (b), apply the same inequality to the empirical distribution of the p_i: $\frac{1}{N}\sum(1-p_i)^k \geq (1-\bar{p})^k$ and $\frac{1}{N}\sum p_i^k \geq \bar{p}^{\,k}$. □

p	pass@5	$\mathbb{E}$[unbiased]	$\mathbb{E}$[plug-in]	pass^5	$\mathbb{E}[(c/n)^5]$
0.02	0.0961	0.0961	0.0793	3.20×10^{-9}	8.92×10^{-6}
0.05	0.2262	0.2262	0.1889	3.13×10^{-7}	6.45×10^{-5}
0.10	0.4095	0.4095	0.3485	1.00×10^{-5}	3.78×10^{-4}
0.20	0.6723	0.6723	0.5936	3.20×10^{-4}	2.90×10^{-3}
0.50	0.9688	0.9687	0.9331	3.12×10^{-2}	6.69×10^{-2}

Exhibit 2.8 (one problem, $n = 10$ answers, $k = 5$). Expectations computed exactly over the binomial distribution of c; at $p = 0.05$ the plug-in averages 0.158, 0.189, 0.207, 0.218 and 0.224 for $n = 5, 10, 20, 50, 200$, against 0.226. Lab 2c.

k	set's pass@k	from the mean pass rate
1	0.248	0.248
5	0.545	0.759
20	0.753	0.997
100	0.887	1.000

Exhibit 2.9 (an average of curves). A hard, varied set: pass probabilities from Beta(0.5, 1.5), mean 0.248; 11.3 percent of its problems are never solved in a hundred tries. Its pass^2 is 0.123 against $\bar{p}^{\,2} = 0.061$, its pass^5 0.040 against 0.0009. Lab 2c.

Pass to the k. Yao et al. (2024), introducing tau-bench: "pass^k (pass hat k), defined as the chance that all k i.i.d. task trials are successful, averaged across tasks", estimated without bias by $\binom{c}{k}/\binom{n}{k}$ (Theorem 2.9). Their headline: "Even for the best-performing gpt-4o function calling agent which has a $>$ 60% average task success, pass^8 drops to $<$ 25%." The project's leaderboard lists, for gpt-4o on the retail tasks, pass^1 0.604 and pass^4 0.383; $0.604^4 = 0.133$, Proposition 2.10(b) in action.

Remark 2.11 (The majority vote). Majority voting over n samples (maj@n, cons@n) scores the modal answer. As n grows it comes to exceed a single answer's accuracy on problems where the correct answer is the single most probable one, and to fall below it where a wrong answer is more probable than the right one (Problem 2.11). It is a different quantity, not a better estimate of the same one.

Protocol — Box 2.1. Reporting a score

1. State the number of questions, and whether and how they cluster.
2. State the samples per question, the temperature, and the combining rule: one answer, the mean of n, the majority of n, pass at k, pass to the k.
3. Estimate pass at k and pass to the k problem by problem with the unbiased estimators (Theorem 2.9); never through a formula from the mean (Proposition 2.10).
4. Report an interval suited to the set: clustered where the questions cluster (Proposition 2.4); Wilson or Bayesian below a few hundred questions (Definition 2.8).
5. Compare two checkpoints by the paired difference, from stored per-question results (Proposition 2.5).
6. Before reading a set for a difference, compute its minimum detectable effect (Proposition 2.7).
7. Compare only like with like: the same procedure in every line.

2.8 The Examiner's Question

The Examiner's Question

The question a laboratory puts. Checkpoint B scores three and a third points above checkpoint A on a thirty-question set, one sample per question — a single question's difference. Is B better, and what would you need to know?

How a strong answer runs. (1) The evidence is one discordant question: paired, the difference is one question with a standard error of about one question, $z \approx 1$; an exact test on one discordant pair gives $p = 1$. (2) The set cannot see three points: its minimum detectable effect is twenty to thirty-six points (Exhibit 2.6), so the reading is "this set cannot tell", not "no difference". (3) What would tell: a larger set of the same kind, compared question by question (Exhibit 2.5); more samples steady the answers but cannot lift the floor of thirty questions (Proposition 2.3); cluster the error bar if the questions group; match the procedures. (4) Decide on evidence that can see the difference, or on other grounds, and say so.

What a weak answer misses. "B is better" reads one question as a trend. "No difference" mistakes a set that cannot see for a set that saw nothing.

2.9 The Whiteboard

For the run review.

- Say how a number was made before giving it an error bar; compare like with like (Exhibit 2.1).
- A tolerance scales with the standard error, not with the batch (Propositions 2.1 and 2.2).
- Which questions you asked sets the error bar; more samples cannot rescue a small set (Proposition 2.3); cluster the error bar where questions group (Proposition 2.4).
- Pair everything; keep per-question results (Proposition 2.5).
- A difference between two runs must exceed the seed variance, which no single run can see; measure it once with several seeds (Proposition 2.6, Exhibit 2.4).
- Ask what the set could have seen before you read what it saw (Proposition 2.7).
- Below a few hundred questions, Wilson, not Wald (Definition 2.8).
- Unbiased estimators, problem by problem; never a formula from the mean (Theorem 2.9, Proposition 2.10).

The register. Debts paid: the trial the title names, and the root-n law in it (from Chapter 1); the anatomy of the error bar, the third draw of the training run (seed variance) included; the paired difference, with power and the minimum detectable effect. Debts issued: the remedy in the fleet's alerts (Chapter 4); decision accuracy, named here with DataDecide's four in five, and the cloze form of MMLU (Chapter 3); the trial's jury, and its history beyond MacMahon's day, if it can be read at source (Chapter 5). Episode Two: 8,325 spoken words. Drift: the opening is the constitution's second candidate (Gemini Ultra's two MMLU figures), the trial's history at

page level being unreadable from the production environment; the trial is told from Garcia's thesis on MacMahon, read at source. Part Four, on seed variance, is an addition to the episode's specification, a source of noise the specification had left out.

2.10 Problems

Tier I — Calisthenics

Problem 2.1 (Remedies)**.** A consignment holds 400 coins of one kind, each allowed r, a tolerance at 1.96 standard deviations σ of the coin's error. Give the Master's Remedy for the consignment, MacMahon's, and their ratio; the common bias per coin at which MacMahon's remedy flags the consignment half the time; and the bias it flags four times in five.

Problem 2.2 (A floor)**.** A set of 100 questions has $\mathrm{Var}(p) = 0.05$ and $\mathbb{E}[p(1-p)] = 0.2$. Give the standard error of the score with one, four and infinitely many samples per question.

Problem 2.3 (Clusters)**.** Three hundred questions come in clusters of ten with within-cluster correlation 0.3, at a pass rate near one half. Give the naive and the clustered standard errors.

Problem 2.4 (Pairing)**.** Two checkpoints each carry a standard error of three points on the same questions, and their per-question results correlate at 0.5. Give the standard error of their difference, unpaired and paired.

Problem 2.5 (Two single runs)**.** Two data mixtures are compared by one 7B run each; the second scores one point higher on ARC-C. Using Exhibit 2.4, is that evidence?

Problem 2.6 (Pass at five from counts)**.** Ten answers are drawn to a problem and two pass. Estimate pass at five without bias, and compare the plug-in.

Tier II — The Real Thing

Problem 2.7 (Sabotage: the pooled standard error)**.** An analyst draws 64 answers to each of 30 questions, with pass probabilities from $\mathrm{Beta}(2, 2)$, and reports the score's standard error as $\sqrt{\hat{p}(1-\hat{p})/1920}$, treating all answers as independent. Show the claim is fatal: give the true standard error, the reported one, and the true coverage of the reported ninety-five percent interval.

Problem 2.8 (Power for three points)**.** How many questions are needed to detect a three-point difference at power 0.8, paired at correlation 0.5, pass rates near one half?

Problem 2.9 (Unbiasedness)**.** Prove Theorem 2.9 by direct computation, summing over the binomial distribution of c.

Problem 2.10 (An average of curves)**.** A set holds two problems, with pass probabilities 0.9 and 0. Give its pass at five, and the figure computed from its mean pass rate.

Problem 2.11 (The majority vote)**.** On a problem the correct answer has probability 0.4, one wrong answer 0.5, and the rest is spread thinly. Compare the accuracy of one answer with that of the majority of thirty-two, as the number of samples grows.

Problem 2.12 (Thirty for thirty)**.** A model solves all thirty problems of a set. Give the Wald and Wilson ninety-five percent intervals, and say what each claims.

Tier III — For the Ambitious (starred)

Problem 2.13 (∗ The plug-in's bias to first order)**.** Show that the plug-in pass at k has bias approximately $-\frac{k(k-1)}{2}(1-p)^{k-2}\,p(1-p)/n$, and compare with the exact value at $p = 0.05$, $n = 10$, $k = 5$.

Problem 2.14 (∗ Questions or samples)**.** A new question costs c_q and a sampled answer c_s. For a fixed budget, find the number of samples per question that minimises the variance of Proposition 2.3.

2.11 Hints

Hint (2.1)**.** Proposition 2.1 for the remedies; Proposition 2.2 for the bias.

Hint (2.2)**.** Proposition 2.3, term by term.

Hint (2.3)**.** The naive standard error is $\sqrt{p(1-p)/N}$; multiply by $\sqrt{1+(m-1)\rho}$.

Hint (2.4)**.** Proposition 2.5 with equal standard errors.

Hint (2.5)**.** Proposition 2.6: two seeds alone differ within the band.

Hint (2.6)**.** The chance that five of the ten, chosen without replacement, all fail.

Hint (2.7)**.** Proposition 2.3 for the truth; the reported standard error treats 1920 answers as 1920 questions.

Hint (2.8)**.** Proposition 2.7 with $V = 2 \cdot \frac{1}{4}(1-\rho)$.

Hint (2.9)**.** Write the ratio of binomial coefficients as a product and use the identity $\binom{n}{c}\binom{n-c}{k} = \binom{n}{k}\binom{n-k}{c}$.

Hint (2.10)**.** Average the two problems' curves; then compare the curve of the average.

Hint (2.11)**.** The majority of many samples converges on the modal answer.

Hint (2.12)**.** Definition 2.8 with $\hat{p} = 1$.

Hint (2.13)**.** Expand $(1-\hat{p})^k$ to second order about p, and use $\mathrm{Var}(\hat{p}) = p(1-p)/n$.

Hint (2.14)**.** Minimise $\mathrm{Var}(p)/N + \mathbb{E}[p(1-p)]/(Nn)$ subject to $N(c_q + nc_s)$ fixed.

2.12 Solutions

Solution (2.1)**.** The Master's Remedy is $400r$, MacMahon's $20r$, a ratio of 20. MacMahon's remedy flags the consignment half the time at a common bias of $r/20 = 0.05\,r$ ($0.098\,\sigma$), and four times in five at $2.80\,\sigma/20 = 0.140\,\sigma$, or $0.071\,r$ (lab 2d). The Master's lets any bias short of r through.

Solution (2.2)**.** $\sqrt{0.05/100 + 0.2/100} = 5.00$ points with one sample; $\sqrt{0.05/100 + 0.2/400} = 3.16$ with four; the floor $\sqrt{0.05/100} = 2.24$ (lab 2d).

Solution (2.3)**.** Naive: $\sqrt{0.25/300} = 2.89$ points. Design effect $1 + 9 \times 0.3 = 3.70$, factor 1.92; clustered: 5.55 points (lab 2d).

Solution (2.4)**.** Unpaired $\sqrt{9+9} = 4.24$ points; paired $\sqrt{18 \times 0.5} = 3.00$ (lab 2d).

Solution (2.5)**.** No. Two runs of one recipe differ by chance within about ±2.2 points on ARC-C (Exhibit 2.4), before any allowance for the questions; a one-point gain is well inside it. Several seeds per recipe, or a measured seed spread at this scale, are needed.

Solution (2.6)**.** $1 - \binom{8}{5}/\binom{10}{5} = 1 - 56/252 = 0.778$; the plug-in $1 - 0.8^5 = 0.672$, lower, as Proposition 2.10(a) requires (lab 2d).

Solution (2.7)**.** By Proposition 2.3, with $\mathrm{Var}(p) = 0.05$ and $\mathbb{E}[p(1-p)] = 0.2$, the true standard error is $\sqrt{0.05/30 + 0.2/1920} = 4.21$ points. The reported one is $\sqrt{0.25/1920} = 1.14$ points, 3.69 times too small. The reported interval, $\pm 1.96 \times 1.14$ points, covers the truth with probability $2\Phi(1.96 \times 1.14/4.21) - 1 = 0.405$: four times in ten, where it promises ninety-five (lab 2d). The error is the questions' part, which no number of answers can reduce. The claim of significance fails with it: two checkpoints $3\frac{1}{3}$ points apart, judged by the pooled standard error of the difference, $\sqrt{2} \times 1.14 = 1.61$ points, give $z \approx 2.07$ and are declared different; the true unpaired standard error, $\sqrt{2} \times 4.21 = 5.95$, gives $z \approx 0.56$.

Solution (2.8)**.** $N = 7.849 \times 0.25/0.03^2 \approx 2{,}180$ (lab 2d).

Solution (2.9)**.**

$$\sum_c \binom{n}{c} p^c (1-p)^{n-c} \frac{\binom{n-c}{k}}{\binom{n}{k}} = \sum_c \binom{n-k}{c} p^c (1-p)^{n-c} = (1-p)^k \sum_c \binom{n-k}{c} p^c (1-p)^{n-k-c} = (1-p)^k.$$

The second identity follows the same way with $\binom{c}{k}$.

Solution (2.10)**.** Pass at five: $\big((1-0.1^5)+0\big)/2 = 0.500$. From the mean pass rate 0.45: $1-0.55^5 = 0.950$ (lab 2d). The unsolvable problem can never be solved, however many tries; the mean hides it.

Solution (2.11)**.** One answer is right with probability 0.4. The majority of n samples converges, as n grows, on the modal answer, which is wrong. With the thin remainder never modal and ties split, maj@32 is right with probability about 0.27 and maj@100 about 0.15, falling toward nought (lab 2d). Where the correct answer is the mode, the vote raises accuracy instead. The vote measures a different quantity.

Solution (2.12)**.** Wald: 1 ± 0, the single point 1, which claims certainty. Wilson: $(0.886, 1.000)$ (lab 2b), which says the true rate may be as low as eighty-nine in a hundred.

Tier III: by standing policy, hints only.

2.13 The Reading

Miller, "Adding Error Bars to Evals", 2024, with Anthropic's "A statistical approach to model evaluations", 19 November 2024. The two parts of the error bar, clustering, pairing and power, in ten pages; the post for its plain summary and its correlation range.

Chen et al., "Evaluating Large Language Models Trained on Code", 2021, §2.1 and Appendix A. The unbiased estimator, its stable form, and the plug-in's underestimate.

Bowyer, Aitchison and Ivanova, "Position: Don't Use the CLT in LLM Evals With Fewer Than a Few Hundred Datapoints", ICML 2025, PMLR 267. The collapse at zero and one, and the coverage at a hundred questions.

Yao et al., "tau-bench", 2024, §§3 and 5. Pass to the k, defined and measured on agents.

Hochlehnert et al., "A Sober Look at Progress in Language Model Reasoning", 2025, §3. What one question does to AIME, and the case for many seeds.

Madaan et al., "Quantifying Variance in Evaluation Benchmarks", 2024, §3 and Table 1. The seed's spread set beside the interval, and the cloze form of MMLU.

Magnusson et al., "DataDecide: How to Predict Best Pretraining Data with Small Experiments", ICML 2025, §§2.1 and 3.4. The rule that a decision must clear the run-to-run noise, and the four in five.

DeepSeek-AI, "DeepSeek-R1", 2025, §3 (evaluation setup). Why a laboratory samples many answers, and pass@1 beside cons@64.

Garcia, "The life and work of Major Percy Alexander MacMahon", PhD thesis, Open University, 2006, pp. 95–96. The trial in MacMahon's day, and the Master's Remedy.