




05

Custom Model Building with SQL in BigQuery ML


Custom Model Building with SQL in BigQuery ML

- | | |
|----|--------------------------------------|
| 01 | BigQuery ML for quick model building |
| 02 | Supported models |




Custom Model Building with SQL in BigQuery ML


- | | |
|----|--------------------------------------|
| 01 | BigQuery ML for quick model building |
| 02 | Supported models |




BigQuery ML is a way to build custom models



BigQuery ML is a way to build custom models



Working with BigQuery ML



Where was this article published?

- 1 Techcrunch
- 2 GitHub
- 3 NY Times

Unlikely Partnership in House Gives Lawmakers Hope for Border Deal


Representatives Nita M. Lowey and Kay Granger are the first women to lead the House Appropriations Committee. Their bond gives lawmakers optimism for the work to come.

By EMILY COCHRANE



Fitbit's newest fitness tracker is just for employees and health insurance members

Fitbit has a new fitness tracker, but it's one that you can't buy in stores. The company quietly uncorked the Inspire on Friday, releasing its first product that is available only to co...



1 hour ago Jon Russell

Downloading the Android Studio Project Folder

FTC Engineering edited this page on Sep 19, 2017 · 1 revision

Downloading the Android Studio Project Folder

SQL query to extract data

```
SELECT
  url, title
FROM
  `bigquery-public-data.hacker_news.stories`
WHERE
  LENGTH(title) > 10
  AND LENGTH(url) > 0
LIMIT 10
```

url	title
http://www.bbc.co.uk/news/business-27732743	Vodafone reveals direct government wiretaps
https://www.kickstarter.com/projects/appdocu/a...	Doc – App: The Human Story
http://www.starwebworld.com/android-jelly-bean...	Android Jelly Bean: Streaming Audio Through th...
http://www.myplanetdigital.com/digital_strateg...	Why Canadian Tech Entrepreneurs Need to Man/Wo...
http://startupislandconference.com/index.html	StartupConference June 13. - 16. 2013, HVAR Cr...
http://kopimism.org/	Kopimism Hactivism Meetup Tomorrow (Sunday) in...
http://unearthedgadget.com/xbox-live-gold-2/14...	Xbox Live Gold Membership Is It Really Worth -...
https://evertale.com	Evertale changes the way people remember
http://www.racketboy.com/retro/commodore-amiga...	Commodore Amiga: A Beginner's Guide
http://www.extremetech.com/extreme/156393-cold...	Cold fusion reactor "independently verified"

*no clusters, no indexes,
ad hoc query!

Use regex to get
source + train on
words of title

txtclass_words

LINK SHARING

```
1 WITH extracted AS (  
2 SELECT source, REGEXP_REPLACE(LOWER(REGEXP_REPLACE(title, '[^a-zA-Z0-9 $.-]', ' ')), " "  
FROM  
3 (SELECT  
4 ARRAY_REVERSE(SPLIT(REGEXP_EXTRACT(url, '.*://([^/]+)/'), '.')[OFFSET(1)] AS source  
5 title  
6 FROM  
7 `bigquery-public-data.hacker_news.stories`  
8 WHERE  
9 REGEXP_CONTAINS(REGEXP_EXTRACT(url, '.*://([^/]+)/'), '.com$')  
10 AND LENGTH(title) > 10  
11 )  
12 )  
13 , ds AS (  
14 SELECT ARRAY_CONCAT(SPLIT(title, " "), ['NULL', 'NULL', 'NULL', 'NULL', 'NULL']) AS words  
15 extracted  
16 WHERE (source = 'github' OR source = 'nytimes' OR source = 'techcrunch')  
17 )  
18 SELECT  
19 source,  
20 words[OFFSET(0)] AS word1,  
21 words[OFFSET(1)] AS word2,  
22 words[OFFSET(2)] AS word3,  
23 words[OFFSET(3)] AS word4,  
24 words[OFFSET(4)] AS word5  
FROM ds
```

Run

Save query

Save view

More

This query will process 204.

Query results

SAVE RESULTS

EXPLORE IN DATA STUDIO

37293	nytimes	the	socratic	shrink	NULL	NULL
37294	nytimes	still	stuck	in	a	climate
37295	nytimes	as	unlimited	data	plans	are
37296	nytimes	disney	s	neuroscience	advertising	lab
37297	nytimes	hold	that	thought	the	google

Create model

Query to extract
training data

```
CREATE OR REPLACE MODEL advdata.txtclass
OPTIONS(model_type='logistic_reg', input_label_cols=['source'])
AS
```

```
WITH extracted AS (
  ...
)
, ds AS (
  SELECT ARRAY_CONCAT(SPLIT(title, " "), ['NULL', 'NULL', 'NULL',
    'NULL', 'NULL']) AS words, source FROM extracted
  WHERE (source = 'github' OR source = 'nytimes' OR source =
    'techcrunch')
)
```

```
SELECT
  source,
  words[OFFSET(0)] AS word1,
  words[OFFSET(1)] AS word2,
  words[OFFSET(2)] AS word3,
  words[OFFSET(3)] AS word4,
  words[OFFSET(4)] AS word5
FROM ds
```

Evaluate model

```
SELECT * FROM ML.EVALUATE(MODEL advdata.txtclass)
```

precision	recall	accuracy	f1_score	log_loss	roc_auc
0.783	0.783	0.79	0.783	0.858	0.918

Actual labels	Predicted labels			
	github	nytimes	techcrunch	% samples
github	88.8%	5.29%	5.9%	37.83%
nytimes	6.34%	70.92%	22.74%	31.26%
techcrunch	5.54%	19.35%	75.11%	30.9%

(BigQuery ML splits the training data and reports evaluation statistics on the held-out set)

Predict using trained model


```
SELECT * FROM ML.PREDICT(MODEL advdata.txtclass,(
  SELECT 'government' AS word1, 'shutdown' AS word2, 'leaves' AS word3,
  'workers' AS word4, 'reeling' AS word5
  UNION ALL SELECT 'unlikely', 'partnership', 'in', 'house', 'gives'
  UNION ALL SELECT 'fitbit', 's', 'fitness', 'tracker', 'is'
  UNION ALL SELECT 'downloading', 'the', 'android', 'studio', 'project'
))
```

“Batch prediction”

Row	Predicted_source	word1	word2	word3	word4	word5
1	nytimes	government	shutdown	leaves	workers	reeling
2	nytimes	unlikely	partnership	in	house	gives
3	techcrunch	fitbit	s	fitness	tracker	is
4	techcrunch	downloading	the	android	studio	project


Demo

Train a model with BigQuery ML
to predict NYC taxi fares



Custom Model Building with SQL in BigQuery ML

- | | |
|----|--------------------------------------|
| 01 | BigQuery ML for quick model building |
| 02 | Supported models |



Linear Classifier (Logistic regression)

```
#standardsql
CREATE OR REPLACE MODEL flights.ontime
OPTIONS
  (model_type='logistic_reg', input_label_cols=['on_time']) AS
SELECT
  IF(arr_delay < 15, 1, 0) AS on_time,
  carrier,
  origin,
  dest,
  dep_delay,
  taxi_out,
  distance
FROM
  `cloud-training-demos.flights.tzcorr`
WHERE
  arr_delay IS NOT NULL
```


DNN Classifier

```
#standardsql
CREATE OR REPLACE MODEL flights.ontime
OPTIONS
  (model_type='dnn_classifier', hidden_units = [47,29,18],
   input_label_cols=['on_time']) AS
SELECT
  IF(arr_delay < 15, 1, 0) AS on_time,
  carrier,
  origin,
  dest,
  dep_delay,
  taxi_out,
  distance
FROM
  `cloud-training-demos.flights.tzcorr`
WHERE
  arr_delay IS NOT NULL
```

xgboost Classifier

```
#standardsql
CREATE OR REPLACE MODEL flights.ontime
OPTIONS
  (model_type='boosted_tree_classifier', input_label_cols=['on_time']) AS
SELECT
  IF(arr_delay < 15, 1, 0) AS on_time,
  carrier,
  origin,
  dest,
  dep_delay,
  taxi_out,
  distance
FROM
  `cloud-training-demos.flights.tzcorr`
WHERE
  arr_delay IS NOT NULL
```

Linear Regression

```
CREATE OR REPLACE MODEL
  taxi.taxifare_dnn OPTIONS (model_type='linear_reg', labels=['fare_amount']) AS
SELECT
  fare_amount,
  hourofday, dayofweek,
  pickuplon, pickuplat, dropofflon, dropofflat,
  passenger_count
FROM
  `taxi.taxi3m`
```

DNN Regression

```
CREATE OR REPLACE MODEL
  taxi.taxifare_dnn OPTIONS (model_type='dnn_regressor',
    hidden_units=[144,89,55], labels=['fare_amount']) AS
SELECT
  fare_amount,
  hourofday, dayofweek,
  pickuplon, pickuplat, dropofflon, dropofflat,
  passenger_count
FROM
  `taxi.taxi3m`
```

xgboost Regression

```
CREATE OR REPLACE MODEL
  taxi.taxifare_xgboost
  OPTIONS (model_type='boosted_tree_regressor', labels=['fare_amount']) AS
SELECT
  fare_amount,
  hourofday, dayofweek,
  pickuplon, pickuplat, dropofflon, dropofflat,
  passenger_count
FROM
  `taxi.taxi3m`
```

Train on TF, predict with BigQuery

```
CREATE OR REPLACE MODEL advdata.txtclass_tf2
OPTIONS (model_type='tensorflow',

model_path='gs://cloud-training-demos-ml/txtcls/trained_finetune_native/export/exporter/1
549825580/*')
```

```
SELECT
  input,
  (SELECT AS STRUCT(p, ['github', 'nytimes', 'techcrunch'][ORDINAL(s)]) prediction FROM
    (SELECT p, ROW_NUMBER() OVER() AS s FROM
      (SELECT * FROM UNNEST(dense_1) AS p))
  ORDER BY p DESC LIMIT 1).*

FROM ML.PREDICT(MODEL advdata.txtclass_tf2,
(
SELECT 'Unlikely Partnership in House Gives Lawmakers Hope for Border Deal' AS input
UNION ALL SELECT "Fitbit\'s newest fitness tracker is just for employees and health
insurance members"
UNION ALL SELECT "Show HN: Hello, a CLI tool for managing social media"
))
```

Recommendation engine (matrix factorization)

```
create or replace model models.suggested_products_1or2_example
options(model_type='matrix_factorization',
        user_col='user_id', item_col='product_id', rating_col='rating',
        l2_reg=10)
AS

with purchases AS (
  select product_id, user_id from
  operations.orders_with_lines, unnest(order_lines)
),

total_purchases as (
  select product_id, user_id, count(*) as numtimes
  from purchases
  group by product_id, user_id
)

select
product_id, user_id,
IF(numtimes < 2, 1, 2) AS rating
FROM total_purchases
```


So what do we recommend for a given set of users?

```
with users AS (  
  SELECT  
    user_id, count(*) as num_orders  
  from operations.orders_with_lines  
  group by user_id  
  order by num_orders desc  
  limit 10  
)  
  
products as (  
  select product_id, count(*) as num_orders  
  from operations.orders_with_lines, unnest(order_lines)  
  group by product_id  
  order by num_orders desc  
  limit 10  
)  
  
SELECT * FROM ML.PREDICT(MODEL models.suggested_products_1or2,  
(SELECT user_id, product_id  
FROM users, products)  
)
```

So what do we recommend for a given set of users?

Row	predicted_rating	user_id	product_id
1	1.5746015507788755	101797	26209
2	1.8070705987455633	101797	13176
3	1.7171094544245578	101797	27845
4	1.9763373899260837	101797	47209
5	1.8659380090171271	101797	21137
6	1.721610848530093	101797	47766
7	1.9516130703939483	101797	21903

Clustering

```
CREATE OR REPLACE MODEL  
demos_eu.london_station_clusters  
OPTIONS(model_type='kmeans', num_clusters=4,  
standardize_features = true) AS
```

```
WITH hs AS ...,  
stationstats AS ...
```

```
SELECT * except(station_name, isweekday)  
from stationstats
```

- 1 4 clusters (hardcoded)
- 2 Standardize features since different dynamic ranges
- 3 Remove the cluster “id” fields (keep just the attributes)

Which cluster?

```
WITH hs AS ...,
stationstats AS ...,

SELECT * except(nearest_centroids_distance)
FROM ML.PREDICT(MODEL demos_eu.london_station_clusters,
(SELECT * FROM stationstats WHERE
REGEXP_CONTAINS(station_name, 'Kennington'))))
```


Row	CENTROID_ID	station_name	isweekday	duration	num_trips	bikes_count	distance_from_city_center
1	3	Kennington Lane Tesco, Vauxhall	weekday	911.5810637908974	5471	9	1.8345619962343163
2	3	Kennington Lane Rail Bridge, Vauxhall	weekday	979.3919952622995	20263	19	2.175032834765301
3	4	Doddington Grove, Kennington	weekday	1397.7189755200225	7067	28	1.468140527379382
4	4	Kennington Cross, Kennington	weekday	911.5238777770538	15349	35	1.4625875338501981

Find cluster attributes

```
WITH T AS (  
  SELECT  
    centroid_id,  
    ARRAY_AGG(STRUCT(numerical_feature AS name, ROUND(feature_value,1) AS value) ORDER BY  
    centroid_id) AS cluster  
  FROM ML.CENTROIDS(MODEL demos_eu.london_station_clusters)  
  GROUP BY centroid_id  
)  
SELECT  
  CONCAT('Cluster#', CAST(centroid_id AS STRING)) AS centroid,  
  (SELECT value from unnest(cluster) WHERE name = 'duration') AS duration,  
  (SELECT value from unnest(cluster) WHERE name = 'num_trips') AS num_trips,  
  (SELECT value from unnest(cluster) WHERE name = 'bikes_count') AS bikes_count,  
  (SELECT value from unnest(cluster) WHERE name = 'distance_from_city_center') AS  
  distance_from_city_center  
FROM T  
ORDER BY centroid_id ASC
```

Visualize attributes in Google Data Studio

Row	centroid	duration	num_trips	bikes_count	distance_from_city_center
1	Cluster#1	3079.5	3026.1	14.0	6.2
2	Cluster#2	1564.0	3635.1	11.5	6.5
3	Cluster#3	1319.6	9654.8	6.4	2.9
4	Cluster#4	1527.7	4846.8	22.6	3.5




Reminder: BigQuery ML Cheatsheet

- **Label** = alias a column as 'label' or specify column in OPTIONS using input_label_cols
- **Feature** = passed through to the model as part of your SQL SELECT statement
`SELECT * FROM ML.FEATURE_INFO(MODEL `mydataset.mymodel`)`
- **Model** = an object created in BigQuery that resides in your BigQuery dataset
- **Model Types** = Linear Regression, Logistic Regression
`CREATE OR REPLACE MODEL <dataset>.<name>
OPTIONS(model_type='<type>') AS
<training dataset>`
- **Training Progress** = `SELECT * FROM ML.TRAINING_INFO(MODEL `mydataset.mymodel`)`
- **Inspect Weights** = `SELECT * FROM ML.WEIGHTS(MODEL `mydataset.mymodel`, (<query>))`
- **Evaluation** = `SELECT * FROM ML.EVALUATE(MODEL `mydataset.mymodel`)`
- **Prediction** = `SELECT * FROM ML.PREDICT(MODEL `mydataset.mymodel`, (<query>))`

Lab Intro

Predict Bike Trip Duration with a
Regression Model in BigQuery ML



Lab objectives

01

Query and explore the London bicycles dataset for feature engineering

02

Create a linear regression model in BigQuery ML

03

Evaluate the performance of your machine learning model


04

Extract your model weights



Lab Intro

Movie Recommendations in
BigQuery ML



Lab objectives

01

Create a BigQuery dataset to store and load MovieLens data

02

Explore the MovieLens dataset

03

Use a trained model to make recommendations in BigQuery

04

Make product predictions for both single users and batch users



Summary

You can train and evaluate machine learning models directly in BigQuery.

