

CQC A TÜV ROHS

型号说明 Ordering Information



电路特性 Circuitry trait

型号 Model No	电路特性 Circuitry trait			类型	端子数
				Type	Terminals
MTS-101	ON	_	0FF	SPST	2P
MTS-102	ON	_	ON	SPDT	3P
MTS-112	ON	_	(ON)	SPDT	3P
MTS-103	ON	0FF	ON	SPDT	3P
MTS-113	ON	0FF	(ON)	SPDT	3P
MTS-123	(ON)	0FF	(ON)	SPDT	3P

型号 Model No	电路特性 Circuitry trait			类型	端子数
				Type	Terminals
MTS-201	ON	_	0FF	DPST	4P
MTS-202	ON	_	ON	DPDT	6P
MTS-212	ON	_	(ON)	DPDT	6P
MTS-203	ON	0FF	ON	DPDT	6P
MTS-213	ON	0FF	(ON)	DPDT	6P
MTS-223	(ON)	0FF	(ON)	DPDT	6P

()回弹指示Indicates Momentary

技术特性 Specification


- 1.规格 Rating:6A 125VAC;3A 250VAC
- 2.接触电阻 Contact Resistance:20mΩ max
- 3.绝缘电阻 Insulation Resistance:500VDC 1000MΩ min
- 4.耐电压 Dielectric Strength:1500VAC,1Minute
- 5.操作温度 Operating Temperature:-25℃~+85℃
- 6.电气寿命 Electrical Life:10,000 Cycles 基座颜色 Base color

材料 Material	基座颜色 Base color			
塑料 PBT	蓝 Blue			
电木 Bakelite	红 Red	黑 Black		


防水帽 Water proof cap



手柄种类 Handle options




端子种类 Terminal options





MTS-101 ON-OFF SPST 2P	62.4	24*
MTS-102 ON-ON MTS-103 ON-OFF-ON Metric thread:M6×0.75 MTS-112 ON-(ON) MTS-113 ON-OFF-(ON) MTS-123 (ON)-OFF-(ON) Inch thread:1/4'-40NS SPDT 3P	924 64 1/4IN	M6X0.75 1/4-40NS 0 0 0 1/4-40NS
MTS-201 ON-OFF DPST 4P	64	08 47 132 127
MTS-202 ON-ON MTS-203 ON-OFF-ON MTS-2033 ON-ON-ON Metric thread:M6×0.75 MTS-212 ON-(ON) MTS-213 ON-OFF-(ON) MTS-223 (ON)-OFF-(ON) Inch thread:1/4'-40NS DPDT 6P	65.4 6.4 6.4	93 MXX0.75 1/4-40NS 06 07 07 08 08 08 08 08 08 08 08 08 08
MTS-302 ON-ON MTS-303 ON-OFF-ON 3PDT 9P	# <u>P.4</u> #66	08 47 47 48 48 18 18
MTS-402 ON-ON MTS-403 ON-OFF-ON 4PDT 12P	624	0.08 4.7 4.7 4.2 4.8 4.8 4.8 2.2 23
MTS-101-A2 ON-OFF SPST 2P	924 96	132 132 132 132 132 132 132 132 132 132








MTS-102-C4 ON-ON MTS-112-C4 ON-(ON) MTS-103-C4 ON-OFF-ON MTS-113-C4 ON-OFF-(ON) MTS-123-C4 (ON)-OFF-(ON) SPDT 3P	5-619 0 05 08 08 08 12 12 12 12 12 12 12 12 12 12 12 12 12
MTS-202-C4 ON-ON MTS-212-C4 ON-(ON) MTS-203-C4 ON-OFF-ON MTS-213-C4 ON-OFF-(ON) MTS-223-C4 (ON)-OFF-(ON) DPDT 6P	12.7 2.8 3.8 6.9 7.1 12.95 3.8 3.8 5
MTS-101-E1 ON-OFF SPST 2P (PLASTIC FLAT LEVER)	0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0 0.0
MTS-102-E1 ON-ON MTS-112-E1 ON-(ON) MTS-103-E1 ON-OFF-ON MTS-113-E1 ON-OFF-(ON) MTS-123-E1 (ON)-OFF-(ON) SPDT 3P (PLASTIC FLAT LEVER)	824 864 964 964 964 965 964 965 965 966 966 966 966 966 966
MTS-202-E1 ON-ON MTS-212-E1 ON-(ON) MTS-203-E1 ON-OFF-ON MTS-213-E1 ON-OFF-(ON) MTS-223-E1 (ON)-OFF-(ON) DPDT 6P (PLASTIC FLAT LEVER)	92.4 96.4 96.4 96.4 96.4 97.4 97.4 97.4 97.4 97.4 97.4 97.4 97
MTS-101-F1 ON-OFF SPST 2P (METAL FLAT LEVER)	924 924 924 924 924 95 95 96 96 1/4-40NS
MTS-102-F1 ON-ON MTS-112-F1 ON-(ON) MTS-103-F1 ON-OFF-ON MTS-113-F1 ON-OFF-(ON) MTS-123-F1 (ON)-OFF-(ON) SPDT 3P (METAL FLAT LEVER)	95 1/4-49NS 108 108 108 108 108 108 108 108 108 108







	MTS-102-A1-2 ON-ON MTS-112-A1-2 (ON)-ON SPDT 3P	96	0.8	M6X0.75
	MTS-102-A1-2L ON-ON MTS-112-A1-2L (ON)-ON SPDT 3P	°55	24'	M6x0.75
The state of the s	MTS-102-F1-2 ON-ON MTS-112-F1-2 (ON)-ON SPDT 3P	⁰⁶	23 7 7 7 7 132	M6X0.75
	MTS-102-F1-2L ON-ON MTS-112-F1-2L (ON)-ON SPDT 3P	²⁶	28 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	M650.75
	MTS-102-G1 ON-ON MTS-112-G1 (ON)-ON SPDT 3P	02.4	24*	1/4-40NS
	MTS-102-L1 ON-ON MTS-103-L1 ON-OFF-ON SPDT 3P	932	24	M2x0.75
	MTS-101-DL ON-OFF SPST 2P MTS-102-DL ON-ON MTS-103-DL ON-OFF-ON SPDT 3P	**************************************	0.8 4.7 4.7 1 13.2 4 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	93.5 M6X0.75