

## SOLUTION OF EXERCISESHEET 3

## Exercise 3-1

Trying some values:

$$\begin{array}{llllll}
 k = 2 & a = 27 & b = 72 & c = |b - a| = 72 - 27 = 45 & d = 45 & e = 54 \\
 k = 3 & a = 398 & b = 983 & c = |983 - 398| = 585 & d = 585 & e = 558 \\
 k = 3 & a = 398 & b = 938 & c = |983 - 938| = 441 & d = 441 & e = 144 \\
 k = 3 & a = 321 & b = 213 & c = |321 - 213| = 108 & d = 18 & e = 81
 \end{array}$$

In the table above one can see that the sum of the digits of  $d$ , respectively  $e$  is always a multiple of 9.

The reason for this lies in the construction of the 'pseudorandom generator'.  $b$  has the same digits like  $a$  only in an other order. To get  $c$  we subtract the greater number of those from the smaller, so  $c$  is always positive. Then we remove all 0-digits to get  $d$  and scramble the letters again for  $e$ . The sum of digits didn't change after the computation of  $c$ , so we look at  $c$  to argue that this sum is always a multiple of 9.

If  $a > b$  we compute for the sum of the digits of  $c = a - b$ :  $(a_1 - b_1) + (a_2 - b_2) + \dots + (a_n - b_n) = a_1 + a_2 + \dots + a_n - (b_1 + b_2 + \dots + b_n)$ . But this only hold if  $a_n > b_n$ .

If  $a_i < b_i$  then it is  $(a_1 - b_1) + (a_2 - b_2) + \dots + (a_{i-1} - b_{i-1} - 1) + (a_i - b_i + 10) + \dots + (a_n - b_n) = a_1 + a_2 + \dots + a_n - (b_1 + b_2 + \dots + b_n) + 9$

The sum of the digit of  $a$  has to be the same like the sum of the digits from  $b$ , because  $b$  has the same digits like  $a$  only in an other order, so  $a_1 + a_2 + \dots + a_n - (b_1 + b_2 + \dots + b_n) = 0$ .

If  $a_i < b_i$  holds for  $y$  positions the sum of the digits is  $9 \cdot y$ .  $a$  and  $b$  have the same digits, so  $a_i < b_i$  holds at least for one position, so  $y \geq 1$ .

This argumentation is the same for  $b > a$ , so the sum of the digits from  $c$ , respectively  $d$  or  $e$ , is always a multiple from 9.

If now all but the last digit of  $e$  are given one can always determine the last digit, because the sum of all digits has to be a multiple of 9. If the sum of the digits is already 9, the last bit has to be 9 as well, because all 0-digits had erased. If this is not the case, we could not determine if the last digit has to be 0 or 9.

So the described generator does not pass the next-character test.

## Exercise 3-2