



# 딥러닝 이해하기

leejeyeol92@gmail.com

# Transfer Learning

# Transfer learning


Pretrained model





학습



Weights




얻은 weights로 초기화




finetuning


# Transfer learning




# Autoencoder



# Autoencoder




# Transposed convolution



## 실습 12

CNN Autoencoder 만들고 weight 저장하기





## 실습 12

### colab + 구글드라이브



```
from google.colab import drive
drive.mount('/content/gdrive/')
```

... Go to this URL in a browser: [https://accounts.google.com/o/oauth2/auth?client\\_id=947318989803-6bn6gk8adgf4n4g6](https://accounts.google.com/o/oauth2/auth?client_id=947318989803-6bn6gk8adgf4n4g6)

Enter your authorization code:

링크 클릭 후 로그인.

로그인 이후 나오는 코드를 아래쪽 빈칸에 입력.

Mounted at /content/gdrive/ 라고 나오면 성공

## 실습 12

### colab + 구글드라이브

```
import os
#os.mkdir("/content/gdrive/My Drive/AI") #폴더를 만드는 코드이니 한번만 실행하세요. 구글드라이브에서 직접 폴더 만들어도 됩니다.
with open('/content/gdrive/My Drive/AI/hello.txt', 'w') as f:
    f.write('Hello Google Drive colab !') # 테스트용 텍스트파일 생성
!cat /content/gdrive/My Drive/AI/hello.txt #텍스트 파일 내용 출력하기
```

## 실습 12

```
class MNIST_CNN_Encoder(nn.Module):
    def __init__(self):
        super().__init__()

        self.encoder = nn.Sequential(
            nn.Conv2d(1, 16, 3, stride=3, padding=1),
            nn.ReLU(True),
            nn.MaxPool2d(2, stride=2),
            nn.Conv2d(16, 8, 3, stride=2, padding=1),
            nn.ReLU(True),
            nn.MaxPool2d(2, stride=1)
        )

    def forward(self, x):
        z = self.encoder(x)
        return z

class MNIST_CNN_Decoder(nn.Module):
    def __init__(self):
        super().__init__()

        self.decoder = nn.Sequential(
            nn.ConvTranspose2d(8, 16, 3, stride=2),
            nn.ReLU(True),
            nn.ConvTranspose2d(16, 8, 5, stride=3, padding=1),
            nn.ReLU(True),
            nn.ConvTranspose2d(8, 1, 2, stride=2, padding=1),
            nn.Tanh()
        )

    def forward(self, z):
        x_ = self.decoder(z)
        return x_
```

## 실습 12

```
epochs = 10
learning_rate = 0.01
batch_size = 100
loss_function = nn.MSELoss()

# load the dataset
dataset = datasets.MNIST('../data', train=True,
                          download=True, transform=transforms.Compose([
                              transforms.ToTensor()
                              , transforms.Normalize((0.5,), (0.5,))
                          ]))
```

-1~1 scaling으로 normalize하였으며 test loader도 이렇게 만들어줍니다.

## 실습 12

```
encoder = MNIST_CNN_Encoder().cuda()
encoder.apply(weight_init)

decoder = MNIST_CNN_Decoder().cuda()
decoder.apply(weight_init)

net_params = list(encoder.parameters()) + list(decoder.parameters())
optimizer = optim.Adam(net_params, betas=(0.5, 0.999), lr=learning_rate)
```

## 실습 12

```
train_loss_list = []
val_loss_list = []
encoder.train()
decoder.train()
for epoch in range(epochs):
    for i, (X, _) in enumerate(train_loader):
        X = X.cuda()
        z = encoder(X)
        recon_X = decoder(z)

        loss = loss_function(recon_X, X)
        optimizer.zero_grad()
        loss.backward()
        optimizer.step()

    # validation loss 계산.
    if i % 100 == 0:
        with torch.no_grad():
            val_100_loss = []
            for (X, _) in valid_loader:
                X = X.cuda()
                z = encoder(X)
                recon_X = decoder(z)
                loss = loss_function(recon_X, X)

            val_100_loss.append(loss)
            train_loss_list.append(loss)
            val_loss_list.append(np.asarray(val_100_loss).sum() / len(valid_loader))
            print("[%d/%d] [%d/%d] loss : %f" % (i, len(train_loader), epoch, epochs, loss))
```

## 실습 12

```
# 학습된 모델의 weight를 저장하는 코드
project_root_path = '/content/gdrive/My Drive/Al'
encoder_save_path = '%s/pretrained_encoder.pth' % (project_root_path)
torch.save(encoder.state_dict(), encoder_save_path)
```


## 실습 12

```
print("testing")
encoder.eval()
decoder.eval()
correct = 0
with torch.no_grad():
    for i, (X, _) in enumerate(test_loader):
        X = X.cuda()
        z = encoder(X)
        recon_X = decoder(z)

    print("오토인코더 테스트 결과")
    for i in range(5):
        plt.imshow(X[i].cpu().reshape(28, 28))
        plt.gray()
        plt.show()

        plt.imshow(recon_X[i].cpu().reshape(28, 28))
        plt.gray()
        plt.show()
    break


plt.plot(np.column_stack((train_loss_list, val_loss_list)))
```





## 실습 12

weight 저장된 weight 이용하여 모델 초기화하고 finetuning 하기



## 실습 12

```
fcn = MNIST_FCN(class_num=10).cuda()
fcn.apply(weight_init)

# 저장해둔 weight를 불러와 해당 weight로 초기화 시킨다.
pretrained_encoder = MNIST_CNN_Encoder().cuda()
project_root_path = '/content/gdrive/My Drive/AI'
encoder_save_path = '%s/pretrained_encoder.pth' % (project_root_path)
saved_weights = torch.load(encoder_save_path)
pretrained_encoder.load_state_dict(saved_weights)
#pretrained_encoder.apply(weight_init) # 처음부터 학습하는 것을 테스트하고 싶을 경우
```

```
epochs = 5
learning_rate = 0.01
batch_size = 100
loss_function = nn.BCELoss()
```

```
optimizer = optim.Adam(list(fcn.parameters())+list(pretrained_encoder.parameters()), betas=(0.5, 0.999), lr=learning_rate)
#optimizer = optim.Adam(fcn.parameters(), betas=(0.5, 0.999), lr=learning_rate) # Adam optimizer로 변경. betas =(0.5, 0.999) # encoder는 고정하고 fcn만 학습하는 코드
```

## 실습 12

```
train_loss_list = []
fcn.train()
for epoch in range(epochs):
    for i, (X, t) in enumerate(train_loader):
        X = X.cuda()
        t = one_hot_embedding(t, 10).cuda()
        z = pretrained_encoder(X)
        Y = fcn(z)


        loss = loss_function(Y, t)
        train_loss_list.append(loss)
        optimizer.zero_grad()
        loss.backward()
        optimizer.step()
    print("[%d/%d] [%d/%d] loss : %f"%(i, len(train_loader), epoch, epochs, loss))
```

test 부분도 이런 구조로 짜줘야합니다!

# Deep Convolutional Neural Networks

# legends


## Layers



## Activation Functions




## Other Functions




## Modules/Blocks


Modules (groups of convolutional, pooling and merge operations), in **yellow, green, or orange**. The operations that make up these modules will also be shown.




## Repeated layers or modules/blocks




# Lenet-5



# Alexnet




# VGG-16








# Inception-V1




# Inception-V3




# Resnet-50





Conv block




Identity block




# Xception



Conv A



Conv B




Conv C

## Depthwise separable convolution


$$\begin{bmatrix} 3 & 6 & 9 \\ 4 & 8 & 12 \\ 5 & 10 & 15 \end{bmatrix} = \begin{bmatrix} 3 \\ 4 \\ 5 \end{bmatrix} \times [1 \quad 2 \quad 3]$$

# Depthwise separable convolution


## Simple Convolution




## Spatial Separable Convolution



# Depthwise separable convolution




# Depthwise separable convolution







# Depthwise separable convolution










# Depthwise separable convolution




## Spatial Separable Convolution






# Inception-V4



# Inception-Resnet-V2



# ResNeXt-50



# 비교

Model	Size	Top-1 Accuracy	Top-5 Accuracy	Parameters	Depth
VGG16	528 MB	0.713	0.901	138,357,544	23
InceptionV3	92 MB	0.779	0.937	23,851,784	159
ResNet50	98 MB	0.749	0.921	25,636,712	-
Xception	88 MB	0.790	0.945	22,910,480	126
InceptionResNetV2	215 MB	0.803	0.953	55,873,736	572
ResNeXt50	96 MB	0.777	0.938	25,097,128	-

The top-1 and top-5 accuracy refers to the model's performance on the ImageNet validation dataset.

Depth refers to the topological depth of the network. This includes activation layers, batch normalization layers etc.

# AutoML and NAS(Neural Architecture Search)


머신러닝 구조 찾는 머신러닝 방법

Automated Feature Learning

**Architecture Search** => 강화학습 (2017), 유전알고리즘, DARTS...NASnet


Hyperparameter Optimization

# NAS






# NASnet




- $h_i$
- $h_{i-1}$
- $h_{i,0}$
- $h_{i,1}$
- $h_{i,2}$
- $h_{i,3}$

- Identity
- conv 1x7 + 7x1
- conv 1x3 + 3x1
- avg 3x3
- max 3x3
- max 5x5
- max 7x7
- conv 1x1
- conv 3x3
- sep 3x3
- sep 5x5
- sep 7x7
- dilated 3x3

- add
- concat



# NASnet



# NASnet

Model	image size	# parameters	Mult-Adds	Top 1 Acc. (%)	Top 5 Acc. (%)
Inception V2 [29]	224×224	11.2 M	1.94 B	74.8	92.2
<b>NASNet-A (5 @ 1538)</b>	<b>299×299</b>	<b>10.9 M</b>	<b>2.35 B</b>	<b>78.6</b>	<b>94.2</b>
Inception V3 [59]	299×299	23.8 M	5.72 B	78.0	93.9
Xception [9]	299×299	22.8 M	8.38 B	79.0	94.5
Inception ResNet V2 [57]	299×299	55.8 M	13.2 B	80.4	95.3
<b>NASNet-A (7 @ 1920)</b>	<b>299×299</b>	<b>22.6 M</b>	<b>4.93 B</b>	<b>80.8</b>	<b>95.3</b>
ResNeXt-101 (64 x 4d) [67]	320×320	83.6 M	31.5 B	80.9	95.6
PolyNet [68]	331×331	92 M	34.7 B	81.3	95.8
DPN-131 [8]	320×320	79.5 M	32.0 B	81.5	95.8
<b>SENet [25]</b>	<b>320×320</b>	<b>145.8 M</b>	<b>42.3 B</b>	<b>82.7</b>	<b>96.2</b>
<b>NASNet-A (6 @ 4032)</b>	<b>331×331</b>	<b>88.9 M</b>	<b>23.8 B</b>	<b>82.7</b>	<b>96.2</b>

# AutoML - activation function

Swish is defined as  $x \cdot \sigma(\beta x)$ , where  $\sigma(z) = (1 + \exp(-z))^{-1}$




Figure 4: The Swish activation function.





Figure 5: First derivatives of Swish.

## 실습 13


```
import torchvision.models as models
resnet18 = models.resnet18(pretrained=True)
alexnet = models.alexnet(pretrained=True)
squeezenet = models.squeezenet1_0(pretrained=True)
vgg16 = models.vgg16(pretrained=True)
densenet = models.densenet161(pretrained=True)
inception = models.inception_v3(pretrained=True)
googlenet = models.googlenet(pretrained=True)
shufflenet = models.shufflenet_v2_x1_0(pretrained=True)
mobilenet = models.mobilenet_v2(pretrained=True)
resnext50_32x4d = models.resnext50_32x4d(pretrained=True)
wide_resnet50_2 = models.wide_resnet50_2(pretrained=True)
mnasnet = models.mnasnet1_0(pretrained=True)
```

# 실습 13



# 실습 13

resnet-18



## 실습 13

dataset link:

[https://download.pytorch.org/tutorial/hymenoptera\\_data.zip](https://download.pytorch.org/tutorial/hymenoptera_data.zip)

받아서 구글드라이브에 저장해주세요.

저는 **dataset** 폴더를 만들어 그 안에 저장했습니다.



## 실습 13

```
# License: BSD
# Author: Sasank Chilamkurthy

import torch
import torch.nn as nn
import torch.optim as optim
from torch.optim import lr_scheduler
import numpy as np
import torchvision
from torchvision import datasets, models, transforms
import matplotlib.pyplot as plt
import time
import os
import copy

plt.ion() # interactive mode
```

## 실습 13

```
# Data augmentation and normalization for training
# Just normalization for validation
data_transforms = {
    'train': transforms.Compose([
        transforms.RandomResizedCrop(224),
        transforms.RandomHorizontalFlip(),
        transforms.ToTensor(),
        transforms.Normalize([0.485, 0.456, 0.406], [0.229, 0.224, 0.225])
    ]),
    'val': transforms.Compose([
        transforms.Resize(256),
        transforms.CenterCrop(224),
        transforms.ToTensor(),
        transforms.Normalize([0.485, 0.456, 0.406], [0.229, 0.224, 0.225])
    ]),
}

data_dir = '/content/gdrive/My Drive/Al/dataset/hymenoptera_data'
image_datasets = {x: datasets.ImageFolder(os.path.join(data_dir, x),
                                                    data_transforms[x])
                  for x in ['train', 'val']}
dataloaders = {x: torch.utils.data.DataLoader(image_datasets[x], batch_size=4,
                                                shuffle=True, num_workers=4)
               for x in ['train', 'val']}
dataset_sizes = {x: len(image_datasets[x]) for x in ['train', 'val']}
class_names = image_datasets['train'].classes

device = torch.device("cuda:0" if torch.cuda.is_available() else "cpu")
```

## 실습 13

```
def imshow(inp, title=None):
    """Imshow for Tensor."""
    inp = inp.numpy().transpose((1, 2, 0))
    mean = np.array([0.485, 0.456, 0.406])
    std = np.array([0.229, 0.224, 0.225])
    inp = std * inp + mean
    inp = np.clip(inp, 0, 1)
    plt.imshow(inp)
    if title is not None:
        plt.title(title)
    plt.pause(0.001) # pause a bit so that plots are updated

# Get a batch of training data
inputs, classes = next(iter(dataloaders['train']))

# Make a grid from batch
out = torchvision.utils.make_grid(inputs)

imshow(out, title=[class_names[x] for x in classes])
```

## 실습 13

```
def train_model(model, criterion, optimizer, scheduler, num_epochs=25):
    since = time.time()

    best_model_wts = copy.deepcopy(model.state_dict())
    best_acc = 0.0

    for epoch in range(num_epochs):
        print('Epoch {}/{}'.format(epoch, num_epochs - 1))
        print('-' * 10)

        # Each epoch has a training and validation phase
        for phase in ['train', 'val']:
            if phase == 'train':
                model.train() # Set model to training mode
            else:
                model.eval() # Set model to evaluate mode

            running_loss = 0.0
            running_corrects = 0

            # Iterate over data.
            for inputs, labels in dataloaders[phase]:
                inputs = inputs.to(device)
                labels = labels.to(device)

                # zero the parameter gradients
                optimizer.zero_grad()
```

## 실습 13

```
# zero the parameter gradients
optimizer.zero_grad()

# forward
# track history if only in train
with torch.set_grad_enabled(phase == 'train'):
    outputs = model(inputs)
    _, preds = torch.max(outputs, 1)
    loss = criterion(outputs, labels)

# backward + optimize only if in training phase
if phase == 'train':
    loss.backward()
    optimizer.step()

# statistics
running_loss += loss.item() * inputs.size(0)
running_corrects += torch.sum(preds == labels.data)
if phase == 'train':
    scheduler.step()

epoch_loss = running_loss / dataset_sizes[phase]
epoch_acc = running_corrects.double() / dataset_sizes[phase]

print('{} Loss: {:.4f} Acc: {:.4f}'.format(
    phase, epoch_loss, epoch_acc))

# deep copy the model
if phase == 'val' and epoch_acc > best_acc:
    best_acc = epoch_acc
    best_model_wts = copy.deepcopy(model.state_dict())

print()

time_elapsed = time.time() - since
print('Training complete in {:.0f}m {:.0f}s'.format(
    time_elapsed // 60, time_elapsed % 60))
print('Best val Acc: {:.4f}'.format(best_acc))

# load best model weights
model.load_state_dict(best_model_wts)
return model
```

## 실습 13

```
def visualize_model(model, num_images=6):
    was_training = model.training
    model.eval()
    images_so_far = 0
    fig = plt.figure()

    with torch.no_grad():
        for i, (inputs, labels) in enumerate(dataloaders['val']):
            inputs = inputs.to(device)
            labels = labels.to(device)

            outputs = model(inputs)
            _, preds = torch.max(outputs, 1)

            for j in range(inputs.size()[0]):
                images_so_far += 1
                ax = plt.subplot(num_images//2, 2, images_so_far)
                ax.axis('off')
                ax.set_title('predicted: {}'.format(class_names[preds[j]]))
                imshow(inputs.cpu().data[j])

            if images_so_far == num_images:
                model.train(mode=was_training)
                return
    model.train(mode=was_training)
```

## 실습 13

```
model_ft = models.resnet18(pretrained=True)
num_fts = model_ft.fc.in_features
# Here the size of each output sample is set to 2.
# Alternatively, it can be generalized to nn.Linear(num_fts, len(class_names)).
model_ft.fc = nn.Linear(num_fts, 2)

model_ft = model_ft.to(device)

criterion = nn.CrossEntropyLoss()


# Observe that all parameters are being optimized
optimizer_ft = optim.SGD(model_ft.parameters(), lr=0.001, momentum=0.9)

# Decay LR by a factor of 0.1 every 7 epochs
exp_lr_scheduler = lr_scheduler.StepLR(optimizer_ft, step_size=7, gamma=0.1)

model_ft = train_model(model_ft, criterion, optimizer_ft, exp_lr_scheduler,
                        num_epochs=25)
```

```
visualize_model(model_ft)
```

# 실습 13





## 실습 13

```
model_conv = models.resnet18(pretrained=True)
for param in model_conv.parameters():
    param.requires_grad = False

# Parameters of newly constructed modules have requires_grad=True by default
num_ftrs = model_conv.fc.in_features
model_conv.fc = nn.Linear(num_ftrs, 2) # 마지막 fc 레이어 초기화.

model_conv = model_conv.to(device)

criterion = nn.CrossEntropyLoss()

# Observe that only parameters of final layer are being optimized as
# opposed to before.
optimizer_conv = optim.SGD(model_conv.fc.parameters(), lr=0.001, momentum=0.9)

# Decay LR by a factor of 0.1 every 7 epochs
exp_lr_scheduler = lr_scheduler.StepLR(optimizer_conv, step_size=7, gamma=0.1)

model_conv = train_model(model_conv, criterion, optimizer_conv,
                          exp_lr_scheduler, num_epochs=25)
```

```
visualize_model(model_conv)

plt.ioff()
plt.show()
```