

Locals and outputs Lab 1.6

Use locals and functions to generate a unique value, and add a couple of outputs.

Overview

In this lab you will

- work with terraform console
- use a local variable and functions
- add outputs for the FQDN and public IP address

Starting point

Your files should look similar to this:

- provider.tf
 - terraform {
 - required_providers {
 - azurerm = {
 - source = "hashicorp/azurerm"
 - version = "~>3.1"
 - }
 - }
 - }
 -
 - provider "azurerm" {
 - features {}
 -
 - storage_use_azuread = true
 - }
- variables.tf
 - variable "resource_group_name" {
 - description = "Name for the resource group"
 - type = string
 - default = "terraform-basics"
 - }
 -
 - variable "location" {
 - description = "Azure region"
 - type = string
 - default = "West Europe"
 - }
 -

- variable "container_group_name" {
- description = "Name of the container group"
- type = string
- default = "terraform-basics"
- }
-
- variable "prefix" {
- description = "Prefix string to ensure FQDNs are globally unique"
- type = string
- }
-
- main.tf
-
- resource "azurerm_resource_group" "basics" {
- name = var.resource_group_name
- location = var.location
- }
-
- resource "azurerm_container_group" "example" {
- name = var.container_group_name
- location = azurerm_resource_group.basics.location
- resource_group_name = azurerm_resource_group.basics.name
- ip_address_type = "Public"
- dns_name_label = "\${var.prefix}-\${var.container_group_name}"
- os_type = "Linux"
-
- container {
- name = "inspectorgadget"
- image = "jelledruyts/inspectorgadget:latest"
- cpu = "0.5"
- memory = "1.0"
-
- ports {
- port = 80
- protocol = "TCP"
- }
- }
- }
-
- terraform.tfvars
-
- location = "UK South"
- prefix = "terrauser"

Using a hash substring is closer in behaviour to the commonly used `uniqueString()` function in ARM templates. The resource ID of a resource group is commonly used as a seed. It contains the subscription ID, so meets the uniqueness requirement, yet will always produce the same result in your config even if you were to destroy the environment and start again, which is a good fit for idempotency.

If you wanted to have a newly generated random string each time then look at [random id](#), which is in the random provider available in the [Terraform Registry](#). OK, let's work out how to find the right function and

1. Search on "terraform functions" in your browser

You should find the [Terraform Built-in Functions](#) page.

Feel free to browse the available functions.

2. Select the Hash and Crypto Functions
3. Select the `sha1` function

The sha1 encryption is not the strongest from a security perspective, but we only need this to provide a hash from the given string.

The function call is `sha1("string")`.

Terraform console

We now know the function and how to call it. Test it out in the Terraform console.

1. List the objects in state
2. `terraform state list`

Example output:

```
azurerm_container_group.example
azurerm_resource_group.basics
```

The correct Terraform identifier for the resource group is `azurerm_resource_group.basics`. You will need that later when working out how to get the resource ID for the resource group.

3. Open the Terraform console
4. `terraform console`

This is an interactive console which is ideal for testing expressions and interpolation and for interrogating the state.

Use CTRL+D at an empty prompt to exit the console. This is the end of file (EOF) character.

5. Test the *sha1* function
6. `sha1("This is a string")`

Expected hash:

```
"f72017485fbf6423499baf9b240daa14f5f095a1"
```

If you use the up arrow to recall the command you can see it will always return the same hash.

7. Find the resource ID attribute for the resource group

Remember when you looked at the documentation page for `azurerm_resource_group` that `id` was one of the attributes.

```
azurerm_resource_group.basics
```

Example response:

```
{
  "id" = "/subscriptions/2ca40be1-7e80-4f2b-92f7-06b2123a68cc/resourceGroups/terraform-basics"
  "location" = "uksouth"
  "name" = "terraform-basics"
  "tags" = tomap({})
  "timeouts" = null /* object */
}
```

8. Drill down to the `id` attribute
9. `azurerm_resource_group.basics.id`

Example response:

```
"/subscriptions/2ca40be1-7e80-4f2b-92f7-06b2123a68cc/resourceGroups/terraform-basics"
```

Your response will contain a different subscription ID.

10. Retest *sha1* with the `resourceId`

11. `sha1(azurem_resource_group.basics.id)`

Example output:

```
"c3818179c2946e2352e5210e826239e65f5c3396"
```

That is a little long. Eight characters should be sufficient to make it unique.

Your response will be different as your resource group ID contains a different subscription ID.

12. Find a suitable function

14. Exit the console

Use CTRL+d to leave the console prompt and go back to the shell. The console is great for forming and testing expressions. We have settled on `substr(sha1(azurerm_resource_group.basics.id), 0, 8)` which will be used as a suffix. Let's declare the local.

Locals

The variables we have been using so far are more accurately called input variables, i.e. `var.<variable_name>`. (Close to the *parameters* in ARM and Bicep templates.) It is common to place more complex expression into locals so that the main resource and data source blocks are more readable. (Much like the *variables* in ARM and Bicep templates.)

We'll define a local variable for the unique value, and call it *uniq*. Local variables are defined in a locals block.

1. Add the following block to the top of your main.tf
2. `locals {`
3. `uniq = substr(sha1(azurerm_resource_group.basics.id), 0, 8)`
4. `}`
5. Modify value for `dns_name_label`

Update the interpolation expression for `dns_name_label` in the `azurerm_container_group` resource:

```
dns_name_label = "${var.container_group_name}-${local.uniq}"
```

Note that locals are referenced as `local.<local_name>`.

6. **Delete** the prefix variable

This is no longer required. Remove it from `variables.tf` and `terraform.tfvars`.

Outputs

There are a couple of attributes whose values are unknown until they've been created. One is the public IPv4 address, and the other is the fully qualified domain name now that it is suffixed with the *uniq* local variable.

The convention with Terraform is to place all outputs in a file called `outputs.tf`. The lab will walk you through creating one and then you'll be challenged to do the other.

ip_address

1. Open the console
2. terraform console
3. Query the Azure Container Instance
4. azurerm_container_group.example
5. Use dot notation to get the public IPv4 address
6. azurerm_container_group.example.ip_address

This should return you container instance's current public IP address.

7. Create a file called outputs.tf and add the following block

```
8. output "ip_address" {  
9.   value = azurerm_container_group.example.ip_address  
10.}
```

fqdn

OK, time for another little challenge section.

You will use both of these more and more as your Terraform code becomes more ambitious. Locals are important for readability as the expressions become more complex. Outputs are useful at this level, but become far more important when you start creating your own modules.

In the next section we will manipulate state a little using imports, refresh, renames and taints.
