

# Adding resources Lab1.5

Use the `azurerm` documentation to add a resource to your configuration.

## Overview

In this lab you will

- browse the [aka.ms/terraform](https://aka.ms/terraform) documentation
- add a resource to create an Azure Container Instance
- plan and apply the change

## Starting point

Your files should still look like this:

- `provider.tf`
- ```
terraform {  
  required_providers {  
    azurerm = {  
      source  = "hashicorp/azurerm"  
      version = "~>3.1"  
    }  
  }  
}
```
- `provider "azurerm" {  
 features {}  
  
 storage_use_azuread = true  
}`
- `variables.tf`
- ```
variable "resource_group_name" {  
  description = "Name for the resource group"  
  type        = string  
  default     = "terraform-basics"  
}
```
- ```
variable "location" {  
  description = "Azure region"  
  type        = string  
  default     = "West Europe"  
}
```
-

- main.tf
- ```
resource "azurerm_resource_group" "basics" {  
  name      = var.resource_group_name  
  location = var.location  
}
```
- terraform.tfvars
- ```
location = "UK South"
```
- You may have set a different value for *location*.

## Azure Resource Group

There is a short URL for the azure provider's resource documentation.

1. Browse to [aka.ms/terraform](https://aka.ms/terraform) in a new tab

Commit this short URL to memory! You'll be using it often.

Note the azurerm version drop down at the top of the page. Default is the latest version.



HashiCorp

Terraform

Registry



Providers



hashicorp



azurerm



Version 3.0.2



azurerm



## AZURERM DOCUMENTATION



resource group

6 matching results

▼ Base

▼ Resources

● [azurerm\\_resource\\_group](#)



▼ Data Sources

azurerm\_resource\_group

▼ Cost Management

▼ Resources

azurerm\_resource\_group\_cost

This is the documentation page for the resource group you've already created.

Each resource page shows an example, plus the arguments (*name, location, tags*) and the exported attributes (all arguments plus *id*).

## Azure Container Instance

In the next section you will add a new `azurerm_container_group` resource to create an Azure Container Instance. Look at the documentation page for the resource.

1. Filter to "container" on the [aka.ms/terraform](https://aka.ms/terraform) page
2. Select the **`azurerm_container_group`** resource



HashiCorp

Terraform

Registry



Providers



hashicorp



azurerm



Version 3.0.2



azurerm



## AZURERM DOCUMENTATION



container

24 matching results

▼ Container

▼ Resources

● [azurerm\\_container\\_group](#)



azurerm\_container\_registry

azurerm\_container\_registry\_  
scope\_map

azurerm\_container\_registry\_task

azurerm\_container\_registry\_  
token

This is a more complex resource with a larger number of arguments and attributes.

Here is the Example Usage from the page:

```
resource "azurerm_resource_group" "example" {
  name      = "example-resources"
  location  = "West Europe"
}

resource "azurerm_container_group" "example" {
  name                = "example-continst"
  location            = azurerm_resource_group.example.location
  resource_group_name = azurerm_resource_group.example.name
  ip_address_type     = "public"
  dns_name_label      = "aci-label"
  os_type             = "Linux"

  container {
    name     = "hello-world"
    image    = "mcr.microsoft.com/azuredocs/aci-helloworld:latest"
    cpu      = "0.5"
    memory   = "1.5"

    ports {
      port      = 443
      protocol  = "TCP"
    }
  }

  container {
    name     = "sidecar"
    image    = "mcr.microsoft.com/azuredocs/aci-tutorial-sidecar"
    cpu      = "0.5"
    memory   = "1.5"
  }

  tags = {
    environment = "testing"
  }
}
```

Note that as well as top level arguments (name, location, os\_type etc.) that there are also blocks. This example has container blocks. Some blocks support multiples. (The example container group contains two containers.) There can be blocks within blocks, such as the ports block within the first container block.

The documentation shows which arguments are required and optional within each block type, and detail on the permitted values.

In the example it uses `azurerm_resource_group.example.location` as the location value, rather than `"UK South"` or `var.location`.

This creates an implicit dependency between `azurerm_container_group.example` and `azurerm_resource_group.example`.

These become linked nodes in the graph that Terraform generates to understand the order of operations, parallelism, dependencies etc.

You can also define explicit dependencies using the **`depends_on = [ ]`** meta-argument.

## Challenge



This would use the "bare" format, i.e. `var.container_group_name`

- The DNS label should concatenate the *prefix* and the *container\_group\_name*

The interpolation format is `"${var.prefix}-${var.container_group_name}"`. [Interpolation](#) allows us to generate more complex expressions. Terraform knows to evaluate the variables surrounded with `${}` to get their values.

- Use the Inspector Gadget image for the container
  - `name: inspectorgadget`
  - `image: "jelledruyts/inspectorgadget:latest"`  
The [Inspector Gadget](#) image should be the only container in the container group.
  - Reduce the memory requirement to 1GB
  - Set the container port to 80 (HTTP)
- No tags

Don't forget to save all of your files.



2. Open a new tab in the browser and go to the site

## Request

|                                  |                |
|----------------------------------|----------------|
| URL                              | http://terra   |
| HTTP Method                      | GET            |
| Is HTTPS                         | False          |
| Request ID                       | 0HMGNRA        |
| Client Certificate Serial Number |                |
| Local IP Address                 | ::ffff:192.16  |
| Local Port                       | 80             |
| Remote IP Address                | ::ffff:10.92.0 |
| Remote Port                      | 61877          |

## HTTP Headers

|                 |                                        |
|-----------------|----------------------------------------|
| Accept          | text/html,application/javascript;q=0.9 |
| Accept-Encoding | gzip, deflate                          |
| Accept-Language | en-GB,en;q=0.9                         |
| Connection      | keep-alive                             |

If your screen is similar to the one above then you have been successful! If not then check if your config differs from the one shown at the start of the next lab. (Note that the value of your prefix should be different.)

## Summary

You successfully updated the config and added a resource.

Being able to navigate the documentation is a key skill when you are adding and modifying resources. You will also need to have a good working understanding of Azure, how the resources work and relate to each other.

If you find the documentation is a little vague on an argument and its possible values then check the documentation for the [Azure Resource Manager REST APIs](#) as they can sometimes add insight where the resources closely match the properties found in those REST API calls.

In the next lab we will use locals and add an output.

---