

Literature Review: Set Theoretic Estimation

Working notes toward a Lean mechanization

Project `thejeb`

July 19, 2026

Abstract

Working notes reviewing set theoretic estimation (STE) from its unifying statement [4] through its topological-space, cryptographic instantiation [3], oriented toward identifying which results are ripe for machine-checked formalization in Lean 4 / Mathlib. These notes are exploratory and cite the primary sources; only claims discharged in the CI-checked `Ste` library are asserted as proven.

1 The set theoretic paradigm (Combettes 1993)

Conventional estimation optimizes an objective function; the solvability and realism of that optimization is a persistent difficulty [4]. STE replaces optimization with *feasibility*.

Fix a *solution space* Ξ and a true object (estimandum) h . Each piece of information $i \in I$ is a proposition on Ξ ; at a chosen confidence level it yields a *property set*

$$S_i = \{a \in \Xi \mid \Psi_i(a) \geq \psi_i\}, \quad \Psi_i : \Xi \rightarrow [0, 1], \quad (1)$$

the set of estimates consistent with information i (Combettes Eq. 3). The *feasibility set* is their intersection,

$$S = \bigcap_{i \in I} S_i \quad (\text{Combettes Eq. 4}). \quad (2)$$

Any $a \in S$ is a *set theoretic estimate*. The formulation is *consistent* if $S \neq \emptyset$, *fair* if $h \in S$, and *ideal* if $S = \{h\}$. When Ξ is a real Hilbert space and each S_i is closed and convex, S is closed convex and can be reached by projection algorithms (POCS, 6; cyclic projections, 2; survey 1).

What we formalized. The *crisp* core — where Ψ_i is $\{0, 1\}$ -valued so S_i is an ordinary subset — is machine-checked in `Ste.Basic`: feasibility set, membership, refinement of each constraint, information monotonicity, the fair/consistent link, the inconsistency $\Rightarrow$ invalid-information self-diagnostic, and the ideal-information identification theorem. Convexity of the feasibility set is `Ste.Convex`. The graded/fuzzy case and the projection *algorithms* (as opposed to the geometry) remain open.

2 Topological-space STE for decryption (Carlson 2012)

Carlson [3] makes two moves. First, a *spatial* move: prior STE works in a Hilbert / metric space and simplifies processing with Optimal Bounding Ellipsoid (OBE) algorithms, but an OBE is not confined to the original feasibility volume and can spuriously *expand* the solution set. Carlson instead works in a *topological space*, where property sets are static a priori information that never expand, avoiding the OBE pathology. Second, an *application* move: STE is applied to decryption for the first time.

The decryption reduction. The solution space is a finite key space K . Each intercepted ciphertext c induces a property set of keys under which c decrypts to a meaningful message; the feasible key set is the STE feasibility set of these property sets, and decryption succeeds when it collapses to the true key — the set theoretic form of Shannon’s unicity [5].

Named results (extracted from the dissertation text).

- **Lemma 2.1:** the error e (number of keys lacking an encryption property Φ_i) is bounded, $0 \leq e \leq |K| - 1$.
- **Lemma 2.2:** property sets behave as independent variables whose intersection is no larger than the smallest set; if $\Phi_j \subseteq \Phi_k$ then Φ_k is subsumed.
- **Theorem 2.3:** each property set is an AEP typical set; hence information theory falls under the STE umbrella.
- **Lemma 4.1:** a substitution (S) cipher on message M admits $(|A| - |T|)!$ isomorphic (equivalent) keys, where T is the set of distinct symbols occurring in M .
- **Theorem 4.1:** a permutation (P) cipher admits $\binom{|S_t|}{C}(|B| - |S_t|)!$ unique keys, S_t the static-bit set.
- **Theorem 5.2:** a permutation encryption reduces to a substitution encryption within a symbol’s bit representation.
- **Corollary 5.3:** a boundary-aligned PSP cipher is idempotent to a single S cipher; therefore every block cipher is a block substitution cipher, so one attack (BCBB) suffices.

What we formalized. The topological substrate — closedness and, via compactness and the finite intersection property, existence of feasible points — is **Ste.Topology**; it specializes cleanly to Carlson’s finite (discrete, hence compact) key spaces. The STE-decryption skeleton (cipher systems, key property sets, feasible keys, fairness of genuine traffic, unicity as ideal information, observation monotonicity) is **Ste.Cipher**.

3 Assessment: what is ripe to mechanize

1. **Most tractable:** the cipher counting results (Lemma 4.1, Theorem 4.1). These are finite combinatorics over **Fin**-indexed symbol/bit alphabets; Mathlib’s **Fintype.card_perm** ($|\text{Perm } \alpha| = (\#\alpha)!$) and factorial API supply the scaffolding.
2. **Structural:** the reduction chain (Theorem 5.2, Corollary 5.3) reducing all block ciphers to substitution ciphers — an algebraic argument once ciphers are modeled as keyed permutations.
3. **Analytic:** POCS convergence (1, 6) atop **Ste.Convex**, using Mathlib’s Hilbert-space projection theory.
4. **Deepest:** Theorem 2.3 (property sets as AEP typical sets), which requires a probabilistic model and Mathlib’s measure/information theory.

4 Distrust discipline

Per project rule, no result here is asserted proven unless it compiles in the `Ste` library checked by CI on every push to `main`. The Carlson named results above are *quoted from the source*, not yet independently verified; they are targets, and their statuses live in `log/2026-07-19-hypotheses-ste-core.md` (H9–H12, OPEN).

References

- [1] Heinz H. Bauschke and Jonathan M. Borwein. On projection algorithms for solving convex feasibility problems. *SIAM Review*, 38(3):367–426, 1996. doi: 10.1137/S0036144593251710.
- [2] Lev M. Bregman. The relaxation method of finding the common point of convex sets and its application to the solution of problems in convex programming. *USSR Computational Mathematics and Mathematical Physics*, 7(3):200–217, 1967. doi: 10.1016/0041-5553(67)90040-7.
- [3] Albert H. Carlson. *Set Theoretic Estimation Applied to the Information Content of Ciphers and Decryption*. Ph.d. dissertation, University of Idaho, Moscow, Idaho, USA, May 2012. Major professors R. E. Hiromoto and R. B. Wells. Retrieved via Internet Archive snapshot (2024-07-13) of the author’s ResearchGate full text, publication 349064680.
- [4] Patrick L. Combettes. The foundations of set theoretic estimation. *Proceedings of the IEEE*, 81(2):182–208, 1993. doi: 10.1109/5.214546. Retrieved from the author’s page, <https://pcombet.math.ncsu.edu/proc.pdf>.
- [5] Claude E. Shannon. Communication theory of secrecy systems. *Bell System Technical Journal*, 28(4):656–715, 1949. doi: 10.1002/j.1538-7305.1949.tb00928.x.
- [6] Dan C. Youla and Heywood Webb. Image restoration by the method of convex projections: Part 1—theory. *IEEE Transactions on Medical Imaging*, 1(2):81–94, 1982. doi: 10.1109/TMI.1982.4307555.