

A Machine-Checked Core for Set Theoretic Estimation

Project `thejeb`

July 19, 2026

Abstract

We report a first, machine-checked formalization in Lean 4 / Mathlib of the core of set theoretic estimation (STE) as founded by Combettes [3] and recast over topological spaces for decryption by Carlson [2]. The formalization covers the feasibility set and its lattice-theoretic properties, the consistent / fair / ideal taxonomy, information monotonicity, an inconsistency-based invalid-information detector, closedness and compactness-based existence of estimates on topological spaces, convexity of the feasibility set, a skeleton of Carlson’s STE-decryption reduction, and — new in this revision — Carlson’s key-counting Lemma 4.1 and the cipher-reduction chain (Theorem 5.2, Lemma 5.1, Corollary 5.3). Every theorem stated here is verified by continuous integration on each push; nothing is asserted proven otherwise.

1 Introduction

Set theoretic estimation abandons the search for an optimum in favor of *feasibility*: an estimate is acceptable exactly when it is consistent with every available piece of information [3]. This shifts the mathematical content from analysis of an objective function to the set algebra and topology of a family of constraint sets and their intersection. That content is a natural target for a proof assistant. We mechanize it in Lean 4 on Mathlib (pinned v4.32.0), adopting a strict discipline: a statement counts as established only when it type-checks in our library under the project’s CI. This paper is the human-readable companion to that library; every displayed result names its Lean identifier.

2 The formal model

Let Ξ be the solution space and I an index set of information pieces. A *property set family* is $S : I \rightarrow \mathcal{P}(\Xi)$; S_i holds the estimates consistent with information i . We mechanize the crisp case (Combettes’s membership function Ψ_i being $\{0,1\}$ -valued, so S_i is a subset).

Definition 1 (feasibility set; `STE.feasibilitySet`). $S = \bigcap_{i \in I} S_i$ (Combettes Eq. 4). A point of S is a set theoretic estimate.

```
def feasibilitySet (S : I -> Set Xi) : Set Xi := iInter i, S i
theorem mem_feasibilitySet : a in feasibilitySet S <=> forall i, a in S i
```

3 Results (all machine-checked)

Refinement and monotonicity. The feasibility set refines each constraint (`feasibilitySet_subset`: $S \subseteq S_j$). Writing $S_J = \bigcap_{i \in J} S_i$ for the *partial* feasibility set, enforcing more information shrinks it:

Proposition 1 (`partialFeasibilitySet_antitone`). $J \subseteq K \implies S_K \subseteq S_J$.

This is the STE reading of “more information never enlarges the acceptable set,” and it descends to Carlson’s key search as `feasibleKeys_antitone`.

Consistency, fairness, invalid information. Call the family *fair* for h when $h \in S_i$ for all i (`STE.Fair`); this is exactly $h \in S$ (`fair_iff_mem_feasibilitySet`).

Theorem 1 (`feasibilitySet_nonempty_of_fair`). *Fair information is consistent: if the truth satisfies every piece of information then $S \neq \emptyset$.*

Contrapositively, inconsistency is a certificate that some information is wrong:

Theorem 2 (`exists_unfair_of_feasibilitySet_eq_empty`). *If $S = \emptyset$ then for every candidate h there is an i with $h \notin S_i$.*

Ideal information. The family is *ideal* for h when $S = \{h\}$ (`STE.Ideal`).

Theorem 3 (`Ideal.eq_of_mem`, `ideal_iff_fair_and_subsingleton`). *Under ideal information every estimate equals the truth; and idealness is equivalent to fairness together with feasibility being a subsingleton.*

Topology (Carlson’s setting).

Theorem 4 (`isClosed_feasibilitySet`, `feasibilitySet_nonempty_of_compact`). *If each S_i is closed then S is closed. If moreover Ξ is compact and every finite subfamily is consistent (the finite intersection property, *FiniteConsistency*), then $S \neq \emptyset$.*

The compactness result is the abstract reason STE is well posed on Carlson’s finite key spaces (discrete $\implies$ compact; `isClosed_feasibilitySet_of_discrete`) and on bounded closed convex constraint sets.

Convexity (Combettes’s Hilbert-space setting).

Theorem 5 (`convex_feasibilitySet`). *If each S_i is convex then S (and every partial feasibility set) is convex.*

This is the geometric precondition for the projection algorithms of Bauschke and Borwein [1], Youla and Webb [4], a planned extension.

STE decryption skeleton (Carlson). A `CipherSystem` is a keyed family of injective encryption maps. Observing a ciphertext c induces the key property set $\{k \mid \exists m \in \text{Meaning}, \text{enc } k \ m = c\}$; the feasible key set is the STE feasibility set of these. The cipher module now lives in the `STE.Carlson` namespace.

Theorem 6 (`STE.Carlson.CipherSystem.fair_of_genuine`, `STE.Carlson.CipherSystem.feasibleKeys_nonempty_of_genuine`). *Genuine traffic (ciphertexts that really are encryptions of meaningful messages under a true key k_0) is fair for k_0 ; hence the feasible key set is nonempty.*

Theorem 7 (`STE.Carlson.CipherSystem.Unicity.eq_of_feasible`). *At unicity (feasible key set $= \{k_0\}$, i.e. ideal information) every feasible key is the true key: decryption succeeds by feasibility alone.*

Cipher key counting (Carlson, Lemma 4.1; new). Model a substitution cipher over a finite alphabet A by its key space $\text{Perm } A$. Given a message whose distinct symbols form $T \subseteq A$, two keys decrypt it identically exactly when they agree on T ; Carlson’s Lemma 4.1 counts the keys equivalent to the true key.

Theorem 8 (`STE.Carlson.card_consistent_keys`). *For a substitution cipher with true key σ over A and observed symbol set T ,*

$$\#\{\tau \in \text{Perm } A : \forall a \in T, \tau a = \sigma a\} = (|A| - |T|)!,$$

the size of the STE feasible key set after one observation.

The proof reduces, by left-translating the constraint by σ^{-1} (an explicit bijection), to the fixing-set count `STE.Carlson.card_perm_fixing`: the permutations fixing T pointwise number $(|A| - |T|)!$, via `Equiv.Perm.subtypeEquivSubtypePerm` and `Fintype.card_perm`. The total key count is `STE.Carlson.card_substitution_keys`: $\#\text{Perm } A = |A|!$.

Cipher reduction (Carlson, Theorem 5.2 / Lemma 5.1 / Corollary 5.3; new). Model an n -bit permutation cipher by $\text{Perm}(\text{Fin } n)$ acting on the value space $\text{Fin } n \rightarrow \text{Bool}$: a position permutation ρ induces the value permutation $\text{coperm } \rho$, acting by $(\text{coperm } \rho) f x = f(\rho^{-1}x)$.

Theorem 9 (`STE.Carlson.permutation_reduces_to_substitution`, `STE.Carlson.coperm_injective`). *Every permutation-cipher key is a substitution-cipher key, and the realization coperm is injective: distinct position permutations induce distinct value permutations. This upgrades Theorem 5.2 to a genuine embedding of permutation ciphers into substitution ciphers.*

Theorem 10 (`STE.Carlson.card_permutation_lt_card_substitution`, `STE.Carlson.substitution_not_reduces_to_permutation`). *For an n -bit block with $n \geq 2$ there are strictly more substitution keys than permutation keys ($n! < (2^n)!$), so no injective realization of permutation keys as substitution keys is onto: some substitution cipher is not a permutation cipher (Lemma 5.1 / Corollary 5.2). The non-surjectivity is quantified over every faithful embedding, so it does not depend on a particular construction.*

Theorem 11 (`STE.Carlson.psp_reduces_to_substitution`). *A permutation–substitution–permutation composition is again a single value permutation: every block cipher is a block substitution cipher (Corollary 5.3).*

4 Verification method

The environment used to author this work cannot download a Lean toolchain (egress policy). We therefore treat the GitHub Action as the trusted verifier: every push to `main` builds the `Ste` library with `leanprover/lean-action` against the pinned Mathlib cache. A result is considered established only once its build is green. This operationalizes the project’s rule to distrust results that are not machine proven.

5 Future work

With Lemma 4.1 and the reduction chain (Theorems 5.2, Lemma 5.1, Corollary 5.3) now discharged, the remaining targets, in increasing depth, are: Carlson’s general counting Theorem 4.1 (the $\binom{|S_t|}{C}(|B| - |S_t|)!$ count with a chosen-symbol constraint); POCS convergence over Hilbert spaces; and Theorem 2.3, that property sets are AEP typical sets, placing information theory under STE. Targets and their open/proven status are tracked in the project `log/`.

References

- [1] Heinz H. Bauschke and Jonathan M. Borwein. On projection algorithms for solving convex feasibility problems. *SIAM Review*, 38(3):367–426, 1996. doi: 10.1137/S0036144593251710.
- [2] Albert H. Carlson. *Set Theoretic Estimation Applied to the Information Content of Ciphers and Decryption*. Ph.d. dissertation, University of Idaho, Moscow, Idaho, USA, May 2012. Major professors R. E. Hiromoto and R. B. Wells. Retrieved via Internet Archive snapshot (2024-07-13) of the author’s ResearchGate full text, publication 349064680.
- [3] Patrick L. Combettes. The foundations of set theoretic estimation. *Proceedings of the IEEE*, 81(2):182–208, 1993. doi: 10.1109/5.214546. Retrieved from the author’s page, <https://pcombet.math.ncsu.edu/proc.pdf>.
- [4] Dan C. Youla and Heywood Webb. Image restoration by the method of convex projections: Part 1—theory. *IEEE Transactions on Medical Imaging*, 1(2):81–94, 1982. doi: 10.1109/TMI.1982.4307555.