
CONNECTOME-BASED ATTRACTOR DYNAMICS UNDERLIE BRAIN ACTIVITY IN REST, TASK, AND DISEASE

Robert Englert

Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany
Department of Diagnostic and Interventional Radiology and Neuroradiology, University Medicine Essen, Germany

Balint Kincses

Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany
Department of Neurology, University Medicine Essen, Germany

Raviteja Kotikalapudi

Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany
Department of Neurology, University Medicine Essen, Germany

Giuseppe Gallitto

Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany
Department of Neurology, University Medicine Essen, Germany

Jialin Li

Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany
Department of Neurology, University Medicine Essen, Germany
Max Planck School of Cognition, Leipzig, Germany

Kevin Hoffschlag

Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany
Department of Neurology, University Medicine Essen, Germany

Choong-Wan Woo

Center for Neuroscience Imaging Research, Institute for Basic Science, Suwon, South Korea
Department of Biomedical Engineering, Sungkyunkwan University, Suwon, South Korea

Tor D. Wager

Department of Psychological and Brain Sciences, Dartmouth College, Hanover, NH, USA

Dagmar Timmann

Department of Neurology, University Medicine Essen, Germany
Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany

Ulrike Bingel

Department of Neurology, University Medicine Essen, Germany
Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany

 **Tamas Spisak¹**

Department of Diagnostic and Interventional Radiology and Neuroradiology, University Medicine Essen, Germany
Center for Translational Neuro- and Behavioral Sciences (C-TNBS), University Medicine Essen, Germany

Thursday 4th April, 2024

¹Correspondence to: tamas.spisak@uk-essen.de

Keywords

1 Introduction

Brain function is characterized by the continuous activation and deactivation of anatomically distributed neuronal populations [Buzsaki, 2006]. Irrespective of the presence or absence of explicit stimuli, brain regions appear to work in concert, giving rise to a rich and spatiotemporally complex fluctuation [Bassett and Sporns, 2017]. This fluctuation is neither random nor stationary over time [Liu and Duyn, 2013, Zalesky et al., 2014]. It is organized around large-scale gradients [Margulies et al., 2016, Huntenburg et al., 2018] and exhibits quasi-periodic properties, with a limited number of recurring patterns known as “brain states” [Greene et al., 2023, Vidaurre et al., 2017, Liu and Duyn, 2013].

A wide variety of descriptive techniques have been previously employed to characterize whole-brain dynamics [Smith et al., 2012, Vidaurre et al., 2017, Liu and Duyn, 2013, Chen et al., 2018]. These efforts have provided accumulating evidence not only for the existence of dynamic brain states but also for their clinical significance [Hutchison et al., 2013, Barttfeld et al., 2015, Meer et al., 2020]. However, the underlying driving forces remain elusive due to the descriptive nature of such studies.

Conventional computational approaches attempt to solve this puzzle by going all the way down to the biophysical properties of single neurons, and aim to construct a model of larger neural populations, or even the entire brain [Breakspear, 2017]. These approaches have shown numerous successful applications [Murray et al., 2018, Kriegeskorte and Douglas, 2018, Heinz et al., 2019]. However, such models need to estimate a vast number of neurobiologically motivated free parameters to fit the data. This hampers their ability to effectively bridge the gap between explanations at the level of single neurons and the complexity of behavior [Breakspear, 2017]. Recent efforts using coarse-grained brain network models [Schirner et al., 2022, Schiff et al., 1994, Papadopoulos et al., 2017, Seguin et al., 2023] and linear network control theory [Chiêm et al., 2021, Scheid et al., 2021, Gu et al., 2015] opted to trade biophysical fidelity to phenomenological validity.

Such models have provided insights into some of the inherent key characteristics of the brain as a dynamic system; for instance, the importance of stable patterns, so-called “attractor states”, in governing brain dynamics [Deco et al., 2012, Golos et al., 2015, Hansen et al., 2015]. While attractor networks have become established models of micro-scale canonical brain circuits in the last four decades [Khona and Fiete, 2022], these studies highlighted that attractor dynamics are essential characteristics of macro-scale brain dynamics as well. However, the standard practice among these studies is the use of models that capitalize on information about the structural wiring of the brain, leading to the grand challenge of modeling the relationship between the structural wiring of the brain and functional connectivity.

The “neuroconnectionist” approach [Doerig et al., 2023] makes another step towards trading biophysical detail to “cognitive/behavioral fidelity” [Kriegeskorte and Douglas, 2018], by using artificial neural networks (ANNs) that are trained to perform various tasks, as brain models. However, the need to train ANNs for specific tasks inherently limits their ability to explain task-independent, spontaneous neural dynamics [Richards et al., 2019].

Here we propose a minimal phenomenological model for large-scale brain dynamics that combines the advantages of large-scale attractor network models [Golos et al., 2015], neuroconnectionism [Doerig et al., 2023], and recent advances in understanding the flow of brain activity across regions [Cole et al., 2016], to investigate brain dynamics. Similar to neuroconnectionism, we utilize an ANN as an abstract, high-level computational model of the brain. However, our model is not explicitly trained for a specific task. Instead, we set its weights empirically.

Specifically, we employ a continuous-space Hopfield Neural Network (HNN) [Hopfield, 1982, Krotov, 2023], similar to the spin-glass and Hopfield-style attractor network models applied e.g. by Deco et al. [2012], Golos et al. [2015], where the nodes of the network model represent large-scale brain areas. However, in contrast to these previous efforts that starting from the structural wiring of the brain, we initialize the edge weights of the network based on direct estimates node-to-node information transfer. Our decision to employ a direct proxy of interregional communication, rather than biophysical wiring, capitalizes on the “activity flow” [Cole et al., 2016, Ito et al., 2017] principle, a thoroughly validated phenomenological model of the association between brain activity and functional connectivity, as measured with functional magnetic resonance imaging. This allows us to circumvent the necessity of comprehensively understanding and accurately modeling structural-functional coupling in the brain. Instead, we can concentrate on the overarching dynamical properties of the system.

Based on the topology of the functional connectome, our model establishes an energy level for any arbitrary activation patterns and determines a “trajectory of least action” towards one of the finite number of stable patterns, known as *attractor states*, that minimize this energy. In the proposed framework, macro-scale brain dynamics can be conceptualized as an intricate, high-dimensional path on the energy landscape (??C), arising from the activity flow [Cole et al., 2016] within the functional connectome and constrained by the “gravitational pull” of the attractor states of the system. The generative nature of the proposed framework offers testable predictions for the effect of various perturbations and alterations of these dynamics, from task-induced activity to changes related to brain disorders.

References

- Gyorgy Buzsaki. *Rhythms of the Brain*. Oxford university press, 2006.
- Danielle S Bassett and Olaf Sporns. Network neuroscience. *Nature neuroscience*, 20(3):353–364, 2017.
- Xiao Liu and Jeff H Duyn. Time-varying functional network information extracted from brief instances of spontaneous brain activity. *Proceedings of the National Academy of Sciences*, 110(11):4392–4397, 2013.
- Andrew Zalesky, Alex Fornito, Luca Cocchi, Leonardo L Gollo, and Michael Breakspear. Time-resolved resting-state brain networks. *Proceedings of the National Academy of Sciences*, 111(28):10341–10346, 2014.
- Daniel S Margulies, Satrajit S Ghosh, Alexandros Goulas, Marcel Falkiewicz, Julia M Huntenburg, Georg Langs, Gleb Bezgin, Simon B Eickhoff, F Xavier Castellanos, Michael Petrides, et al. Situating the default-mode network along a principal gradient of macroscale cortical organization. *Proceedings of the National Academy of Sciences*, 113(44):12574–12579, 2016.
- Julia M Huntenburg, Pierre-Louis Bazin, and Daniel S Margulies. Large-scale gradients in human cortical organization. *Trends in cognitive sciences*, 22(1):21–31, 2018.
- Abigail S Greene, Corey Horien, Daniel Barson, Dustin Scheinost, and R Todd Constable. Why is everyone talking about brain state? *Trends in Neurosciences*, 2023.
- Diego Vidaurre, Stephen M Smith, and Mark W Woolrich. Brain network dynamics are hierarchically organized in time. *Proceedings of the National Academy of Sciences*, 114(48):12827–12832, 2017.
- Stephen M Smith, Karla L Miller, Steen Moeller, Junqian Xu, Edward J Auerbach, Mark W Woolrich, Christian F Beckmann, Mark Jenkinson, Jesper Andersson, Matthew F Glasser, et al. Temporally-independent functional modes of spontaneous brain activity. *Proceedings of the National Academy of Sciences*, 109(8):3131–3136, 2012.
- Richard H Chen, Takuya Ito, Kaustubh R Kulkarni, and Michael W Cole. The human brain traverses a common activation-pattern state space across task and rest. *Brain Connectivity*, 8(7):429–443, 2018.
- R Matthew Hutchison, Thilo Womelsdorf, Elena A Allen, Peter A Bandettini, Vince D Calhoun, Maurizio Corbetta, Stefania Della Penna, Jeff H Duyn, Gary H Glover, Javier Gonzalez-Castillo, et al. Dynamic functional connectivity: promise, issues, and interpretations. *Neuroimage*, 80:360–378, 2013.
- Pablo Barttfeld, Lynn Uhrig, Jacobo D Sitt, Mariano Sigman, Béchir Jarraya, and Stanislas Dehaene. Signature of consciousness in the dynamics of resting-state brain activity. *Proceedings of the National Academy of Sciences*, 112(3):887–892, 2015.
- Johan N van der Meer, Michael Breakspear, Luke J Chang, Saurabh Sonkusare, and Luca Cocchi. Movie viewing elicits rich and reliable brain state dynamics. *Nature communications*, 11(1):5004, 2020.
- Michael Breakspear. Dynamic models of large-scale brain activity. *Nature neuroscience*, 20(3):340–352, 2017.
- John D Murray, Murat Demirtaş, and Alan Anticevic. Biophysical modeling of large-scale brain dynamics and applications for computational psychiatry. *Biological Psychiatry: Cognitive Neuroscience and Neuroimaging*, 3(9):777–787, 2018.
- Nikolaus Kriegeskorte and Pamela K Douglas. Cognitive computational neuroscience. *Nature neuroscience*, 21(9):1148–1160, 2018.
- Andreas Heinz, Graham K Murray, Florian Schlagenhauf, Philipp Sterzer, Anthony A Grace, and James A Waltz. Towards a unifying cognitive, neurophysiological, and computational neuroscience account of schizophrenia. *Schizophrenia bulletin*, 45(5):1092–1100, 2019.
- Michael Schirner, Xiaolu Kong, BT Thomas Yeo, Gustavo Deco, and Petra Ritter. Dynamic primitives of brain network interaction. *NeuroImage*, 250:118928, 2022.

- Steven J Schiff, Kristin Jerger, Duc H Duong, Taeun Chang, Mark L Spano, and William L Ditto. Controlling chaos in the brain. *Nature*, 370(6491):615–620, 1994.
- Lia Papadopoulos, Jason Z Kim, Jürgen Kurths, and Danielle S Bassett. Development of structural correlations and synchronization from adaptive rewiring in networks of kuramoto oscillators. *Chaos: An Interdisciplinary Journal of Nonlinear Science*, 27(7), 2017.
- Caio Seguin, Olaf Sporns, and Andrew Zalesky. Brain network communication: concepts, models and applications. *Nature Reviews Neuroscience*, 24(9):557–574, 2023.
- Benjamin Chiêm, Frédéric Crevecoeur, and Jean-Charles Delvenne. Structure-informed functional connectivity driven by identifiable and state-specific control regions. *Network Neuroscience*, 5(2):591–613, 2021.
- Brittany H Scheid, Arian Ashourvan, Jennifer Stiso, Kathryn A Davis, Fadi Mikhail, Fabio Pasqualetti, Brian Litt, and Danielle S Bassett. Time-evolving controllability of effective connectivity networks during seizure progression. *Proceedings of the National Academy of Sciences*, 118(5):e2006436118, 2021.
- Shi Gu, Fabio Pasqualetti, Matthew Cieslak, Qawi K Telesford, Alfred B Yu, Ari E Kahn, John D Medaglia, Jean M Vettel, Michael B Miller, Scott T Grafton, et al. Controllability of structural brain networks. *Nature communications*, 6(1):8414, 2015.
- Gustavo Deco, Mario Senden, and Viktor Jirsa. How anatomy shapes dynamics: a semi-analytical study of the brain at rest by a simple spin model. *Frontiers in computational neuroscience*, 6:68, 2012.
- Mathieu Golos, Viktor Jirsa, and Emmanuel Daucé. Multistability in large scale models of brain activity. *PLoS computational biology*, 11(12):e1004644, 2015.
- Enrique CA Hansen, Demian Battaglia, Andreas Spiegler, Gustavo Deco, and Viktor K Jirsa. Functional connectivity dynamics: modeling the switching behavior of the resting state. *Neuroimage*, 105:525–535, 2015.
- Mikail Khona and Ila R Fiete. Attractor and integrator networks in the brain. *Nature Reviews Neuroscience*, 23(12):744–766, 2022.
- Adrien Doerig, Rowan P Sommers, Katja Seeliger, Blake Richards, Jenann Ismael, Grace W Lindsay, Konrad P Kording, Talia Konkle, Marcel AJ Van Gerven, Nikolaus Kriegeskorte, et al. The neuroconnectionist research programme. *Nature Reviews Neuroscience*, pages 1–20, 2023.
- Blake A Richards, Timothy P Lillicrap, Philippe Beaudoin, Yoshua Bengio, Rafal Bogacz, Amelia Christensen, Claudia Clopath, Rui Ponte Costa, Archy de Berker, Surya Ganguli, et al. A deep learning framework for neuroscience. *Nature neuroscience*, 22(11):1761–1770, 2019.
- Michael W Cole, Takuya Ito, Danielle S Bassett, and Douglas H Schultz. Activity flow over resting-state networks shapes cognitive task activations. *Nature neuroscience*, 19(12):1718–1726, 2016.
- John J Hopfield. Neural networks and physical systems with emergent collective computational abilities. *Proceedings of the national academy of sciences*, 79(8):2554–2558, 1982.
- Dmitry Krotov. A new frontier for hopfield networks. *Nature Reviews Physics*, pages 1–2, 2023.
- Takuya Ito, Kaustubh R Kulkarni, Douglas H Schultz, Ravi D Mill, Richard H Chen, Levi I Solomyak, and Michael W Cole. Cognitive task information is transferred between brain regions via resting-state network topology. *Nature communications*, 8(1):1027, 2017.