

Best Arm Identification with Limited Precision Sampling

P. N. Karthik

Institute of Data Science
National University of Singapore
March 23, 2023

Joint Work With



Kota Srinivas Reddy
IIT Chennai




Nikhil Karamchandani
IIT Mumbai



Jayakrishnan Nair
IIT Mumbai


PROBLEM SETUP

- M boxes, K arms per box




PROBLEM SETUP

- M boxes, K arms per box
- Agent can only pick boxes




PROBLEM SETUP

- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$




PROBLEM SETUP




- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$

PROBLEM SETUP




- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$
- $\nu_k = \mathcal{N}(\mu_k, 1)$, $k \in [K]$

PROBLEM SETUP




- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$
- $\nu_k = \mathcal{N}(\mu_k, 1)$, $k \in [K]$
- Unknowns:

PROBLEM SETUP




- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$
- $\nu_k = \mathcal{N}(\mu_k, 1)$, $k \in [K]$
- Unknowns:
 - $\mathbf{q} = \{q_{m,k}\}_{m,k}$

PROBLEM SETUP




- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$
- $\nu_k = \mathcal{N}(\mu_k, 1)$, $k \in [K]$
- Unknowns:
 - $\mathbf{q} = \{q_{m,k}\}_{m,k}$
 - $\boldsymbol{\mu} = \{\mu_k\}_k$

PROBLEM SETUP




- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$
- $\nu_k = \mathcal{N}(\mu_k, 1)$, $k \in [K]$
- Unknowns:
 - $\mathbf{q} = \{q_{m,k}\}_{m,k}$
 - $\boldsymbol{\mu} = \{\mu_k\}_k$
- Best arm: $k^* = \arg \max_k \mu_k$

PROBLEM SETUP




- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$
- $\nu_k = \mathcal{N}(\mu_k, 1)$, $k \in [K]$
- Unknowns:
 - $\mathbf{q} = \{q_{m,k}\}_{m,k}$
 - $\boldsymbol{\mu} = \{\mu_k\}_k$
- Best arm: $k^* = \arg \max_k \mu_k$
- Goal: Fixed-confidence BAI

PROBLEM SETUP



- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$
- $\nu_k = \mathcal{N}(\mu_k, 1)$, $k \in [K]$
- Unknowns:
 - $\mathbf{q} = \{q_{m,k}\}_{m,k}$
 - $\boldsymbol{\mu} = \{\mu_k\}_k$
- Best arm: $k^* = \arg \max_k \mu_k$
- Goal: Fixed-confidence BAI

PROBLEM SETUP




- M boxes, K arms per box
- Agent can only pick boxes
- $P(\text{arm} = k | \text{box} = m) = q_{m,k}$
- Instance: $\nu = (\nu_1, \dots, \nu_K)$
- $\nu_k = \mathcal{N}(\mu_k, 1)$, $k \in [K]$
- Unknowns:
 - $\mathbf{q} = \{q_{m,k}\}_{m,k}$
 - $\boldsymbol{\mu} = \{\mu_k\}_k$
- Best arm: $k^* = \arg \max_k \mu_k$
- Goal: Fixed-confidence BAI

The key: determining the optimal box weight(s)

PRELIMINARIES


The key: determining the optimal box weight(s)

- Agent sees the pulled arm and its reward at each time



PRELIMINARIES


The key: determining the optimal box weight(s)



- Agent sees the pulled arm and its reward at each time
- SE-type or LUCB-type algorithms cannot be applied verbatim

PRELIMINARIES


The key: determining the optimal box weight(s)



- Agent sees the pulled arm and its reward at each time
- SE-type or LUCB-type algorithms cannot be applied verbatim
- To pull a certain arm k :

PRELIMINARIES


The key: determining the optimal box weight(s)



- Agent sees the pulled arm and its reward at each time
- SE-type or LUCB-type algorithms cannot be applied verbatim
- To pull a certain arm k :
 - If $\mathbf{q} = \{q_{m,k}\}_{m,k}$ is known, then choose box $m^* \in \arg \max_m q_{m,k}$

PRELIMINARIES

The key: determining the optimal box weight(s)



- Agent sees the pulled arm and its reward at each time
- SE-type or LUCB-type algorithms cannot be applied verbatim
- To pull a certain arm k :
 - If $\mathbf{q} = \{q_{m,k}\}_{m,k}$ is known, then choose box $m^* \in \arg \max_m q_{m,k}$
 - If $\mathbf{q} = \{q_{m,k}\}_{m,k}$ is unknown, then?
If $\{q_{m,k}\}_k = \{q_{m',k}\}_k$ for all m, m' , then every box weight is optimal

Outline

1 Asymptotic Analysis

- Converse
- Non-Uniqueness of Optimal Box Weights
- Achievability: D-Tracking for Non-Unique Box Weights

2 Non-Asymptotic Analysis: Arms Partitioned Among Boxes

- Non-Asymptotic Analysis : Converse
- Achievability: Successive Elimination

ASYMPTOTIC ANALYSIS

CONVERSE

Fix a problem instance $\mathbf{q}_0 = \{q_{m,k}^0\}_{m,k}$, $\boldsymbol{\mu}_0 = \{\mu_k^0\}_k$

CONVERSE

Fix a problem instance $\mathbf{q}_0 = \{q_{m,k}^0\}_{m,k}$, $\boldsymbol{\mu}_0 = \{\mu_k^0\}_k$

Theorem

$$\liminf_{\delta \downarrow 0} \inf_{\pi \text{ } \delta\text{-PC}} \frac{\mathbb{E}[\tau_\pi]}{\log(1/\delta)} \geq \frac{1}{T^*(\mathbf{q}_0, \boldsymbol{\mu}_0)},$$


where $T^*(\mathbf{q}_0, \boldsymbol{\mu}_0)$ is given by

$$T^*(\mathbf{q}_0, \boldsymbol{\mu}_0) = \sup_{\mathbf{w} \in \Sigma_M} \inf_{\boldsymbol{\lambda} \in \text{ALT}(\boldsymbol{\mu}_0)} \sum_{m=1}^M \sum_{k=1}^K w_m q_{m,k}^0 \frac{(\mu_k^0 - \lambda_k)^2}{2}.$$

The supremum is over $\Sigma_M = \{\mathbf{w} = (w_1, \dots, w_M) : w_m \geq 0 \ \forall m, \ \sum_{m=1}^M w_m = 1\}$.

■ From transportation Lemma 1 of [Kaufmann et al. \[2016\]](#),

$$\pi \text{ } \delta\text{-PC} \implies \inf_{\lambda \in \text{ALT}(\mu_0)} \sum_{k=1}^K \underbrace{\mathbb{E}[N_k(\tau_\pi)]}_{\text{\# pulls of arm } k} \frac{(\mu_k^0 - \lambda_k)^2}{2} \geq D_{\text{KL}}(\text{Ber}(\delta) \parallel \text{Ber}(1 - \delta)).$$




$$T^*(q_0, \mu_0) = \sup_{\mathbf{w} \in \Sigma_M} \inf_{\lambda \in \text{ALT}(\mu_0)} \sum_{m=1}^M \sum_{k=1}^K w_m q_{m,k}^0 \frac{(\mu_k^0 - \lambda_k)^2}{2}$$

- From transportation Lemma 1 of [Kaufmann et al. \[2016\]](#),

$$\pi \text{ } \delta\text{-PC} \implies \inf_{\lambda \in \text{ALT}(\mu_0)} \sum_{k=1}^K \underbrace{\mathbb{E}[N_k(\tau_\pi)]}_{\text{\# pulls of arm } k} \frac{(\mu_k^0 - \lambda_k)^2}{2} \geq D_{\text{KL}}(\text{Ber}(\delta) \parallel \text{Ber}(1 - \delta)).$$

- For each $k \in [K]$,

$$\mathbb{E}[N_k(\tau_\pi)] = \sum_{m=1}^M q_{m,k}^0 \underbrace{\mathbb{E}[N(\tau_\pi, m)]}_{\text{\# selections of box } m}.$$



$$T^*(q_0, \mu_0) = \sup_{\mathbf{w} \in \Sigma_M} \inf_{\lambda \in \text{ALT}(\mu_0)} \sum_{m=1}^M \sum_{k=1}^K w_m q_{m,k}^0 \frac{(\mu_k^0 - \lambda_k)^2}{2}$$

NON-UNIQUENESS OF OPTIMAL BOX WEIGHTS

Example (1)

$\{q_{m,k}^0\}_k$ independent of m , i.e., $\{q_{m,k}^0\}_k = \{q_{m',k}^0\}_k = \{\alpha_k\}_k$ for all m, m' . In this case,

$$\sum_{m=1}^M w_m q_{m,k}^0 = \sum_{m=1}^M w_m \alpha_k = \alpha_k \quad \forall k \in [K], \mathbf{w} \in \Sigma_M.$$

Example (2)

$M = 2, K = 4, \mu_0 = \{0.5, 0.4, 0.3, 0.3\}, \mathbf{q}_0 = \begin{pmatrix} 0.3 & 0.3 & 0.3 & 0.1 \\ 0.3 & 0.3 & 0.1 & 0.3 \end{pmatrix}$

For the above examples, every $\mathbf{w} \in \Sigma_M$ is optimal

ACHIEVABILITY: PRELIMINARIES

- **Set** of optimal box weights under $(\mathbf{q}, \boldsymbol{\mu})$:

$$\mathcal{W}^*(\mathbf{q}, \boldsymbol{\mu}) = \arg \sup_{\mathbf{w} \in \Sigma_M} \inf_{\boldsymbol{\lambda} \in \text{ALT}(\boldsymbol{\mu})} \sum_{m=1}^M \sum_{k=1}^K w_m q_{m,k} \frac{(\mu_k - \lambda_k)^2}{2}$$

ACHIEVABILITY: PRELIMINARIES

- **Set** of optimal box weights under $(\mathbf{q}, \boldsymbol{\mu})$:

$$\mathcal{W}^*(\mathbf{q}, \boldsymbol{\mu}) = \arg \sup_{\mathbf{w} \in \Sigma_M} \inf_{\boldsymbol{\lambda} \in \text{ALT}(\boldsymbol{\mu})} \sum_{m=1}^M \sum_{k=1}^K w_m q_{m,k} \frac{(\mu_k - \lambda_k)^2}{2}$$

- $(\mathbf{q}, \boldsymbol{\mu}) \mapsto \mathcal{W}^*(\mathbf{q}, \boldsymbol{\mu})$ is compact-valued and upper hemicontinuous

ACHIEVABILITY: PRELIMINARIES

- **Set** of optimal box weights under (\mathbf{q}, μ) :

$$\mathcal{W}^*(\mathbf{q}, \mu) = \arg \sup_{\mathbf{w} \in \Sigma_M} \inf_{\lambda \in \text{ALT}(\mu)} \sum_{m=1}^M \sum_{k=1}^K w_m q_{m,k} \frac{(\mu_k - \lambda_k)^2}{2}$$

- $(\mathbf{q}, \mu) \mapsto \mathcal{W}^*(\mathbf{q}, \mu)$ is compact-valued and upper hemicontinuous
- $\mathcal{W}^*(\mathbf{q}, \mu)$ is **convex** for each (\mathbf{q}, μ)

ACHIEVABILITY: MODIFIED D-TRACKING (1)

- Parameter estimates at time t :

$$\hat{q}_{m,k}(t) = \frac{\text{\# times box } m \text{ selected and arm } k \text{ pulled}}{N(t, m)}, \quad \hat{\mu}_k(t) = \frac{1}{N_k(t)} \sum_{s=1}^t \mathbf{1}_{\{A_s=k\}} X_s$$

ACHIEVABILITY: MODIFIED D-TRACKING (1)

- Parameter estimates at time t :

$$\hat{q}_{m,k}(t) = \frac{\text{\# times box } m \text{ selected and arm } k \text{ pulled}}{N(t, m)}, \quad \hat{\mu}_k(t) = \frac{1}{N_k(t)} \sum_{s=1}^t \mathbf{1}_{\{A_s=k\}} X_s$$

- $f(t) = \frac{\sqrt{t}}{\sqrt{M}}, \quad N(0, m) = 0$ for all m

ACHIEVABILITY: MODIFIED D-TRACKING (1)

- Parameter estimates at time t :

$$\hat{q}_{m,k}(t) = \frac{\text{\# times box } m \text{ selected and arm } k \text{ pulled}}{N(t, m)}, \quad \hat{\mu}_k(t) = \frac{1}{N_k(t)} \sum_{s=1}^t \mathbf{1}_{\{A_s=k\}} X_s$$

- $f(t) = \frac{\sqrt{t}}{\sqrt{M}}, \quad N(0, m) = 0 \text{ for all } m$

- $i_0 = 0, \quad i_{t+1} = (i_t \bmod M) + \underbrace{\mathbf{1}_{\{\min_{m \in [M]} N(t, m) < f(t)\}}}_{\text{round-robin box selection counter}} \quad \text{for all } t \geq 0$

ACHIEVABILITY: MODIFIED D-TRACKING (1)

- Parameter estimates at time t :

$$\hat{q}_{m,k}(t) = \frac{\text{\# times box } m \text{ selected and arm } k \text{ pulled}}{N(t, m)}, \quad \hat{\mu}_k(t) = \frac{1}{N_k(t)} \sum_{s=1}^t \mathbf{1}_{\{A_s=k\}} X_s$$

- $f(t) = \frac{\sqrt{t}}{\sqrt{M}}, \quad N(0, m) = 0 \text{ for all } m$

- $i_0 = 0, \quad i_{t+1} = (i_t \bmod M) + \underbrace{\mathbf{1}_{\{\min_{m \in [M]} N(t, m) < f(t)\}}}_{\text{round-robin box selection counter}} \quad \text{for all } t \geq 0$

- Let $\{\mathbf{w}(t) : t \geq 1\}$ be such that $\mathbf{w}(t+1) \in \mathcal{W}^*(\hat{\mathbf{q}}(t), \hat{\boldsymbol{\mu}}(t))$ for all t

ACHIEVABILITY: MODIFIED D-TRACKING (2)

- The modified D-Tracking rule:

$$B_{t+1} = \begin{cases} i_t, & \min_{m \in [M]} N(t, m) < f(t), \\ b_t, & \text{otherwise,} \end{cases}$$

where $\{b_t : t \geq 1\}$ is specified by

$$b_t = \arg \min_{m \in \text{supp}(\sum_{s=1}^t w(s))} N(t, m) - \sum_{s=1}^t w_m(s).$$

ACHIEVABILITY: MODIFIED D-TRACKING (2)

- The modified D-Tracking rule:

$$B_{t+1} = \begin{cases} i_t, & \min_{m \in [M]} N(t, m) < f(t), \\ b_t, & \text{otherwise,} \end{cases}$$

where $\{b_t : t \geq 1\}$ is specified by

$$b_t = \arg \min_{m \in \text{supp}(\sum_{s=1}^t w(s))} N(t, m) - \sum_{s=1}^t w_m(s).$$

- Inspired from [Jedra and Proutiere \[2020\]](#)

TRACKING THE OPTIMAL SET

■ Define $d_{\infty}(\mathbf{x}, \mathbf{y}) = \max_i |x_i - y_i|$, $d_{\infty}(\mathbf{x}, \mathcal{C}) = \min_{\mathbf{y} \in \mathcal{C}} d_{\infty}(\mathbf{x}, \mathbf{y})$

TRACKING THE OPTIMAL SET

■ Define $d_{\infty}(\mathbf{x}, \mathbf{y}) = \max_i |x_i - y_i|$, $d_{\infty}(\mathbf{x}, \mathcal{C}) = \min_{\mathbf{y} \in \mathcal{C}} d_{\infty}(\mathbf{x}, \mathbf{y})$

TRACKING THE OPTIMAL SET

■ Define $d_\infty(\mathbf{x}, \mathbf{y}) = \max_i |x_i - y_i|$, $d_\infty(\mathbf{x}, \mathcal{C}) = \min_{\mathbf{y} \in \mathcal{C}} d_\infty(\mathbf{x}, \mathbf{y})$

Lemma

Under the modified D-tracking rule,

$$\lim_{t \rightarrow \infty} d_\infty((N(t, m)/t)_{m \in [M]}, \mathcal{W}^*(\mathbf{q}_0, \boldsymbol{\mu}_0)) = 0 \quad a.s..$$

TRACKING THE OPTIMAL SET

- Define $d_\infty(\mathbf{x}, \mathbf{y}) = \max_i |x_i - y_i|$, $d_\infty(\mathbf{x}, \mathcal{C}) = \min_{\mathbf{y} \in \mathcal{C}} d_\infty(\mathbf{x}, \mathbf{y})$

Lemma

Under the modified D-tracking rule,

$$\lim_{t \rightarrow \infty} d_\infty((N(t, m)/t)_{m \in [M]}, \mathcal{W}^*(\mathbf{q}_0, \boldsymbol{\mu}_0)) = 0 \quad a.s..$$

- Inspired by [Degenne and Koolen \[2019\]](#), the key idea in the proof is to track the behaviour of $\bar{\mathbf{w}}(t) = \frac{1}{t} \sum_{s=1}^t \mathbf{w}(s) \in \mathcal{W}^*(\hat{\mathbf{q}}(t-1), \hat{\boldsymbol{\mu}}(t-1))$

TRACKING THE OPTIMAL SET

■ Define $d_\infty(\mathbf{x}, \mathbf{y}) = \max_i |x_i - y_i|$, $d_\infty(\mathbf{x}, \mathcal{C}) = \min_{\mathbf{y} \in \mathcal{C}} d_\infty(\mathbf{x}, \mathbf{y})$

Lemma

Under the modified D-tracking rule,

$$\lim_{t \rightarrow \infty} d_\infty((N(t, m)/t)_{m \in [M]}, \mathcal{W}^*(\mathbf{q}_0, \boldsymbol{\mu}_0)) = 0 \quad \text{a.s..}$$

■ When $\mathcal{W}^*(\mathbf{q}_0, \boldsymbol{\mu}_0) = \{\mathbf{w}^*\}$, we recover the classical tracking result

$$\frac{N(t, m)}{t} \xrightarrow{t \rightarrow \infty} w_m^* \quad \forall m, \quad \text{a.s..}$$

STOPPING & RECOMMENDATION RULES

- The GLLR statistic between arms $a, b \in [K]$ at time t is

$$Z_{a,b}(t) = \begin{cases} N_a(t) \frac{(\hat{\mu}_a(t) - \hat{\mu}_{a,b}(t))^2}{2} + N_b(t) \frac{(\hat{\mu}_b(t) - \hat{\mu}_{a,b}(t))^2}{2}, & \hat{\mu}_a(t) \geq \hat{\mu}_b(t), \\ -Z_{b,a}(t), & \text{otherwise,} \end{cases}$$

where $\hat{\mu}_{a,b}(t) = \frac{N_a(t)}{N_a(t) + N_b(t)} \hat{\mu}_a(t) + \frac{N_b(t)}{N_a(t) + N_b(t)} \hat{\mu}_b(t)$.

STOPPING & RECOMMENDATION RULES

- The GLLR statistic between arms $a, b \in [K]$ at time t is

$$Z_{a,b}(t) = \begin{cases} N_a(t) \frac{(\hat{\mu}_a(t) - \hat{\mu}_{a,b}(t))^2}{2} + N_b(t) \frac{(\hat{\mu}_b(t) - \hat{\mu}_{a,b}(t))^2}{2}, & \hat{\mu}_a(t) \geq \hat{\mu}_b(t), \\ -Z_{b,a}(t), & \text{otherwise,} \end{cases}$$

where $\hat{\mu}_{a,b}(t) = \frac{N_a(t)}{N_a(t) + N_b(t)} \hat{\mu}_a(t) + \frac{N_b(t)}{N_a(t) + N_b(t)} \hat{\mu}_b(t)$.

- Let $Z(t) = \max_a \min_{b \neq a} Z_{a,b}(t)$

STOPPING & RECOMMENDATION RULES

- The GLLR statistic between arms $a, b \in [K]$ at time t is

$$Z_{a,b}(t) = \begin{cases} N_a(t) \frac{(\hat{\mu}_a(t) - \hat{\mu}_{a,b}(t))^2}{2} + N_b(t) \frac{(\hat{\mu}_b(t) - \hat{\mu}_{a,b}(t))^2}{2}, & \hat{\mu}_a(t) \geq \hat{\mu}_b(t), \\ -Z_{b,a}(t), & \text{otherwise,} \end{cases}$$

where $\hat{\mu}_{a,b}(t) = \frac{N_a(t)}{N_a(t) + N_b(t)} \hat{\mu}_a(t) + \frac{N_b(t)}{N_a(t) + N_b(t)} \hat{\mu}_b(t)$.

- Let $Z(t) = \max_a \min_{b \neq a} Z_{a,b}(t)$
- Given $\delta \in (0, 1)$, let $\beta(t, \delta, \rho) = \log \frac{Ct^{1+\rho}}{\delta}$, where C is a predetermined constant

STOPPING & RECOMMENDATION RULES

- The GLLR statistic between arms $a, b \in [K]$ at time t is

$$Z_{a,b}(t) = \begin{cases} N_a(t) \frac{(\hat{\mu}_a(t) - \hat{\mu}_{a,b}(t))^2}{2} + N_b(t) \frac{(\hat{\mu}_b(t) - \hat{\mu}_{a,b}(t))^2}{2}, & \hat{\mu}_a(t) \geq \hat{\mu}_b(t), \\ -Z_{b,a}(t), & \text{otherwise,} \end{cases}$$

where $\hat{\mu}_{a,b}(t) = \frac{N_a(t)}{N_a(t) + N_b(t)} \hat{\mu}_a(t) + \frac{N_b(t)}{N_a(t) + N_b(t)} \hat{\mu}_b(t)$.

- Let $Z(t) = \max_a \min_{b \neq a} Z_{a,b}(t)$
- Given $\delta \in (0, 1)$, let $\beta(t, \delta, \rho) = \log \frac{C t^{1+\rho}}{\delta}$, where C is a predetermined constant
- **Stopping rule:** $\tau_{\delta, \rho} = \min\{t \geq 1 : Z(t) \geq \beta(t, \delta, \rho) \text{ and } \min_{k \in [K]} N_k(t) > 0\}$

STOPPING & RECOMMENDATION RULES

- The GLLR statistic between arms $a, b \in [K]$ at time t is

$$Z_{a,b}(t) = \begin{cases} N_a(t) \frac{(\hat{\mu}_a(t) - \hat{\mu}_{a,b}(t))^2}{2} + N_b(t) \frac{(\hat{\mu}_b(t) - \hat{\mu}_{a,b}(t))^2}{2}, & \hat{\mu}_a(t) \geq \hat{\mu}_b(t), \\ -Z_{b,a}(t), & \text{otherwise,} \end{cases}$$

where $\hat{\mu}_{a,b}(t) = \frac{N_a(t)}{N_a(t) + N_b(t)} \hat{\mu}_a(t) + \frac{N_b(t)}{N_a(t) + N_b(t)} \hat{\mu}_b(t)$.

- Let $Z(t) = \max_a \min_{b \neq a} Z_{a,b}(t)$
- Given $\delta \in (0, 1)$, let $\beta(t, \delta, \rho) = \log \frac{C t^{1+\rho}}{\delta}$, where C is a predetermined constant
- **Stopping rule:** $\tau_{\delta, \rho} = \min\{t \geq 1 : Z(t) \geq \beta(t, \delta, \rho) \text{ and } \min_{k \in [K]} N_k(t) > 0\}$
- **Recommendation rule:** $\hat{k} = \arg \max_k \hat{\mu}_k(\tau_{\delta, \rho})$

RESULTS

Under the box sampling, stopping, and recommendation rules stated before:

Theorem

$$\blacksquare P(\tau_{\delta, \rho} < \infty, \hat{k} \neq k^*) \leq \delta$$

RESULTS

Under the box sampling, stopping, and recommendation rules stated before:

Theorem

■ $P(\tau_{\delta,\rho} < \infty, \hat{k} \neq k^*) \leq \delta$

■ $\tau_{\delta,\rho}$ satisfies

$$\tau_{\delta,\rho} \leq \frac{1 + \rho}{T^*(\mathbf{q}_0, \boldsymbol{\mu}_0)} \log(1/\delta) + o(\log(1/\delta)) \quad \text{a.s..}$$

Hence, $P(\tau_{\delta,\rho} < \infty) = 1$.

RESULTS

Under the box sampling, stopping, and recommendation rules stated before:

Theorem

■ $P(\tau_{\delta,\rho} < \infty, \hat{k} \neq k^*) \leq \delta$

■ $\tau_{\delta,\rho}$ satisfies

$$\tau_{\delta,\rho} \leq \frac{1 + \rho}{T^*(\mathbf{q}_0, \boldsymbol{\mu}_0)} \log(1/\delta) + o(\log(1/\delta)) \quad \text{a.s..}$$

Hence, $P(\tau_{\delta,\rho} < \infty) = 1$.

■ Asymptotic upper bound on $\mathbb{E}[\tau_{\delta,\rho}]$:

$$\limsup_{\delta \downarrow 0} \frac{\mathbb{E}[\tau_{\delta,\rho}]}{\log(1/\delta)} \leq \frac{1 + \rho}{T^*(\mathbf{q}_0, \boldsymbol{\mu}_0)}.$$

NON-ASYMPTOTIC ANALYSIS:

PRELIMINARIES

- In SE-type algorithms, multiple arms are pulled at each time instant; sub-optimal arms are eliminated on-the-fly

PRELIMINARIES

- In SE-type algorithms, multiple arms are pulled at each time instant; sub-optimal arms are eliminated on-the-fly
- In LUCB-type algorithms, two arms are pulled at each time instant

PRELIMINARIES

- In SE-type algorithms, multiple arms are pulled at each time instant; sub-optimal arms are eliminated on-the-fly
- In LUCB-type algorithms, two arms are pulled at each time instant
- In our setup, the learner **cannot** pull arms directly

PRELIMINARIES

- In SE-type algorithms, multiple arms are pulled at each time instant; sub-optimal arms are eliminated on-the-fly
- In LUCB-type algorithms, two arms are pulled at each time instant
- In our setup, the learner **cannot** pull arms directly
- To maximise the chances of pulling a given arm k :

PRELIMINARIES

- In SE-type algorithms, multiple arms are pulled at each time instant; sub-optimal arms are eliminated on-the-fly
- In LUCB-type algorithms, two arms are pulled at each time instant
- In our setup, the learner **cannot** pull arms directly
- To maximise the chances of pulling a given arm k :
 - When q_0 is known: select box $m^* \in \arg \max_m q_{m,k}^0$

PRELIMINARIES

- In SE-type algorithms, multiple arms are pulled at each time instant; sub-optimal arms are eliminated on-the-fly
- In LUCB-type algorithms, two arms are pulled at each time instant
- In our setup, the learner **cannot** pull arms directly
- To maximise the chances of pulling a given arm k :
 - When q_0 is known: select box $m^* \in \arg \max_m q_{m,k}^0$
 - When q_0 is unknown: select $m^* \in \arg \max_m \hat{q}_{m,k}(t)$ at time t


PRELIMINARIES

- In SE-type algorithms, multiple arms are pulled at each time instant; sub-optimal arms are eliminated on-the-fly
- In LUCB-type algorithms, two arms are pulled at each time instant
- In our setup, the learner **cannot** pull arms directly
- To maximise the chances of pulling a given arm k :
 - When \mathbf{q}_0 is known: select box $m^* \in \arg \max_m \mathbf{q}_{m,k}^0$
 - When \mathbf{q}_0 is unknown: select $m^* \in \arg \max_m \hat{\mathbf{q}}_{m,k}(t)$ at time t
- **Open question:** Are the above strategies optimal?

PRELIMINARIES

- In SE-type algorithms, multiple arms are pulled at each time instant; sub-optimal arms are eliminated on-the-fly
- In LUCB-type algorithms, two arms are pulled at each time instant
- In our setup, the learner **cannot** pull arms directly
- To maximise the chances of pulling a given arm k :
 - When \mathbf{q}_0 is known: select box $m^* \in \arg \max_m \mathbf{q}_{m,k}^0$
 - When \mathbf{q}_0 is unknown: select $m^* \in \arg \max_m \hat{\mathbf{q}}_{m,k}(t)$ at time t
- **Open question:** Are the above strategies optimal?
- Simplified setting: arms **partitioned** across boxes

SIMPLIFIED PROBLEM SETUP: PARTITION



Goal: fixed-confidence BAI

- Arms partitioned across boxes
- Arm k of box m indexed as $A_{m,k}$ or simply as (m, k)
- \mathcal{A}_m : set of arms in box m
- $\sum_{m=1}^M |\mathcal{A}_m| = K$
- Agent **knows** $\mathcal{A}_1, \dots, \mathcal{A}_M$
- Unknowns:
 - $\mathbf{q}_0 = \{q_{m,k}^0\}_{m,k}$
 - $\boldsymbol{\mu}_0 = \{\mu_{m,k}^0\}_{m,k}$
- Best arm: $(m^*, k^*) = \arg \max_{m,k} \mu_{m,k}^0$

CONVERSE

- WLOG, let $(1, 1)$ be the best arm
- Let $\Delta_{m,k} = \mu_{1,1}^0 - \mu_{m,k}^0$ for all $(m, k) \neq (1, 1)$, and $\Delta_{1,1} = \min_{(m,k) \neq (1,1)} \Delta_{m,k}$

CONVERSE

- WLOG, let $(1, 1)$ be the best arm
- Let $\Delta_{m,k} = \mu_{1,1}^0 - \mu_{m,k}^0$ for all $(m, k) \neq (1, 1)$, and $\Delta_{1,1} = \min_{(m,k) \neq (1,1)} \Delta_{m,k}$

Theorem

Under any δ -PC algorithm,

$$\mathbb{E}[\tau_\pi] \geq \log\left(\frac{1}{2.4\delta}\right) \cdot \sum_{m=1}^M \max_{k \in \mathcal{A}_m} \frac{1}{q_{m,k}^0 \Delta_{m,k}^2}.$$

- Technique: change-of-measure arguments of [Garivier and Kaufmann \[2016\]](#)

ACHIEVABILITY: SUCCESSIVE ELIMINATION

Notations:

■ $t_{m,k}(n)$: # pulls of arm $A_{m,k}$ up to round n

■ $\alpha_\delta(x) = \sqrt{\frac{2 \ln(8 K x^2 / \delta)}{x}}$

■ $\text{UCB}_{m,k}(n) = \hat{\mu}_{m,k}(n) + \alpha_\delta(t_{m,k}(n))$

■ $\text{LCB}_{m,k}(n) = \hat{\mu}_{m,k}(n) - \alpha_\delta(t_{m,k}(n))$

Select box until each active arm is pulled n times in round n

Algorithm 1 Successive Elimination

Input: $K, M, \delta > 0, \mathcal{A}_m$ for $m \in [M]$

Output: $\hat{a} \in [K]$ (best arm).

Initialization: $S = [K], B = [M], S_m = [a_m], n = 0,$

$\hat{\mu}_{m,k}(n) = 0 \forall k, m, S_m = \mathcal{A}_m \forall m, t = 0.$

```
1: while  $|S| > 1$  do
2:    $n \leftarrow n + 1$ 
3:   For each  $m \in B$ , select box  $m$  until every active arm  $A_{m,k}$  in box  $m$  is pulled at least  $n$  times.
4:   For every box selection, increment  $t$  by 1.
5:   Update  $t_{m,k}(n), \hat{\mu}_{m,k}(n), \text{UCB}_{m,k}(n)$  and  $\text{LCB}_{m,k}(n)$  for all the active arms.
6:   if  $\exists A_{m',k'} \in S$  such that  $\text{UCB}_{m,k}(n) < \text{LCB}_{m',k'}(n)$  then
7:      $S_m \leftarrow S_m \setminus A_{m,k}, S \leftarrow \bigcup_{m \in [M]} S_m,$ 
8:      $B \leftarrow \{m : S_m \neq \emptyset\}.$ 
9:   end if
10:  if  $|S| = 1$  then
11:     $\hat{a} \leftarrow a \in S, S \leftarrow \emptyset, B \leftarrow \emptyset.$ 
12:  end if
13: end while
14: return  $\hat{a}.$ 
```

RESULTS

Theorem

Fix $\delta \in (0, 1)$. With probability greater than $1 - \delta$:

- The SE algorithm outputs the correct best arm
- The SE algorithm stops at time $\leq \sum_{m=1}^M U_m$, where U_m is a random variable with

$$P \left(U_m = \max_{k \in \mathcal{A}_m} O \left(\frac{\ln \left(\frac{K}{\delta \Delta_{m,k}} \right)}{q_{m,k}^0 \Delta_{m,k}^2} \right) \right) \geq 1 - \frac{\delta |\mathcal{A}_m|}{K}.$$

RESULTS

Theorem

Fix $\delta \in (0, 1)$. With probability greater than $1 - \delta$:

- The SE algorithm outputs the correct best arm
- The SE algorithm stops at time $\leq \sum_{m=1}^M U_m$, where U_m is a random variable with

$$P \left(U_m = \max_{k \in \mathcal{A}_m} O \left(\frac{\ln \left(\frac{K}{\delta \Delta_{m,k}} \right)}{q_{m,k}^0 \Delta_{m,k}^2} \right) \right) \geq 1 - \frac{\delta |\mathcal{A}_m|}{K}.$$

- Lower bound = $\Omega \left(\sum_{m=1}^M \max_{k \in \mathcal{A}_m} \frac{1}{q_{m,k}^0 \Delta_{m,k}^2} \right)$ (order-wise matching in problem unknowns)

In Summary

- Problem studied: BAI with limited precision sampling
- Modified D-tracking algorithm to handle non-unique optimal box weights
- Partition setting: SE algorithm that selects each box until each active arm is pulled n times in round n
- Non-partition setting: SE/LUCB-type algorithm design is an open question

Thank You!

Questions? Hit me up!
Email: karthik@nus.edu.sg
Web: <https://karthikpn.com>

REFERENCES

- Rémy Degenne and Wouter M Koolen. Pure exploration with multiple correct answers. *Advances in Neural Information Processing Systems*, 32, 2019.
- Aurélien Garivier and Emilie Kaufmann. Optimal best arm identification with fixed confidence. In *Conference on Learning Theory*, pages 998–1027. PMLR, 2016.
- Yassir Jedra and Alexandre Proutiere. Optimal best-arm identification in linear bandits. *Advances in Neural Information Processing Systems*, 33:10007–10017, 2020.
- Emilie Kaufmann, Olivier Cappé, and Aurélien Garivier. On the complexity of best-arm identification in multi-armed bandit models. *The Journal of Machine Learning Research*, 17(1):1–42, 2016.