

Almost Cost-Free Communication in Federated Best Arm Identification

Workshop on Information Theory and Data Science
Institute for Mathematical Sciences
National University of Singapore

16 January 2023



P. N. Karthik

Research Fellow
Institute of Data Science
National University of Singapore
karthik@nus.edu.sg
<https://karthikpn.com>

Joint Work with





Kota Srinivas Reddy





Vincent Y. F. Tan

Federated Best Arm Identification




* Pics only for demonstration, courtesy Google

Federated Best Arm Identification




* Pics only for demonstration, courtesy Google

Federated Best Arm Identification




* Pics only for demonstration, courtesy Google

Problem Abstraction




Problem Abstraction

- Single server, M clients




Problem Abstraction

- Single server, M clients
- Each client has access to a K -armed bandit




Problem Abstraction

- Single server, M clients
- Each client has access to a K -armed bandit
- Independent Gaussian rewards from each arm (unit variance)




Problem Abstraction

- Single server, M clients
- Each client has access to a K -armed bandit
- Independent Gaussian rewards from each arm (unit variance)
- $\mu_{k,m}$ – mean reward from arm k of client m



Problem Abstraction


- Single server, M clients
- Each client has access to a K -armed bandit
- Independent Gaussian rewards from each arm (unit variance)
- $\mu_{k,m}$ – mean reward from arm k of client m
- Local best arm of client m – $\arg \max_k \mu_{k,m}$



Problem Abstraction

- Single server, M clients
- Each client has access to a K -armed bandit
- Independent Gaussian rewards from each arm (unit variance)
- $\mu_{k,m}$ – mean reward from arm k of client m
- Local best arm of client m – $\arg \max_k \mu_{k,m}$

- Global best arm – $\arg \max_k \frac{1}{M} \sum_{m=1}^M \mu_{k,m}$




Problem Abstraction

- Single server, M clients
- Each client has access to a K -armed bandit
- Independent Gaussian rewards from each arm (unit variance)
- $\mu_{k,m}$ – mean reward from arm k of client m
- Local best arm of client m – $\arg \max_k \mu_{k,m}$


- Global best arm – $\arg \max_k \frac{1}{M} \sum_{m=1}^M \mu_{k,m}$
- Uplink communication cost: $C \geq 0$ per usage per client,

Downlink cost: nil



Problem Abstraction

- Single server, M clients
- Each client has access to a K -armed bandit
- Independent Gaussian rewards from each arm (unit variance)
- $\mu_{k,m}$ – mean reward from arm k of client m
- Local best arm of client m – $\arg \max_k \mu_{k,m}$



- Global best arm – $\arg \max_k \frac{1}{M} \sum_{m=1}^M \mu_{k,m}$
- Uplink communication cost: $C \geq 0$ per usage per client,

Downlink cost: nil

Find local (clients) & global (server) best arms

$$\min \quad \mathbb{E} \left[\underbrace{\text{no. of arm pulls + communication cost}}_{\text{total cost}} \right]$$

s.t. error probability $\leq \delta$

Results at a Glance – 1/3

Results at a Glance – 1/3

- A federated BAI algorithm
- Based on successive elimination – FedElim
- With exponentially sparse comm. at time instants $n \in \{2^t\}_{t=0}^\infty$

Results at a Glance – 1/3

- A federated BAI algorithm
- Based on successive elimination – FedElim
- With exponentially sparse comm. at time instants $n \in \{2^t\}_{t=0}^\infty$
- Comparisons with other algos:

Per(H) – Succ. elim. + comm. at $n \in \{1 + tH\}_{t=0}^\infty$

SupExp – Succ. elim. + comm. at $n \in \{2^{2^t}\}_{t=0}^\infty$

Results at a Glance – 1/3

- A federated BAI algorithm
- Based on successive elimination – FedElim
- With exponentially sparse comm. at time instants $n \in \{2^t\}_{t=0}^\infty$
- Comparisons with other algos:
 - Per(H) – Succ. elim. + comm. at $n \in \{1 + tH\}_{t=0}^\infty$
 - SupExp – Succ. elim. + comm. at $n \in \{2^{2^t}\}_{t=0}^\infty$
- Performance evaluation on 2 synthetic datasets + MovieLens dataset

Results at a Glance – 1/3


almost cost-free communication

- A federated BAI algorithm
- Based on successive elimination – FedElim
- With exponentially sparse comm. at time instants $n \in \{2^t\}_{t=0}^\infty$
- Comparisons with other algos:

Per(H) – Succ. elim. + comm. at $n \in \{1 + tH\}_{t=0}^\infty$

SupExp – Succ. elim. + comm. at $n \in \{2^{2^t}\}_{t=0}^\infty$

- Performance evaluation on 2 synthetic datasets + MovieLens dataset



For any $C > 0$, $\forall \delta$ small,

$$P\left(\text{total cost of FedElim} \lesssim 3 \times \text{total cost of Per}(1) \text{ when } C = 0\right) \geq 1 - \delta$$

Key takeaway 1


Results at a Glance – 2/3

- A federated BAI algorithm
- Based on successive elimination – FedElim
- With exponentially sparse comm. at time instants $n \in \{2^t\}_{t=0}^\infty$
- Comparisons with other algos:

Per(H) – Succ. elim. + comm. at $n \in \{1 + tH\}_{t=0}^\infty$

SupExp – Succ. elim. + comm. at $n \in \{2^{2^t}\}_{t=0}^\infty$

- Performance evaluation on 2 synthetic datasets + MovieLens dataset



FedElim operates at a sweet spot

Key takeaway 2

Results at a Glance – 3/3

- A federated BAI algorithm
- Based on successive elimination – FedElim
- With exponentially sparse comm. at time instants $n \in \{2^t\}_{t=0}^\infty$
- Comparisons with other algos:

Per(H) – Succ. elim. + comm. at $n \in \{1 + tH\}_{t=0}^\infty$

SupExp – Succ. elim. + comm. at $n \in \{2^{2^t}\}_{t=0}^\infty$

Scheme	No. of arm pulls	Comm. cost	Total cost
Per(H)	$O(T)$	$O(CT/H)$	$O(T+CT/H)$
FedElim*	$2T$	$O(C \log(T))$	$3T$
SupExp	$O(T^2)$	$O(C \log\log(T))$	$O(T^2)$

* for sufficiently small error probabilities

- Performance evaluation on 2 synthetic datasets + MovieLens dataset

FedElim carefully balances no. of arm pulls and comm. cost

Key takeaway 3

Related Works

- Shi, Shen, and Yang (2021) – similar setting, regret minimisation

- Mitra, Hassani, and Pappas (2021)

- Arm sets disjoint across clients
- Only global best arm identification
- Local best arms can be eliminated along the way
- Periodic communication scheme

- Tao, Zhang, and Zhou (2019), Hillel et al. (2013)

- Identical arm distributions at all the clients
- Collaborative learning of the best arm

Federated Multi-armed Bandits with Personalization

Chengshuai Shi
University of Virginia

Cong Shen
University of Virginia

Jing Yang
The Pennsylvania State University

Abstract

A general framework of personalized federated multi-armed bandits (PF-MAB) is proposed, which is a new learning paradigm analogous to the federated learning (FL) framework in supervised learning and enjoys some features of the MAB problem. Under the PF-MAB framework, a mixed bandit learning problem that flexibly balances generalization and personalization is studied. The theoretical analysis for the mixed model is presented. We then propose the Personalized Federated Upper Confidence Bound (PF-UCB) algorithm, where the exploration length is chosen carefully to achieve the desired balance of learning the local model and supplying global information for the federated learning problem. Theoretical analysis proves that PF-UCB achieves an $O(\log(T))$ regret regardless of the degree of personalization. It also has no cross-dependency as the lower bound. Experiments using both synthetic and real-world datasets confirm the theoretical analysis and demonstrate the effectiveness of the proposed algorithm.

While the main focus of the state-of-the-art FL with personalization is on the supervised learning setting, we extend it to its counterparts to the multi-armed bandit (MAB) problem. This is motivated by a corpus of practical applications, including:

- **Cognitive radio.** Consider a cellular network where one base station (BS) serves many devices (e.g., smartphones) that are geographically spread out in the coverage area. Each device wants to use the individual best channel in terms of its own communication quality.

Exploiting Heterogeneity in Robust Federated Best-Arm Identification

Aritra Mitra, George J. Pappas, and Hamed Hassani *

Abstract

We study a federated variant of the best-arm identification problem in stochastic multi-armed bandits: a set of clients, each of whom can sample only a subset of the arms, collaborate via a server to identify the best arm (i.e., the arm with the highest mean reward) with prescribed confidence. For this problem, we propose **Fed-SEL**, a simple communication-efficient algorithm that identifies the best arm after $\tilde{O}(\sqrt{d})$ rounds of communication at the clients. To study the performance of Fed-SEL, we introduce a notion of arm-heterogeneity that captures the level of dissimilarity between distributions of arms corresponding to different clients. Interestingly, our analysis reveals the benefits of arm-heterogeneity in reducing both the sample- and communication-complexity of Fed-SEL. As a special case of our analysis, we show that for certain heterogeneous problem instances, Fed-SEL outputs the best-arm after just one round of communication. Our findings have the following key implication: unlike federated supervised learning where recent work has shown that statistical heterogeneity can lead to poor performance, one can provably reap the benefits of both local computation and heterogeneity for federated best-arm identification. As our final contribution, we develop variants of Fed-SEL, both for federated and peer-to-peer settings, that are robust to the presence of Byzantine clients, and hence suitable for deployment in harsh, adversarial environments.

2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS)

Collaborative Learning with Limited Interaction:
Tight Bounds for Distributed Exploration in
Multi-Armed Bandits

Chao Tao¹, Qin Zhang¹, Yuan Zhou²

¹Computer Science Department, Indiana University
Email: tao@cs.indiana.edu
²Computer Science Department, Indiana University
Email: qzhangcs@indiana.edu


²Computer Science Department, Indiana University
and
Department of ISE, University of Illinois at Urbana-Champaign
Email: yuanz@illinois.edu

The $C = 0$ Case


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost




Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost




Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)


Algorithmic
details

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)


Algorithmic
details

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)




$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)




$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)




$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

FedElim for $C = 0$ (FedElim0)




$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost




Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost




Comm. at **every time instant**




FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**




Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$


1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$

$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$


1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$

$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$


1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server

$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$


1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server

$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$


1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server
4. Eliminate $k \in \mathcal{S}_g$ if $\frac{1}{M} \sum_{m=1}^M \hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_g} \frac{1}{M} \sum_{m=1}^M \hat{\mu}_{a,m}(n) - 2\alpha_g(n)$

$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server
4. Eliminate $k \in \mathcal{S}_g$ if $\frac{1}{M} \sum_{m=1}^M \hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_g} \frac{1}{M} \sum_{m=1}^M \hat{\mu}_{a,m}(n) - 2\alpha_g(n)$


$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$

$$\alpha_g(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{Mn}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server
4. Eliminate $k \in \mathcal{S}_g$ if $\frac{1}{M} \sum_{m=1}^M \hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_g} \frac{1}{M} \sum_{m=1}^M \hat{\mu}_{a,m}(n) - 2\alpha_g(n)$


$$\alpha_l(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{n}}$$

$$\alpha_g(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{Mn}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server
4. Eliminate $k \in \mathcal{S}_g$ if $\frac{1}{M} \sum_{m=1}^M \hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_g} \frac{1}{M} \sum_{m=1}^M \hat{\mu}_{a,m}(n) - 2\alpha_g(n)$
5. Server sends updated \mathcal{S}_g to all clients


$$\alpha_l(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{n}}$$

$$\alpha_g(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{Mn}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server
4. Eliminate $k \in \mathcal{S}_g$ if $\frac{1}{M} \sum_{m=1}^M \hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_g} \frac{1}{M} \sum_{m=1}^M \hat{\mu}_{a,m}(n) - 2\alpha_g(n)$
5. Server sends updated \mathcal{S}_g to all clients


$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$

$$\alpha_g(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{Mn}}$$


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at **every time instant**



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server
4. Eliminate $k \in \mathcal{S}_g$ if $\frac{1}{M} \sum_{m=1}^M \hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_g} \frac{1}{M} \sum_{m=1}^M \hat{\mu}_{a,m}(n) - 2\alpha_g(n)$
5. Server sends updated \mathcal{S}_g to all clients

$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$


$$\alpha_g(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{Mn}}$$

Elim. at client m continues until $|\mathcal{S}_{l,m}| = 1$ (local best arm)


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. at every time instant



Initialise: $\mathcal{S}_{l,m} = [K] \forall m, \mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server
4. Eliminate $k \in \mathcal{S}_g$ if $\frac{1}{M} \sum_{m=1}^M \hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_g} \frac{1}{M} \sum_{m=1}^M \hat{\mu}_{a,m}(n) - 2\alpha_g(n)$
5. Server sends updated \mathcal{S}_g to all clients

$$\alpha_l(n) = \sqrt{\frac{2 \ln(8KMn^2/\delta)}{n}}$$

$$\alpha_g(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{Mn}}$$

Elim. at client m continues until $|\mathcal{S}_{l,m}| = 1$ (local best arm)

Comm. with server stops when $|\mathcal{S}_g| = 1$ (global best arm)

Performance of FedElim0 ($C = 0$)

Performance of FedElim0 ($C = 0$)

- Stops in finite time w.p.1

Performance of FedElim0 ($C = 0$)

- Stops in finite time w.p.1
- Error probability $\leq \delta$

Performance of FedElim0 ($C = 0$)

- Stops in finite time w.p.1
- Error probability $\leq \delta$
- Total cost of FedElim0 (T_{FedElim0}) satisfies

$$P\left(T_{\text{FedElim0}} \leq \underbrace{\sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}}_{=T}\right) \geq 1 - \delta,$$

$$T_{k,m} = 102 \cdot \frac{\ln\left(\frac{64\sqrt{\frac{8KM}{\delta}}}{\Delta_{k,m}^2}\right)}{\Delta_{k,m}^2} + 1, \quad T_k = 102 \cdot \frac{\ln\left(\frac{64\sqrt{\frac{8K}{\delta}}}{M\Delta_k^2}\right)}{M\Delta_k^2} + 1,$$

$\Delta_{k,m} = \max_a \mu_{a,m} - \mu_{k,m}$ (local sub-optimality gap),


$\Delta_k = \max_a \frac{1}{M} \sum_{m=1}^M (\mu_{a,m} - \mu_{k,m})$ (global sub-optimality gap),

The $C > 0$ Case


FedElim for $C = 0$ (FedElim0)

$$\begin{aligned} \min \quad & \mathbb{E}[\text{no. of arm pulls} + \text{communication cost}] \\ \text{s.t.} \quad & \text{error probability} \leq \delta \end{aligned}$$

= total cost



Comm. only at exponential time instants $n \in \{2^t : t \geq 0\}$



Initialise: $\mathcal{S}_{l,m} = [K]$, $\mathcal{S}_g = [K]$

1. Pull each arm $k \in \mathcal{S}_m$ and update its empirical mean $\hat{\mu}_{k,m}(n)$
2. Eliminate $k \in \mathcal{S}_{l,m}$ if $\hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_{l,m}} \hat{\mu}_{a,m}(n) - 2\alpha_l(n)$
Update $\mathcal{S}_{l,m}$
3. Client m sends $\{\hat{\mu}_{k,m}(n) : k \in \mathcal{S}_g\}$ and \mathcal{S}_g to server if $n \in \{2^t\}_{t=0}^\infty$
4. Eliminate $k \in \mathcal{S}_g$ if $\frac{1}{M} \sum_{m=1}^M \hat{\mu}_{k,m}(n) \leq \max_{a \in \mathcal{S}_g} \frac{1}{M} \sum_{m=1}^M \hat{\mu}_{a,m}(n) - 2\alpha_g(n)$
5. Server sends updated \mathcal{S}_g to all clients

$$\alpha_l(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{n}}$$

$$\alpha_g(n) = \sqrt{\frac{2 \ln(8Kn^2/\delta)}{Mn}}$$

Elim. at client m continues until $|\mathcal{S}_{l,m}| = 1$ (local best arm)

Comm. with server stops when $|\mathcal{S}_g| = 1$ (global best arm)

Performance of FedElim ($C > 0$)

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

Performance of FedElim ($C > 0$)

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- Stops in finite time w.p.1

Performance of FedElim ($C > 0$)

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- Stops in finite time w.p.1
- Error probability $\leq \delta$

Performance of FedElim ($C > 0$)

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- Stops in finite time w.p.1
- Error probability $\leq \delta$
- With prob. $1 - \delta$,

Performance of FedElim ($C > 0$)

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- Stops in finite time w.p.1
- Error probability $\leq \delta$
- With prob. $1 - \delta$,
 - Total no. of arm pulls (T_{FedElim}) satisfies $T_{\text{FedElim}} \leq \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, 2T_k\} \leq 2\tau$

Performance of FedElim ($C > 0$)

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- Stops in finite time w.p.1
- Error probability $\leq \delta$
- With prob. $1 - \delta$,
 - Total no. of arm pulls (T_{FedElim}) satisfies $T_{\text{FedElim}} \leq \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, 2T_k\} \leq 2\tau$
 - Comm cost ($C_{\text{FedElim}}^{\text{comm}}$) satisfies $C_{\text{FedElim}}^{\text{comm}} \leq C \times M \times \sum_{k=1}^K \left\lceil \frac{\ln T_k}{\ln 2} \right\rceil \leq \tau^*$

Performance of FedElim ($C > 0$)

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- Stops in finite time w.p.1
- Error probability $\leq \delta$
- With prob. $1 - \delta$,
 - Total no. of arm pulls (T_{FedElim}) satisfies $T_{\text{FedElim}} \leq \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, 2T_k\} \leq 2\tau$
 - Comm cost ($c_{\text{FedElim}}^{\text{comm}}$) satisfies $c_{\text{FedElim}}^{\text{comm}} \leq C \times M \times \sum_{k=1}^K \left\lceil \frac{\ln T_k}{\ln 2} \right\rceil \leq \tau^*$

* for sufficiently small δ

Performance of FedElim ($C > 0$)

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- Stops in finite time w.p.1
- Error probability $\leq \delta$
- With prob. $1 - \delta$,
 - Total no. of arm pulls (T_{FedElim}) satisfies $T_{\text{FedElim}} \leq \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, 2T_k\} \leq 2\tau$
 - Comm cost ($C_{\text{FedElim}}^{\text{comm}}$) satisfies $C_{\text{FedElim}}^{\text{comm}} \leq C \times M \times \sum_{k=1}^K \left\lceil \frac{\ln T_k}{\ln 2} \right\rceil \leq \tau^*$
 - $T_{\text{FedElim}} + C_{\text{FedElim}}^{\text{comm}} \leq 3\tau$

* for sufficiently small δ

Numerical Results

Synthetic Gaussian Data – 1/3

$$\mu = \begin{bmatrix} 0.9 & 0.1 & 0.1 \\ 0.1 & 0.9 & 0.1 \\ 0.1 & 0.1 & 0.9 \\ 0.5 & 0.5 & 0.5 \end{bmatrix}$$

Arms

Clients


Local best arm of client 1 = 1

Local best arm of client 2 = 2

Local best arm of client 3 = 3

Global best arm = 4

Synthetic Gaussian Data – 1/3




$$\mu = \begin{bmatrix} 0.9 & 0.1 & 0.1 \\ 0.1 & 0.9 & 0.1 \\ 0.1 & 0.1 & 0.9 \\ 0.5 & 0.5 & 0.5 \end{bmatrix}$$

Arms

Local best arm of client 1 = 1
Local best arm of client 2 = 2
Local best arm of client 3 = 3
Global best arm = 4

Synthetic Gaussian Data – 1/3



Length of blue bar $\leq T$

$$\mu = \begin{bmatrix} 0.9 & 0.1 & 0.1 \\ 0.1 & 0.9 & 0.1 \\ 0.1 & 0.1 & 0.9 \\ 0.5 & 0.5 & 0.5 \end{bmatrix}$$

Clients


Local best arm of client 1 = 1

Local best arm of client 2 = 2

Local best arm of client 3 = 3

Global best arm = 4

Synthetic Gaussian Data – 1/3



$$\mu = \begin{bmatrix} 0.9 & 0.1 & 0.1 \\ 0.1 & 0.9 & 0.1 \\ 0.1 & 0.1 & 0.9 \\ 0.5 & 0.5 & 0.5 \end{bmatrix}$$


Arms

Local best arm of client 1 = 1
Local best arm of client 2 = 2
Local best arm of client 3 = 3
Global best arm = 4

Length of blue bar $\leq T$

Length of yellow bar $\leq 2T$

Synthetic Gaussian Data – 1/3



$$\mu = \begin{bmatrix} 0.9 & 0.1 & 0.1 \\ 0.1 & 0.9 & 0.1 \\ 0.1 & 0.1 & 0.9 \\ 0.5 & 0.5 & 0.5 \end{bmatrix}$$

Arms


Local best arm of client 1 = 1
Local best arm of client 2 = 2
Local best arm of client 3 = 3
Global best arm = 4

Length of blue bar $\leq T$

Length of yellow bar $\leq 2T$

Length of any bar $\leq 3T$

Synthetic Gaussian Data – 2/3




$$\mu = \begin{bmatrix} 0.9 & 0.1 & 0.1 \\ 0.1 & 0.9 & 0.1 \\ 0.1 & 0.1 & 0.9 \\ 0.5 & 0.5 & 0.5 \end{bmatrix}$$

Arms

Local best arm of client 1 = 1
Local best arm of client 2 = 2
Local best arm of client 3 = 3
Global best arm = 4

Synthetic Gaussian Data – 3/3



$$\mu = \begin{bmatrix} 0.9 & 0.1 & 0.1 \\ 0.1 & 0.9 & 0.1 \\ 0.1 & 0.1 & 0.9 \\ 0.5 & 0.5 & 0.5 \end{bmatrix}$$

Arms

Clients


Local best arm of client 1 = 1

Local best arm of client 2 = 2

Local best arm of client 3 = 3

Global best arm = 4

Synthetic Gaussian Data – 3/3



FedElim operates at a “sweet spot”


$$\mu = \begin{bmatrix} 0.9 & 0.1 & 0.1 \\ 0.1 & 0.9 & 0.1 \\ 0.1 & 0.1 & 0.9 \\ 0.5 & 0.5 & 0.5 \end{bmatrix}$$

- Arms
- Local best arm of client 1 = 1
 - Local best arm of client 2 = 2
 - Local best arm of client 3 = 3
 - Global best arm = 4

$$C = 10$$

$$T_{\text{arm}} = \text{no. of pulls} + 10 \times t$$


$$T_k = 1000 \text{ (depends on } \delta)$$



$$C = 10$$

$$T_{\text{arm}} = \text{no. of pulls} + 10 \times t$$



$$T_k = 1000 \text{ (depends on } \delta)$$



$$C = 10$$

$$T_{\text{arm}} = \text{no. of pulls} + 10 \times t$$





$$T_k = 1000 \text{ (depends on } \delta)$$



$$C = 10$$

$$T_{\text{arm}} = \text{no. of pulls} + 10 \times t$$



$$T_k = 1000 \text{ (depends on } \delta)$$



$$C = 10$$

$$T_{\text{arm}} = \text{no. of pulls} + 10 \times t$$



$$T_k = 1000 \text{ (depends on } \delta)$$



$$C = 10$$

$$T_{\text{arm}} = \text{no. of pulls} + 10 \times t$$



$$T_k = 1000 \text{ (depends on } \delta)$$




$$C = 10$$

$$T_{\text{arm}} = \text{no. of pulls} + 10 \times t$$

$$T_k = 1000 \text{ (depends on } \delta)$$




More Datasets – 1/3



MovieLens dataset (Cantador et al. (2011))

38 countries (clients), 20 genres (arms)


2.04M movie ratings



Bernoulli dataset from Mitra, Hassani, and Pappas (2021)

$$\boldsymbol{\mu} = \begin{bmatrix} 0.9 & 0.85 & 0.1 \\ 0.85 & 0.8 & 0.3 \\ 0.7 & 0.6 & 0.5 \end{bmatrix}$$


More Datasets – 2/3



MovieLens dataset ([Cantador et al. \(2011\)](#))

38 countries (clients), 20 genres (arms)


2.04M movie ratings



Bernoulli dataset from [Mitra, Hassani, and Pappas \(2021\)](#)

$$\boldsymbol{\mu} = \begin{bmatrix} 0.9 & 0.85 & 0.1 \\ 0.85 & 0.8 & 0.3 \\ 0.7 & 0.6 & 0.5 \end{bmatrix}$$


More Datasets – 3/3



MovieLens dataset ([Cantador et al. \(2011\)](#))

38 countries (clients), 20 genres (arms)

2.04M movie ratings




Bernoulli dataset from [Mitra, Hassani, and Pappas \(2021\)](#)

$$\boldsymbol{\mu} = \begin{bmatrix} 0.9 & 0.85 & 0.1 \\ 0.85 & 0.8 & 0.3 \\ 0.7 & 0.6 & 0.5 \end{bmatrix}$$

Comparison with Per(H) and SupExp

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$


- $\tau_{\text{Per}(H)} \leq \sum_{k=1}^K \sum_{m=1}^M \max \left\{ T_{k,m}, \left\lceil \frac{T_k}{H} \right\rceil H \right\} = O\left(\tau + (H \times M \times K)\right)$
- $c_{\text{Per}(H)}^{\text{comm}} \leq C \times M \times \sum_{k=1}^K \left\lceil \frac{T_k}{H} \right\rceil = O\left(C \times \frac{\tau}{H} + C \times M \times K\right)$



Comparison with Per(H) and SupExp

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- $\tau_{\text{Per}(H)} \leq \sum_{k=1}^K \sum_{m=1}^M \max \left\{ T_{k,m}, \left\lceil \frac{T_k}{H} \right\rceil H \right\} = O\left(\tau + (H \times M \times K)\right)$
- $c_{\text{Per}(H)}^{\text{comm}} \leq C \times M \times \sum_{k=1}^K \left\lceil \frac{T_k}{H} \right\rceil = O\left(C \times \frac{\tau}{H} + C \times M \times K\right)$




$$H_{\text{opt}} = \sqrt{\frac{C \cdot \tau}{M \cdot K}}$$

Comparison with $\text{Per}(H)$ and SupExp

$$\tau = \sum_{m=1}^M \sum_{k=1}^K \max\{T_{k,m}, T_k\}$$

- $T_{\text{Per}(H)} \leq \sum_{k=1}^K \sum_{m=1}^M \max \left\{ T_{k,m}, \left\lceil \frac{T_k}{H} \right\rceil H \right\} = O\left(\tau + (H \times M \times K)\right)$
- $C_{\text{Per}(H)}^{\text{comm}} \leq C \times M \times \sum_{k=1}^K \left\lceil \frac{T_k}{H} \right\rceil = O\left(C \times \frac{\tau}{H} + C \times M \times K\right)$



$$H_{\text{opt}} = \sqrt{\frac{C \cdot \tau}{M \cdot K}}$$

Scheme	No. of arm pulls	Comm. cost	Total cost
$\text{Per}(H)$	$O(\tau)$	$O(CT/H)$	$O(\tau + CT/H)$
FedElim^*	2τ	$O(C \log(\tau))$	3τ
SupExp	$O(\tau^2)$	$O(C \log\log(\tau))$	$O(\tau^2)$

High-probability upper bounds

Summary and Future Directions

Summary and Future Directions

- For all δ small, $P(T_{\text{FedElim}} \lesssim 3T_{\text{FedElim0}}) \geq 1 - \delta$

Summary and Future Directions

- For all δ small, $P(T_{\text{FedElim}} \lesssim 3T_{\text{FedElim0}}) \geq 1 - \delta$
- FedElim = sweet spot between Per(H) and SupExp

Summary and Future Directions

- For all δ small, $P(T_{\text{FedElim}} \lesssim 3T_{\text{FedElim0}}) \geq 1 - \delta$
- FedElim = sweet spot between Per(H) and SupExp
- FedElim \approx Per(H_{opt})

Summary and Future Directions

- For all δ small, $P(T_{\text{FedElim}} \lesssim 3T_{\text{FedElim0}}) \geq 1 - \delta$
- FedElim = sweet spot between $\text{Per}(H)$ and SupExp
- $\text{FedElim} \approx \text{Per}(H_{\text{opt}})$
- Future directions:
 - High-probability upper bound on total cost —> upper bound on expected total cost
 - Rate-limited uplink communication
 - Quantisation of uplink information

Summary and Future Directions

- For all δ small, $P(T_{\text{FedElim}} \lesssim 3T_{\text{FedElim0}}) \geq 1 - \delta$
- FedElim = sweet spot between $\text{Per}(H)$ and SupExp
- $\text{FedElim} \approx \text{Per}(H_{\text{opt}})$
- Future directions:
 - High-probability upper bound on total cost —> upper bound on expected total cost
 - Rate-limited uplink communication
 - Quantisation of uplink information

Thank You!

More details: arXiv:2208.09215

References

- Shi, C., Shen, C., & Yang, J. (2021). Federated multi-armed bandits with personalization. In International Conference on Artificial Intelligence and Statistics (pp. 2917–2925). PMLR.
- Mitra, A., Hassani, H., & Pappas, G. (2021). Exploiting heterogeneity in robust federated best-arm identification. arXiv preprint arXiv:2109.05700.
- Tao, C., Zhang, Q., & Zhou, Y. (2019, November). Collaborative learning with limited interaction: Tight bounds for distributed exploration in multi-armed bandits. In 2019 IEEE 60th Annual Symposium on Foundations of Computer Science (FOCS) (pp. 126–146). IEEE.
- Hillel, E., Karnin, Z. S., Koren, T., Lempel, R., & Somekh, O. (2013). Distributed exploration in multi-armed bandits. Advances in Neural Information Processing Systems, 26.
- Cantador, I., Brusilovsky, P., & Kuflik, T. (2011, October). Second workshop on information heterogeneity and fusion in recommender systems (HetRec2011). In Proceedings of the fifth ACM conference on Recommender systems (pp. 387–388).