

Specification

Nominal Voltage	12V	
Nominal Capacity(20HR)	35.0AH	
Dimensions	Length	195±2mm (7.68 inches)
	Width	130±2mm (5.12 inches)
	Container Height	164±2mm (6.46 inches)
	Total Height (with Terminal)	167±2mm (6.57 inches)
Approx Weight	Approx 10.2 kg (22.5lbs)	
Terminal	Copper Insert	
Container Material	ABS	
Rated Capacity	35.0 AH/1.75A	(20hr , 1.80V/cell, 25°C/77°F)
	32.2 AH/3.22A	(10hr, 1.80V/cell, 25°C/77°F)
	28.9 AH/5.79A	(5hr, 1.75V/cell, 25°C/77°F)
	25.2 AH/8.39A	(3hr, 1.75V/cell, 25°C/77°F)
	20.8 AH/20.8A	(1hr, 1.60V/cell, 25°C/77°F)
Max. Discharge Current	525A (5s)	
Internal Resistance	Approx 11mΩ	
Operating Temp. Range	Discharge : -15~50°C (5~122°F)	
	Charge : 0~40°C (32~104°F)	
	Storage : -15~40°C (5~104°F)	
Nominal Operating Temp. Range	25±3°C (77±5°F)	
Cycle Use	Initial Charging Current less than 10.5A. Voltage 14.4V~15.0V at 25°C(77°F)Temp. Coefficient -30mV/°C	
Standby Use	No limit on Initial Charging Current Voltage 13.5V~13.8V at 25°C(77°F)Temp. Coefficient -20mV/°C	
Capacity affected by Temperature	40°C (104°F)	103%
	25°C (77°F)	100%
	0°C (32°F)	86%
Self Discharge	Duracell® Ultra batteries may be stored for up to 6 months at 25°C (77°F) and then a freshening charge is required. For higher temperatures the time interval will be shorter.	



Applications

- ◆ All purpose
- ◆ Uninterruptable Power Supply (UPS)
- ◆ Electric Power System (EPS)
- ◆ Emergency backup power supply
- ◆ Emergency light
- ◆ Railway signal
- ◆ Aircraft signal
- ◆ Alarm and security system
- ◆ Electronic apparatus and equipment
- ◆ Communication power supply
- ◆ DC power supply
- ◆ Auto control system



Constant Current Discharge (Amperes) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	54.1	38.0	32.3	29.0	24.2	19.1	16.0	10.0	7.57	6.25	5.35	4.64	3.71	3.12	1.73
1.80V/cell	67.2	46.8	38.8	33.6	27.3	21.1	17.4	10.8	8.11	6.66	5.63	4.85	3.85	3.22	1.75
1.75V/cell	83.2	54.6	43.5	37.5	29.4	22.7	18.4	11.2	8.39	6.83	5.79	4.99	3.96	3.30	1.77
1.70V/cell	98.5	61.7	48.4	40.8	31.5	23.9	19.3	11.6	8.61	6.99	5.92	5.10	4.02	3.35	1.80
1.65V/cell	109.9	67.4	52.2	44.0	33.3	25.0	20.0	12.0	8.86	7.18	6.06	5.20	4.09	3.40	1.82
1.60V/cell	122.5	73.5	56.4	46.6	35.1	26.1	20.8	12.3	9.08	7.36	6.19	5.32	4.17	3.45	1.83

Constant Power Discharge (Watts) at 25 °C (77°F)

F.V/Time	5min	10min	15min	20min	30min	45min	1h	2h	3h	4h	5h	6h	8h	10h	20h
1.85V/cell	100.8	71.1	60.8	54.6	46.0	36.7	30.8	19.4	14.8	12.2	10.5	9.12	7.33	6.18	3.43
1.80V/cell	121.6	85.8	71.7	62.9	51.5	40.2	33.3	20.8	15.7	12.9	11.0	9.49	7.59	6.36	3.46
1.75V/cell	148.9	99.0	79.8	69.5	55.0	43.0	35.2	21.6	16.2	13.2	11.3	9.74	7.78	6.51	3.49
1.70V/cell	174.0	110.5	87.9	75.2	58.6	45.0	36.6	22.3	16.6	13.5	11.5	9.94	7.89	6.61	3.55
1.65V/cell	191.3	118.8	93.6	80.2	61.5	46.8	37.8	23.0	17.0	13.8	11.7	10.1	8.00	6.68	3.60
1.60V/cell	209.4	127.7	99.4	83.6	64.1	48.4	39.1	23.5	17.3	14.1	11.9	10.3	8.15	6.79	3.61




DURACELL® ULTRA

General Purpose DURA12-35C


Dimensions

■ Copper Insert


Unit: mm




Discharge Characteristics




Float Charging Characteristics




Temperature Effects in Relation to Battery Capacity




Effect of Temperature on Long Term Float Life



Cycle Life in Relation to Depth of Discharge



Self Discharge Characteristics



A No supplementary charge required
(Carry out supplementary charge before use if 100% capacity is required.)

B Supplementary charge required before use. Optional charging way as below:
1. Charged for above 3 days at limited current 0.25CA and constant voltage 2.25V/cell.
2. Charged for above 20 hours at limited current 0.25CA and constant voltage 2.45V/cell.
3. Charged for 8-10 hours at limited current 0.05CA.

C Supplementary charge may often fail to recover the capacity.
The battery should never be left standing till this is reached.

www.batteriesplus.com

Batteries + Bulbs

© 2014 DURACELL, a division of the Gillette Company, Bethel, CT 06801. DURACELL is a registered trademark of the Gillette Company, used under license. All rights reserved.
The information contained on this specification is generally descriptive only and is not intended to make or imply any representation guarantee or warranty with respect to any cells and batteries. Cell and battery design/ specification are subject to modification without notice.