Bootstrap

Practice Solution

Ans

HTML Code :

```
<!DOCTYPE html>
<html lang="en">
<head>
<meta charset="UTF-8">
<meta http-equiv="X-UA-Compatible" content="IE=edge">
<meta name="viewport" content="width=device-width,
initial-scale=1.0">
<link rel="stylesheet"
href="https://cdn.jsdelivr.net/npm/bootstrap@5.3.0/dist/css/boo
tstrap.min.css">
<title>Pricing Page</title>
</head>
<body>
<h1 class="text-center">Pricing</h1>
<p class="text-center">Please checkout our most effective
payment models</p>

<div class="row text-center justify-content-evenly">
<div class="card col-sm-5 col-md-3 mb-3 me-3">
<div class="card-header">
<h4>Free</h4>
```

```
</div>
<div class="card-body">
<h1 class="card-title">$0 / mo</h1>
<ul class="list-unstyled">
<li>10 users included</li>
<li>2 GB of storage</li>
<li>Email support</li>
</ul>
<button href="#" class="btn btn-outline-primary">Sign up for
free</button>
</div>
</div>

<div class="card col-sm-5 col-md-3 mb-3 me-3">
<div class="card-header">
<h4>Pro</h4>
</div>
<div class="card-body">
<h1 class="card-title">$15 / mo</h1>
<ul class="list-unstyled">
<li>20 users included</li>
<li>10 GB of storage</li>
<li>Priority email support</li>
</ul>
<button href="#" class="btn btn-primary">Get started</button>
</div>
</div>
```

```
<div class="card col-sm-10 col-md-3 mb-3 me-3">
<div class="card-header">
<h4>Enterprise</h4>
</div>
<div class="card-body">
<h1 class="card-title">$29 / mo</h1>
<ul class="list-unstyled">
<li>30 users included</li>
<li>15 GB of storage</li>
<li>Phone & email support</li>
</ul>
<button href="#" class="btn btn-primary">Contact us</button>
</div>
</div>
</div>
</body>
</html>
```

github.com/apnacollege