HTML

 —— - Paragraph

<h1> </h1> - Heading

  - Bold

Nesting = Nested Tags

When we use another element b/w another tag.

Standard Code [Boilerplate]

Root —— <!Doctype html>
<html>
metadata —— <head>
<title> </title>
</head>
<body>
</body>
</html>

(!) — shortcut

Indentation
↳ Spacing

Scanned by TapScanner

Classes & Bst 9599299633

```
<ul>
  <li>        </li>

</ul>
```

To make a unordered list

Anchor Tag

Hyper Text reference

```
<a> href = " link "
</a>
```

Image Tag

```
<img src = " loc. " alt = " " >
```

Comment

```
<!-- >
```

Scanned by TapScanner

Block Elements
→ Takes up full width available
→ Starts with new line

Heading Element
Paragraph Element

Inline Elements
→ Take up only necessary width
→ Don't start from new line

Anchor Tag
Image Tag

Div Element

⇒ (Block Element)
⇒

⇒ It is used to group diff. elements.

Span Element

⇒ [Inline Element].
⇒

⇒ It is used to group diff element.

<hr> tag Divider

Superscript - <sup>
Subscript - <sub>

Scanned by TapScanner

9990799633 Specialised in Economics & Bst 9599299633

Semantic Markup

1. <Header> Tag - Top Heading
2. <Main> Tag - It contain content
3. <Footer> Tag - It is at the end of the page
4. <nav> Tag - It is used for navigation
5. <article> Tag
6. <Section> Tag
7. <aside> Tag

HTML Entities

1. Starts with (&) ends with (;)
2. Space -
3. lesser than - <
4. greater than >
5. ♥
6. " - " "
7. & - &

Scanned by TapScanner

Table

1. <tr> - Rows
2. <td> - Data
3. <th> - Table header
4. <thead>
5. <tbody>
6. <tfoot>

7. rowspan
8. colspan

Forms

<form action = "/action.php" >

- input type = "text" placeholder = "enter" id = "username" name = "username" />

To create box for message/ feedback, etc.

<textarea name = "message" id = "message" cols "30" rows = "4" ></textarea>

<Select name = "profession" & id = "prof" >
<option value " " > </option>

Scanned by TapScanner

★ Action Attribute → It is used to tell where collected data will be sent.

```
< form action = "/action.php" >
< form action = "/action" >
```

Input Element (Checkbox)

```
<input type = "checkbox" name = "age" id = "age" />
< label for = "age" > I am 18+ < /label >
```

Id

(Radio Button) Input Element

```
< input type = "radio" name = "sex" id = "Male" > value = "M"
    < label for = "Male" > Male < /label >
< input type = "radio" > name = "sex" id = "female" >
    < label for = "Female" > Female < /label > value "F"
```

Value of name should be same.

Scanned by TapScanner

Range (Input Element)

```
<label for="volume"> Volume </label>
<input type="range" min="x" max="y" name="vol"/>
                                    id="volume" >
```

Select (Input Element) (Dropdown)

```
<select name="profession" id="profession">
    <option value="Stu"> student </option>
    <option value="Dev."> Developer </option>
</select>
```

Scanned by TapScanner

Deepanshu Makkar Classes
9990799633 Specialised in Economics & Bst. 9599299633

Textarea

< label for="feedback"> Enter your feedback </label>

< textarea id="feedback" > </feedback>

To change row — we use rows = " "
column — we use cols = " "

Scanned by TapScanner

CSS [Cascading Style Sheets]

§ Basic Format

h1 { color : red ; }

selector — property — value

1. # Inline Style [It isn't suitable for large websites]

<h1 style = "color : red" > Abna </h1>

2. # < Style > </ Style > tag [It isn't suitable for more than 1 webpage]

In < head > tag

< style >
    § h1 { color : red ;
        background color : Orange ; }
</style>

Scanned by TapScanner

Deepanshu Makkar Classes
9990799633 Specialised in Economics & Bst 9599299633

3 # External Stylesheet:

Linking HTML with CSS File

```
<head>
    <link rel="stylesheet" href="style.css">
</head>
```

rel → relation
href → File location

Color System | color: rgb(255, 0, 140)
R G B

1. rgb (R, G, B) → R, G, B - 0 to 255 values

2. hex or hexatecimal (Base 16) code

White ← #FFFFFF → color: #000000; - Black

Red | Green | Blue

Scanned by TapScanner

Text properties

text-align: left / start;

text-align: right / end;

font weight

font-weight: normal // 400;

font-weight: bolder;

font-weight: lighter;

} parent

text decoration

text-decoration: underline; / overline; / line-through;

underline → abc

overline → abc

line-through → abc

color

style

wavy double underline double dotted

text-decoration-color: teal;

Scanned by TapScanner

Deepanshu Makkar Classes
9990799633 Specialised in Economics & Bst 9599299633

line height [to increase the gap b/w 2 line]

line-height: 2.5/0.5;

letter spacing [control horizontal gap b/w character]

letter-spacing : 10px; / normal;

Font Size units in CSS

(fixed value) Absolute		Relative (	
96px = 1 inch	px	%	px = not suitable for responsive website
72pt = 1 inch	pt	em	
	pc	rem	

Scanned by TapScanner

font-family [font type]

Uppercase all letters

```
text-transform: uppercase;
```

text-decoration

text-decoration: teal double underline;

To style the link

In CSS.

We use

```
* → a { }
```

Universal Selector

[*]

Asterisk

ID Selector

```
# id { }
```

Code

Class Selector

```
.a { }
```

Code

```
<h class='a'>
<button class='a'>
<p class='a'>
```

Scanned by TapScanner

9990799633 Punjabi Makkar Classes Specialised in Economics & Bst 9599299633

Descendant Selector

```
div p {
}
```

div is Outer Element
p is Inner "

Code

Adjacent Sibling Combinator

```
p + h3 {
}
```

Code

Attribute Selector

```
input[attr = "value"] {
}
```

[type = "text"]

Code

Scanned by TapScanner

Pseudo Class

element: pseudo { } ← Code

hover / active / checked / nth of type

Pseudo Element

element:: pseudo { } ← Code

first letter / first line / selection

Selector Specificity

1. id > class > element
2. more selector > less selector
3. If specificity same ⇒ cascading

id	class, attribut, pseudo class	element, pseudo element

Scanned by TapScanner

9599299633 Specialised in Economics & Bst

Box Model

- Height
- Width
- Border
- Padding
- Margin

```
div {
    height : 100px;
    width : 300px;
    border width : 5px;
    border style : dotted;
    border color : orange;

    border : 2px solid orange; }
```

element — div

Code

Shorthand

Border Sides

- border - left / right / top / bottom

Border Radius

```
div { border radius 100px; }
```

— Code

Scanned by TapScanner

If width and height is same, then border radius: 50% will form a Circle on Webpage.

Padding Property

div { padding left/ right/ top/ bottom : 50px ;

Sherthand

1. top & bottom / left & right
div { padding : 1px 2px ; }

2. top / left & right / bottom
div { padding : 10px 20px 10px ; }

3. top / right / bottom / left

div { padding : 10px 10px 10px 10px ; }

Scanned by TapScanner

9990799633 Deepanshu Makkar Classes Specialised in Economics & Bst 9999299633

Display Properties

[display: inline / block ;]

[display: inline - block;]

↓

To make element inline.

CSS

They will hold properties like block element

Relative Units

(em) — To increase / decrease related to parental element

OR

Rel. to elemental properties

Rem — Root element

Scanned by TapScanner

Deepanshu Makkar Classes
Specialised in Economics & Bst.
9990799633 9599299633

To appear text in center. (margin: 0, auto;)
Code

visibleness

Alpha Channel [Sets the opacity for a color]

rgba (255, 0, 255, 0.3) [Alpha value varies from 0 to 1]

Red / Blue / Green / ∝ (Alpha)

Opacity [Set opacity for the element]

CSS Transition

div { transition : 2s } — Code

div { transition delay : 2s }

Delay

div { transition : 1s 1s }

Transition / Shorthand Code

CSS Transform { transform : rotate(10deg); scale (1.5); translateX (50px); } Shorthand

i) Rotate
transform: rotate (45 deg);

ii) Scale
transform : scale(1.5);

iii) Translate
transform : translate (50px 50px);
x / y

iv) Skew
transform : skew(30 deg);

Scanned by TapScanner

Box Shadow

y-offset

div { box-shadow : 2px, 2px, 10px green; }

x-offset Blur Color

Background Image

div { background-image: url(File location); }

Most commonly used

background-size : contain / cover / auto; }

contain: Crop✗ Scale✗ repeat✓

cover: Crop✓ Scale✗

auto: Stretch

Scanned by TapScanner

Card Hover Effect

```
.card:hover { box-shadow: 0px 8px 18px green; }
```

Position Property (div { position : Static / fixed / Absolute / Relative; })

1. Static	2. Relative	3 Absolute
No Change in Position	Change in position with respect to its position	Change in position with respect to parental element or inital cont: block
	Space is created for Relative Block	No Space for Absolute Block is created

4. Fixed
Change in position with respect to inital containing block.

Scanned by TapScanner

Deepanshu Makkar Classes
Specialised in Economics & Bst.
9990799633
9599299633

Flexbox

display: flex; → Code (Row)

flex-direction: column / row / reverse row / reverse-column;

Justify Content (main-axis ki direction ma)

justify-content: flex-start / flex-end / center;

justify-content: space-between / space-around / space-evenly;

(Between) (Left, Right)

Flex Wrap

flex-wrap: nowrap / wrap / wrap-reverse;

Default — Cross axis ki direction ma

Scanned by TapScanner

Deepanshu Makkar Classes
9990799633 Specialised in Economics & Bst 9599299633

Align Items [Cross - axis ki direction ma]

↳ align - items : flex - start / flex - end / center / baseline ;

Align Content

↳ align - content : flex - start / flex - end / center ,
space - between / space - around / evenly ;
baseline ;

Condition :
display
flex - direction
justify - content
flex - wrap

Scanned by TapScanner

Flex Shorthand

flex - grow | flex - shrink | flex - basis ;

grow | flex - basis ;

grow ;

flex - basis ;

Scanned by TapScanner