TI Spins Motors

DRV830x EVM Hardware Reference Guide

Version 2.0 – June 2012 *Motor Solutions*

Fig 1: DRV830x EVM with controlCARD

Abstract

The Low Voltage, High Current Motor Drive EVM (DRV8301, DRV8302 , Figure 1), provides a great way to learn and experiment with digital control of sub 60 volt brushless motors to increase efficiency of operation. The board is available in two configurations, the DRV8301 or the DRV8302. This document goes over the typical kit contents and hardware details, and explains the functions and locations of jumpers and connectors present on the board. This document supersedes all the documents available for the kit.

WARNING

This EVM is meant to be operated in a lab environment only and is not considered by TI to be a finished end-product fit for general consumer use

This EVM must be used only by qualified engineers and technicians familiar with risks associated with handling high voltage electrical and mechanical components, systems and subsystems.

This equipment operates at voltages and currents that can result in electrical shock, fire hazard and/or personal injury if not properly handled or applied. Equipment must be used with necessary caution and appropriate safeguards employed to avoid personal injury or property damage.

It is the user's responsibility to confirm that the voltages and isolation requirements are identified and understood, prior to energizing the board and or simulation. When energized, the EVM or components connected to the EVM should not be touched.

Table of Contents

Getting Familiar with the Kit

Kit Contents

The DRV830x EVM is usually available packaged as a full solution kit:

- MCU controlCARD
- DRV830x EVM board with slot for the controlCARD
- USB Cable
- USB/DVD with CCStudio IDE, GUI, and all documentation and code
- Some versions ship with a tabletop 24V 2.5A power supply and 24V Motor with built-in Hall Sensors and Encoder

The DRV830x EVM board can accept many of the TI MCU controlCARDs, but we recommend using the versions that ship with the kits that include the JTAG emulator, USB to serial, and isolation on the controlCARD. All controlCARDs are shipped with a software example pre-programmed into flash that will work with the GUI included on the USB/DVD. It is recommended to always check for any updates to the GUI executable and MCU program. If you aren't sure what is programmed on the controlCARD it is always best to re-program.

Kit Features:

The kit has the following features

- **Three-Phase Power Stage, DRV830x** capable of driving 3-phase brushless DC motors and Permanent Magnet Synchronous Motors.
  - 60V DC max input voltage
  - 60A peak output current per phase
  - Up to 200khz driver switching frequency
  - Integrated 1A buck converter to provide logic and analog power
  - Dual integrated current sense amplifiers
- Isolated CAN and SPI communication (will only work if MCU supports and SW is enabled)
- MCU controlCARD with on-board isolated JTAG emulation and serial port
- JTAG connector for external emulators
- Quadrature Encoder Interface and Hall Sensor Interface available for speed and position measurement (only if MCU supports and SW is enabled)
- High precision low-side current sensing using integrated current sense amplifiers in the DRV830x (2-ch) or external 3-ch (Starting with DRV8301 RevD)
- Over current protection on the inverter stage by DRV830x
- Hardware Developer's Package that includes schematics and bill of materials
- Closed-loop digital control with feedback using the MCU's on-chip PWM and ADC peripherals

Warning: about low switching frequencies on the DRV830x

When the DRV830x runs at a low switching frequency (e.g. less than 20 kHz with 100 nF bootstrap capacitor), the bootstrap capacitor voltage might not be able to maintain a proper voltage level for the high-side gate driver. A bootstrap capacitor under voltage protection circuit (BST_UVP) will start under this circumstance to prevent the potential failure of the high-side MOSFET. In this circumstance, both the FAULT and OTW pins should pull low and the device should self-protect itself. The motor's inductance and the inverter's bootstrap capacitance will allow the DRV830x to run efficiently until approximately 10 kHz (with margin). Setting the PWM switching frequency below 10 kHz may cause issues on the inverter output and is not recommended. Please reference the datasheet.

Most software examples available with the DRV8312 use 20 KHz PWM switching.

Hardware Overview

The example projects made available with the kit may be done with a supplied 24V power supply, but many of the examples will work with an externally supplied laboratory power supply of a different voltage or current limit. The DRV8312 EVM has all the power and control blocks that constitute a typical motor drive system for a BLDC system: Communications + Control + Feedback + Feedforward + Drive

Macro Blocks

The motor control board is separated into functional groups that enable a complete motor drive system, these are referred to as macro blocks. Following is a list of the macro blocks present on the board and their functions:

- controlCARD socket – Socket for a controlCARD (preferably using built-in emulation).
- DC Bus Connection
    - "PVDD/GND" Terminals – Connect an external 8-60V DC lab supply here making sure to observe correct polarity..
- DRV830x – This module includes either the DRV8301 or DRV8302 Three Phase Pre-Driver as well as all of the necessary external passive components.
- Current Sense – Low-side shunt current sensing on each half-bridge.
- Quadrature Encoder Connections – Connections are available for an optional shaft encoder to interface to the MCU's QEP peripheral.
- Hall Effect Sensor Connections – Connections are available for optional Hall Effect Sensors.

Fig 2, illustrates the position of these macro blocks on the board. The use of a macro block approach, for different power stages enables easy debug and testing of one stage at a time. All the PWM's and ADC signals which are the actuation and sense signals have designated test points on the board, which makes it easy for an application developer to try out new algorithms and strategies.



Fig2: DRV830x-EVM Board Macros

Powering the Board

The board is separated into two power domains*, the low voltage Controller Power domain that powers the controller and the logic circuit present on the board, and the medium voltage power delivery line that is used to carry the medium voltage and current like the DC power for the Inverter also referred to as DC Bus.

1) **Controller Power** comprises of the 5V and 3.3V that the board uses to power the controller and the logic and sensing circuit present on the board. This power is regulated from the DC bus by the DRV830x integrated buck converter.

2) **DC Bus Power** is the medium voltage line – up to 60V - that provides the voltage to the inverter stage to generate 3 phases to control the motor

Note: Do not apply power to board before you have verified these settings!

The kit ships with the control card inserted and the jumper and switch settings pre done for connecting with the GUI. However the user must ensure that these settings are valid on the board.

1. Make sure nothing is connected to the board, and no power is being supplied to the board.
2. Insert the Control card into the controlCARD connector if not already populated.
3. Make sure the following jumpers & connector settings are valid i.e.
    a. JP2 is installed
4. Make sure that the switches for the controlCARD are set as described in the specific document for each controlCARD (they handle where power is supplied, how it boots, etc)
5. Connect a USB cable from computer to USB connector on control card
6. Connect the motor you want to spin to the “MOTOR” terminal block as shown below. The order is not important. If ground is available with your motor it should also be used.



Fig3: DRV830x-HC-EVM Motor Connections

7. Connect an 8-60V DC power supply to the PVDD and GND terminals.

Hardware Resource Mapping

Resource Allocation

Table 1 illustrates the major connections and feedback values that are being mapped to the MCU.

J1 Pin no.	GPIO	Signal Name	Function (DRV8301/DRV8302)
23	GPIO-00	PWM_AH	DRV830x Phase AH PWM input
73	GPIO-01	PWM_AL	DRV830x Phase AL PWM input
24	GPIO-02	PWM_BL	DRV830x Phase BH PWM input
74	GPIO-03	PWM_BL	DRV830x Phase BL PWM input
25	GPIO-04	PWM_CH	DRV830x Phase CH PWM input
75	GPIO-05	PWM_CL	DRV830x Phase CL PWM input
26	GPIO-06	DAC_PWM4	PWM DAC
76	GPIO-07	STOP	Push button input
28	GPIO-08	DAC_PWM3	PWM DAC
78	GPIO-09	START	Push button input
29	GPIO-10	DAC_PWM1	PWM DAC

79	GPIO-11	DAC_PWM2	PWM DAC
33	GPIO-12	LED-1	User LED
83	GPIO-13	OCTWn	Over-temperature warning
84	GPIO-14	FAULTn	Over-current fault
34	GPIO-15	LED-2	User LED
38	GPIO-16	SPI-SIMO	Isolated SPI Interface
88	GPIO-17	SPI-SOMI	Isolated SPI Interface
39	GPIO-18	SPI-CLK	Isolated SPI Interface
89	GPIO-19	SPI-STE	Isolated SPI Interface
40	GPIO-20	QEPA	Encoder A
90	GPIO-21	QEPB	Encoder B
41	GPIO-22	STATUS	User LED
91	GPIO-23	QEPI	Encoder Index
35	GPIO-24	SDI	SPI Data In/M_DC
85	GPIO-25	SDO	SPI Data Out/GAIN
36	GPIO-26	SCLK	SPI ClockDC_ADJ
86	GPIO-27	/SCS	/SCS/M_PWM
44	GPIO-30	CAN-RX	Isolated CAN Interface
94	GPIO-31	CAN-TX	Isolated CAN Interface
30	GPIO-40	CAP1	Hall Input 1
80	GPIO-41	CAP2	Hall Input 2
31	GPIO-42	CAP3	Hall Input 3
81	GPIO-43	DC-CAL	Short DC current sense amplifier inputs to ground, calibrate offset
59	ADC-A1	IA-FB	Current sense phase A

61	ADC-A2	I-TOTAL	DC Bus current sense
63	ADC-A3	IC-FB	Current sense phase C
67	ADC-A5	IC-FB	Current sense phase C
71	ADC-A7	ADC-Vhb2	Phase Voltage sense B
7	ADC-B0	TSI	Tach/Pot input
9	ADC-B1	IB-FB	Current sense phase B
11	ADC-B2	VDCBUS	DC Bus voltage sense
13	ADC-B3	IA-FB	Current sense phase A
15	ADC-B4	ADC-Vhb3	Phase Voltage sense C
17	ADC-B5	IB-FB	Current sense phase B
21	ADC-B7	ADC-Vhb1	Phase Voltage sense A

Table 1: GPIO and ADC resource allocation

Jumpers and Connectors

The Tables below show the various connections available on the board.

List of Connectors

Connector Reference	# of Pins	Name
J2	2	HEADER2x1
J4	5	HEADER5x1
J5	40	HEADER20x2
J6	5	HEADER5x1
J7	3	HEADER3x1

J8	5	HEADER5x1
J10	5	HEADER5x1
J11	4	TERM BLOCK HEADER 4x1
J12	2	HEADER2x1
J13	2	HEADER2x1
J20	10	HEADER5x2
J21	14	HEADER7x2
J23	2	HEADER2x1
J24	2	HEADER2x1
J25	2	TERM BLOCK HEADER 2X1
J26	2	TERM BLOCK HEADER 2X2

Table 2: List of Connectors

J2 (User Power Access)

Pin #	Signal
1	VCC_5V
2	GND

J4 (Optional Encoder)

Pin #	Signal
1	E1A
2	E1B
3	E1C
4	VCC_5V
5	GND

J6 (PWM DAC)

Pin #	Signal
1	DAC1
2	DAC2
3	DAC3
4	DAC4
5	GND

J7 (CAN)

Pin #	Signal
1	CAN-H
2	CAN-L
3	IGND

J8 (User SPI)

Pin #	Signal
1	iSD-O
2	iCLK-O
3	iSD-I
4	iGPIO
5	IGND

J10 (HALL Sensor)

Pin #	Signal
1	E2A
2	E2B
3	E2C
4	VCC_5V
5	GND

J11 (Motor)

Pin #	Signal
1	Phase A
2	Phase B
3	Phase C
4	GND

J12 (GPIO/SCI)

Pin #	Signal
1	GPIO-28
2	GPIO-29

J13 (User Power Access)

Pin #	Signal
1	VCC_3.3V
2	GND

J20 (DRV8301 SPI))

Pin #	Signal
1	NC
2	GND
3	NC
4	NC
5	SDO
6	NC
7	SCLK
8	SDI
9	/SCS
10	GND

J23 (Push Button)

Pin #	Signal
1	START
2	GND

J24 (Push Button)

Pin #	Signal
1	STOP
2	GND

J21 (External JTAG)

Pin #	Signal
1	TMS
2	TRSTn
3	TDI
4	GND
5	VCC_3.3V
6	NC
7	TDO
8	GND
9	TCK
10	GND
11	TCK
12	GND
13	EMU0
14	EMU1

J25 (Power Input)

Pin #	Signal
1	PVDD
2	PVDD

J26 (Power Input)

Pin #	Signal
1	GND
2	GND

Tables3-17 Individual Connector Pinouts

J5 (External Controller Access)

Pin #	Signal	Pin #	Signal
1	VCC_5V	2	GND
3	VCC_5V	4	GND
5	STATUS	6	EN_GATE
7	QEPA	8	QEPI
9	FAULTn	10	QEPB
11	CAP3	12	OCTWn
13	DC_CAL	14	CAP1
15	DAC_PWM1	16	CAP2
17	DAC_PWM3	18	DAC_PWM2
19	GND	20	GND
21	DACE_PWM4	22	PWM_CL
23	PWM_AL	24	PWM_BL
25	PWM_AH	26	PWM_CH
27	GND	28	PWM_BH
29	ADC-Vhb1	30	GND
31	ADC-Vhb2	32	ADC-Vhb3
33	IC-FB	34	VDCBUS
35	I_TOTAL	36	IB-FB
37	IA-FB	38	TSI
39	GND	40	GND

Table 18: J5 Pinout

Test Points

Test Point	Net Connection
TP1	VCC_5V
TP2	VCC_5V_R5
TP3	PWRGD
TP4	VCC_3.3V
TP5	REF_1.65V
TP6	PVDD
TP7	GND
TP8	GND
TP9	GND
TP10	GND
TP11	VCC_5V
TP12	SH_A
TP13	SH_B
TP14	SH_C
TP15	S02
TP16	IB-FB
TP17	IA-FB
TP18	U10_1
TP19	IC-FB
TP20	IGND
TP21	S01
TP22	U11_1
TP23	I-TOTAL

Jumpers

Reference	Function
JP2	VCC_5V to controlCARD
JP4	CAN termination

Table 20: Testpoints and Jumpers

SCHEMATIC DISCLAIMER AND WARNINGS

TI provides the DRV830x EVM schematic drawings to help users develop DRV30x & TI MCU based reference design products. Application safety, safety of the Medium Voltage DMC kit and design integrity of such reference designs are solely responsibility of the user. Any reference designs generated off these schematics must take into account necessary product safety design requirements, including interface components and load motors in order to avoid user risks including potential for fire hazard, electrical shock hazard and personal injury, including considerations for anticipated agency certification compliance requirements.

Such product safety design criteria shall include but not be limited to critical circuit creepages and clearances, component selection, ratings compatibility of controlled motor loads, and required protective means (ie output fusing) depending on the specific loads being controlled.

TI accepts no responsibility for design integrity of any reference designs based on supplied schematic drawings and the schematics are strictly for development purposes.

EVALUATION BOARD/KIT IMPORTANT NOTICE

Texas Instruments (TI) provides the enclosed product(s) under the following conditions:
This evaluation board/kit is intended for use for **ENGINEERING DEVELOPMENT, DEMONSTRATION, OR EVALUATION PURPOSES ONLY** and is not considered by TI to be a finished end-product fit for general consumer use. Persons handling the product(s) must have electronics training and observe good engineering practice standards. As such, the goods being provided are not intended to be complete in terms of required design-, marketing-, and/or manufacturing-related protective considerations, including product safety and environmental measures typically found in end products that incorporate such semiconductor components or circuit boards. This evaluation board/kit does not fall within the scope of the European Union directives regarding electromagnetic compatibility, restricted substances (RoHS), recycling (WEEE), FCC, CE or UL, and therefore may not meet the technical requirements of these directives or other related directives.
Should this evaluation board/kit not meet the specifications indicated in the User's Guide, the board/kit may be returned within 30 days from the date of delivery for a full refund. THE FOREGOING WARRANTY IS THE EXCLUSIVE WARRANTY MADE BY SELLER TO BUYER AND IS IN LIEU OF ALL OTHER WARRANTIES, EXPRESSED, IMPLIED, OR STATUTORY, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR PURPOSE.
The user assumes all responsibility and liability for proper and safe handling of the goods. Further, the user indemnifies TI from all claims arising from the handling or use of the goods. Due to the open construction of the product, it is the user's responsibility to take any and all appropriate precautions with regard to electrostatic discharge.
EXCEPT TO THE EXTENT OF THE INDEMNITY SET FORTH ABOVE, NEITHER PARTY SHALL BE LIABLE TO THE OTHER FOR ANY INDIRECT, SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.
TI currently deals with a variety of customers for products, and therefore our arrangement with the user **is not exclusive**.

TI assumes **no liability for applications assistance, customer product design, software performance, or infringement of patents or services described herein**.
Please read the User's Guide and, specifically, the Warnings and Restrictions notice in the User's Guide prior to handling the product. This notice contains important safety information about temperatures and voltages. For additional information on TI's environmental and/or safety programs, please contact the TI application engineer or visit www.ti.com/esh.
No license is granted under any patent right or other intellectual property right of TI covering or relating to any machine, process, or combination in which such TI products or services might be or are used.

Mailing Address:

Texas Instruments

Post Office Box 655303

Dallas, Texas 75265

FCC Warning

This evaluation board/kit is intended for use for **ENGINEERING DEVELOPMENT, DEMONSTRATION, OR EVALUATION PURPOSES ONLY** and is not considered by TI to be a finished end-product fit for general consumer use. It generates, uses, and can radiate radio frequency energy and has not been tested for compliance with the limits of computing devices pursuant to part 15 of FCC rules, which are designed to provide reasonable protection against radio frequency interference. Operation of this equipment in other environments may cause interference with radio communications, in which case the user at his own expense will be required to take whatever measures may be required to correct this interference.