```
apiVersion: v1
kind: ConfigMap
metadata:
name: gift-config
 labels:
   app: gift-service
   project: gift-service
  tier: backend
data:
API_GATEWAY_URI: http://api-gateway-svc:8080
KAKAO_REDIRECT_URI: http://localhost:8080/members/login/oauth2/code/kakao
SERVICE_PRODUCT_URI: http://product-service-svc:8081
 SERVICE_WISH_URI: http://wish-service-svc:8082
 SERVICE_USER_URI: http://user-service-svc:8084
FRONT_DOMAIN: http://localhost:8080
apiVersion: v1
kind: Secret
metadata:
name: gift-secret
labels:
   app: gift-service
   project: gift-service
  tier: backend
data:
JWT_SECRET: WW4ya2ppYmRkRkFXdG5QSjJBRmxMOFdYbW9oSk1DdmlnUWdnYUV5cGE1RT0=
 KAKAO_CLIENT_ID: YWMyMGQ4NGY5N2I2NzlmMGJiZDlhODA2NWJhODIzZjM=
 KAKAO_CLIENT_SECRET: RnczSmlMNVBrcGV2WFZaOU9pVk04YmZiZ0hVUEQ1RUE=
apiVersion: apps/v1
kind: Deployment
metadata:
name: api-gateway
labels:
   app: api-gateway
   project: gift-service
  tier: backend
spec:
 replicas: 1
 selector:
   matchLabels:
     app: api-gateway
template:
   metadata:
     labels:
       app: api-gateway
   spec:
     containers:
     name: api-gateway
       image: sk124590/api-gateway:2.1
```

```
ports:
       - containerPort: 8080
       resources:
         requests:
           cpu: "100m"
           memory: "256Mi"
         limits:
           cpu: "500m"
           memory: "512Mi"
       env:
       - name: JWT_SECRET
         valueFrom:
           secretKeyRef:
             name: gift-secret
             key: JWT_SECRET
       - name: SERVICE_USER_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: SERVICE_USER_URI
       - name: SERVICE_PRODUCT_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: SERVICE_PRODUCT_URI
       - name: SERVICE_WISH_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: SERVICE_WISH_URI
       - name: SERVICE ORDER URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: SERVICE_ORDER_URI
apiVersion: v1
kind: Service
metadata:
name: api-gateway-svc
labels:
   app: api-gateway
   project: gift-service
  tier: backend
spec:
type: ClusterIP
ports:
 - port: 8080
  targetPort: 8080
selector:
   app: api-gateway
apiVersion: apps/v1
kind: Deployment
```

```
metadata:
 name: user-service
labels:
   app: user-service
   project: gift-service
  tier: backend
spec:
replicas: 1
selector:
   matchLabels:
     app: user-service
template:
   metadata:
     labels:
       app: user-service
   spec:
     containers:
     - name: user-service
       image: sk124590/user-service:2.1
       ports:
       - containerPort: 8084
       resources:
         requests:
           cpu: "100m"
           memory: "512Mi"
         limits:
           cpu: "500m"
           memory: "1Gi"
       env:
       name: JWT_SECRET
         valueFrom:
           secretKeyRef:
             name: gift-secret
             key: JWT_SECRET
       - name: KAKAO_CLIENT_ID
         valueFrom:
           secretKeyRef:
             name: gift-secret
             key: KAKAO_CLIENT_ID
       - name: KAKAO_CLIENT_SECRET
         valueFrom:
           secretKeyRef:
             name: gift-secret
             key: KAKAO_CLIENT_SECRET
       - name: KAKAO_REDIRECT_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: KAKAO_REDIRECT_URI
apiVersion: v1
kind: Service
metadata:
 name: user-service-svc
```

```
labels:
   app: user-service
   project: gift-service
  tier: backend
spec:
type: ClusterIP
ports:
 - port: 8084
  targetPort: 8084
selector:
  app: user-service
apiVersion: apps/v1
kind: Deployment
metadata:
name: product-service
labels:
   app: product-service
   project: gift-service
  tier: backend
spec:
replicas: 1
selector:
  matchLabels:
     app: product-service
template:
  metadata:
     labels:
       app: product-service
   spec:
     containers:
     - name: product-service
       image: sk124590/product-service:2.1
       ports:
       - containerPort: 8081
       resources:
         requests:
           cpu: "150m"
           memory: "512Mi"
         limits:
           cpu: "1000m"
           memory: "1Gi"
apiVersion: v1
kind: Service
metadata:
name: product-service-svc
labels:
   app: product-service
   project: gift-service
  tier: backend
spec:
 type: ClusterIP
 ports:
```

```
- port: 8081
  targetPort: 8081
 selector:
  app: product-service
apiVersion: apps/v1
kind: Deployment
metadata:
name: wish-service
labels:
   app: wish-service
  project: gift-service
  tier: backend
spec:
replicas: 1
 selector:
   matchLabels:
     app: wish-service
template:
   metadata:
     labels:
       app: wish-service
   spec:
     containers:
     - name: wish-service
       image: sk124590/wish-service:2.1
       ports:
       - containerPort: 8082
       resources:
         requests:
           cpu: "100m"
           memory: "512Mi"
         limits:
           cpu: "700m"
           memory: "1Gi"
       env:
       - name: SERVICE_PRODUCT_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: SERVICE_PRODUCT_URI
apiVersion: v1
kind: Service
metadata:
name: wish-service-svc
labels:
   app: wish-service
  project: gift-service
  tier: backend
spec:
type: ClusterIP
 ports:
 - port: 8082
```

```
targetPort: 8082
 selector:
  app: wish-service
apiVersion: apps/v1
kind: Deployment
metadata:
name: order-service
labels:
  app: order-service
  project: gift-service
  tier: backend
spec:
replicas: 1
selector:
  matchLabels:
     app: order-service
template:
  metadata:
     labels:
       app: order-service
  spec:
     containers:
     - name: order-service
       image: sk124590/order-service:2.1
       ports:
       - containerPort: 8083
       resources:
         requests:
           cpu: "100m"
           memory: "512Mi"
         limits:
           cpu: "700m"
           memory: "1Gi"
       env:
       - name: SERVICE_PRODUCT_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: SERVICE_PRODUCT_URI
       - name: SERVICE WISH URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: SERVICE_WISH_URI
       - name: SERVICE_USER_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: SERVICE_USER_URI
       - name: FRONT_DOMAIN
         valueFrom:
           configMapKeyRef:
             name: gift-config
```

```
key: FRONT_DOMAIN
       - name: KAKAO_CLIENT_ID
         valueFrom:
           secretKeyRef:
             name: gift-secret
             key: KAKAO_CLIENT_ID
       name: KAKAO_CLIENT_SECRET
         valueFrom:
           secretKeyRef:
             name: gift-secret
             key: KAKAO_CLIENT_SECRET
apiVersion: v1
kind: Service
metadata:
name: order-service-svc
labels:
   app: order-service
   project: gift-service
  tier: backend
spec:
type: ClusterIP
ports:
 - port: 8083
  targetPort: 8083
selector:
   app: order-service
apiVersion: apps/v1
kind: Deployment
metadata:
name: gift-app
labels:
   app: gift-app
   project: gift-service
  tier: frontend
spec:
replicas: 1
 selector:
   matchLabels:
     app: gift-app
template:
   metadata:
     labels:
       app: gift-app
   spec:
     containers:
     - name: gift-app
       image: sk124590/gift-app:2.1
       ports:
       - containerPort: 8085
       resources:
         requests:
           cpu: "150m"
```

```
memory: "512Mi"
         limits:
           cpu: "1000m"
           memory: "1Gi"
       - name: API_GATEWAY_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: API_GATEWAY_URI
       - name: KAKAO_REDIRECT_URI
         valueFrom:
           configMapKeyRef:
             name: gift-config
             key: KAKAO_REDIRECT_URI
apiVersion: v1
kind: Service
metadata:
name: gift-app-svc
labels:
  app: gift-app
  project: gift-service
  tier: frontend
spec:
type: LoadBalancer
 ports:
 - port: 8080
  targetPort: 8085
selector:
  app: gift-app
```

YAML 위치와 내 용	참조된 Source	비고
(해당 없음)	(해당 없음)	제공된 YAML에 # From source_X 주석이 없어 매핑할 항목이 없습 니다.

특징: 배포 실패. 각 서비스에서 필요한 환경 변수를 모두 주입해줒 않음.