

```
apiVersion: v1
kind: Secret
metadata:
  name: gift-secret
  labels:
    app: gift-service
    project: gift-service
    tier: backend
# 민감 정보는 Base64로 인코딩되어야 합니다.
data:
  JWT_SECRET: WW4ya2ppYmRkRkFXdG5QSjJBRmxMOFdYbW9oSk1Ddm1nUWdnYUV5cGE1RT0=
  KAKAO_CLIENT_ID: YWMyMGQ4NGY5N2I2NzlmMGJiZDlhODA2NWJhODIzZjM=
  KAKAO_CLIENT_SECRET: RnczSm1MNVBrcGV2WFZaOU9pVk04YmZiZ0hVUEQ1RUE=
---
apiVersion: v1
kind: ConfigMap
metadata:
  name: gift-config
  labels:
    app: gift-service
    project: gift-service
    tier: backend
data:
  SERVICE_PRODUCT_URI: http://product-service-svc:8081
  KAKAO_REDIRECT_URI: http://localhost:8080/members/login/oauth2/code/kakao
  API_GATEWAY_URI: http://api-gateway-svc:8080
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: api-gateway
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
spec:
  replicas: 1 # From source_4
  selector:
    matchLabels:
      app: api-gateway
  template:
    metadata:
      labels:
        app: api-gateway
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: api-gateway
          image: sk124590/api-gateway:2.1
          ports:
            - containerPort: 8080
```

```
    envFrom:
      - configMapRef:
          name: gift-config
      - secretRef:
          name: gift-secret
    resources:
      requests:
        cpu: "100m"
        memory: "256Mi"
      limits:
        cpu: "500m"
        memory: "512Mi"
  ---
  apiVersion: v1
  kind: Service
  metadata:
    name: api-gateway-svc
    labels:
      app: api-gateway
      project: gift-service
      tier: backend
  spec:
    type: ClusterIP
    ports:
      - port: 8080
        targetPort: 8080
    selector:
      app: api-gateway
  ---
  apiVersion: apps/v1
  kind: Deployment
  metadata:
    name: user-service
    labels:
      app: user-service
      project: gift-service
      tier: backend
  spec:
    replicas: 1 # From source_4
    selector:
      matchLabels:
        app: user-service
    template:
      metadata:
        labels:
          app: user-service
          project: gift-service
          tier: backend
      spec:
        containers:
          - name: user-service
            image: sk124590/user-service:2.1
            ports:
              - containerPort: 8084
```

```
    envFrom:
    - secretRef:
        name: gift-secret
    resources:
      requests:
        cpu: "100m"
        memory: "512Mi"
      limits:
        cpu: "700m"
        memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: user-service-svc
  labels:
    app: user-service
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  ports:
    - port: 8084
      targetPort: 8084
  selector:
    app: user-service
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: product-service
  labels:
    app: product-service
    project: gift-service
    tier: backend
spec:
  replicas: 1 # From source_4
  selector:
    matchLabels:
      app: product-service
  template:
    metadata:
      labels:
        app: product-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: product-service
          image: sk124590/product-service:2.1
          ports:
            - containerPort: 8081
          resources:
            requests:
```

```
      cpu: "150m"
      memory: "512Mi"
    limits:
      cpu: "1000m"
      memory: "1Gi"
  ---
apiVersion: v1
kind: Service
metadata:
  name: product-service-svc
  labels:
    app: product-service
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  ports:
    - port: 8081
      targetPort: 8081
  selector:
    app: product-service
  ---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: wish-service
  labels:
    app: wish-service
    project: gift-service
    tier: backend
spec:
  replicas: 1 # From source_4
  selector:
    matchLabels:
      app: wish-service
  template:
    metadata:
      labels:
        app: wish-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: wish-service
          image: sk124590/wish-service:2.1
          ports:
            - containerPort: 8082
          envFrom:
            - configMapRef:
                name: gift-config
          resources:
            requests:
              cpu: "100m"
              memory: "512Mi"
```

```
      limits:
        cpu: "700m"
        memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: wish-service-svc
  labels:
    app: wish-service
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  ports:
    - port: 8082
      targetPort: 8082
  selector:
    app: wish-service
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: order-service
  labels:
    app: order-service
    project: gift-service
    tier: backend
spec:
  replicas: 1 # From source_4
  selector:
    matchLabels:
      app: order-service
  template:
    metadata:
      labels:
        app: order-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: order-service
          image: sk124590/order-service:2.1
          ports:
            - containerPort: 8083
          envFrom:
            - configMapRef:
                name: gift-config
            - secretRef:
                name: gift-secret
      resources:
        requests:
          cpu: "100m"
          memory: "512Mi"
```

```
      limits:
        cpu: "500m"
        memory: "512Mi"
    ---
apiVersion: v1
kind: Service
metadata:
  name: order-service-svc
  labels:
    app: order-service
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  ports:
    - port: 8083
      targetPort: 8083
  selector:
    app: order-service
    ---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: gift-app
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
spec:
  replicas: 1 # From source_4
  selector:
    matchLabels:
      app: gift-app
  template:
    metadata:
      labels:
        app: gift-app
        project: gift-service
        tier: frontend
    spec:
      containers:
        - name: gift-app
          image: sk124590/gift-app:2.1
          ports:
            - containerPort: 8085
          envFrom:
            - configMapRef:
                name: gift-config
            - secretRef:
                name: gift-secret
      resources:
        requests:
          cpu: "100m"
          memory: "512Mi"
```

```
      limits:
        cpu: "700m"
        memory: "1Gi"
    ---
apiVersion: v1
kind: Service
metadata:
  name: gift-app-svc
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
spec:
  type: LoadBalancer
  ports:
    - port: 8080
      targetPort: 8085
  selector:
    app: gift-app
```

YAML 위치와 내용	참조된 Source	비고
api-gateway.Deployment.spec.replicas = 1	source_4	api-gateway의 복제 수 설정 값
user-service.Deployment.spec.replicas = 1	source_4	user-service의 복제 수 설정 값
product-service.Deployment.spec.replicas = 1	source_4	product-service의 복제 수 설정 값
wish-service.Deployment.spec.replicas = 1	source_4	wish-service의 복제 수 설정 값
order-service.Deployment.spec.replicas = 1	source_4	order-service의 복제 수 설정 값
gift-app.Deployment.spec.replicas = 1	source_4	gift-app의 복제 수 설정 값

특징: 배포 실패. configMap에 서비스 URI가 모두 정의되지 않아서 필요한 환경변수를 주입해주지 못함