```
apiVersion: v1
kind: Secret
metadata:
  name: gift-secret
  labels:
    app: gift-service
    project: gift-service
    tier: backend
data:
  JWT_SECRET: WW4ya2ppYmRkRkFXdG5QSjJBRmxMOFdYbW9oSk1DdmlnUWdnYUV5cGE1RT0=
  KAKAO_CLIENT_ID: YWMyMGQ4NGY5N2I2NzlmMGJiZDlhODA2NWJhODIzZjM=
  KAKAO_CLIENT_SECRET: RnczSmlMNVBrcGV2WFZaOU9pVk04YmZiZ0hVUEQ1RUE=
apiVersion: v1
kind: ConfigMap
metadata:
  name: gift-config
  labels:
    app: gift-service
    project: gift-service
    tier: backend
data:
  API_GATEWAY_URI: http://api-gateway-svc:8080
  SERVICE_USER_URI: http://user-service-svc:8084
  SERVICE_PRODUCT_URI: http://product-service-svc:8081
  SERVICE_WISH_URI: http://wish-service-svc:8082
  SERVICE_ORDER_URI: http://order-service-svc:8083
  KAKAO_REDIRECT_URI: http://localhost:8080/members/login/oauth2/code/kakao
  FRONT_DOMAIN: http://localhost:8080
apiVersion: apps/v1
kind: Deployment
metadata:
 name: api-gateway
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: api-gateway
  template:
    metadata:
      labels:
        app: api-gateway
        project: gift-service
        tier: backend
    spec:
      containers:
      name: api-gateway
```

```
image: sk124590/api-gateway:2.1
        ports:
        - containerPort: 8080
        resources:
          requests:
            cpu: "100m"
            memory: "256Mi"
          limits:
            cpu: "500m"
            memory: "512Mi"
        env:
        - name: SERVICE_USER_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_USER_URI
        - name: SERVICE_PRODUCT_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_PRODUCT_URI
        - name: SERVICE_WISH_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_WISH_URI
        - name: SERVICE_ORDER_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE ORDER URI
        - name: JWT_SECRET
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: JWT_SECRET
apiVersion: v1
kind: Service
metadata:
  name: api-gateway-svc
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
spec:
 ports:
  - port: 8080
   targetPort: 8080
  selector:
    app: api-gateway
  type: ClusterIP
apiVersion: apps/v1
```

```
kind: Deployment
metadata:
  name: user-service
  labels:
    app: user-service
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: user-service
  template:
    metadata:
      labels:
        app: user-service
        project: gift-service
        tier: backend
    spec:
      containers:
      - name: user-service
        image: sk124590/user-service:2.1
        ports:
        - containerPort: 8084
        resources:
          requests:
            cpu: "150m"
            memory: "512Mi"
          limits:
            cpu: "1000m"
            memory: "1Gi"
        env:
        - name: KAKAO_REDIRECT_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: KAKAO_REDIRECT_URI
        - name: JWT SECRET
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: JWT_SECRET
        - name: KAKAO_CLIENT_ID
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: KAKAO_CLIENT_ID
        - name: KAKAO_CLIENT_SECRET
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: KAKAO_CLIENT_SECRET
apiVersion: v1
```

```
kind: Service
metadata:
  name: user-service-svc
  labels:
    app: user-service
    project: gift-service
    tier: backend
spec:
  ports:
  - port: 8084
    targetPort: 8084
  selector:
    app: user-service
  type: ClusterIP
apiVersion: apps/v1
kind: Deployment
metadata:
  name: product-service
  labels:
    app: product-service
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: product-service
  template:
    metadata:
      labels:
        app: product-service
        project: gift-service
        tier: backend
    spec:
      containers:
      - name: product-service
        image: sk124590/product-service:2.1
        ports:
        - containerPort: 8081
        resources:
          requests:
            cpu: "150m"
            memory: "512Mi"
          limits:
            cpu: "1000m"
            memory: "1Gi"
apiVersion: v1
kind: Service
metadata:
  name: product-service-svc
  labels:
    app: product-service
```

```
project: gift-service
    tier: backend
spec:
  ports:
  - port: 8081
   targetPort: 8081
  selector:
    app: product-service
 type: ClusterIP
apiVersion: apps/v1
kind: Deployment
metadata:
 name: wish-service
  labels:
    app: wish-service
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: wish-service
  template:
    metadata:
      labels:
        app: wish-service
        project: gift-service
        tier: backend
    spec:
      containers:
      - name: wish-service
        image: sk124590/wish-service:2.1
        ports:
        - containerPort: 8082
        resources:
          requests:
            cpu: "100m"
            memory: "512Mi"
          limits:
            cpu: "700m"
            memory: "1Gi"
        - name: SERVICE PRODUCT URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_PRODUCT_URI
apiVersion: v1
kind: Service
metadata:
  name: wish-service-svc
  labels:
```

```
app: wish-service
    project: gift-service
    tier: backend
spec:
  ports:
  - port: 8082
    targetPort: 8082
  selector:
    app: wish-service
 type: ClusterIP
apiVersion: apps/v1
kind: Deployment
metadata:
  name: order-service
  labels:
    app: order-service
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: order-service
  template:
    metadata:
      labels:
        app: order-service
        project: gift-service
        tier: backend
    spec:
      containers:
      - name: order-service
        image: sk124590/order-service:2.1
        ports:
        - containerPort: 8083
        resources:
          requests:
            cpu: "100m"
            memory: "512Mi"
          limits:
            cpu: "700m"
            memory: "1Gi"
        - name: SERVICE_PRODUCT_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_PRODUCT_URI
        - name: SERVICE_WISH_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_WISH_URI
```

```
- name: SERVICE_USER_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_USER_URI
        - name: FRONT_DOMAIN
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: FRONT_DOMAIN
        - name: KAKAO_CLIENT_ID
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: KAKAO_CLIENT_ID
        - name: KAKAO_CLIENT_SECRET
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: KAKAO_CLIENT_SECRET
apiVersion: v1
kind: Service
metadata:
 name: order-service-svc
  labels:
    app: order-service
    project: gift-service
    tier: backend
spec:
  ports:
  - port: 8083
   targetPort: 8083
  selector:
    app: order-service
  type: ClusterIP
apiVersion: apps/v1
kind: Deployment
metadata:
  name: gift-app
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: gift-app
 template:
    metadata:
      labels:
        app: gift-app
```

```
project: gift-service
        tier: frontend
    spec:
      containers:
      - name: gift-app
        image: sk124590/gift-app:2.1
        ports:
        - containerPort: 8085
        resources:
          requests:
            cpu: "100m"
            memory: "512Mi"
          limits:
            cpu: "500m"
            memory: "1Gi"
        env:
        - name: API_GATEWAY_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: API_GATEWAY_URI
        - name: KAKAO_REDIRECT_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: KAKAO_REDIRECT_URI
        - name: JWT_SECRET
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: JWT_SECRET
        - name: KAKAO_CLIENT_ID
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: KAKAO_CLIENT_ID
        - name: KAKAO_CLIENT_SECRET
          valueFrom:
            secretKeyRef:
              name: gift-secret
              key: KAKAO CLIENT SECRET
apiVersion: v1
kind: Service
metadata:
  name: gift-app-svc
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
spec:
  ports:
  - port: 8080
    targetPort: 8085
```

selector:
 app: gift-app
type: LoadBalancer

## YAML 위치와 내용 참조된 Source 비고