

```

apiVersion: v1
kind: Secret
metadata:
  name: gift-secret
  labels:
    app: gift-service
    project: gift-service
    tier: backend
# Secret 데이터는 민감 정보로, Base64로 인코딩되어 저장됩니다.
data:
  JWT_SECRET: WW4ya2ppYmRkRkFXdG5QSjJBRmxMOFdYbW9oSk1DdmInUWdnYUV5cGE1RT0=
  KAKAO_CLIENT_ID: YWMyMGQ4NGY5N2I2NzlmMGJiZDlhODA2NWJhODIzZjM=
  KAKAO_CLIENT_SECRET: RnczSmIMNVBrcGV2WFZaOU9pVk04YmZiZ0hVUEQ1RUE=
---
apiVersion: v1
kind: ConfigMap
metadata:
  name: gift-config
  labels:
    app: gift-service
    project: gift-service
    tier: backend
# 일반 구성 변수와 서비스 URI를 저장합니다.
data:
  API_GATEWAY_URI: http://api-gateway-svc:8080
  SERVICE_USER_URI: http://user-service-svc:8084
  SERVICE_PRODUCT_URI: http://product-service-svc:8081
  SERVICE_WISH_URI: http://wish-service-svc:8082
  SERVICE_ORDER_URI: http://order-service-svc:8083
  KAKAO_REDIRECT_URI: http://localhost:8080/members/login/oauth2/code/kakao
  FRONT_DOMAIN: http://localhost:8080
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: api-gateway
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: api-gateway
  template:
    metadata:
      labels:
        app: api-gateway
        project: gift-service
        tier: backend
    spec:

```

```

containers:
- name: api-gateway
  image: sk124590/api-gateway:2.1
  ports:
  - containerPort: 8080
  env:
  - name: SERVICE_USER_URI
    valueFrom:
      configMapKeyRef:
        name: gift-config
        key: SERVICE_USER_URI
  - name: SERVICE_PRODUCT_URI
    valueFrom:
      configMapKeyRef:
        name: gift-config
        key: SERVICE_PRODUCT_URI
  - name: SERVICE_WISH_URI
    valueFrom:
      configMapKeyRef:
        name: gift-config
        key: SERVICE_WISH_URI
  - name: SERVICE_ORDER_URI
    valueFrom:
      configMapKeyRef:
        name: gift-config
        key: SERVICE_ORDER_URI
  - name: JWT_SECRET
    valueFrom:
      secretKeyRef:
        name: gift-secret
        key: JWT_SECRET
  resources:
    requests:
      cpu: "100m"
      memory: "256Mi"
    limits:
      cpu: "500m"
      memory: "512Mi"
---
apiVersion: v1
kind: Service
metadata:
  name: api-gateway-svc
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  selector:
    app: api-gateway
  ports:
  - port: 8080
    targetPort: 8080

```

```
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: user-service
  labels:
    app: user-service
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: user-service
  template:
    metadata:
      labels:
        app: user-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: user-service
          image: sk124590/user-service:2.1
          ports:
            - containerPort: 8084
          env:
            - name: JWT_SECRET
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: JWT_SECRET
            - name: KAKAO_CLIENT_ID
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_ID
            - name: KAKAO_CLIENT_SECRET
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_SECRET
            - name: KAKAO_REDIRECT_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: KAKAO_REDIRECT_URI
      resources:
        requests:
          cpu: "150m"
          memory: "512Mi"
        limits:
          cpu: "1000m"
          memory: "1Gi"
```

```
---
apiVersion: v1
kind: Service
metadata:
  name: user-service-svc
  labels:
    app: user-service
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  selector:
    app: user-service
  ports:
    - port: 8084
      targetPort: 8084
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: product-service
  labels:
    app: product-service
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: product-service
  template:
    metadata:
      labels:
        app: product-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: product-service
          image: sk124590/product-service:2.1
          ports:
            - containerPort: 8081
          resources:
            requests:
              cpu: "150m"
              memory: "512Mi"
            limits:
              cpu: "1000m"
              memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: product-service-svc
```

```
labels:
  app: product-service
  project: gift-service
  tier: backend
spec:
  type: ClusterIP
  selector:
    app: product-service
  ports:
    - port: 8081
      targetPort: 8081
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: wish-service
  labels:
    app: wish-service
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: wish-service
  template:
    metadata:
      labels:
        app: wish-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: wish-service
          image: sk124590/wish-service:2.1
          ports:
            - containerPort: 8082
          env:
            - name: SERVICE_PRODUCT_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: SERVICE_PRODUCT_URI
      resources:
        requests:
          cpu: "100m"
          memory: "512Mi"
        limits:
          cpu: "700m"
          memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
```

```
name: wish-service-svc
labels:
  app: wish-service
  project: gift-service
  tier: backend
spec:
  type: ClusterIP
  selector:
    app: wish-service
  ports:
    - port: 8082
      targetPort: 8082
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: order-service
  labels:
    app: order-service
    project: gift-service
    tier: backend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: order-service
  template:
    metadata:
      labels:
        app: order-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: order-service
          image: sk124590/order-service:2.1
          ports:
            - containerPort: 8083
          env:
            - name: SERVICE_PRODUCT_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: SERVICE_PRODUCT_URI
            - name: SERVICE_WISH_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: SERVICE_WISH_URI
            - name: SERVICE_USER_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: SERVICE_USER_URI
```

```

- name: FRONT_DOMAIN
  valueFrom:
    configMapKeyRef:
      name: gift-config
      key: FRONT_DOMAIN
- name: KAKAO_CLIENT_ID
  valueFrom:
    secretKeyRef:
      name: gift-secret
      key: KAKAO_CLIENT_ID
- name: KAKAO_CLIENT_SECRET
  valueFrom:
    secretKeyRef:
      name: gift-secret
      key: KAKAO_CLIENT_SECRET
resources:
  requests:
    cpu: "100m"
    memory: "512Mi"
  limits:
    cpu: "700m"
    memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: order-service-svc
  labels:
    app: order-service
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  selector:
    app: order-service
  ports:
    - port: 8083
      targetPort: 8083
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: gift-app
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
spec:
  replicas: 1
  selector:
    matchLabels:
      app: gift-app
  template:
    metadata:

```

```

labels:
  app: gift-app
  project: gift-service
  tier: frontend
spec:
  containers:
  - name: gift-app
    image: sk124590/gift-app:2.1
    ports:
    - containerPort: 8085
    env:
    - name: API_GATEWAY_URI
      valueFrom:
        configMapKeyRef:
          name: gift-config
          key: API_GATEWAY_URI
    - name: KAKAO_REDIRECT_URI
      valueFrom:
        configMapKeyRef:
          name: gift-config
          key: KAKAO_REDIRECT_URI
    - name: JWT_SECRET
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: JWT_SECRET
    - name: KAKAO_CLIENT_ID
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: KAKAO_CLIENT_ID
    - name: KAKAO_CLIENT_SECRET
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: KAKAO_CLIENT_SECRET
  resources:
    requests:
      cpu: "100m"
      memory: "512Mi"
    limits:
      cpu: "500m"
      memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: gift-app-svc
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
spec:
  type: LoadBalancer

```



```
selector:  
  app: gift-app  
ports:  
- port: 8080  
  targetPort: 8085
```

YAML 위치와 내용 **참조된 Source** **비고**
