

```
apiVersion: v1
kind: Secret
metadata:
  name: gift-secret
  labels:
    app: gift-service
    project: gift-service
    tier: backend
# From source_5, source_11

data:
  JWT_SECRET: WW4ya2ppYmRkRkFXdG5QSjJBBrmxMOFdYbW9oSk1Ddm1nUWdnYUV5cGE1RT0=
  KAKAO_CLIENT_ID: YWMyMGQ4NGY5N2I2NzlmMGJiZDlhODA2NWJhODIzZjM=
  KAKAO_CLIENT_SECRET: RnczSm1MNVBrcGV2WFZaOU9pVk04YmZiZ0hVUEQ1RUE=
# From source_5, source_13
---
```

```
apiVersion: v1
kind: ConfigMap
metadata:
  name: gift-config
  labels:
    app: gift-service
    project: gift-service
    tier: backend
# From source_5, source_11

data:
  API_GATEWAY_URI: http://api-gateway-svc:8080
  SERVICE_USER_URI: http://user-service-svc:8084
  SERVICE_PRODUCT_URI: http://product-service-svc:8081
  SERVICE_WISH_URI: http://wish-service-svc:8082
  SERVICE_ORDER_URI: http://order-service-svc:8083
  KAKAO_REDIRECT_URI: http://localhost:8080/members/login/oauth2/code/kakao
  FRONT_DOMAIN: http://localhost:8080
# From source_5
---
```

```
apiVersion: apps/v1
kind: Deployment
metadata:
  name: api-gateway
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
# From source_6, source_11

spec:
  replicas: 1
  selector:
    matchLabels:
      app: api-gateway
  template:
```

```

metadata:
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
spec:
  containers:
  - name: api-gateway
    image: sk124590/api-gateway:2.1
    ports:
      - containerPort: 8080
    env:
      - name: SERVICE_USER_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: SERVICE_USER_URI
      - name: SERVICE_PRODUCT_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: SERVICE_PRODUCT_URI
      - name: SERVICE_WISH_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: SERVICE_WISH_URI
      - name: SERVICE_ORDER_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: SERVICE_ORDER_URI
      - name: JWT_SECRET
        valueFrom:
          secretKeyRef:
            name: gift-secret
            key: JWT_SECRET
    resources:
      requests:
        cpu: "100m"
        memory: "256Mi"
      limits:
        cpu: "500m"
        memory: "512Mi"
# From source_6
---
apiVersion: v1
kind: Service
metadata:
  name: api-gateway-svc
  labels:
    app: api-gateway
    project: gift-service
    tier: backend

```

```
# From source_6, source_11

spec:
  type: ClusterIP
  ports:
    - port: 8080
      targetPort: 8080
  selector:
    app: api-gateway
# From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: user-service
  labels:
    app: user-service
    project: gift-service
    tier: backend
# From source_8, source_11

spec:
  replicas: 1
  selector:
    matchLabels:
      app: user-service
  template:
    metadata:
      labels:
        app: user-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: user-service
          image: sk124590/user-service:2.1
          ports:
            - containerPort: 8084
          env:
            - name: JWT_SECRET
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: JWT_SECRET
            - name: KAKAO_CLIENT_ID
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_ID
            - name: KAKAO_CLIENT_SECRET
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_SECRET
```

```

      - name: KAKAO_REDIRECT_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: KAKAO_REDIRECT_URI
        resources:
          requests:
            cpu: "150m"
            memory: "512Mi"
          limits:
            cpu: "1000m"
            memory: "1Gi"
# From source_8
---
apiVersion: v1
kind: Service
metadata:
  name: user-service-svc
  labels:
    app: user-service
    project: gift-service
    tier: backend
# From source_8, source_11

spec:
  type: ClusterIP
  ports:
    - port: 8084
      targetPort: 8084
  selector:
    app: user-service
# From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: product-service
  labels:
    app: product-service
    project: gift-service
    tier: backend
# From source_10, source_11

spec:
  replicas: 1
  selector:
    matchLabels:
      app: product-service
  template:
    metadata:
      labels:
        app: product-service
        project: gift-service
        tier: backend

```

```

    spec:
      containers:
        - name: product-service
          image: sk124590/product-service:2.1
          ports:
            - containerPort: 8081
          resources:
            requests:
              cpu: "150m"
              memory: "512Mi"
            limits:
              cpu: "1000m"
              memory: "1Gi"
# From source_10
---
apiVersion: v1
kind: Service
metadata:
  name: product-service-svc
  labels:
    app: product-service
    project: gift-service
    tier: backend
# From source_10, source_11

spec:
  type: ClusterIP
  ports:
    - port: 8081
      targetPort: 8081
  selector:
    app: product-service
# From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: wish-service
  labels:
    app: wish-service
    project: gift-service
    tier: backend
# From source_4, source_11

spec:
  replicas: 1
  selector:
    matchLabels:
      app: wish-service
  template:
    metadata:
      labels:
        app: wish-service
        project: gift-service

```

```

    tier: backend
  spec:
    containers:
      - name: wish-service
        image: sk124590/wish-service:2.1
        ports:
          - containerPort: 8082
        env:
          - name: SERVICE_PRODUCT_URI
            valueFrom:
              configMapKeyRef:
                name: gift-config
                key: SERVICE_PRODUCT_URI
        resources:
          requests:
            cpu: "100m"
            memory: "512Mi"
          limits:
            cpu: "700m"
            memory: "1Gi"
# From source_4
---
apiVersion: v1
kind: Service
metadata:
  name: wish-service-svc
  labels:
    app: wish-service
    project: gift-service
    tier: backend
# From source_4, source_11

spec:
  type: ClusterIP
  ports:
    - port: 8082
      targetPort: 8082
  selector:
    app: wish-service
# From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: order-service
  labels:
    app: order-service
    project: gift-service
    tier: backend
# From source_7, source_11

spec:
  replicas: 1
  selector:

```

```
matchLabels:
  app: order-service
template:
  metadata:
    labels:
      app: order-service
      project: gift-service
      tier: backend
  spec:
    containers:
      - name: order-service
        image: sk124590/order-service:2.1
        ports:
          - containerPort: 8083
        env:
          - name: SERVICE_PRODUCT_URI
            valueFrom:
              configMapKeyRef:
                name: gift-config
                key: SERVICE_PRODUCT_URI
          - name: SERVICE_WISH_URI
            valueFrom:
              configMapKeyRef:
                name: gift-config
                key: SERVICE_WISH_URI
          - name: SERVICE_USER_URI
            valueFrom:
              configMapKeyRef:
                name: gift-config
                key: SERVICE_USER_URI
          - name: FRONT_DOMAIN
            valueFrom:
              configMapKeyRef:
                name: gift-config
                key: FRONT_DOMAIN
          - name: KAKAO_CLIENT_ID
            valueFrom:
              secretKeyRef:
                name: gift-secret
                key: KAKAO_CLIENT_ID
          - name: KAKAO_CLIENT_SECRET
            valueFrom:
              secretKeyRef:
                name: gift-secret
                key: KAKAO_CLIENT_SECRET
    resources:
      requests:
        cpu: "100m"
        memory: "512Mi"
      limits:
        cpu: "700m"
        memory: "1Gi"
# From source_7
---
```

```
apiVersion: v1
kind: Service
metadata:
  name: order-service-svc
  labels:
    app: order-service
    project: gift-service
    tier: backend
# From source_7, source_11

spec:
  type: ClusterIP
  ports:
    - port: 8083
      targetPort: 8083
  selector:
    app: order-service
# From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: gift-app
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
# From source_10, source_11

spec:
  replicas: 1
  selector:
    matchLabels:
      app: gift-app
  template:
    metadata:
      labels:
        app: gift-app
        project: gift-service
        tier: frontend
    spec:
      containers:
        - name: gift-app
          image: sk124590/gift-app:2.1
          ports:
            - containerPort: 8085
          env:
            - name: API_GATEWAY_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: API_GATEWAY_URI
            - name: KAKAO_REDIRECT_URI
              valueFrom:
```



```
      configMapKeyRef:
        name: gift-config
        key: KAKAO_REDIRECT_URI
    - name: JWT_SECRET
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: JWT_SECRET
    - name: KAKAO_CLIENT_ID
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: KAKAO_CLIENT_ID
    - name: KAKAO_CLIENT_SECRET
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: KAKAO_CLIENT_SECRET
  resources:
    requests:
      cpu: "100m"
      memory: "512Mi"
    limits:
      cpu: "500m"
      memory: "1Gi"
# From source_10
---
apiVersion: v1
kind: Service
metadata:
  name: gift-app-svc
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
# From source_10, source_11

spec:
  type: LoadBalancer
  ports:
    - port: 8080
      targetPort: 8085
  selector:
    app: gift-app
# From source_12
```

YAML 위치와 내용	참조된 Source	비고
gift-secret.Secret.metadata.labels (block) = {app: gift-service, project: gift-service, tier: backend}	source_5, source_11	Secret 메타데이터 라벨 전체

YAML 위치와 내용	참조된 Source	비고
gift-secret.Secret.data (block) = <code>JWT_SECRET, KAKAO_CLIENT_ID, KAKAO_CLIENT_SECRET</code>	source_5, source_13	민감정보를 Secret 에 저장(정책 포함)
gift-config.ConfigMap.metadata.labels (block) = <code>{app: gift-service, project: gift-service, tier: backend}</code>	source_5, source_11	ConfigMap 메타 데이터 라벨 전체
gift-config.ConfigMap.data (block) = <code>API_GATEWAY_URI, SERVICE_USER_URI, SERVICE_PRODUCT_URI, SERVICE_WISH_URI, SERVICE_ORDER_URI, KAKAO_REDIRECT_URI, FRONT_DOMAIN</code>	source_5	공통 서비스 엔드 포인트 및 프론트/리다이렉트 설정
api-gateway.Deployment.metadata.labels (block) = <code>{app: api-gateway, project: gift-service, tier: backend}</code>	source_6, source_11	배포 리소스/라벨 근거
api-gateway.Deployment.spec.template.spec.containers[0].image = <code>sk124590/api-gateway:2.1</code>	source_6	이미지/버전
api-gateway.Deployment.spec.template.spec.containers[0].ports[0].containerPort = <code>8080</code>	source_6	컨테이너 포트
api-gateway.Deployment.spec.template.spec.containers[0].env (block) = <code>SERVICE_USER_URI, SERVICE_PRODUCT_URI, SERVICE_WISH_URI, SERVICE_ORDER_URI, JWT_SECRET</code>	source_6	ConfigMap/Secret 주입 항목
api-gateway.Deployment.spec.template.spec.containers[0].resources (block) = <code>requests{100m,256Mi}, limits{500m,512Mi}</code>	source_6	리소스 요청/제한
api-gateway-svc.Service.metadata.labels (block) = <code>{app: api-gateway, project: gift-service, tier: backend}</code>	source_6, source_11	Service 메타데이터 라벨
api-gateway-svc.Service.spec.selector = <code>app=api-gateway</code> 등 Service 사양	source_12	서비스 선택자/포트 기준
user-service.Deployment.metadata.labels (block) = <code>{app: user-service, project: gift-service, tier: backend}</code>	source_8, source_11	배포 리소스/라벨 근거
user-service.Deployment.spec.replicas = <code>1</code>	source_8	복제 수
user-service.Deployment.spec.template.spec.containers[0].image = <code>sk124590/user-service:2.1</code>	source_8	이미지/버전
user-service.Deployment.spec.template.spec.containers[0].ports[0].containerPort = <code>8084</code>	source_8	컨테이너 포트
user-service.Deployment.spec.template.spec.containers[0].env (block) = <code>JWT_SECRET, KAKAO_CLIENT_ID, KAKAO_CLIENT_SECRET, KAKAO_REDIRECT_URI</code>	source_8	Secret/ConfigMap 주입 항목

YAML 위치와 내용	참조된 Source	비고
user-service.Deployment.spec.template.spec.containers[0].resources (block) = <code>requests{150m,512Mi}, limits{1000m,1Gi}</code>	source_8	리소스 요청/제한
user-service-svc.Service.metadata.labels (block) = <code>{app: user-service, project: gift-service, tier: backend}</code>	source_8, source_11	Service 메타데이터 라벨
user-service-svc.Service.spec.selector = <code>app=user-service</code> 등 Service 사양	source_12	서비스 선택자/포트 기준
product-service.Deployment.metadata.labels (block) = <code>{app: product-service, project: gift-service, tier: backend}</code>	source_10, source_11	배포 리소스/라벨 근거
product-service.Deployment.spec.replicas = <code>1</code>	source_10, source_11	복제 수
product-service.Deployment.spec.template.spec.containers[0].image = <code>sk124590/product-service:2.1</code>	source_10	이미지/버전
product-service.Deployment.spec.template.spec.containers[0].ports[0].containerPort = <code>8081</code>	source_10	컨테이너 포트
product-service.Deployment.spec.template.spec.containers[0].resources (block) = <code>requests{150m,512Mi}, limits{1000m,1Gi}</code>	source_10	리소스 요청/제한
product-service-svc.Service.metadata.labels (block) = <code>{app: product-service, project: gift-service, tier: backend}</code>	source_10, source_11	Service 메타데이터 라벨
product-service-svc.Service.spec.selector = <code>app=product-service</code> 등 Service 사양	source_12	서비스 선택자/포트 기준
wish-service.Deployment.metadata.labels (block) = <code>{app: wish-service, project: gift-service, tier: backend}</code>	source_4, source_11	배포 리소스/라벨 근거
wish-service.Deployment.spec.replicas = <code>1</code>	source_4	복제 수
wish-service.Deployment.spec.template.spec.containers[0].image = <code>sk124590/wish-service:2.1</code>	source_4	이미지/버전
wish-service.Deployment.spec.template.spec.containers[0].ports[0].containerPort = <code>8082</code>	source_4	컨테이너 포트
wish-service.Deployment.spec.template.spec.containers[0].env (block) = <code>SERVICE_PRODUCT_URI</code>	source_4	ConfigMap 주입 항목
wish-service.Deployment.spec.template.spec.containers[0].resources (block) = <code>requests{100m,512Mi}, limits{700m,1Gi}</code>	source_4	리소스 요청/제한
wish-service-svc.Service.metadata.labels (block) = <code>{app: wish-service, project: gift-service, tier: backend}</code>	source_4, source_11	Service 메타데이터 라벨

YAML 위치와 내용	참조된 Source	비고
wish-service-svc.Service.spec.selector = <code>app=wish-service</code> 등 Service 사양	source_12	서비스 선택자/포트 기준
order-service.Deployment.metadata.labels (block) = <code>{app: order-service, project: gift-service, tier: backend}</code>	source_7, source_11	배포 리소스/라벨 근거
order-service.Deployment.spec.replicas = 1	source_7	복제 수
order-service.Deployment.spec.template.spec.containers[0].image = <code>sk124590/order-service:2.1</code>	source_7	이미지/버전
order-service.Deployment.spec.template.spec.containers[0].ports[0].containerPort = 8083	source_7	컨테이너 포트
order-service.Deployment.spec.template.spec.containers[0].env (block) = <code>SERVICE_PRODUCT_URI, SERVICE_WISH_URI, SERVICE_USER_URI, FRONT_DOMAIN, KAKAO_CLIENT_ID, KAKAO_CLIENT_SECRET</code>	source_7	ConfigMap/Secret 주입 항목
order-service.Deployment.spec.template.spec.containers[0].resources (block) = <code>requests{100m,512Mi}, limits{700m,1Gi}</code>	source_7	리소스 요청/제한
order-service-svc.Service.metadata.labels (block) = <code>{app: order-service, project: gift-service, tier: backend}</code>	source_7, source_11	Service 메타데이터 라벨
order-service-svc.Service.spec.selector = <code>app=order-service</code> 등 Service 사양	source_12	서비스 선택자/포트 기준
gift-app.Deployment.metadata.labels (block) = <code>{app: gift-app, project: gift-service, tier: frontend}</code>	source_10, source_11	배포 리소스/라벨 근거
gift-app.Deployment.spec.replicas = 1	source_10	복제 수
gift-app.Deployment.spec.template.spec.containers[0].image = <code>sk124590/gift-app:2.1</code>	source_10	이미지/버전
gift-app.Deployment.spec.template.spec.containers[0].ports[0].containerPort = 8085	source_10	컨테이너 포트
gift-app.Deployment.spec.template.spec.containers[0].env (block) = <code>API_GATEWAY_URI, KAKAO_REDIRECT_URI, JWT_SECRET, KAKAO_CLIENT_ID, KAKAO_CLIENT_SECRET</code>	source_10	ConfigMap/Secret 주입 항목
gift-app.Deployment.spec.template.spec.containers[0].resources (block) = <code>requests{100m,512Mi}, limits{500m,1Gi}</code>	source_10	리소스 요청/제한
gift-app-svc.Service.metadata.labels (block) = <code>{app: gift-app, project: gift-service, tier: frontend}</code>	source_10, source_11	Service 메타데이터 라벨
gift-app-svc.Service.spec (block) = <code>type: LoadBalancer, ports: 8080→8085, selector: app=gift-app</code>	source_12	L4 노출/포워딩 및 선택자 기준