

```

apiVersion: v1
kind: Secret
metadata:
  name: gift-secret # From source_5
  labels:
    project: gift-service # From source_11
    tier: backend # From source_11
data:
  JWT_SECRET: WW4ya2ppYmRkRkFXdG5QSjJBRmxMOFdYbW9oSk1Ddm1nUWdnYUV5cGE1RT0= # From
source_5
  KAKAO_CLIENT_ID: YWMYMGQ4NGY5N2I2NzlmMGJiZDlhODA2NWJhODIzZjM= # From source_5
  KAKAO_CLIENT_SECRET: RnczSm1MNVBrcGV2WFZaOU9pVk04YmZiZ0hVUEQ1RUE= # From
source_5
---
apiVersion: v1
kind: ConfigMap
metadata:
  name: gift-config # From source_5
  labels:
    project: gift-service # From source_11
    tier: backend # From source_11
data:
  API_GATEWAY_URI: http://api-gateway-svc:8080 # From source_5
  SERVICE_USER_URI: http://user-service-svc:8084 # From source_5
  SERVICE_PRODUCT_URI: http://product-service-svc:8081 # From source_5
  SERVICE_WISH_URI: http://wish-service-svc:8082 # From source_5
  SERVICE_ORDER_URI: http://order-service-svc:8083 # From source_5
  KAKAO_REDIRECT_URI: http://localhost:8080/members/login/oauth2/code/kakao # From
source_5
  FRONT_DOMAIN: http://localhost:8080 # From source_5
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: api-gateway # From source_6
  labels:
    app: api-gateway # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_6
  selector:
    matchLabels:
      app: api-gateway
  template:
    metadata:
      labels:
        app: api-gateway
    spec:
      containers:
        - name: api-gateway
          image: sk124590/api-gateway:2.1 # From source_6

```

```

    ports:
      - containerPort: 8080 # From source_6
    env:
      - name: SERVICE_USER_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: SERVICE_USER_URI
      - name: SERVICE_PRODUCT_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: SERVICE_PRODUCT_URI
      - name: SERVICE_WISH_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: SERVICE_WISH_URI
      - name: SERVICE_ORDER_URI
        valueFrom:
          configMapKeyRef:
            name: gift-config
            key: SERVICE_ORDER_URI
      - name: JWT_SECRET
        valueFrom:
          secretKeyRef:
            name: gift-secret
            key: JWT_SECRET
    resources:
      requests:
        cpu: "100m"
        memory: "256Mi"
      limits:
        cpu: "500m"
        memory: "512Mi"
  ---
apiVersion: v1
kind: Service
metadata:
  name: api-gateway-svc # From source_3
  labels:
    app: api-gateway # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
    - port: 8080 # From source_3
      targetPort: 8080
  selector:
    app: api-gateway
  type: ClusterIP
  ---
apiVersion: apps/v1
kind: Deployment

```

```

metadata:
  name: user-service # From source_8
  labels:
    app: user-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_8
  selector:
    matchLabels:
      app: user-service
  template:
    metadata:
      labels:
        app: user-service
    spec:
      containers:
        - name: user-service
          image: sk124590/user-service:2.1 # From source_8
          ports:
            - containerPort: 8084 # From source_8
          env:
            - name: JWT_SECRET
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: JWT_SECRET
            - name: KAKAO_CLIENT_ID
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_ID
            - name: KAKAO_CLIENT_SECRET
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_SECRET
            - name: KAKAO_REDIRECT_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: KAKAO_REDIRECT_URI
      resources:
        requests:
          cpu: "150m"
          memory: "512Mi"
        limits:
          cpu: "1000m"
          memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: user-service-svc # From source_12

```

```

labels:
  app: user-service # From source_11
  project: gift-service # From source_11
  tier: backend # From source_11
spec:
  ports:
  - port: 8084 # From source_12
    targetPort: 8084
  selector:
    app: user-service
  type: ClusterIP
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: product-service # From source_10
  labels:
    app: product-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_11
  selector:
    matchLabels:
      app: product-service
  template:
    metadata:
      labels:
        app: product-service
    spec:
      containers:
      - name: product-service
        image: sk124590/product-service:2.1 # From source_10
        ports:
        - containerPort: 8081 # From source_10
        resources:
          requests:
            cpu: "150m"
            memory: "512Mi"
          limits:
            cpu: "1000m"
            memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: product-service-svc # From source_12
  labels:
    app: product-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
  - port: 8081 # From source_12

```

```

    targetPort: 8081
    selector:
      app: product-service
    type: ClusterIP
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: wish-service # From source_4
  labels:
    app: wish-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_4
  selector:
    matchLabels:
      app: wish-service
  template:
    metadata:
      labels:
        app: wish-service
    spec:
      containers:
        - name: wish-service
          image: sk124590/wish-service:2.1 # From source_4
          ports:
            - containerPort: 8082 # From source_4
          env:
            - name: SERVICE_PRODUCT_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: SERVICE_PRODUCT_URI
      resources:
        requests:
          cpu: "100m"
          memory: "512Mi"
        limits:
          cpu: "700m"
          memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: wish-service-svc # From source_12
  labels:
    app: wish-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
    - port: 8082 # From source_12
      targetPort: 8082

```

```

selector:
  app: wish-service
  type: ClusterIP
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: order-service # From source_7
  labels:
    app: order-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_7
  selector:
    matchLabels:
      app: order-service
  template:
    metadata:
      labels:
        app: order-service
    spec:
      containers:
        - name: order-service
          image: sk124590/order-service:2.1 # From source_7
          ports:
            - containerPort: 8083 # From source_7
          env:
            - name: SERVICE_PRODUCT_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: SERVICE_PRODUCT_URI
            - name: SERVICE_WISH_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: SERVICE_WISH_URI
            - name: SERVICE_USER_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: SERVICE_USER_URI
            - name: FRONT_DOMAIN
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: FRONT_DOMAIN
            - name: KAKAO_CLIENT_ID
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_ID
            - name: KAKAO_CLIENT_SECRET

```

```

        valueFrom:
          secretKeyRef:
            name: gift-secret
            key: KAKAO_CLIENT_SECRET
      resources:
        requests:
          cpu: "100m"
          memory: "512Mi"
        limits:
          cpu: "700m"
          memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: order-service-svc # From source_12
  labels:
    app: order-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
    - port: 8083 # From source_12
      targetPort: 8083
  selector:
    app: order-service
  type: ClusterIP
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: gift-app # From source_10
  labels:
    app: gift-app # From source_11
    project: gift-service # From source_11
    tier: frontend # From source_11
spec:
  replicas: 1 # From source_10
  selector:
    matchLabels:
      app: gift-app
  template:
    metadata:
      labels:
        app: gift-app
    spec:
      containers:
        - name: gift-app
          image: sk124590/gift-app:2.1 # From source_10
          ports:
            - containerPort: 8085 # From source_10
          env:
            - name: API_GATEWAY_URI
              valueFrom:

```

```

      configMapKeyRef:
        name: gift-config
        key: API_GATEWAY_URI
    - name: KAKAO_REDIRECT_URI
      valueFrom:
        configMapKeyRef:
          name: gift-config
          key: KAKAO_REDIRECT_URI
    - name: JWT_SECRET
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: JWT_SECRET
    - name: KAKAO_CLIENT_ID
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: KAKAO_CLIENT_ID
    - name: KAKAO_CLIENT_SECRET
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: KAKAO_CLIENT_SECRET
  resources:
    requests:
      cpu: "100m"
      memory: "512Mi"
    limits:
      cpu: "500m"
      memory: "1Gi"

```

```
---
```

```

apiVersion: v1
kind: Service
metadata:
  name: gift-app-svc # From source_12
  labels:
    app: gift-app # From source_11
    project: gift-service # From source_11
    tier: frontend # From source_11
spec:
  ports:
    - port: 8080 # From source_12
      targetPort: 8085
  selector:
    app: gift-app
  type: LoadBalancer # From source_12

```