

```

apiVersion: v1
kind: Secret
metadata:
  name: gift-secret # From source_5
  labels:
    project: gift-service # From source_11
    tier: backend # From source_11
data:
  JWT_SECRET: WW4ya2ppYmRkRkFXdG5QSjJBmRmMOFdYbW9oSk1DdmlnUWdnYUV5cGE1RT0= # From
source_5
  KAKAO_CLIENT_ID: YWMYMGQ4NGY5N2I2NzlmMGJiZDlhODA2NWJhODIzZjM= # From source_5
  KAKAO_CLIENT_SECRET: RnczSmlMNVBrcGV2WFZaOU9pVk04YmZiZ0hVUEQ1RUE= # From source_2
---
apiVersion: v1
kind: ConfigMap
metadata:
  name: gift-config # From source_5
  labels:
    project: gift-service # From source_11
data:
  API_GATEWAY_URI: http://api-gateway-svc:8080 # From source_5
  SERVICE_USER_URI: http://user-service-svc:8084 # From source_5
  SERVICE_PRODUCT_URI: http://product-service-svc:8081 # From source_5
  SERVICE_WISH_URI: http://wish-service-svc:8082 # From source_5
  SERVICE_ORDER_URI: http://order-service-svc:8083 # From source_5
  KAKAO_REDIRECT_URI: http://localhost:8080/members/login/oauth2/code/kakao # From
source_5
  FRONT_DOMAIN: http://localhost:8080 # From source_5
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: api-gateway # From source_1
  labels:
    app: api-gateway # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_6
  selector:
    matchLabels:
      app: api-gateway # From source_11
  template:
    metadata:
      labels:
        app: api-gateway # From source_11
        project: gift-service # From source_11
        tier: backend # From source_11
    spec:
      containers:
        - name: api-gateway
          image: sk124590/api-gateway:2.1 # From source_6
          ports:
            - containerPort: 8080 # From source_6

```

```

resources:
  requests:
    cpu: "100m" # From source_6
    memory: "256Mi" # From source_6
  limits:
    cpu: "500m" # From source_6
    memory: "512Mi" # From source_6
  envFrom:
  - configMapRef:
      name: gift-config # From source_5
  - secretRef:
      name: gift-secret # From source_6
---
apiVersion: v1
kind: Service
metadata:
  name: api-gateway-svc # From source_3
  labels:
    app: api-gateway # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
  - port: 8080 # From source_3
    targetPort: 8080 # From source_6
  selector:
    app: api-gateway # From source_11
  type: ClusterIP # From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: user-service # From source_1
  labels:
    app: user-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_8
  selector:
    matchLabels:
      app: user-service # From source_11
  template:
    metadata:
      labels:
        app: user-service # From source_11
        project: gift-service # From source_11
        tier: backend # From source_11
    spec:
      containers:
      - name: user-service
        image: sk124590/user-service:2.1 # From source_8
        ports:
        - containerPort: 8084 # From source_8
        resources:
          requests:

```

```

      cpu: "150m" # From source_8
      memory: "512Mi" # From source_8
    limits:
      cpu: "1000m" # From source_8
      memory: "1Gi" # From source_8
    envFrom:
    - configMapRef:
        name: gift-config # From source_5
    - secretRef:
        name: gift-secret # From source_8
  ---
apiVersion: v1
kind: Service
metadata:
  name: user-service-svc # From source_3
  labels:
    app: user-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
    - port: 8084 # From source_3
      targetPort: 8084 # From source_8
  selector:
    app: user-service # From source_11
  type: ClusterIP # From source_12
  ---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: product-service # From source_1
  labels:
    app: product-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_11
  selector:
    matchLabels:
      app: product-service # From source_11
  template:
    metadata:
      labels:
        app: product-service # From source_11
        project: gift-service # From source_11
        tier: backend # From source_11
    spec:
      containers:
        - name: product-service
          image: sk124590/product-service:2.1 # From source_10
          ports:
            - containerPort: 8081 # From source_10
          resources:
            requests:
              cpu: "150m" # From source_10
              memory: "512Mi" # From source_10

```

```

        limits:
          cpu: "1000m" # From source_10
          memory: "1Gi" # From source_10
---
apiVersion: v1
kind: Service
metadata:
  name: product-service-svc # From source_3
  labels:
    app: product-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
    - port: 8081 # From source_3
      targetPort: 8081 # From source_10
  selector:
    app: product-service # From source_11
  type: ClusterIP # From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: wish-service # From source_1
  labels:
    app: wish-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_4
  selector:
    matchLabels:
      app: wish-service # From source_11
  template:
    metadata:
      labels:
        app: wish-service # From source_11
        project: gift-service # From source_11
        tier: backend # From source_11
    spec:
      containers:
        - name: wish-service
          image: sk124590/wish-service:2.1 # From source_4
          ports:
            - containerPort: 8082 # From source_4
          resources:
            requests:
              cpu: "100m" # From source_4
              memory: "512Mi" # From source_4
            limits:
              cpu: "700m" # From source_4
              memory: "1Gi" # From source_4
          envFrom:
            - configMapRef:
                name: gift-config # From source_5
---

```

```

apiVersion: v1
kind: Service
metadata:
  name: wish-service-svc # From source_3
  labels:
    app: wish-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
    - port: 8082 # From source_3
      targetPort: 8082 # From source_4
  selector:
    app: wish-service # From source_11
    type: ClusterIP # From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: order-service # From source_1
  labels:
    app: order-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  replicas: 1 # From source_7
  selector:
    matchLabels:
      app: order-service # From source_11
  template:
    metadata:
      labels:
        app: order-service # From source_11
        project: gift-service # From source_11
        tier: backend # From source_11
    spec:
      containers:
        - name: order-service
          image: sk124590/order-service:2.1 # From source_7
          ports:
            - containerPort: 8083 # From source_7
          resources:
            requests:
              cpu: "100m" # From source_7
              memory: "512Mi" # From source_7
            limits:
              cpu: "700m" # From source_7
              memory: "1Gi" # From source_7
          envFrom:
            - configMapRef:
                name: gift-config # From source_5
            - secretRef:
                name: gift-secret # From source_7
---
apiVersion: v1
kind: Service

```

```

metadata:
  name: order-service-svc # From source_3
  labels:
    app: order-service # From source_11
    project: gift-service # From source_11
    tier: backend # From source_11
spec:
  ports:
    - port: 8083 # From source_3
      targetPort: 8083 # From source_7
  selector:
    app: order-service # From source_11
  type: ClusterIP # From source_12
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: gift-app # From source_1
  labels:
    app: gift-app # From source_11
    project: gift-service # From source_11
    tier: frontend # From source_11
spec:
  replicas: 1 # From source_10
  selector:
    matchLabels:
      app: gift-app # From source_11
  template:
    metadata:
      labels:
        app: gift-app # From source_11
        project: gift-service # From source_11
        tier: frontend # From source_11
    spec:
      containers:
        - name: gift-app
          image: sk124590/gift-app:2.1 # From source_10
          ports:
            - containerPort: 8085 # From source_10
          resources:
            requests:
              cpu: "100m" # From source_10
              memory: "512Mi" # From source_10
            limits:
              cpu: "500m" # From source_10
              memory: "1Gi" # From source_10
          envFrom:
            - configMapRef:
                name: gift-config # From source_5
            - secretRef:
                name: gift-secret # From source_10
---
apiVersion: v1
kind: Service
metadata:
  name: gift-app-svc # From source_12

```

```

labels:
  app: gift-app # From source_11
  project: gift-service # From source_11
  tier: frontend # From source_11
spec:
  ports:
    - port: 8080 # From source_12
      targetPort: 8085 # From source_10
  selector:
    app: gift-app # From source_11
    type: LoadBalancer # From source_12

```

YAML 위치와 내용	참조된 Source	비고
gift-secret.Secret.metadata.name = gift-secret	source_5	Secret 이름
gift-secret.Secret.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
gift-secret.Secret.metadata.labels.tier = backend	source_11	공통 라벨: 티어
gift-secret.Secret.data.JWT_SECRET = WW4y...RT0=	source_5	JWT 시크릿 값(Base64)
gift-secret.Secret.data.KAKAO_CLIENT_ID = YWMY...ZjM=	source_5	카카오 클라이언트 ID(Base64)
gift-secret.Secret.data.KAKAO_CLIENT_SECRET = Rncz...RUE=	source_2	카카오 클라이언트 시크릿(Base64)
gift-config.ConfigMap.metadata.name = gift-config	source_5	ConfigMap 이름
gift-config.ConfigMap.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
gift-config.ConfigMap.data.API_GATEWAY_URI = http://api-gateway-svc:8080	source_5	게이트웨이 서비스 URI
gift-config.ConfigMap.data.SERVICE_USER_URI = http://user-service-svc:8084	source_5	사용자 서비스 URI
gift-config.ConfigMap.data.SERVICE_PRODUCT_URI = http://product-service-svc:8081	source_5	상품 서비스 URI
gift-config.ConfigMap.data.SERVICE_WISH_URI = http://wish-service-svc:8082	source_5	위시 서비스 URI
gift-config.ConfigMap.data.SERVICE_ORDER_URI = http://order-service-svc:8083	source_5	주문 서비스 URI

YAML 위치와 내용	참조된 Source	비고
gift-config.ConfigMap.data.KAKAO_REDIRECT_URI = http://localhost:8080/members/login/oauth2/code/kakao	source_5	카카오 리다이렉트 URI
gift-config.ConfigMap.data.FRONT_DOMAIN = http://localhost:8080	source_5	프론트 도메인
api-gateway.Deployment.metadata.name = api-gateway	source_1	Deployment 이름
api-gateway.Deployment.metadata.labels.app = api-gateway	source_11	공통 라벨: 앱
api-gateway.Deployment.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
api-gateway.Deployment.metadata.labels.tier = backend	source_11	공통 라벨: 티어
api-gateway.Deployment.spec.replicas = 1	source_6	레플리카 수
api-gateway.Deployment.spec.selector.matchLabels.app = api-gateway	source_11	셀렉터 라벨
api-gateway.Deployment.spec.template.metadata.labels.app = api-gateway	source_11	파드 라벨: 앱
api-gateway.Deployment.spec.template.metadata.labels.project = gift-service	source_11	파드 라벨: 프로젝트
api-gateway.Deployment.spec.template.metadata.labels.tier = backend	source_11	파드 라벨: 티어
api-gateway.Deployment.spec.template.spec.containers[0].image = sk124590/api-gateway:2.1	source_6	컨테이너 이미지
api-gateway.Deployment.spec.template.spec.containers[0].ports[0].containerPort = 8080	source_6	컨테이너 포트
api-gateway.Deployment.spec.template.spec.containers[0].resources.requests.cpu = 100m	source_6	요청 CPU
api-gateway.Deployment.spec.template.spec.containers[0].resources.requests.memory = 256Mi	source_6	요청 메모리
api-gateway.Deployment.spec.template.spec.containers[0].resources.limits.cpu = 500m	source_6	제한 CPU
api-gateway.Deployment.spec.template.spec.containers[0].resources.limits.memory = 512Mi	source_6	제한 메모리
api-gateway.Deployment.spec.template.spec.containers[0].envFrom[0].configMapRef.name = gift-config	source_5	환경변수 주입: ConfigMap
api-gateway.Deployment.spec.template.spec.containers[0].envFrom[1].secretRef.name = gift-secret	source_6	환경변수 주입: Secret

YAML 위치와 내용	참조된 Source	비고
api-gateway-svc.Service.metadata.name = api-gateway-svc	source_3	Service 이름
api-gateway-svc.Service.metadata.labels.app = api-gateway	source_11	공통 라벨: 앱
api-gateway-svc.Service.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
api-gateway-svc.Service.metadata.labels.tier = backend	source_11	공통 라벨: 티어
api-gateway-svc.Service.spec.ports[0].port = 8080	source_3	서비스 포트
api-gateway-svc.Service.spec.ports[0].targetPort = 8080	source_6	타겟 포트
api-gateway-svc.Service.spec.selector.app = api-gateway	source_11	셀렉터 라벨
api-gateway-svc.Service.spec.type = ClusterIP	source_12	서비스 타입
user-service.Deployment.metadata.name = user-service	source_1	Deployment 이름
user-service.Deployment.metadata.labels.app = user-service	source_11	공통 라벨: 앱
user-service.Deployment.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
user-service.Deployment.metadata.labels.tier = backend	source_11	공통 라벨: 티어
user-service.Deployment.spec.replicas = 1	source_8	레플리카 수
user-service.Deployment.spec.selector.matchLabels.app = user-service	source_11	셀렉터 라벨
user-service.Deployment.spec.template.metadata.labels.app = user-service	source_11	파드 라벨: 앱
user-service.Deployment.spec.template.metadata.labels.project = gift-service	source_11	파드 라벨: 프로젝트
user-service.Deployment.spec.template.metadata.labels.tier = backend	source_11	파드 라벨: 티어
user-service.Deployment.spec.template.spec.containers[0].image = sk124590/user-service:2.1	source_8	컨테이너 이 미지
user-service.Deployment.spec.template.spec.containers[0].ports[0].containerPort = 8084	source_8	컨테이너 포 트
user-service.Deployment.spec.template.spec.containers[0].resources.requests.cpu = 150m	source_8	요청 CPU
user-service.Deployment.spec.template.spec.containers[0].resources.requests.memory = 512Mi	source_8	요청 메모리

YAML 위치와 내용	참조된 Source	비고
user-service.Deployment.spec.template.spec.containers[0].resources.limits.cpu = 1000m	source_8	제한 CPU
user-service.Deployment.spec.template.spec.containers[0].resources.limits.memory = 1Gi	source_8	제한 메모리
user-service.Deployment.spec.template.spec.containers[0].envFrom[0].configMapRef.name = gift-config	source_5	환경변수 주입: ConfigMap
user-service.Deployment.spec.template.spec.containers[0].envFrom[1].secretRef.name = gift-secret	source_8	환경변수 주입: Secret
user-service-svc.Service.metadata.name = user-service-svc	source_3	Service 이름
user-service-svc.Service.metadata.labels.app = user-service	source_11	공통 라벨: 앱
user-service-svc.Service.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
user-service-svc.Service.metadata.labels.tier = backend	source_11	공통 라벨: 티어
user-service-svc.Service.spec.ports[0].port = 8084	source_3	서비스 포트
user-service-svc.Service.spec.ports[0].targetPort = 8084	source_8	타겟 포트
user-service-svc.Service.spec.selector.app = user-service	source_11	셀렉터 라벨
user-service-svc.Service.spec.type = ClusterIP	source_12	서비스 타입
product-service.Deployment.metadata.name = product-service	source_1	Deployment 이름
product-service.Deployment.metadata.labels.app = product-service	source_11	공통 라벨: 앱
product-service.Deployment.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
product-service.Deployment.metadata.labels.tier = backend	source_11	공통 라벨: 티어
product-service.Deployment.spec.replicas = 1	source_11	레플리카 수
product-service.Deployment.spec.selector.matchLabels.app = product-service	source_11	셀렉터 라벨
product-service.Deployment.spec.template.metadata.labels.app = product-service	source_11	파드 라벨: 앱
product-service.Deployment.spec.template.metadata.labels.project = gift-service	source_11	파드 라벨: 프로젝트

YAML 위치와 내용	참조된 Source	비고
product-service.Deployment.spec.template.metadata.labels.tier = backend	source_11	파드 라벨: 티어
product-service.Deployment.spec.template.spec.containers[0].image = sk124590/product-service:2.1	source_10	컨테이너 이미지
product-service.Deployment.spec.template.spec.containers[0].ports[0].containerPort = 8081	source_10	컨테이너 포트
product-service.Deployment.spec.template.spec.containers[0].resources.requests.cpu = 150m	source_10	요청 CPU
product-service.Deployment.spec.template.spec.containers[0].resources.requests.memory = 512Mi	source_10	요청 메모리
product-service.Deployment.spec.template.spec.containers[0].resources.limits.cpu = 1000m	source_10	제한 CPU
product-service.Deployment.spec.template.spec.containers[0].resources.limits.memory = 1Gi	source_10	제한 메모리
product-service-svc.Service.metadata.name = product-service-svc	source_3	Service 이름
product-service-svc.Service.metadata.labels.app = product-service	source_11	공통 라벨: 앱
product-service-svc.Service.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
product-service-svc.Service.metadata.labels.tier = backend	source_11	공통 라벨: 티어
product-service-svc.Service.spec.ports[0].port = 8081	source_3	서비스 포트
product-service-svc.Service.spec.ports[0].targetPort = 8081	source_10	타겟 포트
product-service-svc.Service.spec.selector.app = product-service	source_11	셀렉터 라벨
product-service-svc.Service.spec.type = ClusterIP	source_12	서비스 타입
wish-service.Deployment.metadata.name = wish-service	source_1	Deployment 이름
wish-service.Deployment.metadata.labels.app = wish-service	source_11	공통 라벨: 앱
wish-service.Deployment.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
wish-service.Deployment.metadata.labels.tier = backend	source_11	공통 라벨: 티어
wish-service.Deployment.spec.replicas = 1	source_4	레플리카 수

YAML 위치와 내용	참조된 Source	비고
wish-service.Deployment.spec.selector.matchLabels.app = wish-service	source_11	셀렉터 라벨
wish-service.Deployment.spec.template.metadata.labels.app = wish-service	source_11	파드 라벨: 앱
wish-service.Deployment.spec.template.metadata.labels.project = gift-service	source_11	파드 라벨: 프로젝트
wish-service.Deployment.spec.template.metadata.labels.tier = backend	source_11	파드 라벨: 티어
wish-service.Deployment.spec.template.spec.containers[0].image = sk124590/wish-service:2.1	source_4	컨테이너 이미지
wish-service.Deployment.spec.template.spec.containers[0].ports[0].containerPort = 8082	source_4	컨테이너 포트
wish-service.Deployment.spec.template.spec.containers[0].resources.requests.cpu = 100m	source_4	요청 CPU
wish-service.Deployment.spec.template.spec.containers[0].resources.requests.memory = 512Mi	source_4	요청 메모리
wish-service.Deployment.spec.template.spec.containers[0].resources.limits.cpu = 700m	source_4	제한 CPU
wish-service.Deployment.spec.template.spec.containers[0].resources.limits.memory = 1Gi	source_4	제한 메모리
wish-service.Deployment.spec.template.spec.containers[0].envFrom[0].configMapRef.name = gift-config	source_5	환경변수 주입: ConfigMap
wish-service-svc.Service.metadata.name = wish-service-svc	source_3	Service 이름
wish-service-svc.Service.metadata.labels.app = wish-service	source_11	공통 라벨: 앱
wish-service-svc.Service.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
wish-service-svc.Service.metadata.labels.tier = backend	source_11	공통 라벨: 티어
wish-service-svc.Service.spec.ports[0].port = 8082	source_3	서비스 포트
wish-service-svc.Service.spec.ports[0].targetPort = 8082	source_4	타겟 포트
wish-service-svc.Service.spec.selector.app = wish-service	source_11	셀렉터 라벨
wish-service-svc.Service.spec.type = ClusterIP	source_12	서비스 타입
order-service.Deployment.metadata.name = order-service	source_1	Deployment 이름

YAML 위치와 내용	참조된 Source	비고
order-service.Deployment.metadata.labels.app = order-service	source_11	공통 라벨: 앱
order-service.Deployment.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
order-service.Deployment.metadata.labels.tier = backend	source_11	공통 라벨: 티어
order-service.Deployment.spec.replicas = 1	source_7	레플리카 수
order-service.Deployment.spec.selector.matchLabels.app = order-service	source_11	셀렉터 라벨
order-service.Deployment.spec.template.metadata.labels.app = order-service	source_11	파드 라벨: 앱
order-service.Deployment.spec.template.metadata.labels.project = gift-service	source_11	파드 라벨: 프로젝트
order-service.Deployment.spec.template.metadata.labels.tier = backend	source_11	파드 라벨: 티어
order-service.Deployment.spec.template.spec.containers[0].image = sk124590/order-service:2.1	source_7	컨테이너 이미지
order-service.Deployment.spec.template.spec.containers[0].ports[0].containerPort = 8083	source_7	컨테이너 포트
order-service.Deployment.spec.template.spec.containers[0].resources.requests.cpu = 100m	source_7	요청 CPU
order-service.Deployment.spec.template.spec.containers[0].resources.requests.memory = 512Mi	source_7	요청 메모리
order-service.Deployment.spec.template.spec.containers[0].resources.limits.cpu = 700m	source_7	제한 CPU
order-service.Deployment.spec.template.spec.containers[0].resources.limits.memory = 1Gi	source_7	제한 메모리
order-service.Deployment.spec.template.spec.containers[0].envFrom[0].configMapRef.name = gift-config	source_5	환경변수 주입: ConfigMap
order-service.Deployment.spec.template.spec.containers[0].envFrom[1].secretRef.name = gift-secret	source_7	환경변수 주입: Secret
order-service-svc.Service.metadata.name = order-service-svc	source_3	Service 이름
order-service-svc.Service.metadata.labels.app = order-service	source_11	공통 라벨: 앱

YAML 위치와 내용	참조된 Source	비고
order-service-svc.Service.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
order-service-svc.Service.metadata.labels.tier = backend	source_11	공통 라벨: 티어
order-service-svc.Service.spec.ports[0].port = 8083	source_3	서비스 포트
order-service-svc.Service.spec.ports[0].targetPort = 8083	source_7	타겟 포트
order-service-svc.Service.spec.selector.app = order-service	source_11	셀렉터 라벨
order-service-svc.Service.spec.type = ClusterIP	source_12	서비스 타입
gift-app.Deployment.metadata.name = gift-app	source_1	Deployment 이름
gift-app.Deployment.metadata.labels.app = gift-app	source_11	공통 라벨: 앱
gift-app.Deployment.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
gift-app.Deployment.metadata.labels.tier = frontend	source_11	공통 라벨: 티어
gift-app.Deployment.spec.replicas = 1	source_10	레플리카 수
gift-app.Deployment.spec.selector.matchLabels.app = gift-app	source_11	셀렉터 라벨
gift-app.Deployment.spec.template.metadata.labels.app = gift-app	source_11	파드 라벨: 앱
gift-app.Deployment.spec.template.metadata.labels.project = gift-service	source_11	파드 라벨: 프로젝트
gift-app.Deployment.spec.template.metadata.labels.tier = frontend	source_11	파드 라벨: 티어
gift-app.Deployment.spec.template.spec.containers[0].image = sk124590/gift-app:2.1	source_10	컨테이너 이미지
gift-app.Deployment.spec.template.spec.containers[0].ports[0].containerPort = 8085	source_10	컨테이너 포트
gift-app.Deployment.spec.template.spec.containers[0].resources.requests.cpu = 100m	source_10	요청 CPU
gift-app.Deployment.spec.template.spec.containers[0].resources.requests.memory = 512Mi	source_10	요청 메모리
gift-app.Deployment.spec.template.spec.containers[0].resources.limits.cpu = 500m	source_10	제한 CPU
gift-app.Deployment.spec.template.spec.containers[0].resources.limits.memory = 1Gi	source_10	제한 메모리

YAML 위치와 내용	참조된 Source	비고
gift-app.Deployment.spec.template.spec.containers[0].envFrom[0].configMapRef.name = gift-config	source_5	환경변수 주입: ConfigMap
gift-app.Deployment.spec.template.spec.containers[0].envFrom[1].secretRef.name = gift-secret	source_10	환경변수 주입: Secret
gift-app-svc.Service.metadata.name = gift-app-svc	source_12	Service 이름
gift-app-svc.Service.metadata.labels.app = gift-app	source_11	공통 라벨: 앱
gift-app-svc.Service.metadata.labels.project = gift-service	source_11	공통 라벨: 프로젝트
gift-app-svc.Service.metadata.labels.tier = frontend	source_11	공통 라벨: 티어
gift-app-svc.Service.spec.ports[0].port = 8080	source_12	서비스 포트
gift-app-svc.Service.spec.ports[0].targetPort = 8085	source_10	타겟 포트
gift-app-svc.Service.spec.selector.app = gift-app	source_11	셀렉터 라벨
gift-app-svc.Service.spec.type = LoadBalancer	source_12	서비스 타입