

```

apiVersion: v1
kind: Secret
metadata:
  name: gift-secret
  labels:
    app: gift-service
    project: gift-service
    tier: backend
# 민감 정보를 Base64로 인코딩하여 저장합니다.
data:
  JWT_SECRET: WW4ya2ppYmRkRkFXdG5QSjJBmRmxMOFdybW9oSk1Ddm1nUWdnYUV5cGE1RT0=
  KAKAO_CLIENT_ID: YWMYMGQ4NGY5N2I2NzlmMGJiZDlhODA2NWJhODIzZjM=
  KAKAO_CLIENT_SECRET: RnczSm1MNVBrcGV2WFZaOU9pVk04YmZiZ0hVUEQ1RUE=
---
apiVersion: v1
kind: ConfigMap
metadata:
  name: gift-config
  labels:
    app: gift-service
    project: gift-service
    tier: backend
data:
  SERVICE_PRODUCT_URI: http://product-service-svc:8081
  KAKAO_REDIRECT_URI: http://localhost:8080/members/login/oauth2/code/kakao
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: api-gateway
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
spec:
  replicas: 1 # From source_7
  selector:
    matchLabels:
      app: api-gateway
  template:
    metadata:
      labels:
        app: api-gateway
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: api-gateway
          image: sk124590/api-gateway:2.1
          ports:
            - containerPort: 8080
          env:

```

```

- name: SERVICE_USER_URI
  valueFrom:
    configMapKeyRef:
      name: gift-config
      key: SERVICE_USER_URI
- name: SERVICE_PRODUCT_URI
  valueFrom:
    configMapKeyRef:
      name: gift-config
      key: SERVICE_PRODUCT_URI
- name: SERVICE_WISH_URI
  valueFrom:
    configMapKeyRef:
      name: gift-config
      key: SERVICE_WISH_URI
- name: SERVICE_ORDER_URI
  valueFrom:
    configMapKeyRef:
      name: gift-config
      key: SERVICE_ORDER_URI
- name: JWT_SECRET
  valueFrom:
    secretKeyRef:
      name: gift-secret
      key: JWT_SECRET
resources:
  requests:
    cpu: "100m"
    memory: "256Mi"
  limits:
    cpu: "500m"
    memory: "512Mi"
---
apiVersion: v1
kind: Service
metadata:
  name: api-gateway-svc
  labels:
    app: api-gateway
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  ports:
    - port: 8080
      targetPort: 8080
  selector:
    app: api-gateway
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: user-service
  labels:

```

```
  app: user-service
  project: gift-service
  tier: backend
spec:
  replicas: 1 # From source_5
  selector:
    matchLabels:
      app: user-service
  template:
    metadata:
      labels:
        app: user-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: user-service
          image: sk124590/user-service:2.1
          ports:
            - containerPort: 8084
          env:
            - name: KAKAO_REDIRECT_URI
              valueFrom:
                configMapKeyRef:
                  name: gift-config
                  key: KAKAO_REDIRECT_URI
            - name: JWT_SECRET
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: JWT_SECRET
            - name: KAKAO_CLIENT_ID
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_ID
            - name: KAKAO_CLIENT_SECRET
              valueFrom:
                secretKeyRef:
                  name: gift-secret
                  key: KAKAO_CLIENT_SECRET
      resources:
        requests:
          cpu: "100m"
          memory: "512Mi"
        limits:
          cpu: "700m"
          memory: "1Gi"
  ---
apiVersion: v1
kind: Service
metadata:
  name: user-service-svc
  labels:
```

```
  app: user-service
  project: gift-service
  tier: backend
spec:
  type: ClusterIP
  ports:
    - port: 8084
      targetPort: 8084
  selector:
    app: user-service
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: product-service
  labels:
    app: product-service
    project: gift-service
    tier: backend
spec:
  replicas: 1 # From source_8
  selector:
    matchLabels:
      app: product-service
  template:
    metadata:
      labels:
        app: product-service
        project: gift-service
        tier: backend
    spec:
      containers:
        - name: product-service
          image: sk124590/product-service:2.1
          ports:
            - containerPort: 8081
          resources:
            requests:
              cpu: "150m"
              memory: "512Mi"
            limits:
              cpu: "1000m"
              memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: product-service-svc
  labels:
    app: product-service
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
```

```
ports:
- port: 8081
  targetPort: 8081
selector:
  app: product-service
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: wish-service
  labels:
    app: wish-service
    project: gift-service
    tier: backend
spec:
  replicas: 1 # From source_4
  selector:
    matchLabels:
      app: wish-service
  template:
    metadata:
      labels:
        app: wish-service
        project: gift-service
        tier: backend
    spec:
      containers:
      - name: wish-service
        image: sk124590/wish-service:2.1
        ports:
        - containerPort: 8082
        env:
        - name: SERVICE_PRODUCT_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_PRODUCT_URI
      resources:
        requests:
          cpu: "100m"
          memory: "512Mi"
        limits:
          cpu: "700m"
          memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: wish-service-svc
  labels:
    app: wish-service
    project: gift-service
    tier: backend
spec:
```

```
type: ClusterIP
ports:
- port: 8082
  targetPort: 8082
selector:
  app: wish-service
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: order-service
  labels:
    app: order-service
    project: gift-service
    tier: backend
spec:
  replicas: 1 # From source_6
  selector:
    matchLabels:
      app: order-service
  template:
    metadata:
      labels:
        app: order-service
        project: gift-service
        tier: backend
    spec:
      containers:
      - name: order-service
        image: sk124590/order-service:2.1
        ports:
        - containerPort: 8083
        env:
        - name: SERVICE_PRODUCT_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_PRODUCT_URI
        - name: SERVICE_WISH_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_WISH_URI
        - name: SERVICE_USER_URI
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: SERVICE_USER_URI
        - name: FRONT_DOMAIN
          valueFrom:
            configMapKeyRef:
              name: gift-config
              key: FRONT_DOMAIN
        - name: KAKAO_CLIENT_ID
```

```

      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: KAKAO_CLIENT_ID
    - name: KAKAO_CLIENT_SECRET
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: KAKAO_CLIENT_SECRET
  resources:
    requests:
      cpu: "100m"
      memory: "512Mi"
    limits:
      cpu: "500m"
      memory: "512Mi"
---
apiVersion: v1
kind: Service
metadata:
  name: order-service-svc
  labels:
    app: order-service
    project: gift-service
    tier: backend
spec:
  type: ClusterIP
  ports:
    - port: 8083
      targetPort: 8083
  selector:
    app: order-service
---
apiVersion: apps/v1
kind: Deployment
metadata:
  name: gift-app
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
spec:
  replicas: 1 # From source_10
  selector:
    matchLabels:
      app: gift-app
  template:
    metadata:
      labels:
        app: gift-app
        project: gift-service
        tier: frontend
    spec:
      containers:

```

```

- name: gift-app
  image: sk124590/gift-app:2.1
  ports:
    - containerPort: 8085
  env:
    - name: API_GATEWAY_URI
      valueFrom:
        configMapKeyRef:
          name: gift-config
          key: API_GATEWAY_URI
    - name: KAKAO_REDIRECT_URI
      valueFrom:
        configMapKeyRef:
          name: gift-config
          key: KAKAO_REDIRECT_URI
    - name: JWT_SECRET
      valueFrom:
        secretKeyRef:
          name: gift-secret
          key: JWT_SECRET
  resources:
    requests:
      cpu: "100m"
      memory: "512Mi"
    limits:
      cpu: "700m"
      memory: "1Gi"
---
apiVersion: v1
kind: Service
metadata:
  name: gift-app-svc
  labels:
    app: gift-app
    project: gift-service
    tier: frontend
spec:
  type: LoadBalancer # From source_11
  ports:
    - port: 8080
      targetPort: 8085
  selector:
    app: gift-app

```

YAML 위치와 내용	참조된 Source	비고
api-gateway.Deployment.spec.replicas = 1	source_7	api-gateway 배포의 복제 수 값 참조
user-service.Deployment.spec.replicas = 1	source_5	user-service 배포의 복제 수 값 참조



YAML 위치와 내용	참조된 Source	비고
product-service.Deployment.spec.replicas = 1	source_8	product-service 배포의 복제 수 값 참조
wish-service.Deployment.spec.replicas = 1	source_4	wish-service 배포의 복제 수 값 참조
order-service.Deployment.spec.replicas = 1	source_6	order-service 배포의 복제 수 값 참조
gift-app.Deployment.spec.replicas = 1	source_10	gift-app 배포의 복제 수 값 참조
gift-app-svc.Service.spec.type = LoadBalancer	source_11	gift-app-svc 서비스 노출 유형 값 참조

특징: 배포 실패. configMap에 서비스 URI가 모두 정의되지 않아서 필요한 환경변수를 주입해주지 못함