Language Technology

Chapter 17: Transformers: Encoder-Decoder and Decoder

https://link.springer.com/chapter/10.1007/978-3-031-57549-5_17

Pierre Nugues

Pierre.Nugues@cs.lth.se

October 15, 2026



Machine Translation

Process of translating automatically a text from a source language into a target language
Started after the 2nd world war to translate documents from Russian to English
Early working systems from French to English in Canada
Renewed huge interest with the advent of the web
Google claims it has more than 500m users daily worldwide, with 103 languages.
Massive progress permitted by the encoder-decoder networks



Corpora for Machine Translation

Initial ideas in machine translation: use bilingual dictionaries and formalize grammatical rules to transfer them from a source language to a target language.
Statistical machine translation:

1. Use very large bilingual corpora;
2. Align the sentences or phrases, and
3. Given a sentence in the source language, find the matching sentence in the target language.

Pioneered at IBM on French and English with Bayesian statistics.
As of today, the encoder-decoder architecture is dominant




Parallel Corpora (Swiss Federal Law)


German	French	Italian
Art. 35 Milchtransport	**Art. 35 Transport du lait**	**Art. 35 Trasporto del latte**
1 Die Milch ist schonend und hygienisch in den Verarbeitungsbetrieb zu transportieren. Das Transportfahrzeug ist stets sauber zu halten. Zusammen mit der Milch dürfen keine Tiere und milchfremde Gegenstände transportiert werden, welche die Qualität der Milch beeinträchtigen können.	1 Le lait doit être transporté jusqu'à l'entreprise de transformation avec ménagement et conformément aux normes d'hygiène. Le véhicule de transport doit être toujours propre. Il ne doit transporter avec le lait aucun animal ou objet susceptible d'en altérer la qualité.	1 Il latte va trasportato verso l'azienda di trasformazione in modo accurato e igienico. Il veicolo adibito al trasporto va mantenuto pulito. Con il latte non possono essere trasportati animali e oggetti estranei, che potrebbero pregiudicarne la qualità.



Alignment (Brown et al. 1993)

Canadian Hansard








Transformers: The Encoder-Decoder

1. Transformers were originally developed for machine translation
2. Initial language pairs: English-French, English-German, and the reverse
3. The input corresponds to words in the source language (say English) and the output in the target language (French or German)



Generation

The transformer consists of an encoder and a decoder.

1. The encoder builds a representation of an input sequence, $(x_1, x_2, ..., x_n)$ called the memory, M,

$$\text{encoder}(x_1, x_2, ..., x_n) = M;$$

2. The decoder uses M and a start symbol <s> as first input. The decoder generates a new output and concatenates it until it generates a stop symbol, </s>:

$$\begin{aligned}
\text{decoder}(M, \text{<s>}) &= y'_1, \\
\text{decoder}(M, \text{<s>}, y'_1) &= y'_2, \\
\text{decoder}(M, \text{<s>}, y'_1, y'_2) &= y'_3, \\
&\dots \\
\text{decoder}(M, \text{<s>}, y'_1, y'_2, ..., y'_{p-1}) &= y'_p, \\
\text{decoder}(M, \text{<s>}, y'_1, y'_2, ..., y'_{p-1}, y'_p) &= \text{</s>}.
\end{aligned}$$



Example

For two source and target sequences of characters in English and French:

```
Source: ('H', 'e', 'l', 'l, 'o')
Target: ('B', 'o', 'n', 'j', 'o', 'u', 'r')
```

We first encode *Hello*, the source sequence:

$$\text{encoder}(H, e, l, l, o) = M;$$

Using M and <s>, we decode the target sequence:

$$\begin{aligned}
\text{decoder}(M, \texttt{<s>}) &= B, \\
\text{decoder}(M, \texttt{<s>}, B) &= o, \\
&\dots \\
\text{decoder}(M, \texttt{<s>}, B, o, n, j, o, u) &= r, \\
\text{decoder}(M, \texttt{<s>}, B, o, n, j, o, u, r) &= \texttt{</s>},
\end{aligned}$$




We would need a linear layer to map it to the character predictionn

Decoder (I)

The right part of the initial transformer
Same components:

1. Attention
2. Add and norm
3. Feed-forward




Decoder (II)

But:

1. Two attentions:
   1. **Masked** self-attention on the inputs
   2. **Cross-attention** with the encoded source
2. Second attention module:
   $Q = X_{\text{dec_sublayer}}$, $K = Y_{\text{enc}}$, $V = Y_{\text{enc}}$ with


$$\text{Attention}(Q, K, V) = \text{softmax}(\frac{QK^\intercal}{\sqrt{d_k}})V,$$

3. The decoder predicts the input shifted by one (linear and softmax)



Transformer Embeddings


- In Vaswani's paper, the input and output embeddings and the last linear module share the same matrix (weights)
- Same with BERT in the pretraining step for the input embeddings and last linear layer.
- See code: `https://github.com/google-research/bert/blob/master/run_pretraining.py#L240`)



Prediction with Characters

Translation pairs: (Source sentence, Target sentence)
For instance: (Hello, Bonjour), here with characters

1. Encoder input: *H e l l o*
2. Decoder input: *B o n j o u r* and the encoded *H e l l o*
3. Decoder output: *B o n j o u r* shifted by one to the left
4. We align the decoder strings with <s> and </s>



Training and Inference Steps

1 Training step

			Target output:	B	o	n	j	o	u	r	</s>
	↱	Encoded source:	⟶	↑	↑	↑	↑	↑	↑	↑	↑
Source input:	H e l l o		Target input:	<s>	B	o	n	j	o	u	r

2 Inference:

			Target output:	B	...	
	↱	Encoded source:	⟶	↑		
Source input:	H e l l o		Target input:	<s>	B	...



Vaswani's Attention Scores

The attention scores are scaled and normalized by the softmax function.

$$\text{softmax}(\frac{QK^\intercal}{\sqrt{d_k}}),$$

	i	must	go	back	to	my	ship	and	to	my	crew
i	0.36	0.05	0.07	0.05	0.04	0.19	0.01	0.02	0.04	0.19	0.01
must	0.14	0.20	0.10	0.06	0.11	0.10	0.03	0.05	0.11	0.10	0.02
go	0.18	0.09	0.14	0.09	0.08	0.13	0.02	0.04	0.08	0.13	0.02
back	0.14	0.05	0.09	0.19	0.08	0.12	0.03	0.06	0.08	0.12	0.03
to	0.11	0.11	0.09	0.09	0.15	0.08	0.04	0.07	0.15	0.08	0.03
my	0.19	0.03	0.05	0.04	0.03	0.29	0.01	0.02	0.03	0.29	0.01
ship	0.03	0.03	0.03	0.04	0.05	0.03	0.55	0.03	0.05	0.03	0.13
and	0.10	0.08	0.07	0.10	0.12	0.09	0.04	0.15	0.12	0.09	0.04
to	0.11	0.11	0.09	0.09	0.15	0.08	0.04	0.07	0.15	0.08	0.03
my	0.19	0.03	0.05	0.04	0.03	0.29	0.01	0.02	0.03	0.29	0.01
crew	0.06	0.05	0.05	0.06	0.05	0.06	0.21	0.04	0.05	0.06	0.31



Attention

We use these scores to compute the attention.

$$\text{Attention}(Q, K, Q) = \text{softmax}(\frac{QK^\intercal}{\sqrt{d_k}})V,$$

For *ship:*


```
attention_ship = (0.03 * embeddings_dict['i'] +
                  0.03 * embeddings_dict['must'] +
                  0.03 * embeddings_dict['go'] +
                  0.03 * embeddings_dict['back'] +
                  0.04 * embeddings_dict['to'] +
                  0.05 * embeddings_dict['my'] +
                  0.55 * embeddings_dict['ship'] +
                  0.03 * embeddings_dict['and'] +
                  0.05 * embeddings_dict['to'] +
                  0.03 * embeddings_dict['my'] +
                  0.13 * embeddings_dict['crew'])
```

where the *ship* vector received 13% of its value from *crew*
Is this possible in an autoregressive setting?



Decoder Masking

Masking is used in the training step of a decoder
We use an upper triangular matrix $U_{-\infty}$ to prevent a look ahead
We just replace the gray cells with -10^9 and keep the original values of the red cells



$$\text{MaskedAttention}(Q, K, V, U_{-\infty}) = \text{softmax}\left(\frac{QK^\intercal}{\sqrt{d_k}} + U_{-\infty}\right)V.$$



After Masking

The attention scores after masking.

	i	must	go	back	to	my	ship	and	to	my	crew
i	1.00	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**
must	0.42	0.58	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**
go	0.44	0.22	0.35	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**
back	0.29	0.11	0.19	0.40	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**
to	0.20	0.20	0.16	0.17	0.27	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**
my	0.30	0.05	0.08	0.07	0.04	0.45	**0.00**	**0.00**	**0.00**	**0.00**	**0.00**
ship	0.04	0.04	0.04	0.05	0.06	0.05	0.73	**0.00**	**0.00**	**0.00**	**0.00**
and	0.14	0.10	0.09	0.13	0.16	0.12	0.05	0.21	**0.00**	**0.00**	**0.00**
to	0.12	0.12	0.10	0.11	0.16	0.10	0.04	0.08	0.16	**0.00**	**0.00**
my	0.20	0.03	0.05	0.05	0.03	0.29	0.01	0.02	0.03	0.29	**0.00**
crew	0.06	0.05	0.05	0.06	0.05	0.06	0.21	0.04	0.05	0.06	0.31



Evaluating Translation

The standard metric to evaluate translation is the bilingual evaluation understudy (BLEU) algorithm
BLEU compares the machine translation of a sentence with a corresponding human translation.

- Based on the number of machine-translated words that appear in the human translation divided by the total number of words in the machine-translated sentence
- BLEU extends the computation to n-grams, up to 4, and scales it with a brevity penalty
- The final score is the average on the test set

Although very basic, studies have shown it correlates well with human judgement
Vaswani et al. (2017) reported BLEU scores of 41 for the French-English pair and of 26.4 for German-English



Code Example

Experiments:

- Jupyter Notebook: `17_01_masked_attention.ipynb`
- 6th laboratory on machine translation




Learning Rate

In other labs, we used a constant learning rate
Vaswani et al. (2017) used a variable rate:

$$\text{lrate} = d_{model}^{-0.5} \cdot \textbf{min}(\text{step_num}^{-0.5}, \text{step_num} \cdot \text{warmup_steps}^{-1.5})$$

where warmup_steps = 4000.





Label Smoothing

True labels and predictions:

$$\text{Truth:} \quad (0,0,1,0) \quad \text{Prediction:} \quad (0.1,0.2,0.4,0.3)$$

Cross-entropy loss we used so far:

$$\begin{aligned} -(0,0,1,0)\cdot\log(0.1,0.2,0.4,0.3) &= -(0\cdot\log 0.1+0\cdot\log 0.2+1\cdot\log 0.4+0\cdot\log 0.3) \\ &= -\log 0.4 \end{aligned}$$

Label smoothing: we dedicate a small amount to the wrong predictions:

$$(1-\epsilon)\mathbf{e}_i+\frac{\epsilon}{N_{\text{subwords}}-1}\sum_{j=1,j\neq i}^{N_{\text{subwords}}}\mathbf{e}_j,$$

Cross-entropy loss with $\epsilon=0.1$:

$$-\left(\frac{0.1}{3},\frac{0.1}{3},0.9,\frac{0.1}{3}\right)\cdot\log(0.1,0.2,0.4,0.3) = -\left(\frac{0.1}{3}\cdot\log 0.1+\frac{0.1}{3}\cdot\log 0.2+0.9\cdot\log 0.4+\frac{0.1}{3}\cdot\log 0.3\right)$$



Beam Search

1. In the 6th lab, you will use a greedy decoding: You keep the highest prediction
2. A beam search uses the N highest predictions at each step
3. You rank the prediction sequences (the paths) with the probability product
4. N is called the beam diameter



PyTorch Decoders

PyTorch has a class to create a decoder layer (https://pytorch.org/docs/stable/generated/torch.nn.TransformerDecoderLayer.html):

```
decoder_layer = nn.TransformerDecoderLayer(d_model, nheads)
dec_layer_output = decoder_layer(input, memory)
```

and another to create a stack of N layers (https://pytorch.org/docs/stable/generated/torch.nn.TransformerDecoder.html):

```
decoder = nn.TransformerDecoder(decoder_layer, num_layers)
```


```
decoder = nn.TransformerEncoder(decoder_layer, 6)
dec_output = decoder(input, memory)
```



Autoregressive Models

Reference papers:

1. GPT: *Improving Language Understanding by Generative Pre-Training* by Radford et al. (2018)
   https://cdn.openai.com/research-covers/language-unsupervised/language_understanding_paper.pdf
2. GPT-2: *Language Models are Unsupervised Multitask Learners* by Radford et al. (2018)
   https://cdn.openai.com/better-language-models/language_models_are_unsupervised_multitask_learners.pdf
3. Source code:
   - https://github.com/openai/gpt-2
   - https://github.com/karpathy/nanoGPT
   - https://github.com/karpathy/nanochat/




Transformer Decoder

Pretrained as an autoregressive language model:

$$P(\mathbf{x}) = \prod_{i=1}^{n} P(x_i | x_1, \ldots, x_{i-1}).$$

Note there is no cross-attention



Fine Tuning (I)

Fine-tuning applications in the first paper (GPT)




Figure 1: **(left)** Transformer architecture and training objectives used in this work. **(right)** Input transformations for fine-tuning on different tasks. We convert all structured inputs into token sequences to be processed by our pre-trained model, followed by a linear+softmax layer.

Fine Tuning (II)

The system in the second paper (GPT-2) is pretrained using the same objective function and a more general formulation:

$$P(\text{output}|\text{input})$$

Large corpora encapsulate more knowledge, such as examples of tasks:

$$P(\text{output}|\text{input}, \text{task})$$

Training examples in the second paper:

- translate to French, English text, French text;
- answer the question, document, question, answer



Prompts

Zero-shot

Task description	Translate English to French:
Prompt	cheese ⇒

One-shot

Task description	Translate English to French:
Example	sea otter ⇒ loutre de mer
Prompt	cheese ⇒

Few-shot

Task description	Translate English to French:
Example	sea otter ⇒ loutre de mer
Example	peppermint ⇒ menthe poivrée
Example	plush giraffe ⇒ girafe en peluche
Prompt	cheese ⇒



Prompt Engineering

Many techniques to write prompts
Follow the ones recommended by the language model
See for instance the guide on prompting: `https://huggingface.co/docs/transformers/main/en/tasks/prompting`
Leaderboards:


- Hugging Face `https://huggingface.co/spaces/open-llm-leaderboard/open_llm_leaderboard`
- LiveBench `https://livebench.ai`
- Artificial Analysis `https://artificialanalysis.ai/`

Why does it work? Two explanations:

- `https://x.com/fchollet/status/1709242747293511939`
- `https://arxiv.org/pdf/2212.07677`



Retrieval-Augmented Generation



Credit: Wikipedia, https://en.wikipedia.org/wiki/Retrieval-augmented_generation

- Paper: https://arxiv.org/pdf/2005.11401
- Benchmark: https://huggingface.co/spaces/mteb/leaderboard



Fine-Tuning Chat Decoders

Many large systems like chatGPT do not disclose their models.
The training procedure:

- Starts from an autoregressive decoder model pretrained on large corpora, see Llama (`https://arxiv.org/pdf/2302.13971`)
- Possibly train further the model on dedicated corpora: continued pretraining (`https://docs.unsloth.ai/basics/continued-pretraining`)
- Fined-tuned on instructions with the format: Instruction, Input, Output (`https://docs.unsloth.ai/get-started/fine-tuning-llms-guide`)



Fine-Tuning Strategies

Fine-tuning large models is difficult:

1. Refit all the parameters may destroy the model
2. Unfreeze selected layers is a popular method
3. Low Rank Adaptation (LoRA) has emerged as a key technique.
4. Source: https://arxiv.org/abs/2106.09685




Figure 1: Our reparametrization. We only train A and B.



Low Rank Adaptation

The idea is:

1. Fine-tune the attention matrices only: W^Q, W^K, W^V, and W^O
2. Simplify attention with one head: $W \in \mathbb{R}^{d_{\text{model}} \times d_{\text{model}}}$
3. Freeze the W pretrained matrices
4. Add them the product of two **trainable** low-rank matrices: A and B
5. $B \in \mathbb{R}^{d_{\text{model}} \times r}$ and $A \in \mathbb{R}^{r \times d_{\text{model}}}$ with $r = 4$ for instance
6. There are $2 \cdot r \cdot d_{\text{model}}$ parameters to adjust instead of $d_{\text{model}} \cdot d_{\text{model}}$
7. For an $\mathbf{x}$ input, the output is $W\mathbf{x} + BA\mathbf{x}$




Figure 1: Our reparametrization. We only train A and B.

Source: https://arxiv.org/abs/2106.09685



Human Feedback

1. Large companies often apply supervised fine-tuning, see `https://arxiv.org/pdf/2307.09288.pdf`
2. Instructions could be tedious to write though
3. Answers evaluated by humans and feedback incorporated by simple reinforcement learning: Reinforcement learning with human feedback (RLHF)
   - Start with annotated data on human preferences
   - Learn a policy
   - Let the policy rank the LLM answers
4. The ChatGPT method: `https://openai.com/index/chatgpt/`
5. See how to make a LLM nicer here: `https://github.com/ash80/RLHF_in_notebooks`
6. No unique solution: Rapidly developing field



Self-Instruct

We follow self-instruct from Wang et al. (2023) to minimize human effort:

- Starts with a seed of human-written instructions: less than 200. `https://github.com/yizhongw/self-instruct/blob/main/data/seed_tasks.jsonl`
- The model generates more output from the seed instructions. The autogenerated instructions amount to 50k

Fine-tuning using the

> *concatenat[ion of] the instruction and instance input as a prompt and train the model to generate the instance output in a standard supervised way.*

From Wang et al. (2023) (`https://arxiv.org/pdf/2212.10560.pdf`, `https://github.com/yizhongw/self-instruct`)



Seed Instructions

{"id": "seed_task_0",
"name": "breakfast_suggestion",
"instruction": "Is there anything I can eat for a breakfast that doesn't include eggs, yet includes protein, and has roughly 700-1000 calories?",
"instances": [
{"input": "",
"output": "Yes, you can have 1 oatmeal banana protein shake and 4 strips of bacon. The oatmeal banana protein shake may contain 1/2 cup oatmeal, 60 grams whey protein powder, 1/2 medium banana, 1tbsp flaxseed oil and 1/2 cup watter, totalling about 550 calories. The 4 strips of bacon contains about 200 calories."}],
"is_classification": false}



Self-Instruct

Self-instruct from Wang et al. (2023) (https://arxiv.org/pdf/2212.10560.pdf




Figure 2: A high-level overview of SELF-INSTRUCT. The process starts with a small seed set of tasks as the task pool. Random tasks are sampled from the task pool, and used to prompt an off-the-shelf LM to generate both new instructions and corresponding instances, followed by filtering low-quality or similar generations, and then added back to the initial repository of tasks. The resulting data can be used for the instruction tuning of the language model itself later to follow instructions better. Tasks shown in the figure are generated by GPT3.



Alpaca

Alpaca is another example:
`https://crfm.stanford.edu/2023/03/13/alpaca.html`

- Uses Llama and Llama 2 as autoregressive pretrained decoder model
- Fined-tuned on instructions with the format: Instruction, Input, Output




Corpus Choice

The corpus selection is very important in the quality of answers.


1. Usually starts a large sample of web pages; see LLama and LLama 2 `https://arxiv.org/pdf/2302.13971.pdf`
2. Deduplicates the pages (`https://aclanthology.org/2020.lrec-1.494.pdf`)
3. Computes the proximity with wikipedia and discard distant pages
4. Computes the perplexity with a wikipedia model and discard too simple and too complex sentences



The End?



Credits: https://essentiels.bnf.fr/fr/image/d1ed5fad-ac11-4295-a295-3f9898fb492b-1910-villemard-imagine-e



Οὐροβόρος

Claude writes a significant proportion of Anthropic's code. As of May 2026, more than 80% of the code we merge into Anthropic's codebase was authored by Claude. Before Claude Code launched in research preview in February 2025, this number was in the low single digits.

Source: `https://www.anthropic.com/institute/recursive-self-improvement`



Synesius?

Credits: Bibliothèque nationale de France. Wikipedia



ἓν τὸ πᾶν

Obscurum per obscurius
Ignotum per ignotius
Alchemical motto



Zosimos of Panopolis?
Credits: Biblioteca Marciana, Wikipedia

Ἔτι ἐπεὶ καὶ αὐτὸ τὸ ἓν πολλαχῶς λέγεται ὥσπερ καὶ τὸ ὄν, σκεπτέον τίνα τρόπον λέγουσιν εἶναι ἓν τὸ πᾶν.

"Again, 'one' itself, no less than 'being', is used in many senses, so we must consider in what sense the word is used when it is said that the **All is one***."*

Aristotle, *Physics* I, 2 (185b5)

