TÜV SÜD America Inc.
10040 Mesa Rim Road
San Diego, CA 92121

Phone: (858) 678-1400
Fax: (858) 546-0364
E-mail: info@tuvam.com
www.TUVamerica.com

ATTESTATION

Attestation Number: 72160895-ISO15500-3, Rev. N/A

Issued To: DK-Lok Corporation
7,Golden root-ro 129beon-gil, Juchon-myeon
Gimhae-si, Gyeongsangnam-do 50969
Republic of Korea

Standard: **Road vehicles – Compressed natural gas (CNG) fuel system components**

Part 3: Check Valve

Components: DK-Lok components in various shapes and sizes per annex 1 attached. The Service Pressure is 293 bar with an Operating Temperature range of -40°C to +120°C.

As an independent inspection agency, TÜV SÜD America attests that representative DK-Lok check valve in various shapes and sizes, per annex 1 attached, have met all the design and test qualification requirements of ISO 15500-3:2016.

These components were designed and tested for use with compressed natural gas. These components should be installed, used, and maintained in accordance with the manufacturer's instructions.

Prepared and approved by:

André Frégeau, MPM.
Manager Alternative Fuels
TÜV SÜD America,
Industry Service Division
08/02/2022.

TÜV SÜD America Inc.
10040 Mesa Rim Road
San Diego, CA 92121

Phone: (858) 678-1400
Fax: (858) 546-0364
E-mail: info@tuvam.com
www.TUVamerica.com

ATTESTATION

Attestation Number: 72160895-ISO15500-4, Rev. N/A

Issued To: DK-Lok Corporation
7,Golden root-ro 129beon-gil, Juchon-myeon
Gimhae-si, Gyeongsangnam-do 50969
Republic of Korea

Standard: **Road vehicles – Compressed natural gas (CNG) fuel system components**

Part 4: Manual Valve

Components: DK-Lok components in various shapes and sizes per annex 1 attached. The Service Pressure is 293 bar with an Operating Temperature range of -40°C to +120°C.

As an independent inspection agency, TÜV SÜD America attests that representative DK-Lok manual valve in various shapes and sizes, per annex 1 attached, have met all the design and test qualification requirements of ISO 15500-4:2020.

These components were designed and tested for use with compressed natural gas. These components should be installed, used, and maintained in accordance with the manufacturer's instructions.

Prepared and approved by:

André Frégeau, MPM.
Manager Alternative Fuels
TÜV SÜD America,
Industry Service Division
08/02/2022.

TÜV AMERICA INCORPORATED
TÜV SÜD AMERICA

TÜV SÜD America Inc.
10040 Mesa Rim Road
San Diego, CA 92121

Phone: (858) 678-1400
Fax: (858) 546-0364
E-mail: info@tuvam.com
www.TUVamerica.com

ATTESTATION

Attestation Number: 72160895-ISO15500-12, Rev. N/A

Issued To: DK-Lok Corporation
7,Golden root-ro 129beon-gil, Juchon-myeon
Gimhae-si, Gyeongsangnam-do 50969
Republic of Korea

Standard: **Road vehicles – Compressed natural gas (CNG) fuel system components**

Part 12: Pressure Relief Valve

Components: DK-Lok components in various shapes and sizes per annex 1 attached. The Service Pressure is 322,8 bar with an Operating Temperature range of -40°C to +120°C.

As an independent inspection agency, TÜV SÜD America attests that representative DK-Lok pressure relief valve in various shapes and sizes, per annex 1 attached, have met all the design and test qualification requirements of ISO 15500-12:2015.

These components were designed and tested for use with compressed natural gas. These components should be installed, used, and maintained in accordance with the manufacturer's instructions.

Prepared and approved by:

André Frégeau, MPM.
Manager Alternative Fuels
TÜV SÜD America,
Industry Service Division
08/02/2022.

TÜV AMERICA INCORPORATED
TÜV SÜD AMERICA

TÜV SÜD America Inc.
10040 Mesa Rim Road
San Diego, CA 92121

Phone: (858) 678-1400
Fax: (858) 546-0364
E-mail: info@tuvam.com
www.TUVamerica.com

ATTESTATION

Attestation Number: 72160895-ISO15500-18, Rev. N/A

Issued To: DK-Lok Corporation
7,Golden root-ro 129beon-gil, Juchon-myeon
Gimhae-si, Gyeongsangnam-do 50969
Republic of Korea

Standard: **Road vehicles – Compressed natural gas (CNG) fuel system components**

Part 18: Filter

Components: DK-Lok components in various shapes and sizes per annex 1 attached. The Service Pressure is 293 bar with an Operating Temperature range of -40°C to +120°C.

As an independent inspection agency, TÜV SÜD America attests that representative DK-Lok filer in various shapes and sizes, per annex 1 attached, have met all the design and test qualification requirements of ISO 15500-18:2016.

These components were designed and tested for use with compressed natural gas. These components should be installed, used, and maintained in accordance with the manufacturer's instructions.

Prepared and approved by:

André Frégeau, MPM.
Manager Alternative Fuels
TÜV SÜD America,
Industry Service Division
08/02/2022.