



No. SPVDC-1
DEC.2022

Low Pressure Pneumatic Switch Diaphragm Valves Standard Type

Features

- Maximum flow & Compact designed inner capacity.
- Minimal contributions of moisture, Oxygen and Hydrocarbon, Minimal particle generation.
- DK-LOK's own electropolished.
- DI water cleaned, assembled, tested & packaged in the certified clean room.
- PCTFE seat material with remarkable chemical & thermal resistance.
- Valve counter possible via switch



Specification

Size	1/4"	3/8", 1/2"	3/4"
Cv Value	0.3	0.7	0.7
Max. Working Pressure	10 bar (145 psig)		
Max. Working Temperature	PCTFE : -10° ~ 80°C		
Actuator Pressure Ration	4 ~ 6 bar (58 ~ 87 psig)		
Internal Leakage Allowance – He Holding Time ≥ 15 sec	≤ 1x10 ⁻⁹ atm.cc/s		
External Leakage Allowance – He Holding Time ≥ 1 min	≤ 1x10 ⁻⁹ atm.cc/s		
Particle Inspection (EP Only) Pressure : 60~80psi N2 Gas Sample Volume : 1CFM 0.1 μm and Larger	No count		

Product Grade

Level	AP	BA	EP
Inner Surface Roughness	Ry ≤ 25 μm	Ry ≤ 3.0 μm / Ra 10μin	Ry ≤ 0.7 μm / Ra 5μin
	Cut off Length : 2.5mm	Cut off Length : 0.8mm	Cut off Length : 0.25mm
	Measuring Length : 12.5mm	Measuring Length : 4mm	Measuring Length : 1.25mm
Polishing	Machining Finish	Machining Finish	Electro Polishing Finish


Material of Construction

Description	Materials
Body	316L Stainless Steel
	316L Stainless Steel VAR
Seat	PCTFE
Diaphragm	Ni-Co Alloy, Ni Alloy C22
Actuator	Aluminum

Specifications

Switch Specification	
Working Voltage	DC5 ~ 24V
Steady State Current	≤ 10mA
instantaneous Current	≤ 20mA
Operation Type	Normal Open
Code Length	3m

Switch Circuit Diagram(NO)



- Wetted Components are listed in [blue](#)

Ordering Information and Dimensions

Model	Basic Ordering Number	End Connections	Dimensions (mm)							
			L	h	H	A	B	C	D	ℓ
	U-SPVDC4-DM-	1/4" DCR Male	57	11	67	42	25.4	26	27.2	-
	U-SPVDC8-DM-	1/2" DCR Male	76.2	16	83.8	55	28	37	27.2	-
	U-SPVDC12-DM-	3/4" DCR Male	122	22	89.8	55	28	37	27.2	-
	U-SPVDC4-DF-	1/4" DCR Female	70.6	11	67	42	25.4	26	27.2	-
	U-SPVDC8-DF-	1/2" DCR Female	83	16	83.8	55	28	37	27.2	-
	U-SPVDC12-DF-	3/4" DCR Female	122	22	89.8	55	28	37	27.2	-
	U-SPVDC4-DK-	1/4" DK-LOK	69.5	11	67	42	25.4	26	27.2	55
	U-SPVDC6-DK-	3/8" DK-LOK	82.5	16	83.8	55	28	37	27.2	68
	U-SPVDC8-DK-	1/2" DK-LOK	91	16	83.8	55	28	37	27.2	70
	U-SPVDC12-DK-	3/4" DK-LOK	106	22	89.8	55	28	37	27.2	84
	U-SPVDC4-TW-	1/4" Tube Butt Weld	54	11	67	42	25.4	26	27.2	-
	U-SPVDC6-TW-	3/8" Tube Butt Weld	69	16	83.8	55	28	37	27.2	-
	U-SPVDC8-TW-	1/2" Tube Butt Weld	69	16	83.8	55	28	37	27.2	-
	U-SPVDC12-TW-	3/4" Tube Butt Weld	150	22	89.8	55	28	37	27.2	-

How to order

U	-	SPVDC	-	4	-	DM	-	SL	-	B	-	X
DK-LOK UHP Product		Valve Type		Size		End Connector Type		Material		Inner Surface Level		User Option

Valve Type	Size	End Connector Type	Material	Surface Level	User Option
SPVDC	4 : 1/4"	DM : DCR Male	SL : 316L Stainless Steel	B : BA Grade	Blank : Standard
	6 : 3/8"	DF : DCR Female	DL : 316L Stainless Steel VAR	P : EP Grade	X : Customization No.
	8 : 1/2"	DK : DK-LOK			
	12 : 3/4"	TW : Tube Butt Weld			

Note) DCR : DK-Metal Face Seal

Safe Valve Selection

The selection of a valve for any application or system design must be considered to ensure safe performance. Valve function, valve rating, material compatibility, proper installation, operation and maintenance remain the sole responsibility of the system designer and the user. DK-Lok accepts no liability for any improper selection, installation, operation or maintenance.

© Copyright 2017. All Rights Reserved.

 Fittings & Valves www.dklok.com	DK-LOK Corporation Mailing Address 7, Golden root-ro 129beon-gil, Juchon-myeon, Gimhae-si, Gyeongsangnam-do, South Korea 621-842	DK-Lok contact information		For International customers	
		Tel. (82) 55-338-0114	Tel. (82) 55-338-0031/2	Fax. (82) 55-901-0143	Fax. (82) 55-901-0142
		E-mail : sales@dklok.com		E-mail : dklok@dklok.com	