



# ORIENT

## Photo coupler

### Product Data Sheet

Part Number: OR-M302X(L)/M305X(L)/M307X(L)

Customer: \_\_\_\_\_

Date: \_\_\_\_\_

**SHENZHEN ORIENT COMPONENTS CO., LTD**

Block A 3rd Floor No.4 Building, Tian'an Cyber Park, Huangge Rd, LongGang Dist, Shenzhen, GD

TEL: 0755-29681816

FAX: 0755-29681200

[www.orient-opto.com](http://www.orient-opto.com)

## 1. Features

- (1) High isolation voltage between input and output (Viso:3750 V rms )
- (2) 4pin non zero-cross optoisolators triac driver output
- (3) High repetitive peak off-state voltage VDRM :  
M302X: Min. 400V, M305X: Min. 600V, M307X: Min. 800V
- (4) High critical rate of rise of off-state voltage dv/dt :  
M302X: Typ. 100V /  $\mu$ s , M305X/M307X:MIN . 1000V /  $\mu$ s
- (5) Tape and reel packaging.
- (6) Operating temperature -40 °C to +110 °C
- (7) Safety approval  
UL approved(No.E323844)  
VDE approved(No.40029733)  
CQC approved (No.CQC19001231256 )
- (8) In compliance with RoHS, REACH standards
- (9) MSL Class I




## 2. Description

The OR-M302X(L)/M305X(L)/M307X(L) consists of a non zero crossing photo triac, optically coupled to a gallium arsenide infrared emitting diode. They are housed in the SOP-4 package and guarantees insulation thickness. Therefore, they meet the reinforced insulation class requirements of international safety standards.

## 3. Application Range

- |                       |                          |                      |
|-----------------------|--------------------------|----------------------|
| •AC Motor Drives      | •AC Motor Starters       | •Static power switch |
| •Lighting Controls    | •Solenoid/Valve Controls | •Solid State Relays  |
| •Temperature Controls |                          |                      |

## 4. Functional Diagram



## 5. Absolute Maximum Ratings (Ta=25°C)

Parameter			Symbol	Rated Value	Unit
Input	Forward Current		I <sub>F</sub>	50	mA
	Junction Temperature		T <sub>J</sub>	125	°C
	Reverse Voltage		V <sub>R</sub>	6	V
	Power Dissipation		P	100	mW
Output	Off-State Output Terminal Voltage	OR-M302X	V <sub>DRM</sub>	400	V
		OR-M305X		600	
		OR-M307X		800	
	On state RMS current		I <sub>T(RMS)</sub>	100	mA(RMS)
	Peak Repetitive Surge Current (PW=1ms, 120 pps)		I <sub>TSM</sub>	1	A
	Junction Temperature		T <sub>J</sub>	125	°C
	Collector Power Dissipation		P <sub>C</sub>	300	mW
	Total Power Dissipation			P <sub>tot</sub>	330
*1 Insulation Voltage			V <sub>iso</sub>	3750	Vrms
Working Temperature			T <sub>opr</sub>	-40 ~ + 110	°C
Deposit Temperature			T <sub>stg</sub>	-55 ~ + 125	
*2 Soldering Temperature			T <sub>sol</sub>	260	

Notes:

\*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2&3 are shorted together, and pins 4, 6 are shorted together.

\* 2 For 10 seconds

## 6. Electrical Optical Characteristics at Ta=25°C

Parameter			Symbol	Min	Typ.*	Max	Unit	Condition
Input	Forward Voltage		$V_F$	---	1.2	1.6	V	$I_F=10\text{mA}$
	Reverse Current		$I_R$	---	---	5	$\mu\text{A}$	$V_R=6\text{V}$
Output	*1.Peak Blocking Current, Either Direction		$I_{\text{DRM}}$	---	10	100	nA	$V_{\text{DRM}} = \text{Rated } V_{\text{DRM}}$
	Peak On-State Voltage, Either Direction		$V_{\text{TM}}$	---	---	2.5	V	$I_{\text{TM}}=100\text{mA}$ Peak
	*2.Critical rate of Rise of Off-State Voltage	OR-M302X	$dv/dt$	---	100	---	$\text{V}/\mu\text{s}$	$V_{\text{in}}=240\text{Vrms}$
		OR-M305X OR-M307X		1000	---	---		
Transfer Characteristics	*3.Led Trigger Current, Current Required to Latch Output, Either Direction	OR-M3020 OR-M3050 OR-M3070	$I_{\text{FT}}$	---	---	30	mA	Main Terminal Voltage = 3V
		OR-M3021 OR-M3051 OR-M3071		---	---	15		
		OR-M3022 OR-M3052 OR-M3072		---	---	10		
		OR-M3023 OR-M3053 OR-M3073		---	---	5		
		OR-M3024 OR-M3054 OR-M3074		---	---	3		
	Holding Current, Either Direction		$I_H$	0.5	1.0	5.0	mA	
	Turn-On Time		$T_{\text{on}}$	---	---	100	$\mu\text{s}$	$V_D=6\text{V}$ $R_L=100\Omega$ $I_F=20\text{mA}$

\*1. Test voltage must be applied within  $dv/dt$  rating.

\*2. This is static  $dv/dt$ . Commutating  $dv/dt$  is a function of the load-driving thyristor(s) only.

\*3. All devices are guaranteed to trigger at an  $I_F$  value less than or equal to max  $I_{\text{FT}}$ . Therefore, recommended operating  $I_F$  lies between max  $I_{\text{FT}}$ , 30 mA for OR-M3020 and OR-M3050, 15 mA for OR-M3021 and OR-M3051, 10 mA for OR-M3022 and OR-M3052, 5 mA for OR-M3023 and OR-M3053, 3 mA for OR-M3024 and OR-M3054, and absolute max  $I_F$  (50mA).



## 7. Order Information

### Part Number

**OR-M302X(L)-W-Y-Z**

**OR-M305X(L)-W-Y-Z**

**or OR-M307X(L)-W-Y-Z**

### Note

M302X(L)/M305X(L)/M307X(L) = Part Number(X = 0,1,2,3 or 4)

W = Tape and reel option (TP or TP1).


Y = 'V' code for VDE safety (This options is not necessary).

Z = 'G' code for Halogen free.

\* VDE Code can be selected.

Option	Description	Packing quantity
TP	Surface mount lead form (low profile) + TP tape & reel option	3000 units per reel
TP1	Surface mount lead form (low profile) + TP1 tape & reel option	3000 units per reel

## 8. Naming Rule




1. Manufacturer : ORIENT.
2. Part Number : M30□□.
3. Year Code □□ : '21' means '2021' and so on.
4. Week Code □□: 01 means the first week, 02 means the second week and so on.
5. VDE Code □□. (Optional)
6. HF Code 'G': Halogen Free.
7. Anode.
8. Identification.


\* VDE Code can be selected.

## 9. Package Dimension

OR-M30XX




## 10. Recommended Foot Print Patterns (Mount Pad)




unit: mm

## 11. Taping Dimensions

### (1)TP Type



### (2)TP1 Type



Description	Symbol	Dimension in mm (inch)
Tape wide	W	12±0.3 (0.472)
Pitch of sprocket holes	P0	4±0.1 (0.157)
Distance of compartment	F	5.5±0.1 (0.217)
	P2	2±0.1 (0.079)
Distance of compartment to compartment	P1	8±0.1 (0.315)

Package Type	TP/TP1
Quantities(pcs)	3000






## 12. Package Dimension

### (1) package dimension

Packing Information	
Packing type	Reel type
Tape Width	12mm
Qty per Reel	3,000pcs
Small box (inner) Dimension	345*345*45mm
Large box (Outer) Dimension	480x360x360mm
Max qty per small box	6,000pcs
Max qty per large box	60,000pcs

### (2)Packing Label Sample

Material Code : 120PCXXXXXX

|||||

P/N : OR-XXXXXX

|||||

Lot No. : XXXXXX-XXXXX-TX-X

|||||

D/C : XXXX

|||||

Qty : XXXX PCS

|||||

内箱码

外箱码

“XXXXXXXXXXXXXXXX” (一体机序列码)

Made in China

#### Note:


1. Material Code :Product ID.
2. P/N :Contents with "Order Information" in the specification.
3. Lot No. :Product data.
4. D/C :Product weeks.
5. Quantity :Packaging quantity.

### 13. Temperature Profile Of Soldering

#### (1) IR Reflow soldering (JEDEC-STD-020C compliant)

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.


Profile item	Conditions
Preheat	
- Temperature Min (T Smin )	150°C
- Temperature Max (T Smax )	200°C
- Time (min to max) (ts)	90±30 sec
Soldering zone	
- Temperature (TL )	217°C
- Time (t L )	60 sec
Peak Temperature	260°C
Peak Temperature time	20 sec
Ramp-up rate	3°C / sec max.
Ramp-down rate from peak temperature	3~6°C / sec
Reflow times	≤3



## (2) Wave soldering (JEDEC22A111 compliant)

One time soldering is recommended within the condition of temperature.

Temperature	260+0/-5°C
Time	10 sec
Preheat temperature	5 to 140°C
Preheat time	30 to 80 sec



## (3) Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.

Temperature	380+0/-5°C
Time	3 sec max

## 14. CHARACTERISTICS CURVES (TYPICAL PERFORMANCE)

Fig.1 Forward current vs Ambient temperature




Fig.2 On-state current vs. Ambient temperature




Fig.3 Minimum Trigger Current vs. Ambient temperature




Fig.4 Forward current vs. Forward voltage




Fig.5 On-state voltage vs. Ambient temperature




Fig.6 Holding current vs. Ambient temperature




Fig.7 Repetitive peak off-state current vs. Temperature




Fig.8 On-state current vs. On-state voltage




Fig9. Basic Operation Circuit Medium/High Power Triac Drive Circuit





Fig10.Static dv/dt Test Circuit & Waveform



## Measurement Method

The high voltage pulse is set to the required  $V_{PEAK}$  value and applied to the D.U.T. output side through the RC circuit above. LED current is not applied. The waveform  $V_T$  is monitored using a x100 scope probe. By varying  $R_{TEST}$ , the  $dv/dt$  (slope) is increased, until the D.U.T. is observed to trigger (waveform collapses). The  $dv/dt$  is then decreased until the D.U.T. stops triggering. At this point,  $\tau_{RC}$  is recorded and the  $dv/dt$  calculated.

$$dv/dt = \frac{0.632 \times V_{PEAK}}{\tau_{RC}}$$

$$dv/dt = \frac{0.632 \times V_{PEAK}}{\tau_{RC}}$$

For example,  $V_{PEAK} = 600V$  for EL306X series. The  $dv/dt$  value is calculated as follows:

$$dv/dt = \frac{0.63 \times 600}{\tau_{RC}} = \frac{378}{\tau_{RC}}$$