

TASKCARD

A/C TYPE	Effectivity	DESCRIPTION							WORK ORDER NO.	
		B737-800 - DAILY CHECK.								
A/C REG.	A/C MSN.	ACCESS							TASKCARD NO.	
									B789-05-999-02-01-BTK-IDN	
A/C TSN.	A/C CSN.	192G	413AL	414AR	423AL	424AR			THRESHOLD	INTERVAL
:									0	0
OPERATOR	PLACE	ZONE							TASK	REVISION
		211 632	212 713	414 734	424 744	531	532	631	DET	23
START DATE	FINISH DATE	NOTE							ATA	SKILL
		☐ ETOPS ☐ RVSM ☐ RNP10 ☐ RII ☐ CDCCL							05-20	

REFERENCE			
Doc No.	Doc Description	Doc No.	Doc Description
AMM 12-11-00-680-801	Fuel System Sumping	AMM 12-13-21-200-801	IDG Oil Level Check
AMM 12-13-21-600-801	IDG Servicing (Oil Fill)	AMM 12-15-21-210-801	Crew Oxygen Cylinder Dispatch Pressure Check
AMM 12-13-31-200-801	APU Oil Level Inspection	AMM 12-15-51-610-802	Add Nitrogen or Air to the Tire
AMM 24-22-00-860-811	Supply Electrical Power	AMM 24-22-00-860-814	Remove External Power
AMM 24-34-00-710-801	The Operational Test of the Standby Power System	AMM 28-10-00-280-021	Collect the Fuel Sample
FIM 31-62 TASK 801	BITE Procedure	AMM 32-00-01-480-801	Landing Gear Downlock Pins Installation
AMM 32-45-00-700-801	Wheels Fast Check (Wheel Installed on the Airplane)	AMM 32-45-00-700-803	Tires Inspection
EI B737NG-EI-34-226	pitot probe covers		

TOOLS REQUIRED		
PART NUMBER	DESCRIPTION	QUANTITY
1001089-1	COVER - PROBE, PITOT STATIC	1
14-6806-6011	TYRE PRESSURE GAUGE	1
F70199-1	TIRE INFLATION TOOL	1
F80201-1	DRAIN TL	1
H3310	HEADPHONE - 600 OHM, WITH 1/4 INCH MONO RCAAUDIO PLUG / GROUND HEAD SET	1
SPC-101	STATIC PORT COVER	1
SPC-102	STATIC PORT COVER	1
SPL-1880	EQUIPMENT - DOWNLOCK, NLG AND MLG (FLYAWAY KIT)	1
STD-1055	CONTAINER-OIL RESISTANT, 5 U.S-GAL (19 L)	1

MATERIAL REQUIRED		
PART NUMBER	DESCRIPTION	QUANTITY
ALCOHOL-70	ISOPROPYL ALCOHOL, REAGENT GRADE	1
BMS3-32TYII	MINERAL HYDRAULIC FLUID & ADDITIVES - DAMPER LANDING GEAR	1
CP2442	OIL	1
G00018	NITROGEN BOTTLE	1
LD4	FLUID - HYDRAULIC, EROSION ARRESTING, FIRE RESISTANT	1

BARCODE:  B789-05-999-02-01-BTK-IDN
--

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-02-01-BTK-IDN

MATERIAL REQUIRED		
PART NUMBER	DESCRIPTION	QUANTITY
MAJUN	CLOTH - CLEAN, DRY, LINT-FREE, WHITE, COTTON	1
MJOILII	OIL	1
NASM20995	OXIDIZED INCONNEL LOCKWIRE DIA 0.032 INCH	.2
SKYDROL PE-5	FLUID - HYDRAULIC, EROSION ARRESTING, FIRE RESISTANT	1

ACCOMPLISHMENT			
NO.	INSTRUCTION	PERFORMED BY	INSPECTED BY
1	INTERVAL NOTE: Perform at interval 24 HR and not to exceed to 48 HR (Elapsed Clock Hours – ECH) APPLICABLE FOR: MLI, ILF, DEA and GEF - ALL		
2	B.JOBSET-UP: (1) Ensure that aircraft arrival and parking areas are cleared of debris and obstructions. (2) Install nose and main landing gear ground downlock pins and install Wheel Chocks. (3) Perform Pitot Probe, AOA Sensor, and TAT Probe Heater - System Test RESULT / FOUND: (4) Perform normal parking maintenance procedures (5) Supply external electrical power as necessary	A/P	
3	EXTERNALWALK AROUNDCHECK C.FORWARDFUSELAGE 1. Make a general visual inspection as far as visible from the Ground of Forward Fuselage, with particular attention to any missing or loose fastener/rivets.	A/P	
4	D.NOSELANDINGGEARANDDOORS 1. Do a general visual inspection of the nose landing gear and doors from ground as far as visible	A/P	
5	E.CENTERFUSELAGE (1) Do a general visual inspection of the forward center fuselage from ground as far as visible (2) Check exterior lights and lens for condition, security, or burned out bulbs (3) Check all external required placards. Replace or install any damaged or missing required placards.	A/P	

BARCODE:

B789-05-999-02-01-BTK-IDN

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-02-01-BTK-IDN

ACCOMPLISHMENT												
NO.	INSTRUCTION	PERFORMED BY	INSPECTED BY									
6	<u>F.WINGS</u> (1) Do a general visual inspection of the RH and the LH wing from ground as far as visible (2) Collect the Fuel Sample	A/P										
7	<u>G.POWERPLANT,PYLON&AFTFUSELAGE</u> (1) Do a general visual inspection of the power plant and pylon from ground as far as visible, including (cowl doors closed) <table><tr><th>Engine Position</th><th>Engine #1</th><th>Engine #2</th></tr><tr><td>Platform Finding</td><td></td><td></td></tr><tr><td>(please state if there is finding or no, and state the platform position)</td><td></td><td></td></tr></table> (2) Check left and right engine oil quantity and service as required. LEFT ENGINE (Uplift:.....Qts), RIGHT ENGINE (Uplift:.....Qts) (3) Aft of the pressure bulkhead.	Engine Position	Engine #1	Engine #2	Platform Finding			(please state if there is finding or no, and state the platform position)			A/P	
Engine Position	Engine #1	Engine #2										
Platform Finding												
(please state if there is finding or no, and state the platform position)												
8	<u>H.MAINLANDINGGEAR/WHEEL-WELL</u> AMM TASK 32-00-10-100-802 (1) Clean exposed surfaces of the left and right main landing gear shock strut. (MP TASKS 32-010-01 & 32-010-02) (2) Inspect (General Visual) main landing gear tires and wheels for condition and wear. from ground as far as visible, (MP Task 32-360-00)	A/P										

BARCODE:

B789-05-999-02-01-BTK-IDN

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-02-01-BTK-IDN

ACCOMPLISHMENT																																																																		
NO.	INSTRUCTION				PERFORMED BY	INSPECTED BY																																																												
	(3) Visually check the left and right brake wear pins for minimum extension. (MP Task 32-270-01 and 32-270-02) (4) Measure the remaining indicator pin length for all brake assemblies and make record for the measurement <table><tr><th colspan="4">BRAKE WEAR PINS RECORD (in mm)</th></tr><tr><th>#1</th><th>#2</th><th>#3</th><th>#4</th></tr><tr><td></td><td></td><td></td><td></td></tr></table> (5) Cross check the control cabin HYD fluid QTY indication with indicators				BRAKE WEAR PINS RECORD (in mm)				#1	#2	#3	#4																																																						
BRAKE WEAR PINS RECORD (in mm)																																																																		
#1	#2	#3	#4																																																															
9	I. TIRES (1) Check NLG and MLG tires for correct pressure, and service as necessary. <table><tr><th colspan="4">NOSE TIRES PRESSURE</th></tr><tr><th colspan="2">LEFT</th><th colspan="2">RIGHT</th></tr><tr><th>Before Top- Up</th><th>After Top-Up</th><th>Before Top- Up</th><th>After Top-Up</th></tr><tr><td></td><td></td><td></td><td></td></tr><tr><th colspan="4">MAIN TIRES PRESSURE</th></tr><tr><th colspan="2">LH #1</th><th colspan="2">RH #2</th></tr><tr><th>Before Top- Up</th><th>After Top-Up</th><th>Before Top- Up</th><th>After Top-Up</th></tr><tr><td></td><td></td><td></td><td></td></tr><tr><th colspan="4">MAIN TIRES PRESSURE</th></tr><tr><th colspan="2">LH #2</th><th colspan="2">RH #2</th></tr><tr><th>Before Top- Up</th><th>After Top-Up</th><th>Before Top- Up</th><th>After Top-Up</th></tr><tr><td></td><td></td><td></td><td></td></tr><tr><th colspan="4">BRAKE</th></tr><tr><th>#1</th><th>#2</th><th>#3</th><th>#4</th></tr><tr><td></td><td></td><td></td><td></td></tr></table> (2) Check torsion link cotter pin and nut for condition				NOSE TIRES PRESSURE				LEFT		RIGHT		Before Top- Up	After Top-Up	Before Top- Up	After Top-Up					MAIN TIRES PRESSURE				LH #1		RH #2		Before Top- Up	After Top-Up	Before Top- Up	After Top-Up					MAIN TIRES PRESSURE				LH #2		RH #2		Before Top- Up	After Top-Up	Before Top- Up	After Top-Up					BRAKE				#1	#2	#3	#4					A/P	
NOSE TIRES PRESSURE																																																																		
LEFT		RIGHT																																																																
Before Top- Up	After Top-Up	Before Top- Up	After Top-Up																																																															
MAIN TIRES PRESSURE																																																																		
LH #1		RH #2																																																																
Before Top- Up	After Top-Up	Before Top- Up	After Top-Up																																																															
MAIN TIRES PRESSURE																																																																		
LH #2		RH #2																																																																
Before Top- Up	After Top-Up	Before Top- Up	After Top-Up																																																															
BRAKE																																																																		
#1	#2	#3	#4																																																															
10	J. FLIGHTCOMPARTMENT AMM TASK 12-15-21-210-801 (1) Do a Crew Oxygen Cylinder Dispatch Pressure Check" <table><tr><th colspan="3">C.O.B. PRESSURE (PSI)</th></tr><tr><td></td><td></td><td></td></tr></table> (2) Do an APU Oil Level Inspection by using APU BITE Procedure. (3) Record APU hours, cycles and CT5ATP (EGT) from APU DMM via CDU <table><tr><th>APU Hours</th><th>APU Cycles</th><th>APU EGT (CT5ATP)</th></tr><tr><td></td><td></td><td></td></tr></table>				C.O.B. PRESSURE (PSI)						APU Hours	APU Cycles	APU EGT (CT5ATP)				A/P																																																	
C.O.B. PRESSURE (PSI)																																																																		
APU Hours	APU Cycles	APU EGT (CT5ATP)																																																																

BARCODE:

B789-05-999-02-01-BTK-IDN



ACCOMPLISHMENT																										
NO.	INSTRUCTION				PERFORMED BY	INSPECTED BY																				
	(4) Check all cockpit lights and Spare bulb (completed it as necessary)																									
	(5) Check flight compartment for condition and cleanliness.																									
	(6) Check IDG disconnect switch for condition and security (guarded and wired).																									
	(7) Check emergency, safety equipment and Medical / Doctor's Kit onboard for condition, security and validity																									
	<table><tr><td>Description</td><td>QTY</td><td>POS#</td><td>Available [YES/NO]</td><td>Valid Until</td></tr><tr><td>Halon Firext</td><td>1 ea</td><td>Cockpit</td><td></td><td></td></tr><tr><td>PBE</td><td>1 ea</td><td>Cockpit</td><td></td><td></td></tr><tr><td>Medical Kit</td><td>1 Box</td><td>Cockpit</td><td></td><td></td></tr></table>						Description	QTY	POS#	Available [YES/NO]	Valid Until	Halon Firext	1 ea	Cockpit			PBE	1 ea	Cockpit			Medical Kit	1 Box	Cockpit		
	Description	QTY	POS#	Available [YES/NO]			Valid Until																			
	Halon Firext	1 ea	Cockpit																							
	PBE	1 ea	Cockpit																							
	Medical Kit	1 Box	Cockpit																							
	(8) Check emergency exit windows and F/O emergency exit handles for condition and security																									
	(9) Operational test all exterior lights																									
	(10) Check all circuit breakers, switches, guards and controls for normal position prior to leave the cockpit.																									
	(11) Operational check of the standby power control unit (SPCU).																									
	(12) Interrogate the FMC CDU for left & Right engine faults.																									
(13) Do the BITE procedure for maintenance messages in CURRENT STATUS on the CDS																										
STATUS :																										
RESULT:.....																										
11	<u>K.PASSENGERCABIN.</u> (1) Visually check that all emergency exit hatches are secured and that handles are properly stowed. (2) Check forward entry doors radius link marked screw have no migration or the straight line mark on screw still inline to the washer RESULT: â€ â€ â€ â€ â€ â€ â€ (3) Check passenger and emergency doors for condition and security (4) Check forward entry doors radius link marked screw have no migration or the straight line mark on screw still inline to the washer				A/P																					

B789-05-999-02-01-BTK-IDN

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-02-01-BTK-IDN

ACCOMPLISHMENT						
NO.	INSTRUCTION				PERFORMED BY	INSPECTED BY
	(5) Check aircraft emergency equipment for condition, proper pressure, safeties and security, including the following a) DOOR					
	Description	QTY	POS#	Available [YES/NO]	Valid Until	
	Escape Slide	1 ea	Main Entry			
	Escape Slide	1 ea	Service Door FWD			
			Service Door Aft R/H			
			Service Door Aft L/H			
	Escape Slide	1 ea	MID Door L/H			
			MID Door R/H			
	b) PASSENGER CABIN					
	Description	QTY	POS#	Available [YES/NO]	Valid Until	
	Halon Firext	1 ea	FWD			
		2 ea	AFT			
	Oxygen Bottle 5LB	1 ea	FWD			
	Oxygen Bottle 5LB	1 ea	FWD			
	Oxygen Bottle 5LB	1 ea	AFT			
	Oxygen Bottle 5LB	1 ea	AFT			
	Oxygen Bottle 5LB	1 ea	AFT			
	PBE	1 ea	FWD			
		1 ea	FWD			
		2 ea	AFT			
	H2O Firext	1 ea	FWD			
		1 ea	AFT			
	First Aid Kit	1 ea	FWD			
		1 ea	AFT L/H			
		1 ea	AFT R/H			
	c) LAVATORY					
	Description	QTY	POS#	Available [YES/NO]	Valid Until	
	Fire Extinguisher	1 ea	FWD			
		1 ea	AFT R/H			

BARCODE:

B789-05-999-02-01-BTK-IDN

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-02-01-BTK-IDN

ACCOMPLISHMENT							
NO.	INSTRUCTION					PERFORMED BY	INSPECTED BY
		1 ea	AFT L/H				
12	<u>L. FINALCHECK</u> (1) Review AFML, CML, NSRDIL, DBC. (2) Review differed maintenance items, log and correct as necessary. (3) Check the following aircraft document for completeness and validity/update : a) Certificate of Airworthiness (C of A). Valid Until : b) Certificate of Registration (C of R). Valid Until : c) Radio Permit & AASL Valid Until : d) Weight and Balance. Date Issued : e) Swing Compass Date Issued : f) Insurance Certificate Valid Until : g) Operation Specifications (OPSPEC). Last Revision : h) Required Navigation Performance (RNP). Date Issued : i) Reduced Vertical Separate Minimal (RVSM). Date Issued: j) Noise Certificate Date Issued :					A/P	

BARCODE:

B789-05-999-02-01-BTK-IDN

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-02-01-BTK-IDN

ACCOMPLISHMENT				
NO.	INSTRUCTION	PERFORMED BY	INSPECTED BY	
	k) Minimum Equipment List			
	Last Revision :			
	l) Dent Buckle & Chart			
	Check any due date of Temp.			YES/NO
	repair repetitive inspection or			
	Permanent repair if required			
	(4) Make necessary entries for work accomplished and sign off airworthiness release in the aircraft maintenance log.			
13	<u>M.JOBCLOSE-UP</u> AMM TASK 24-22-00-860-814 (1) Removed external power source 115 V (+5 V), 400 Hz (+20 Hz) if no longer required.	A/P		
14	----- END OF TASK -----			

START TIME(UTC)	FINISH TIME(UTC)	TOTAL MAN HOUR		DEFECT FOUND M.D.R.R. No:	Y	N
		EST.	ACTUAL			
		2.50				
TASK CARD RELEASE						
DATE (UTC) : TIME (UTC) : SIGNATURE : AUTHORIZATION NO. :						

BARCODE:

B789-05-999-02-01-BTK-IDN