

TASKCARD

A/C TYPE	Effectivity	DESCRIPTION	WORK ORDER NO.	
		B737-800 - PREFLIGHT CHECK(PRE-DEPARTURE SERVICE CHECK - PDSC)		
A/C REG.	A/C MSN.	ACCESS	TASKCARD NO.	
			B789-05-999-01-01-BTK-IDN	
A/C TSN.	A/C CSN.	NONE	THRESHOLD	INTERVAL
:			0	0
OPERATOR	PLACE	ZONE	TASK	REVISION
		100 200 300 400 500 600 700 800	SVC	16
START DATE	FINISH DATE	NOTE	ATA	SKILL
		☐ ETOPS ☐ RVSM ☐ RNP10 ☐ RII ☐ CDCCL	05-20	A/P

REFERENCE			
Doc No.	Doc Description	Doc No.	Doc Description
AMM 12-13-11-600-801	Replenish the Engine Oil	AMM 12-13-31-610-803	Fill the APU Gearbox
AMM 23-71-00-710-801	Voice Recorder System - Operational Test	AMM 24-22-00-860-813	Supply External Power
AMM 24-22-00-860-814	Remove External Power	AMM 28-22-11-865-001	Spar Valve Actuator Operational Test (FAA AD 2015-21-10 & DGCA AD 15-11-005)
AMM 31-31-00-710-801	Flight Data Recorder System - Operational Test	AMM 31-51-00-730-803	Takeoff Warning System Test - SUBTASK 31-51-00-750-067 - check of the speed brake handle input to the takeoff warning system
AMM 49-11-00-990-804	Oil Consumption Limit	AMM 72-21-00-200-801	Power Plant Inlet and Fan Blades Inspection (General Visual)
EI B737NG-EI-34-226	pitot probe covers		

TOOLS REQUIRED		
PART NUMBER	DESCRIPTION	QUANTITY
H3310	HEADPHONE - 600 OHM, WITH 1/4 INCH MONO RCAAUDIO PLUG / GROUND HEAD SET	1

MATERIAL REQUIRED		
PART NUMBER	DESCRIPTION	QUANTITY
BMS3-11 TYPE IV	FLUID - HYDRAULIC, EROSION ARRESTING, FIRE RESISTANT	1
LD4	FLUID - HYDRAULIC, EROSION ARRESTING, FIRE RESISTANT	1
MIL-PRF-5606	FLUID - LANDING GEAR SHOCK STRUT	1
MOBIL JET II	OIL	1

ACCOMPLISHMENT			
NO.	INSTRUCTION	PERFORMED BY	INSPECTED BY
1	INTERVALNOTE : This Pre-Flight (Pre-Departure/Service) Check should be performed at: 1. Prior to each ETOPS flight [A/C Reg. for ETOPS MLI 070-071, 081-082 & 145] 2. Prior to first flight of the day for non-ETOPS Flight. NOTE: Check is to be completed within 2 - 4 hours of ETOPS departure unless a higher level check has been completed At a minimum, the PDSC is to verify the condition of all ETOPS significant systems, verify the status of the airplane by reviewing all applicable maintenance recor		

BARCODE:  B789-05-999-01-01-BTK-IDN
--

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-01-01-BTK-IDN

ACCOMPLISHMENT													
NO.	INSTRUCTION	PERFORMED BY	INSPECTED BY										
	ds, perform an interior and exterior inspection, check engine and APU oil levels and calculate consumptions rates A.GENERAL 1. The PDSC for ETOPS must be performed by an appropriately certified engineer who is ETOPS qualified as defined by the BATIK AIR program. The certified ETOPS engineer must certify, by signature, that the ETOPS PDSC has been completed appropriately. 2. This task contains with the aircraft security inspections. If object(s) or material (powdery, gaseous or liquid) from un-identified origin is/are found, keep off the object (s) or material and immediately report to MCC In-Charge before taking any necessary action.												
2	B.JOBSET-UP: (1) Ensure that aircraft arrival and parking areas are cleared of debris and obstructions. AMM TASK 24-22-00-860-813 (2) Connect external power source 115 V (+5 V), 400 Hz (+20 Hz). (If necessary) AMM TASK 10-11-01-630-001 (3) Remove the covers from the following components: <table><tr><td>â€¢ All pitot probes</td><td>â€¢ Removed</td></tr><tr><td>â€¢ Total air temperature (TAT) probe</td><td>â€¢ Removed</td></tr><tr><td>â€¢ Angle of attack (AOA) sensor.</td><td>â€¢ Removed</td></tr><tr><td>â€¢ All barricade tape and vinyl adhesive tape from</td><td>â€¢ Removed</td></tr><tr><td>all of the static ports.</td><td>â€¢ Removed</td></tr></table>	â€¢ All pitot probes	â€¢ Removed	â€¢ Total air temperature (TAT) probe	â€¢ Removed	â€¢ Angle of attack (AOA) sensor.	â€¢ Removed	â€¢ All barricade tape and vinyl adhesive tape from	â€¢ Removed	all of the static ports.	â€¢ Removed	A/P	
â€¢ All pitot probes	â€¢ Removed												
â€¢ Total air temperature (TAT) probe	â€¢ Removed												
â€¢ Angle of attack (AOA) sensor.	â€¢ Removed												
â€¢ All barricade tape and vinyl adhesive tape from	â€¢ Removed												
all of the static ports.	â€¢ Removed												
3	PROCEDURES C. FLIGHTCOMPARTMENT (1) Review aircraft logbook (AFML, CML, DMI, NSRDIL, DBC) for reported discrepancies and oil consumption from previous flights, Correct as necessary. (2) Verify flight deck indications and/or warnings are resolved or approved dispatch paperwork is applied. AMM TASK 23-71-00-710-801 (3) Operational Test of Cockpit Voice Recorder System (MP TASK 23-040-00) AMM TASK 31-31-00-710-801	A/P											

BARCODE:

B789-05-999-01-01-BTK-IDN

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-01-01-BTK-IDN

ACCOMPLISHMENT			
NO.	INSTRUCTION	PERFORMED BY	INSPECTED BY
	(4) Operational check of flight data recorder by put the TEST/NORMAL switch on the flight recorder test module in the TEST position. (MP TASK 31-999-01) AMM Task 28-22-11-865-001 (5) Do an Operational Test of the left engine fuel AMM Task 28-22-11-865-001 (6) Do an Operational Test of the right engine fuel AMM SUBTASK 31-51-00-750-067 (7) Check of the speed brake handle input to the takeoff AMM Task 30-31-00-730-801 (8) Pitot Probe, AOA Sensor, and TAT Probe Heater - System AMM Task 25-11-00-200-802 (9) Captain's, First Officer's, and Observer's Seat Visual âj Checked and Inertia Reel Operational Check		
4	<u>EXTERNALWALKAROUND</u> <u>D. FLIGHTCONTROL</u> (1) GVI of the vertical stabilizer, rudder, horizontal stabilizers (2) Inspect the tail skid for strike indication and condition	A/P	
5	<u>E. LANDING GEAR</u> 1. GVI of the Nose & main landing gear tires, wheels, and brakes for obvious damage and wear.	A/P	
6	<u>F.FUSELAGE</u> (1) Check fuselage access / service panels, cabin windows, hatches, navigation communication antennas and radome from ground level for obvious damage and security, Verify that cargo door latches are fully engaged. (2) General Visual Inspection (GVI) of ram air inlet/ exhaust doors and cabin pressure out flow valve to ensure there are no obstructions. (3) GVI of the fuselage access and/or service panels, navigation/communication antennas and radome for condition and security. (4) GVI of the fuselage and APU drains masts for fluid	A/P	
7	<u>G.WINGS</u> (1) Check that the fueling station door is secured. (2) GVI of the left and right wing leading edge and associated	A/P	

BARCODE:

B789-05-999-01-01-BTK-IDN

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-01-01-BTK-IDN

ACCOMPLISHMENT												
NO.	INSTRUCTION	PERFORMED BY	INSPECTED BY									
8	H. ENGINES: (1) Remove covers : <table><tr><th>Engine Position</th><th>Engine #1</th><th>Engine #2</th></tr><tr><td>Platform Finding</td><td></td><td></td></tr><tr><td>(please state if there is finding or no, and state the platform position)</td><td></td><td></td></tr></table> See video on this link bit.ly/4gVxDNQ  For more information please download Engineering Information below  (1) GVI of access panels, pressure relief doors, open latches, and signs of fluid leakage (2) GVI of the number left engine thrust reversers, exhaust tail plug, exhaust case struts, exhaust area, visible turbine blades and 4th stage blades on LPT for obvious damage and evidence of metal and/or oil accumulation. AMM TASK AMM 12-13-11-600-801	Engine Position	Engine #1	Engine #2	Platform Finding			(please state if there is finding or no, and state the platform position)			A/P	
Engine Position	Engine #1	Engine #2										
Platform Finding												
(please state if there is finding or no, and state the platform position)												

BARCODE:

B789-05-999-01-01-BTK-IDN

TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-01-01-BTK-IDN

ACCOMPLISHMENT			
NO.	INSTRUCTION	PERFORMED BY	INSPECTED BY
	(3) Verify the #1 engine oil level and service as necessary. (Not as a Dual Maintenance) AMM TASK AMM 12-13-11-600-801 (4) Verify the #2 engine oil level and service as necessary. (Not as a Dual Maintenance) AMM 12-13-31-610-803 (5) Verify and service APU Oil as necessary. (Not as a Dual Maintenance) Record amount added: _____ If any oil uplift, calculate the #1 engine oil consumption rate: Oil consumption rate = $\frac{\text{oil uplift (quarts)}}{\text{flight time since last uplift (hours)}}$ =qrt/hour NOTE: Ensure the oil level is greater than 90% but lower than 100% full prior to departure. Service as necessary if oil level is equal to or lower than 90%. Oil should be added not less than 5 minutes and no greater than 60 minutes after engine shutdown while the oil in the tank is still warm. Oil should be added not less than 5 minutes and no greater than 60 minutes after engine shutdown while the oil in the tank is still warm.		
9	I.FINALCHECK: (1) Make necessary entries for work accomplished and Check and record corrective actions in the aircraft technical log. (2) Remove the nose landing gear the main landing gear (3) Final aircraft walk-around:	A/P	
10	J.JOBCLOSE-UP: AMM 24-22-00-860-814 1. Removed external power source 115 V (+5 V), 400 Hz (+20 Hz), if no longer required.	A/P	
11	----- END OF TASK -----		

BARCODE:

B789-05-999-01-01-BTK-IDN



TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					B789-05-999-01-01-BTK-IDN

START TIME(UTC)	FINISH TIME(UTC)	TOTAL MAN HOUR		DEFECT FOUND M.D.R.R. No:	Y	N
		EST.	ACTUAL			
		0.75				

TASK CARD RELEASE

DATE (UTC) : TIME (UTC) : SIGNATURE : AUTHORIZATION NO. :

BARCODE:



B789-05-999-01-01-BTK-IDN