



TASKCARD

A/C TYPE	Effectivity	DESCRIPTION							WORK ORDER NO.	
		LINE CHECK								
A/C REG.	A/C MSN.	ACCESS							TASKCARD NO.	
									999999-LCC-00000-3-WA	
A/C TSN.	A/C CSN.	195EL	211SZ						THRESHOLD	INTERVAL
:										
OPERATOR	PLACE	ZONE							TASK	REVISION
		195 260	210 711	212 731	220 741	230	240	250	INSP	10
START DATE	FINISH DATE	NOTE							ATA	SKILL
		☐ ETOPS ☐ RVSM ☐ RNP10 ☐ RII ☐ CDCCL								

REFERENCE			
Doc No.	Doc Description	Doc No.	Doc Description
MP A-12-12-29-00ZZZ-212Z-A	HYDRAULIC RESEVOIR REPLENISHING	MP A-12-12-29-01ZZZ-212Z-A	HYDRAULIC RESERVOIR REPLENISHING BY GRAVITY
MP A-29-XX-XX-00ZZZ-281Z-A	HYDRAULIC RESERVOIR SIGHT GLASS VISUAL CHECK	MP A-33-1X-XX-00ZZZ-320Z-A	OPERATIONAL TEST OF ANNUNCIATOR LIGHTS TEST SYSTEM
MP A-32-42-50-00ZZZ-364Z-A	CHECK OF BRAKE ASSY FOR DAMAGES, LEAK AND WEAR	MP A-32-42-80-00ZZZ-320Z-A	ANTI SKID TEST
MP A-32-41-XX-00ZZZ-362Z-A	CHECK OF WHEELS AND TIRES		

TOOLS REQUIRED		
PART NUMBER	DESCRIPTION	QUANTITY
14-6806-6011	TYRE PRESSURE GAUGE	1

MATERIAL REQUIRED		
PART NUMBER	DESCRIPTION	QUANTITY
SKYDROL LD4	FLUID - HYDRAULIC, EROSION ARRESTING, FIRE RESISTANT	1

ACCOMPLISHMENT					
NO.	INSTRUCTION			PERFORMED BY	INSPECTED BY
1	1. GENERAL SECTION Interval Note : 2 calendar days, means that next due time is any time in day 3, if previous accomplishment done any time in day 1.				
2	1. Check of hydraulic fluid level through reservoir sight glass MP: ATR-A-29-XX-XX-00ZZZ-281Z-A) and services as required (MP:ATR-A-12-12-29-00ZZZ-212Z-A/MP:ATR-A-12-12-29-01ZZZ-212Z-A)			A/P	
3	2. A. Check of main and nose landing gear tires for pressure, wear and general condition (MP: ATR-A-32-41-XX-00ZZZ-362Z-A) services tire as required and record tire pressures after servicing Note: IT IS PREFERABLE TO CHECK TIRE PRESSURE WHEN THE TIRE IS COOLED DOWN TO AMBIENT TEMPERATURE OR AT LEAST THREE HOURS AFTER LAST OPERATION, WHICHEVER OCCURS FIRSTLY. HOT TIRE PRESSURE CHECK PROCEDURE SHOULD BE USED ONLY EXCEPTIONALLY.			A/P	
	Nose Tire #1		Nose Tire #2		
	Before Srvcg	After Srvcg	Before Srvcg	After Srvcg	

BARCODE:	 999999-LCC-00000-3-WA
----------	--



TASKCARD

WORK ORDER NO.	A/C REG.	A/C MSN.	A/C Effectivity	OPERATOR	TASK CARD NO.
					999999-LCC-00000-3-WA

ACCOMPLISHMENT									
NO.	INSTRUCTION								PERFORMED BY
	Main Tire #1		Main Tire #2		Main Tire #3		Main Tire #4		
	Before Srvcg	After Srvcg	Before Srvcg	After Srvcg	Before Srvcg	After Srvcg	Before Srvcg	After Srvcg	
	B. Brake assembly check of brake wear indicator (with parking brake on), brake assy for hydraulic leakage and freedom of brake disc. (MP: ATR-A-32-42-50-00ZZZ-364Z-A) record brake wear pin remaining length : #1..... mm #2..... mm #3..... mm #4..... mm Note : if pin remaining length 1 mm, coordination and report to MCC								
4	3. Operational test of antiskid system (MP: ATR-A-32-42-80-00ZZZ-320Z-A).								A/P
5	4. Operational test of the annunciator light test system (MP: ATR-A-33-1X-XX-00ZZZ-320Z-A).								A/P
6	RETURN TO SERVICE <i>"I certify that this aircraft has been inspected in accordance with Line Check inspection and determined to be in airworthy condition"</i>								

START TIME(UTC)	FINISH TIME(UTC)	TOTAL MAN HOUR		DEFECT FOUND M.D.R.R. No:	Y	N
		EST.	ACTUAL			
		0.91				

TASK CARD RELEASE

DATE (UTC) : TIME (UTC) : SIGNATURE : AUTHORIZATION NO. :

BARCODE:



999999-LCC-00000-3-WA