

# Algorithms Associated with Factorization Machines

Yanyu Liang  
Xin Lu  
Xupeng Tong

Carnegie Mellon University

*{yanyul,xlu2,xtong}@andrew.cmu.edu*

December 12, 2016

# Overview

## 1 Our Problem

- Factorization Machines
- Other Formulation
- Our Work

## 2 ADMM for sparse convexFMs

- ConvexFMs with  $l_1$  constraint
- ADMM Formulation
- ADMM Subproblem
- ADMM Results
- ADMM Results (con'd)

# Factorization Machines

- Factorization machines [1] models  $y \in \mathbb{R}$  given  $x \in \mathbb{R}^p$  using the following expression:

$$\begin{aligned}\hat{y} &= w_0 + w^T x + \sum_{i,j} (V_i x_i)^T (V_j x_j) \\ &= w_0 + w^T x + x^T V^T V x\end{aligned}$$

, where  $V_i$  is  $k \times 1$  vector.

- FMs is widely used in recommendation system, since it implicitly regularizes the model complexity by setting a  $k$  which is much smaller than  $p$ .

# Other Formulation

- $\sum_{i,j} (V_i x_i)^T (V_j x_j)$  makes FMs nonconvex, and researcher has proposed convex FMs [2] by replacing low rank constraint by trace norm (replace  $V^T V$  with  $W$ ).
- Also, by replacing one  $V$  in  $V^T V$  with  $U$ , [3] proposed generalized FMs with an online learning algorithm

# Our Goal

- Propose ADMM method to solve convex FMs with element-wise  $l_1$  constraint
- Overview optimization algorithm to solve classic FMs problems

# ConvexFMs with $l_1$ constraint

- $l_1$  penalty is widely used and it is potential helpful in many applications beyond recommendation systems.
- Consider the regression problem in convexFMs with  $l_1$  penalty:

$$\min_{w_0, w, W} \sum_{i=1}^n \underbrace{(y_i - w_0 - w^T x_i - x_i^T W x_i)^2}_{f(w_0, w, W)} + \lambda_1 \|W\|_{\text{tr}} + \lambda_2 \|W\|_1 + \lambda_3 \|w\|_2^2$$

# ADMM Formulation

- By introducing auxiliary variable  $U$ , it can be fit into ADMM framework and the augmented Lagrangian is:

$$\begin{aligned}\mathcal{L}(w_0, w, W) = & f(w_0, w, W) + \lambda_1 \|U\|_{\text{tr}} + \lambda_2 \|W\|_1 + \lambda_3 \|w\|_2^2 \\ & + \langle W - U, u \rangle + m \|W - U\|_2^2\end{aligned}$$

- Then the ADMM loop is:

- 1 Update  $w_0, w, W$ :

$$\begin{aligned}w_0^k, w^k, W^k = & \arg \min_{w_0, w, W} f(w_0, w, W) + \lambda_2 \|W\|_1 \\ & + \frac{\rho}{2} \|W - U^{k-1} + u^{k-1}\|_2^2\end{aligned}$$

- 2 Update  $U$ :

$$U^k = \arg \min_U \lambda_1 \|U\|_{\text{tr}} + \frac{\rho}{2} \|W^k - U + u^{k-1}\|_2^2$$

- 3 Update  $u$ :

$$u^k = u^{k-1} + W^k - U^k$$



# ADMM Subproblem

- The second step can be solve exactly with proximal operator of trace norm.
- We explored two approaches to solve the first subproblem:
  - proximal gradient descent on  $w_0, w, W$  (proximal)
  - blockwise coordinate descent on  $w_0, w$  and  $W$  respectively, where we applied coordinate descent on the first block and tried proximal gradient (coor-proximal) and Quasi-Newton (coor-newton) method on the second block





# ADMM Results

- Quasi-Newton method performs better than proximal gradient descent in solving  $\arg \min_W g(W)$  subproblem (as we expected)
- proximal gradient descent performs better and stable than blockwise coordinate descent



# ADMM Results (con'd)

- ADMM converges and it achieves feasibility along the path
- with the same number of updates (consider inner loop), ADMM outperforms sub-gradient method



# References I



S. Rendle, “Factorization machines,” in 2010 IEEE International Conference on Data Mining. IEEE, 2010, pp. 995–1000.



M. Blondel, A. Fujino, and N. Ueda, “Convex factorization machines,” in Joint European Conference on Machine Learning and Knowledge Discovery in Databases. Springer, 2015, pp. 19–35.



M. Lin and J. Ye, “A non-convex one-pass framework for generalized factorization machine and rank-one matrix sensing,” in Advances In Neural Information Processing Systems, 2016, pp. 1633–1641.

# The End