

Raw

Parsed

```
{
  "rootUrl": "https://workspaceevents.googleapis.com/",
  "discoveryVersion": "v1",
  "documentationLink": "https://developers.google.com/workspace/events",
  "batchPath": "batch",
  "fullyEncodeReservedExpansion": true,
  "parameters": {
    "access_token": {
      "type": "string",
      "description": "OAuth access token.",
      "location": "query"
    },
    "alt": {
      "type": "string",
      "description": "Data format for response.",
      "default": "json",
      "enum": [
        "json",
        "media",
        "proto"
      ],
      "enumDescriptions": [
        "Responses with Content-Type of application/json",
        "Media download with context-dependent Content-Type",
        "Responses with Content-Type of application/x-protobuf"
      ],
      "location": "query"
    },
    "callback": {
      "type": "string",
      "description": "JSONP",
      "location": "query"
    },
    "fields": {
      "type": "string",
      "description": "Selector specifying which fields to include in a partial response.",
      "location": "query"
    },
    "key": {
      "type": "string",
      "description": "API key. Your API key identifies your project and provides you with API access, quota, and reports. Required unless you provide an OAuth 2.0 token.",
      "location": "query"
    },
    "oauth_token": {
      "type": "string",
      "description": "OAuth 2.0 token for the current user.",
      "location": "query"
    },
    "prettyPrint": {
      "type": "boolean",
      "description": "Returns response with indentations and line breaks.",
      "default": "true",

```



```

        "location": "query"
    },
    "quotaUser": {
        "type": "string",
        "description": "Available to use for quota purposes for server-side applications. Can be any arbitrary string assigned to a user, but should not exceed 40 characters.",
        "location": "query"
    },
    "upload_protocol": {
        "type": "string",
        "description": "Upload protocol for media (e.g. \"raw\", \"multipart\").",
        "location": "query"
    },
    "uploadType": {
        "type": "string",
        "description": "Legacy upload protocol for media (e.g. \"media\", \"multipart\").",
        "location": "query"
    },
    "$.xgafv": {
        "type": "string",
        "description": "V1 error format.",
        "enum": [
            "1",
            "2"
        ],
        "enumDescriptions": [
            "v1 error format",
            "v2 error format"
        ],
        "location": "query"
    }
},
"ownerName": "Google",
"auth": {
    "oauth2": {
        "scopes": {
            "https://www.googleapis.com/auth/chat.app.memberships": {
                "description": "On their own behalf, apps in Google Chat can see, add, update, and remove members from conversations and spaces"
            },
            "https://www.googleapis.com/auth/chat.app.messages.readonly": {
                "description": "On their own behalf, apps in Google Chat can see all messages and their associated reactions and message content"
            },
            "https://www.googleapis.com/auth/chat.app.spaces": {
                "description": "On their own behalf, apps in Google Chat can create conversations and spaces and see or update their metadata (including history settings and access settings)"
            },
            "https://www.googleapis.com/auth/chat.bot": {
                "description": "Private Service: https://www.googleapis.com/auth/chat.bot"
            },
            "https://www.googleapis.com/auth/chat.memberships": {

```



```

    "description": "See, add, update, and remove members from conversations and
    spaces in Google Chat"
  },
  "https://www.googleapis.com/auth/chat.memberships.readonly": {
    "description": "View members in Google Chat conversations."
  },
  "https://www.googleapis.com/auth/chat.messages": {
    "description": "See, compose, send, update, and delete messages as well as
    their message content; add, see, and delete reactions to messages."
  },
  "https://www.googleapis.com/auth/chat.messages.reactions": {
    "description": "See, add, and delete reactions as well as their reaction
    content to messages in Google Chat"
  },
  "https://www.googleapis.com/auth/chat.messages.reactions.readonly": {
    "description": "View reactions as well as their reaction content to messages
    in Google Chat"
  },
  "https://www.googleapis.com/auth/chat.messages.readonly": {
    "description": "See messages as well as their reactions and message content
    in Google Chat"
  },
  "https://www.googleapis.com/auth/chat.spaces": {
    "description": "Create conversations and spaces and see or update metadata
    (including history settings and access settings) in Google Chat"
  },
  "https://www.googleapis.com/auth/chat.spaces.readonly": {
    "description": "View chat and spaces in Google Chat"
  },
  "https://www.googleapis.com/auth/drive": {
    "description": "See, edit, create, and delete all of your Google Drive files"
  },
  "https://www.googleapis.com/auth/drive.file": {
    "description": "See, edit, create, and delete only the specific Google Drive
    files you use with this app"
  },
  "https://www.googleapis.com/auth/drive.metadata": {
    "description": "View and manage metadata of files in your Google Drive"
  },
  "https://www.googleapis.com/auth/drive.metadata.readonly": {
    "description": "See information about your Google Drive files"
  },
  "https://www.googleapis.com/auth/drive.readonly": {
    "description": "See and download all your Google Drive files"
  },
  "https://www.googleapis.com/auth/meetings.space.created": {
    "description": "Create, edit, and see information about your Google Meet
    conferences created by the app."
  },
  "https://www.googleapis.com/auth/meetings.space.readonly": {
    "description": "Read information about any of your Google Meet conferences"
  }
}

```



```

    }
  },
  "ownerDomain": "google.com",
  "baseUrl": "https://workspaceevents.googleapis.com/",
  "basePath": "",
  "name": "workspaceevents",
  "version": "v1",
  "mtlsRootUrl": "https://workspaceevents.mtls.googleapis.com/",
  "title": "Google Workspace Events API",
  "protocol": "rest",
  "icons": {
    "x16": "http://www.google.com/images/icons/product/search-16.gif",
    "x32": "http://www.google.com/images/icons/product/search-32.gif"
  },
  "id": "workspaceevents:v1",
  "resources": {
    "operations": {
      "methods": {
        "get": {
          "id": "workspaceevents.operations.get",
          "path": "v1/{+name}",
          "flatPath": "v1/operations/{operationsId}",
          "httpMethod": "GET",
          "parameters": {
            "name": {
              "description": "The name of the operation resource.",
              "pattern": "^operations/.*$",
              "location": "path",
              "required": true,
              "type": "string"
            }
          },
          "parameterOrder": [
            "name"
          ],
          "response": {
            "$ref": "Operation"
          },
          "scopes": [
            "https://www.googleapis.com/auth/chat.bot",
            "https://www.googleapis.com/auth/chat.memberships",
            "https://www.googleapis.com/auth/chat.memberships.readonly",
            "https://www.googleapis.com/auth/chat.messages",
            "https://www.googleapis.com/auth/chat.messages.reactions",
            "https://www.googleapis.com/auth/chat.messages.reactions.readonly",
            "https://www.googleapis.com/auth/chat.messages.readonly",
            "https://www.googleapis.com/auth/chat.spaces",
            "https://www.googleapis.com/auth/chat.spaces.readonly",
            "https://www.googleapis.com/auth/drive",
            "https://www.googleapis.com/auth/drive.file",
            "https://www.googleapis.com/auth/drive.metadata",
            "https://www.googleapis.com/auth/drive.metadata.readonly",
            "https://www.googleapis.com/auth/drive.readonly",

```



```

        "https://www.googleapis.com/auth/meetings.space.created",
        "https://www.googleapis.com/auth/meetings.space.readonly"
    ],
    "description": "Gets the latest state of a long-running operation. Clients
can use this method to poll the operation result at intervals as recommended
by the API service."
}
}
},
{
  "subscriptions": {
    "methods": {
      "create": {
        "id": "workspaceevents.subscriptions.create",
        "path": "v1/subscriptions",
        "flatPath": "v1/subscriptions",
        "httpMethod": "POST",
        "parameters": {
          "validateOnly": {
            "description": "Optional. If set to `true`, validates and previews the
request, but doesn't create the subscription.",
            "location": "query",
            "type": "boolean"
          }
        },
        "parameterOrder": [],
        "request": {
          "$ref": "Subscription"
        },
        "response": {
          "$ref": "Operation"
        },
        "scopes": [
          "https://www.googleapis.com/auth/chat.app.memberships",
          "https://www.googleapis.com/auth/chat.app.messages.readonly",
          "https://www.googleapis.com/auth/chat.app.spaces",
          "https://www.googleapis.com/auth/chat.memberships",
          "https://www.googleapis.com/auth/chat.memberships.readonly",
          "https://www.googleapis.com/auth/chat.messages",
          "https://www.googleapis.com/auth/chat.messages.reactions",
          "https://www.googleapis.com/auth/chat.messages.reactions.readonly",
          "https://www.googleapis.com/auth/chat.messages.readonly",
          "https://www.googleapis.com/auth/chat.spaces",
          "https://www.googleapis.com/auth/chat.spaces.readonly",
          "https://www.googleapis.com/auth/drive",
          "https://www.googleapis.com/auth/drive.file",
          "https://www.googleapis.com/auth/drive.metadata",
          "https://www.googleapis.com/auth/drive.metadata.readonly",
          "https://www.googleapis.com/auth/drive.readonly",
          "https://www.googleapis.com/auth/meetings.space.created",
          "https://www.googleapis.com/auth/meetings.space.readonly"
        ],
        "description": "Creates a Google Workspace subscription. To learn how to use
this method, see [Create a Google Workspace subscription]"
      }
    }
  }
}

```



(<https://developers.google.com/workspace/events/guides/create-subscription>). For a subscription on a [Chat target resource] (<https://developers.google.com/workspace/events/guides/events-chat>), you can create a subscription as: - A Chat app by specifying an authorization scope that begins with `chat.app` and getting one-time administrator approval ([Developer Preview](<https://developers.google.com/workspace/preview>)). To learn more, see [Authorize as a Chat app with administrator approval] (<https://developers.google.com/workspace/chat/authenticate-authorize-chat-app>). - A user by specifying an authorization scope that doesn't include `app` in its name. To learn more, see [Authorize as a Chat user] (<https://developers.google.com/workspace/chat/authenticate-authorize-chat-user>)."

```
},
  "delete": {
    "id": "workspaceevents.subscriptions.delete",
    "path": "v1/{+name}",
    "flatPath": "v1/subscriptions/{subscriptionsId}",
    "httpMethod": "DELETE",
    "parameters": {
      "name": {
        "description": "Required. Resource name of the subscription to delete. Format: `subscriptions/{subscription}`",
        "pattern": "^subscriptions/[^/]+$",
        "location": "path",
        "required": true,
        "type": "string"
      },
      "validateOnly": {
        "description": "Optional. If set to `true`, validates and previews the request, but doesn't delete the subscription.",
        "location": "query",
        "type": "boolean"
      },
      "allowMissing": {
        "description": "Optional. If set to `true` and the subscription isn't found, the request succeeds but doesn't delete the subscription.",
        "location": "query",
        "type": "boolean"
      },
      "etag": {
        "description": "Optional. Etag of the subscription. If present, it must match with the server's etag. Otherwise, request fails with the status `ABORTED`.",
        "location": "query",
        "type": "string"
      }
    },
    "parameterOrder": [
      "name"
    ],
    "response": {
      "$ref": "Operation"
    }
  },
```



```

    "scopes": [
      "https://www.googleapis.com/auth/chat.bot",
      "https://www.googleapis.com/auth/chat.memberships",
      "https://www.googleapis.com/auth/chat.memberships.readonly",
      "https://www.googleapis.com/auth/chat.messages",
      "https://www.googleapis.com/auth/chat.messages.reactions",
      "https://www.googleapis.com/auth/chat.messages.reactions.readonly",
      "https://www.googleapis.com/auth/chat.messages.readonly",
      "https://www.googleapis.com/auth/chat.spaces",
      "https://www.googleapis.com/auth/chat.spaces.readonly",
      "https://www.googleapis.com/auth/drive",
      "https://www.googleapis.com/auth/drive.file",
      "https://www.googleapis.com/auth/drive.metadata",
      "https://www.googleapis.com/auth/drive.metadata.readonly",
      "https://www.googleapis.com/auth/drive.readonly",
      "https://www.googleapis.com/auth/meetings.space.created",
      "https://www.googleapis.com/auth/meetings.space.readonly"
    ],
    "description": "Deletes a Google Workspace subscription. To learn how to use this method, see [Delete a Google Workspace subscription] (https://developers.google.com/workspace/events/guides/delete-subscription).",
  },
  "get": {
    "id": "workspaceevents.subscriptions.get",
    "path": "v1/{+name}",
    "flatPath": "v1/subscriptions/{subscriptionsId}",
    "httpMethod": "GET",
    "parameters": {
      "name": {
        "description": "Required. Resource name of the subscription. Format: `subscriptions/{subscription}`",
        "pattern": "^subscriptions[/\\?]+$",
        "location": "path",
        "required": true,
        "type": "string"
      }
    },
    "parameterOrder": [
      "name"
    ],
    "response": {
      "$ref": "Subscription"
    },
    "scopes": [
      "https://www.googleapis.com/auth/chat.bot",
      "https://www.googleapis.com/auth/chat.memberships",
      "https://www.googleapis.com/auth/chat.memberships.readonly",
      "https://www.googleapis.com/auth/chat.messages",
      "https://www.googleapis.com/auth/chat.messages.reactions",
      "https://www.googleapis.com/auth/chat.messages.reactions.readonly",
      "https://www.googleapis.com/auth/chat.messages.readonly",
      "https://www.googleapis.com/auth/chat.spaces",
      "https://www.googleapis.com/auth/chat.spaces.readonly",

```



```

        "https://www.googleapis.com/auth/drive",
        "https://www.googleapis.com/auth/drive.file",
        "https://www.googleapis.com/auth/drive.metadata",
        "https://www.googleapis.com/auth/drive.metadata.readonly",
        "https://www.googleapis.com/auth/drive.readonly",
        "https://www.googleapis.com/auth/meetings.space.created",
        "https://www.googleapis.com/auth/meetings.space.readonly"
    ],
    "description": "Gets details about a Google Workspace subscription. To learn
how to use this method, see [Get details about a Google Workspace
subscription](https://developers.google.com/workspace/events/guides/get-
subscription).",
  },
  "list": {
    "id": "workspaceevents.subscriptions.list",
    "path": "v1/subscriptions",
    "flatPath": "v1/subscriptions",
    "httpMethod": "GET",
    "parameters": {
      "pageSize": {
        "description": "Optional. The maximum number of subscriptions to
return. The service might return fewer than this value. If unspecified
or set to `0`, up to 50 subscriptions are returned. The maximum value
is 100. If you specify a value more than 100, the system only returns
100 subscriptions.",
        "location": "query",
        "type": "integer",
        "format": "int32"
      },
      "pageToken": {
        "description": "Optional. A page token, received from a previous list
subscriptions call. Provide this parameter to retrieve the subsequent
page. When paginating, the filter value should match the call that
provided the page token. Passing a different value might lead to
unexpected results.",
        "location": "query",
        "type": "string"
      },
      "filter": {
        "description": "Required. A query filter. You can filter subscriptions
by event type (`event_types`) and target resource (`target_resource`).
You must specify at least one event type in your query. To filter for
multiple event types, use the `OR` operator. To filter by both event
type and target resource, use the `AND` operator and specify the full
resource name, such as `//chat.googleapis.com/spaces/{space}`. For
example, the following queries are valid: ```
event_types:\"google.workspace.chat.membership.v1.updated\" OR
event_types:\"google.workspace.chat.message.v1.created\"
event_types:\"google.workspace.chat.message.v1.created\" AND
target_resource=\"//chat.googleapis.com/spaces/{space}\" (
event_types:\"google.workspace.chat.membership.v1.updated\" OR
event_types:\"google.workspace.chat.message.v1.created\" ) AND

```




```

        target_resource="\`chat.googleapis.com/spaces/{space}\`" `` The
        server rejects invalid queries with an `INVALID_ARGUMENT` error.",
        "location": "query",
        "type": "string"
    }
},
"parameterOrder": [],
"response": {
    "$ref": "ListSubscriptionsResponse"
},
"scopes": [
    "https://www.googleapis.com/auth/chat.bot",
    "https://www.googleapis.com/auth/chat.memberships",
    "https://www.googleapis.com/auth/chat.memberships.readonly",
    "https://www.googleapis.com/auth/chat.messages",
    "https://www.googleapis.com/auth/chat.messages.reactions",
    "https://www.googleapis.com/auth/chat.messages.reactions.readonly",
    "https://www.googleapis.com/auth/chat.messages.readonly",
    "https://www.googleapis.com/auth/chat.spaces",
    "https://www.googleapis.com/auth/chat.spaces.readonly",
    "https://www.googleapis.com/auth/drive",
    "https://www.googleapis.com/auth/drive.file",
    "https://www.googleapis.com/auth/drive.metadata",
    "https://www.googleapis.com/auth/drive.metadata.readonly",
    "https://www.googleapis.com/auth/drive.readonly",
    "https://www.googleapis.com/auth/meetings.space.created",
    "https://www.googleapis.com/auth/meetings.space.readonly"
],
"description": "Lists Google Workspace subscriptions. To learn how to use
this method, see [List Google Workspace subscriptions]
(https://developers.google.com/workspace/events/guides/list-subscriptions).",
},
"patch": {
    "id": "workspaceevents.subscriptions.patch",
    "path": "v1/{+name}",
    "flatPath": "v1/subscriptions/{subscriptionsId}",
    "httpMethod": "PATCH",
    "parameters": {
        "name": {
            "description": "Identifier. Resource name of the subscription. Format:
            `subscriptions/{subscription}`",
            "pattern": "^subscriptions/[^/]+$",
            "location": "path",
            "required": true,
            "type": "string"
        },
        "updateMask": {
            "description": "Optional. The field to update. If omitted, updates any
            fields included in the request. You can update one of the following
            fields in a subscription: * `expire_time`: The timestamp when the
            subscription expires. * `ttl`: The time-to-live (TTL) or duration of
            the subscription. * `event_types`: The list of event types to receive
            about the target resource. When using the `*` wildcard (equivalent to

```

```

    `PUT`), omitted fields are set to empty values and rejected if they're
    invalid.",
    "location": "query",
    "type": "string",
    "format": "google-fieldmask"
  },
  "validateOnly": {
    "description": "Optional. If set to `true`, validates and previews the
    request, but doesn't update the subscription.",
    "location": "query",
    "type": "boolean"
  }
},
"parameterOrder": [
  "name"
],
"request": {
  "$ref": "Subscription"
},
"response": {
  "$ref": "Operation"
},
"scopes": [
  "https://www.googleapis.com/auth/chat.app.memberships",
  "https://www.googleapis.com/auth/chat.app.messages.readonly",
  "https://www.googleapis.com/auth/chat.app.spaces",
  "https://www.googleapis.com/auth/chat.memberships",
  "https://www.googleapis.com/auth/chat.memberships.readonly",
  "https://www.googleapis.com/auth/chat.messages",
  "https://www.googleapis.com/auth/chat.messages.reactions",
  "https://www.googleapis.com/auth/chat.messages.reactions.readonly",
  "https://www.googleapis.com/auth/chat.messages.readonly",
  "https://www.googleapis.com/auth/chat.spaces",
  "https://www.googleapis.com/auth/chat.spaces.readonly",
  "https://www.googleapis.com/auth/drive",
  "https://www.googleapis.com/auth/drive.file",
  "https://www.googleapis.com/auth/drive.metadata",
  "https://www.googleapis.com/auth/drive.metadata.readonly",
  "https://www.googleapis.com/auth/drive.readonly",
  "https://www.googleapis.com/auth/meetings.space.created",
  "https://www.googleapis.com/auth/meetings.space.readonly"
],
"description": "Updates or renews a Google Workspace subscription. To learn
how to use this method, see [Update or renew a Google Workspace subscription]
(https://developers.google.com/workspace/events/guides/update-subscription).
For a subscription on a [Chat target resource]
(https://developers.google.com/workspace/events/guides/events-chat), you can
update a subscription as: - A Chat app by specifying an authorization scope
that begins with `chat.app` and getting one-time administrator approval
([Developer Preview](https://developers.google.com/workspace/preview)). To
learn more, see [Authorize as a Chat app with administrator approval]
(https://developers.google.com/workspace/chat/authenticate-authorize-chat-app). - A user by specifying an authorization scope that doesn't include

```



`app` in its name. To learn more, see [Authorize as a Chat user] (<https://developers.google.com/workspace/chat/authenticate-authorize-chat-user>)."

},

```
▼ "reactivate": {
  "id": "workspaceevents.subscriptions.reactivate",
  "path": "v1/{+name}:reactivate",
  "flatPath": "v1/subscriptions/{subscriptionsId}:reactivate",
  "httpMethod": "POST",
  ▼ "parameters": {
    ▼ "name": {
      "description": "Required. Resource name of the subscription. Format: `subscriptions/{subscription}`",
      "pattern": "^subscriptions/[^/]+$",
      "location": "path",
      "required": true,
      "type": "string"
    }
  },
  ▼ "parameterOrder": [
    "name"
  ],
  ▼ "request": {
    "$ref": "ReactivateSubscriptionRequest"
  },
  ▼ "response": {
    "$ref": "Operation"
  },
  ▼ "scopes": [
    "https://www.googleapis.com/auth/chat.app.memberships",
    "https://www.googleapis.com/auth/chat.app.messages.readonly",
    "https://www.googleapis.com/auth/chat.app.spaces",
    "https://www.googleapis.com/auth/chat.memberships",
    "https://www.googleapis.com/auth/chat.memberships.readonly",
    "https://www.googleapis.com/auth/chat.messages",
    "https://www.googleapis.com/auth/chat.messages.reactions",
    "https://www.googleapis.com/auth/chat.messages.reactions.readonly",
    "https://www.googleapis.com/auth/chat.messages.readonly",
    "https://www.googleapis.com/auth/chat.spaces",
    "https://www.googleapis.com/auth/chat.spaces.readonly",
    "https://www.googleapis.com/auth/drive",
    "https://www.googleapis.com/auth/drive.file",
    "https://www.googleapis.com/auth/drive.metadata",
    "https://www.googleapis.com/auth/drive.metadata.readonly",
    "https://www.googleapis.com/auth/drive.readonly",
    "https://www.googleapis.com/auth/meetings.space.created",
    "https://www.googleapis.com/auth/meetings.space.readonly"
  ],
```

"description": "Reactivates a suspended Google Workspace subscription. This method resets your subscription's `State` field to `ACTIVE`. Before you use this method, you must fix the error that suspended the subscription. This method will ignore or reject any subscription that isn't currently in a suspended state. To learn how to use this method, see [Reactivate a Google

Workspace subscription]
(<https://developers.google.com/workspace/events/guides/reactivate-subscription>). For a subscription on a [Chat target resource] (<https://developers.google.com/workspace/events/guides/events-chat>), you can reactivate a subscription as: - A Chat app by specifying an authorization scope that begins with `chat.app` and getting one-time administrator approval ([Developer Preview](<https://developers.google.com/workspace/preview>)). To learn more, see [Authorize as a Chat app with administrator approval] (<https://developers.google.com/workspace/chat/authenticate-authorize-chat-app>). - A user by specifying an authorization scope that doesn't include `app` in its name. To learn more, see [Authorize as a Chat user] (<https://developers.google.com/workspace/chat/authenticate-authorize-chat-user>)."

}

}

}

},

"description": "The Google Workspace Events API lets you subscribe to events and manage change notifications across Google Workspace applications.",

"revision": "20251007",

✖ "schemas": {

✖ "Operation": {

"id": "Operation",

"description": "This resource represents a long-running operation that is the result of a network API call.",

"type": "object",

✖ "properties": {

✖ "name": {

"description": "The server-assigned name, which is only unique within the same service that originally returns it. If you use the default HTTP mapping, the `name` should be a resource name ending with `operations/{unique\_id}`.",

"type": "string"

},

✖ "metadata": {

"description": "Service-specific metadata associated with the operation. It typically contains progress information and common metadata such as create time. Some services might not provide such metadata. Any method that returns a long-running operation should document the metadata type, if any.",

"type": "object",

✖ "additionalProperties": {

"type": "any",

"description": "Properties of the object. Contains field @type with type URL."

}

},

✖ "done": {

"description": "If the value is `false`, it means the operation is still in progress. If `true`, the operation is completed, and either `error` or `response` is available.",

"type": "boolean"

},

✖ "error": {



```

        "description": "The error result of the operation in case of failure or
        cancellation.",
        "$ref": "Status"
    },
    "response": {
        "description": "The normal, successful response of the operation. If the
        original method returns no data on success, such as `Delete`, the response is
        `google.protobuf.Empty`. If the original method is standard
        `Get`/`Create`/`Update`, the response should be the resource. For other
        methods, the response should have the type `XxxResponse`, where `Xxx` is the
        original method name. For example, if the original method name is
        `TakeSnapshot()`, the inferred response type is `TakeSnapshotResponse`.",
        "type": "object",
        "additionalProperties": {
            "type": "any",
            "description": "Properties of the object. Contains field @type with type
            URL."
        }
    }
},
"Status": {
    "id": "Status",
    "description": "The `Status` type defines a logical error model that is suitable for
    different programming environments, including REST APIs and RPC APIs. It is used by
    [gRPC](https://github.com/grpc). Each `Status` message contains three pieces of data:
    error code, error message, and error details. You can find out more about this error
    model and how to work with it in the [API Design Guide]
    (https://cloud.google.com/apis/design/errors).",
    "type": "object",
    "properties": {
        "code": {
            "description": "The status code, which should be an enum value of
            google.rpc.Code.",
            "type": "integer",
            "format": "int32"
        },
        "message": {
            "description": "A developer-facing error message, which should be in English.
            Any user-facing error message should be localized and sent in the
            google.rpc.Status.details field, or localized by the client.",
            "type": "string"
        },
        "details": {
            "description": "A list of messages that carry the error details. There is a
            common set of message types for APIs to use.",
            "type": "array",
            "items": {
                "type": "object",
                "additionalProperties": {
                    "type": "any",
                    "description": "Properties of the object. Contains field @type with
                    type URL."
                }
            }
        }
    }
}

```



```

    },
    "Subscription": {
      "id": "Subscription",
      "description": "A subscription to receive events about a Google Workspace resource. To learn more about subscriptions, see the [Google Workspace Events API overview] (https://developers.google.com/workspace/events).",
      "type": "object",
      "properties": {
        "expireTime": {
          "description": "Non-empty default. The timestamp in UTC when the subscription expires. Always displayed on output, regardless of what was used on input.",
          "type": "string",
          "format": "google-datetime"
        },
        "ttl": {
          "description": "Input only. The time-to-live (TTL) or duration for the subscription. If unspecified or set to `0`, uses the maximum possible duration.",
          "type": "string",
          "format": "google-duration"
        },
        "name": {
          "description": "Identifier. Resource name of the subscription. Format: `subscriptions/{subscription}`",
          "type": "string"
        },
        "uid": {
          "description": "Output only. System-assigned unique identifier for the subscription.",
          "readOnly": true,
          "type": "string"
        },
        "targetResource": {
          "description": "Required. Immutable. The Google Workspace resource that's monitored for events, formatted as the [full resource name] (https://google.aip.dev/122#full-resource-names). To learn about target resources and the events that they support, see [Supported Google Workspace events](https://developers.google.com/workspace/events#supported-events). A user can only authorize your app to create one subscription for a given target resource. If your app tries to create another subscription with the same user credentials, the request returns an `ALREADY_EXISTS` error.",
          "type": "string"
        },
        "eventTypes": {
          "description": "Required. Unordered list. Input for creating a subscription. Otherwise, output only. One or more types of events to receive about the target resource. Formatted according to the CloudEvents specification. The supported event types depend on the target resource of your subscription. For details, see [Supported Google Workspace events]"
        }
      }
    }
  },
  "type": "object"
},

```

```

    (https://developers.google.com/workspace/events/guides#supported-events). By
    default, you also receive events about the [lifecycle of your subscription]
    (https://developers.google.com/workspace/events/guides/events-lifecycle). You
    don't need to specify lifecycle events for this field. If you specify an
    event type that doesn't exist for the target resource, the request returns an
    HTTP `400 Bad Request` status code.",
    "type": "array",
    "items": {
      "type": "string"
    }
  },
  "payloadOptions": {
    "description": "Optional. Options about what data to include in the event
    payload. Only supported for Google Chat and Google Drive events.",
    "$ref": "PayloadOptions"
  },
  "notificationEndpoint": {
    "description": "Required. Immutable. The endpoint where the subscription
    delivers events, such as a Pub/Sub topic.",
    "$ref": "NotificationEndpoint"
  },
  "state": {
    "description": "Output only. The state of the subscription. Determines
    whether the subscription can receive events and deliver them to the
    notification endpoint.",
    "readOnly": true,
    "type": "string",
    "enumDescriptions": [
      "Default value. This value is unused.",
      "The subscription is active and can receive and deliver events to its
      notification endpoint.",
      "The subscription is unable to receive events due to an error. To identify
      the error, see the `suspension_reason` field.",
      "The subscription is deleted."
    ],
    "enum": [
      "STATE_UNSPECIFIED",
      "ACTIVE",
      "SUSPENDED",
      "DELETED"
    ]
  },
  "suspensionReason": {
    "description": "Output only. The error that suspended the subscription. To
    reactivate the subscription, resolve the error and call the
    `ReactivateSubscription` method.",
    "readOnly": true,
    "type": "string",
    "enumDescriptions": [
      "Default value. This value is unused.",
      "The authorizing user has revoked the grant of one or more OAuth scopes.
      To learn more about authorization for Google Workspace, see [Configure the
      OAuth consent screen]

```



```

        (https://developers.google.com/workspace/guides/configure-oauth-consent#choose-scopes).",
        "The target resource for the subscription no longer exists.",
        "The user that authorized the creation of the subscription no longer has access to the subscription's target resource.",
        "The Google Workspace application doesn't have access to deliver events to your subscription's notification endpoint.",
        "The subscription's notification endpoint doesn't exist, or the endpoint can't be found in the Google Cloud project where you created the subscription.",
        "The subscription's notification endpoint failed to receive events due to insufficient quota or reaching rate limiting.",
        "An unidentified error has occurred."
    ],
    "enum": [
        "ERROR_TYPE_UNSPECIFIED",
        "USER_SCOPE_REVOKED",
        "RESOURCE_DELETED",
        "USER_AUTHORIZATION_FAILURE",
        "ENDPOINT_PERMISSION_DENIED",
        "ENDPOINT_NOT_FOUND",
        "ENDPOINT_RESOURCE_EXHAUSTED",
        "OTHER"
    ]
},
"authority": {
    "description": "Output only. The user who authorized the creation of the subscription. When a user authorizes the subscription, this field and the `user_authority` field have the same value and the format is: Format: `users/{user}` For Google Workspace users, the `{user}` value is the [ `user.id` ](https://developers.google.com/admin-sdk/directory/reference/rest/v1/users#User.FIELDS.ids) field from the Directory API. When a Chat app authorizes the subscription, only `service_account_authority` field populates and this field is empty.",
    "readOnly": true,
    "type": "string"
},
"createTime": {
    "description": "Output only. The time when the subscription is created.",
    "readOnly": true,
    "type": "string",
    "format": "google-datetime"
},
"updateTime": {
    "description": "Output only. The last time that the subscription is updated.",
    "readOnly": true,
    "type": "string",
    "format": "google-datetime"
},
"reconciling": {
    "description": "Output only. If `true`, the subscription is in the process of being updated.",

```




```

        "readOnly": true,
        "type": "boolean"
    },
    "etag": {
        "description": "Optional. This checksum is computed by the server based on the value of other fields, and might be sent on update requests to ensure the client has an up-to-date value before proceeding.",
        "type": "string"
    }
},
"PayloadOptions": {
    "id": "PayloadOptions",
    "description": "Options about what data to include in the event payload. Only supported for Google Chat and Google Drive events.",
    "type": "object",
    "properties": {
        "includeResource": {
            "description": "Optional. Whether the event payload includes data about the resource that changed. For example, for an event where a Google Chat message was created, whether the payload contains data about the [Message] (https://developers.google.com/chat/api/reference/rest/v1/spaces.messages) resource. If false, the event payload only includes the name of the changed resource.",
            "type": "boolean"
        },
        "fieldMask": {
            "description": "Optional. If `include_resource` is set to `true`, the list of fields to include in the event payload. Separate fields with a comma. For example, to include a Google Chat message's sender and create time, enter `message.sender,message.createTime`. If omitted, the payload includes all fields for the resource. If you specify a field that doesn't exist for the resource, the system ignores the field.",
            "type": "string",
            "format": "google-fieldmask"
        }
    }
},
"NotificationEndpoint": {
    "id": "NotificationEndpoint",
    "description": "The endpoint where the subscription delivers events.",
    "type": "object",
    "properties": {
        "pubsubTopic": {
            "description": "Immutable. The Pub/Sub topic that receives events for the subscription. Format: `projects/{project}/topics/{topic}` You must create the topic in the same Google Cloud project where you create this subscription. Note: The Google Workspace Events API uses [ordering keys] (https://cloud.google.com/pubsub/docs/ordering) for the benefit of sequential events. If the Cloud Pub/Sub topic has a [message storage policy] (https://cloud.google.com/pubsub/docs/resource-location-restriction#exceptions) configured to exclude the nearest Google Cloud region, publishing events with ordering keys will fail. When the topic

```



```

        receives events, the events are encoded as Pub/Sub messages. For details, see
        the [Google Cloud Pub/Sub Protocol Binding for CloudEvents]
        (https://github.com/googleapis/google-cloudevents/blob/main/docs/spec/pubsub.md).",
        "type": "string"
    }
},
    "ListSubscriptionsResponse": {
        "id": "ListSubscriptionsResponse",
        "description": "The response message for SubscriptionsService.ListSubscriptions.",
        "type": "object",
        "properties": {
            "subscriptions": {
                "description": "List of subscriptions.",
                "type": "array",
                "items": {
                    "$ref": "Subscription"
                }
            },
            "nextPageToken": {
                "description": "A token, which can be sent as `page_token` to retrieve the
                next page. If this field is omitted, there are no subsequent pages.",
                "type": "string"
            }
        }
    },
    "ReactivateSubscriptionRequest": {
        "id": "ReactivateSubscriptionRequest",
        "description": "The request message for
        SubscriptionsService.ReactivateSubscription.",
        "type": "object",
        "properties": {}
    }
},
"kind": "discovery#restDescription",
"version_module": true,
"canonicalName": "Workspace Events",
"servicePath": ""
}

```

