

Hozzáférési kontextuskezelő API

Egy API attribútumalapú hozzáférés-vezérlés beállításához a Google Cloud szolgáltatásokhoz intézett kérésekhez.

Figyelmeztetés: Ne keverje a **v1alpha** és a **v1** API használatát ugyanabban a hozzáférési szabályzatban. A v1alpha API támogatja az Access Context Manager új funkcióit, amelyek eltérő attribútumokkal vagy viselkedésekkel rendelkezhetnek, amelyeket a v1 nem támogat. A vegyes API-használat egy szabályzaton belüli gyakorlata a szabályzat, beleértve a hozzá tartozó hozzáférési szinteket vagy szolgáltatási perimétereket is, frissítésének lehetetlenségét eredményezheti. Nem ajánlott a v1 és a v1alpha együttes használata kritikus szolgáltatási periméterekkel rendelkező szabályzatok módosításához. A v1alpha használatával történő módosításokat a nem éles/nem kritikus szolgáltatási periméterekkel rendelkező szabályzatokra kell korlátozni.

Szolgáltatás : accesscontextmanager.googleapis.com

A szolgáltatás meghívásához a Google által biztosított klienskönyvtárak

(<https://cloud.google.com/apis/docs/client-libraries-explained>) használatát javasoljuk . Ha az alkalmazásnak saját könyvtárakat kell használnia a szolgáltatás meghívásához, az API-kérések végrehajtásakor használja a következő információkat.

Felfedező dokumentum

A Discovery Document (<https://developers.google.com/discovery/v1/reference/apis>) egy géppel olvasható specifikáció a REST API-k leírására és felhasználására. Klienskönyvtárak, IDE bővítmények és más, a Google API-kkal interakcióba lépő eszközök létrehozására szolgál. Egy szolgáltatás több discovery dokumentumot is biztosíthat. Ez a szolgáltatás a következő discovery dokumentumokat biztosítja:

- [https://accesscontextmanager.googleapis.com/\\$discovery/rest?version=v1](https://accesscontextmanager.googleapis.com/$discovery/rest?version=v1)
([https://accesscontextmanager.googleapis.com/\\$discovery/rest?version=v1](https://accesscontextmanager.googleapis.com/$discovery/rest?version=v1))
- [https://accesscontextmanager.googleapis.com/\\$discovery/rest?version=v1alpha](https://accesscontextmanager.googleapis.com/$discovery/rest?version=v1alpha)
([https://accesscontextmanager.googleapis.com/\\$discovery/rest?version=v1alpha](https://accesscontextmanager.googleapis.com/$discovery/rest?version=v1alpha))



Szolgáltatásvégpont

A service endpoint (https://cloud.google.com/apis/design/glossary#api_service_endpoint) is a base URL that specifies the network address of an API service. One service might have multiple service endpoints. This service has the following service endpoint and all URIs below are relative to this service endpoint:

- <https://accesscontextmanager.googleapis.com>

REST Resource: v1alpha.accessPolicies

(/access-context-manager/docs/reference/rest/v1alpha/accessPolicies)

Methods

<u>create</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies/create)	POST /v1alpha/accessPolicies Creates an access policy.
<u>delete</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies/delete)	DELETE /v1alpha/{name=accessPolicies/*} Deletes an <u>access_policy</u> based on the resource name.
<u>get</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies/get)	GET /v1alpha/{name=accessPolicies/*} Returns an <u>access_policy</u> based on the name.
<u>getIamPolicy</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies/getIamPolicy)	POST /v1alpha/{resource=accessPolicies/*}:getIamPolicy Gets the IAM policy for the specified Access Context Manager <u>access_policy</u> .



Methods

<u>list</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies#AccessPolicy) s/list)	GET /v1alpha/accessPolicies Lists all <u>access policies</u> in an organization.
<u>patch</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies#AccessPolicy) s/patch)	PATCH /v1alpha/{policy.name=accessPolicies/*} Updates an <u>access policy</u> .
<u>setIamPolicy</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies#AccessPolicy) s/setIamPolicy)	POST /v1alpha/{resource=accessPolicies/*}:setIamPolicy Sets the IAM policy for the specified Access Context Manager <u>access policy</u> .
<u>testIamPermissions</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies#AccessPolicy) s/testIamPermissions)	POST /v1alpha/{resource=accessPolicies/*}:testIamPermissions Returns the IAM permissions that the caller has on the specified Access Context Manager resource.

REST Resource: v1alpha.accessPolicies.accessLevels

(/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.accessLevels)

Methods

<u>create</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.accessLevels#AccessLevels/create) el)	POST /v1alpha/{parent=accessPolicies/*}/accessLevels Creates an <u>access level</u> .
--	---



Methods

<u>delete</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.accessLevels/delete)	DELETE /v1alpha/{name=accessPolicies/*/accessLevels/*} Deletes an <u>access_level</u> based on the resource name.
<u>get</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.accessLevels/get)	GET /v1alpha/{name=accessPolicies/*/accessLevels/*} Gets an <u>access_level</u> based on the resource name.
<u>list</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.accessLevels/list)	GET /v1alpha/{parent=accessPolicies/*/accessLevels} Lists all <u>access_levels</u> for an access policy.
<u>patch</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.accessLevels/patch)	PATCH /v1alpha/{accessLevel.name=accessPolicies/*/accessLevels/*} Updates an <u>access_level</u>
<u>replaceAll</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.accessLevels/replaceAll)	POST /v1alpha/{parent=accessPolicies/*/accessLevels:replaceAll} Replaces all existing <u>access_levels</u> in an <u>access_policy</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies#AccessPolicy) with the <u>access_levels</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.accessLevels#AccessLevel) provided.



Methods

testIamPermissions POST

(/access-context-manager/docs/reference/rest/v1alpha/{resource=accessPolicies/*/accessLevels/*}:testIamPermissions
est/v1alpha/accessPolicies. Returns the IAM permissions that the caller has on the specified Access Context
s.accessLevels/testIamPe Manager resource.
missions)

REST Resource: v1alpha.accessPolicies.authorizedOrgsDescs

(/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.authorizedOrgsDescs)

Methods

create POST /v1alpha/{parent=accessPolicies/*}/authorizedOrgsDescs
(/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.authorizedOrgsDescs#AuthorizedOrgsDesc)
Creates an authorized orgs desc
est/v1alpha/accessPolicies.authorizedOrgsDescs#AuthorizedOrgsDesc)
s.authorizedOrgsDescs/create)
eate)

delete DELETE /v1alpha/{name=accessPolicies/*/authorizedOrgsDescs/*}
(/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.authorizedOrgsDescs#AuthorizedOrgsDesc)
Deletes an authorized orgs desc
est/v1alpha/accessPolicies.authorizedOrgsDescs#AuthorizedOrgsDesc)
s.authorizedOrgsDescs/delete)
lete) based on the resource name.

get GET /v1alpha/{name=accessPolicies/*/authorizedOrgsDescs/*}
(/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.authorizedOrgsDescs#AuthorizedOrgsDesc)
Gets an authorized orgs desc
est/v1alpha/accessPolicies.authorizedOrgsDescs#AuthorizedOrgsDesc)
s.authorizedOrgsDescs/get)
t) based on the resource name.



Methods

<u>list</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.authorizedOrgsDescs#AuthorizedOrgsDescs/list)	GET /v1alpha/{parent=accessPolicies/*}/authorizedOrgsDescs Lists all <u>authorized orgs desc</u> s for an access policy.
<u>patch</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.authorizedOrgsDescs/patch)	PATCH /v1alpha/{authorizedOrgsDesc.name=accessPolicies/*}/authorizedOrgsDescs/* Updates an <u>authorized orgs desc</u> in an <u>access policy</u> .

REST Resource: v1alpha.accessPolicies.servicePerimeters

(/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters)

Methods

<u>commit</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters/commit)	POST /v1alpha/{parent=accessPolicies/*}/servicePerimeters:commit Commits the dry-run specification for all the <u>service perimeters</u> in an <u>access policy</u> .
<u>create</u> (/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters/create)	POST /v1alpha/{parent=accessPolicies/*}/servicePerimeters Creates a <u>service perimeter</u> in an <u>access policy</u> .



Methods

<u>delete</u> (/access-context- manager/docs/reference/r est/v1alpha/accessPolicie s.servicePerimeters/delete)	DELETE /v1alpha/{name=accessPolicies/*/servicePerimeters/*} Deletes a <u>service perimeter</u> manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters#ServicePerimeter) based on the resource name.
<u>get</u> (/access-context- manager/docs/reference/r est/v1alpha/accessPolicie s.servicePerimeters/get)	GET /v1alpha/{name=accessPolicies/*/servicePerimeters/*} Gets a <u>service perimeter</u> manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters#ServicePerimeter) based on the resource name.
<u>list</u> (/access-context- manager/docs/reference/r est/v1alpha/accessPolicie s.servicePerimeters/list)	GET /v1alpha/{parent=accessPolicies/*/servicePerimeters Lists all <u>service perimeters</u> manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters#ServicePerimeter) for an access policy.
<u>patch</u> (/access-context- manager/docs/reference/r est/v1alpha/accessPolicie s.servicePerimeters/patch)	PATCH /v1alpha/{servicePerimeter.name=accessPolicies/*/servicePerimeters/*} Updates a <u>service perimeter</u> (/access-context- manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters#ServicePerimeter) .
<u>replaceAll</u> (/access-context- manager/docs/reference/r est/v1alpha/accessPolicie s.servicePerimeters/replac eAll)	POST /v1alpha/{parent=accessPolicies/*/servicePerimeters:replaceAll Replace all existing <u>service perimeters</u> (/access-context- manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters#ServicePerimeter) in an <u>access policy</u> (/access-context- manager/docs/reference/rest/v1alpha/accessPolicies#AccessPolicy) with the <u>service perimeters</u>



Methods

(/access-context-manager/docs/reference/rest/v1alpha/accessPolicies.servicePerimeters#ServicePerimeter)
provided.

testIamPermissions POST

(/access-context-manager/docs/reference/rest/v1alpha/{resource=accessPolicies/*/servicePerimeters/*}:testIamPermissions
est/v1alpha/accessPolicies.servicePerimeters/testIamPermissions)
Returns the IAM permissions that the caller has on the specified Access Context Manager resource.

REST Resource: v1alpha.operations

(/access-context-manager/docs/reference/rest/v1alpha/operations)

Methods

get GET /v1alpha/{name=operations/**}
(/access-context-manager/docs/reference/rest/v1alpha/operations/get)
Gets the latest state of a long-running operation.

REST Resource: v1alpha.organizations.gcpUserAccessBindings

(/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings)



Methods

<u>create</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings#create)	POST /v1alpha/{parent=organizations/*}/gcpUserAccessBindings Creates a <u>GcpUserAccessBinding</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings#GcpUserAccessBinding) .
<u>delete</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings/delete)	DELETE /v1alpha/{name=organizations/*/gcpUserAccessBindings/*} Deletes a <u>GcpUserAccessBinding</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings#GcpUserAccessBinding) .
<u>get</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings/get)	GET /v1alpha/{name=organizations/*/gcpUserAccessBindings/*} Gets the <u>GcpUserAccessBinding</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings#GcpUserAccessBinding) with the given name.
<u>list</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings/list)	GET /v1alpha/{parent=organizations/*}/gcpUserAccessBindings Lists all <u>GcpUserAccessBindings</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings#GcpUserAccessBinding) for a Google Cloud organization.
<u>patch</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings/patch)	PATCH /v1alpha/{gcpUserAccessBinding.name=organizations/*/gcpUserAccessBindings/*} Updates a <u>GcpUserAccessBinding</u> (/access-context-manager/docs/reference/rest/v1alpha/organizations.gcpUserAccessBindings#GcpUserAccessBinding) .



REST Resource: v1alpha.services

(/access-context-manager/docs/reference/rest/v1alpha/services)

Methods

<u>get</u> (/access-context-manager/docs/reference/rest/v1alpha/services/get)	GET /v1alpha/services/{name} Get a <u>VPS-SC Supported Service</u> by name. (/access-context-manager/docs/reference/rest/v1alpha/services#SupportedService)
---	---

<u>list</u> (/access-context-manager/docs/reference/rest/v1alpha/services/list)	GET /v1alpha/services Lists all <u>VPC-SC supported services</u> . (/access-context-manager/docs/reference/rest/v1alpha/services#SupportedService)
---	--

REST Resource: v1.accessPolicies

(/access-context-manager/docs/reference/rest/v1/accessPolicies)

Methods

<u>create</u> (/access-context-manager/docs/reference/rest/v1/accessPolicies/create)	POST /v1/accessPolicies Creates an access policy.
--	--

<u>delete</u> (/access-context-manager/docs/reference/rest/v1/accessPolicies/delete)	DELETE /v1/{name=accessPolicies/*} Deletes an <u>access_policy</u> based on the resource name. (/access-context-manager/docs/reference/rest/v1/accessPolicies#AccessPolicy)
--	---

<u>get</u> (/access-context-manager/docs/reference/rest/v1/accessPolicies/get)	GET /v1/{name=accessPolicies/*} Returns an <u>access_policy</u> based on the name. (/access-context-manager/docs/reference/rest/v1/accessPolicies#AccessPolicy)
--	---



Methods

<u>getIamPolicy</u> (/access-context-manager/docs/reference/rest/v1/accessPolicies/getIamPolicy)	POST /v1/{resource=accessPolicies/*}:getIamPolicy Gets the IAM policy for the specified Access Context Manager <u>access_policy</u> resource.
<u>list</u> (/access-context-manager/docs/reference/rest/v1/accessPolicies/list)	GET /v1/accessPolicies Lists all <u>access_policies</u> in an organization.
<u>patch</u> (/access-context-manager/docs/reference/rest/v1/accessPolicies/patch)	PATCH /v1/{policy.name=accessPolicies/*} Updates an <u>access_policy</u> resource.
<u>setIamPolicy</u> (/access-context-manager/docs/reference/rest/v1/accessPolicies/setIamPolicy)	POST /v1/{resource=accessPolicies/*}:setIamPolicy Sets the IAM policy for the specified Access Context Manager <u>access_policy</u> resource.
<u>testIamPermissions</u> (/access-context-manager/docs/reference/rest/v1/accessPolicies/testIamPermissions)	POST /v1/{resource=accessPolicies/*}:testIamPermissions Returns the IAM permissions that the caller has on the specified Access Context Manager resource.

REST Resource: v1.accessPolicies.accessLevels

(/access-context-manager/docs/reference/rest/v1/accessPolicies.accessLevels)



Methods

create POST /v1/{parent=accessPolicies/*/accessLevels
(/access-context- Creates an access level
manager/docs/reference/r (/access-context-
est/v1/accessPolicies.access manager/docs/reference/rest/v1/accessPolicies.accessLevels#AccessLevel)
essLevels/create) .

delete DELETE /v1/{name=accessPolicies/*/accessLevels/*}
(/access-context- Deletes an access level
manager/docs/reference/r (/access-context-
est/v1/accessPolicies.access manager/docs/reference/rest/v1/accessPolicies.accessLevels#AccessLevel)
essLevels/delete) based on the resource name.

get GET /v1/{name=accessPolicies/*/accessLevels/*}
(/access-context- Gets an access level
manager/docs/reference/r (/access-context-
est/v1/accessPolicies.access manager/docs/reference/rest/v1/accessPolicies.accessLevels#AccessLevel)
essLevels/get) based on the resource name.

list GET /v1/{parent=accessPolicies/*/accessLevels
(/access-context- Lists all access levels
manager/docs/reference/r (/access-context-
est/v1/accessPolicies.access manager/docs/reference/rest/v1/accessPolicies.accessLevels#AccessLevel)
essLevels/list) for an access policy.

patch PATCH
(/access-context- /v1/{accessLevel.name=accessPolicies/*/accessLevels/*}
manager/docs/reference/r Updates an access level
est/v1/accessPolicies.access (/access-context-
essLevels/patch) manager/docs/reference/rest/v1/accessPolicies.accessLevels#AccessLevel)
.

replaceAll POST /v1/{parent=accessPolicies/*/accessLevels:replaceAll
(/access-context- Replaces all existing access levels
manager/docs/reference/r (/access-context-
est/v1/accessPolicies.access manager/docs/reference/rest/v1/accessPolicies.accessLevels#AccessLevel)
essLevels/replaceAll) in an access policy
(/access-context-
manager/docs/reference/rest/v1/accessPolicies#AccessPolicy)
with the access levels
(/access-context-
manager/docs/reference/rest/v1/accessPolicies.accessLevels#AccessLevel)
provided.



Methods

testIamPermissions POST

(/access-context-manager/docs/reference/rest/v1/{resource=accessPolicies/*/accessLevels/*}:testIamPermissions) Returns the IAM permissions that the caller has on the specified Access Context Levels/testIamPermissions resource.

REST Resource: v1.accessPolicies.authorizedOrgsDescs

(/access-context-manager/docs/reference/rest/v1/accessPolicies.authorizedOrgsDescs)

Methods

create POST /v1/{parent=accessPolicies/*/authorizedOrgsDescs

(/access-context-manager/docs/reference/rest/v1/accessPolicies.authorizedOrgsDescs#create) Creates an authorized orgs desc based on the resource name.

delete DELETE /v1/{name=accessPolicies/*/authorizedOrgsDescs/*}

(/access-context-manager/docs/reference/rest/v1/accessPolicies.authorizedOrgsDescs/delete) Deletes an authorized orgs desc based on the resource name.

get GET /v1/{name=accessPolicies/*/authorizedOrgsDescs/*}

(/access-context-manager/docs/reference/rest/v1/accessPolicies.authorizedOrgsDescs/get) Gets an authorized orgs desc based on the resource name.



Methods

list GET /v1/{parent=accessPolicies/*}/authorizedOrgsDescs
(/access-context- Lists all authorized orgs desc
manager/docs/reference/r (/access-context-
est/v1/accessPolicies.aut manager/docs/reference/rest/v1/accessPolicies.authorizedOrgsDescs#Authoriz
horizedOrgsDescs/list) edOrgsDesc)
for an access policy.

patch PATCH
(/access-context- /v1/{authorizedOrgsDesc.name=accessPolicies/*/authorizedOrg
manager/docs/reference/r sDescs/*}
est/v1/accessPolicies.aut Updates an authorized orgs desc
horizedOrgsDescs/patch) (/access-context-
manager/docs/reference/rest/v1/accessPolicies.authorizedOrgsDescs#Authoriz
edOrgsDesc)
.

REST Resource: v1.accessPolicies.servicePerimeters

(/access-context-manager/docs/reference/rest/v1/accessPolicies.servicePerimeters)

Methods

commit POST /v1/{parent=accessPolicies/*}/servicePerimeters:commit
(/access-context- Commits the dry-run specification for all the service perimeters
manager/docs/reference/r (/access-context-
est/v1/accessPolicies.ser manager/docs/reference/rest/v1/accessPolicies.servicePerimeters#ServicePeri
vicePerimeters/commit) meter)
in an access policy
(/access-context-
manager/docs/reference/rest/v1/accessPolicies#AccessPolicy)
.

create POST /v1/{parent=accessPolicies/*}/servicePerimeters
(/access-context- Creates a service perimeter
manager/docs/reference/r (/access-context-
est/v1/accessPolicies.ser manager/docs/reference/rest/v1/accessPolicies.servicePerimeters#ServicePeri
vicePerimeters/create) meter)
.



Methods

<u>delete</u> (/access-context- manager/docs/reference/r est/v1/accessPolicies.ser vicePerimeters/delete)	DELETE /v1/{name=accessPolicies/*/servicePerimeters/*} Deletes a <u>service perimeter</u> (/access-context- manager/docs/reference/rest/v1/accessPolicies.servicePerimeters#ServicePeri meter) based on the resource name.
<u>get</u> (/access-context- manager/docs/reference/r est/v1/accessPolicies.ser vicePerimeters/get)	GET /v1/{name=accessPolicies/*/servicePerimeters/*} Gets a <u>service perimeter</u> (/access-context- manager/docs/reference/rest/v1/accessPolicies.servicePerimeters#ServicePeri meter) based on the resource name.
<u>list</u> (/access-context- manager/docs/reference/r est/v1/accessPolicies.ser vicePerimeters/list)	GET /v1/{parent=accessPolicies/*/}/servicePerimeters Lists all <u>service perimeters</u> (/access-context- manager/docs/reference/rest/v1/accessPolicies.servicePerimeters#ServicePeri meter) for an access policy.
<u>patch</u> (/access-context- manager/docs/reference/r est/v1/accessPolicies.ser vicePerimeters/patch)	PATCH /v1/{servicePerimeter.name=accessPolicies/*/servicePerimete rs/*} Updates a <u>service perimeter</u> (/access-context- manager/docs/reference/rest/v1/accessPolicies.servicePerimeters#ServicePeri meter) .
<u>replaceAll</u> (/access-context- manager/docs/reference/r est/v1/accessPolicies.ser vicePerimeters/replaceAll)	POST /v1/{parent=accessPolicies/*/}/servicePerimeters:replaceAll Replace all existing <u>service perimeters</u> (/access-context- manager/docs/reference/rest/v1/accessPolicies.servicePerimeters#ServicePeri meter) in an <u>access policy</u> (/access-context- manager/docs/reference/rest/v1/accessPolicies#AccessPolicy) with the <u>service perimeters</u>



Methods

(/access-context-manager/docs/reference/rest/v1/accessPolicies.servicePerimeters#ServicePerimeter)
provided.

testIamPermissions POST

(/access-context-manager/docs/reference/rest/v1/accessPolicies.servicePerimeters/testIamPermissions) Returns the IAM permissions that the caller has on the specified Access Context Manager resource.
Permissions)

REST Resource: v1.operations

(/access-context-manager/docs/reference/rest/v1/operations)

Methods

cancel POST /v1/{name=operations/**}:cancel
(/access-context-manager/docs/reference/rest/v1/operations/cancel)
Starts asynchronous cancellation on a long-running operation.

delete DELETE /v1/{name=operations/**}
(/access-context-manager/docs/reference/rest/v1/operations/delete)
Deletes a long-running operation.

get GET /v1/{name=operations/**}
(/access-context-manager/docs/reference/rest/v1/operations/get)
Gets the latest state of a long-running operation.

list GET /v1/{name=operations}
(/access-context-manager/docs/reference/rest/v1/operations/list)
Lists operations that match the specified filter in the request.



REST Resource: v1.organizations.gcpUserAccessBindings

(/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings)

Methods

<u>create</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings/create)	POST /v1/{parent=organizations/*}/gcpUserAccessBindings Creates a <u>GcpUserAccessBinding</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings#GcpUserAccessBinding)
<u>delete</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings/delete)	DELETE /v1/{name=organizations/*}/gcpUserAccessBindings/* Deletes a <u>GcpUserAccessBinding</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings#GcpUserAccessBinding)
<u>get</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings/get)	GET /v1/{name=organizations/*}/gcpUserAccessBindings/* Gets the <u>GcpUserAccessBinding</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings#GcpUserAccessBinding) with the given name.
<u>list</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings/list)	GET /v1/{parent=organizations/*}/gcpUserAccessBindings Lists all <u>GcpUserAccessBindings</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings#GcpUserAccessBinding) for a Google Cloud organization.
<u>patch</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings/patch)	PATCH /v1/{gcpUserAccessBinding.name=organizations/*}/gcpUserAccessBindings/* Updates a <u>GcpUserAccessBinding</u> (/access-context-manager/docs/reference/rest/v1/organizations.gcpUserAccessBindings#GcpUserAccessBinding)



REST Resource: v1.services (/access-context-manager/docs/reference/rest/v1/services)

Methods

get GET /v1/services/{name}
(/access-context-manager/docs/reference/rest/v1/services/get) Returns a VPC-SC supported service based on the service name.

list GET /v1/services
(/access-context-manager/docs/reference/rest/v1/services/list) Lists all VPC-SC supported services.

Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 4.0 License](https://creativecommons.org/licenses/by/4.0/) (https://creativecommons.org/licenses/by/4.0/), and code samples are licensed under the [Apache 2.0 License](https://www.apache.org/licenses/LICENSE-2.0) (https://www.apache.org/licenses/LICENSE-2.0). For details, see the [Google Developers Site Policies](https://developers.google.com/site-policies) (https://developers.google.com/site-policies). Java is a registered trademark of Oracle and/or its affiliates.

Last updated 2025-10-01 UTC.

