The Asymmetry of Adaptation: A Literacy-Conditioned Stratification Audit of LLMs

Anonymous ACL submission

Abstract

Large language models (LLMs) now routinely mediate access to specialist knowledge in high-stakes settings, where the substance of an answer, not only its readability, determines whether users can rely on it. A central premise of this mediation is democratisation: users with different levels of prior expertise should be able to access comparable substantive information through natural language. We audit this premise by evaluating frontier and open-source LLMs on 250 high-stakes scenarios under two literacy-signalling conditions: explicit declaration and implicit inference from phrasing. Across linguistic, semantic, logical, and stylistic measures, we find that LLMs adapt linguistic and stylistic register to the user's apparent literacy level, alongside measurable differences in substantive content, semantic alignment, and logical entailment relative to the high-literacy reference. This pattern persists when literacy is inferred from phrasing alone. We do not claim that high-literacy responses are universal gold standards, nor that more detailed responses are inherently better; rather, we show that the same high-stakes topic yields measurably different substantive content when the literacy signal is varied. These findings indicate that information equity, not readability alone, must be evaluated in high-stakes LLM deployments.

1 Introduction

Large language models (LLMs) are increasingly serving as intermediaries between users and specialist knowledge (Sharma et al., 2024b; Chang et al., 2024). Information seeking is central to human decision making and problem solving (Marchionini, 1995; Savolainen, 2022); in high-stakes settings, this mediation is especially consequential. Users may rely on LLMs for information about medical guidance, legal rights, public policy, financial regulation, public benefits, digital privacy, and institutional safety (Singhal et al., 2023; Guha et al., 2023; Cheong et al., 2024; Eloundou et al., 2024; Brynjolfsson et al., 2025), where incomplete or underspecified answers can affect real decisions. This shift is often framed as a democratisation of expertise: natural-language interfaces may allow users with different backgrounds to access information that was previously difficult, costly, or institutionally mediated (Bommasani et al., 2021).

This promise relies on LLMs adapting how information is presented without altering the underlying substance or actionable information provided. This distinction is especially important because LLMs are designed to be adaptive. Prior work on personalisation, steering, and persona-conditioned generation shows that models adjust tone, vocabulary, length, and style in response to user-facing signals (Salemi et al., 2024). Such adaptation is often desirable, particularly when it makes complex information more accessible. In high-stakes settings, however, accessibility is not only a matter of readability. A simplified answer may be easier to read while also omitting named entities, procedural conditions, legal exceptions, thresholds, or other details that make the answer actionable. The relevant question is therefore not whether LLMs simplify language, but whether they preserve substantive informational parity across users (Selbst et al., 2019; Gupta et al., 2024).

This concern connects directly to the plain-language tradition, which holds that simplification should adapt linguistic register while preserving actionable content (Mellinkoff, 1963; Schriver, 1997; Kimble, 2012). Existing text-simplification evaluations have made substantial progress in measuring fluency, readability, and structural rewriting (Alva-Manchego et al., 2020; Laban et al., 2023). Recent work has also begun to quantify information loss using QA or entailment-based methods (Trienes et al., 2024; Laban et al., 2022). However, it remains largely under-examined whether LLMs preserve substantive content when adapting responses to different literacy signals. This question is especially important in high-stakes domains, where

omitted details may affect whether users can act on the information they receive, particularly users least equipped to seek alternatives (Poole-Dayan et al., 2026). It is also motivated by work on faithfulness (Maynez et al., 2020; Ji et al., 2023), bias (Weissburg et al., 2025), adaptation (Rooein et al., 2023), showing that surface fluency, substantive correctness, and differential treatment can diverge.

To examine this question, we conduct a *literacy-conditioned response stratification audit* of LLM behaviour in high-stakes settings. Our study makes four contributions. First, we curate a dataset of 250 high-stakes scenarios spanning 32 legal, regulatory, and safety-critical domains, including digital rights, cybersecurity, refugee rights, and medical safety. Second, we introduce a two-condition prompting framework that separates *explicit* literacy declaration from *implicit* inference based on question phrasing. Third, we define a measurement framework spanning linguistic register, informational content, semantic alignment, logical entailment, and stylistic posture. Fourth, we conduct a cross-model evaluation across frontier and open-source LLMs, with paired statistical analysis and effect-size reporting.

Across models and conditions, we find that LLMs adapt linguistic register to user-signalled literacy, but this adaptation is accompanied by measurable differences in substantive content, semantic alignment, and logical entailment relative to the high-literacy reference. Table 1 previews this pattern through an example.

Level	Response of Gemini 3.1 Pro (explicit) on Automated Decision-Making (GDPR)
High	*"Under the General Data Protection Regulation (**GDPR**) … primarily enshrined in **Article 22**, supported by transparency requirements in Articles 13, 14, and 15, and further contextualized by **Recital 71** … three derogations outlined in **Article 22(2)**: **Contractual Necessity**, **Legal Authorization**, **Explicit Consent** … "*
Mid	*"…The **GDPR** … includes a very specific rule … you have the **"right to a human"** … a few exceptions to this rule: (1) necessary to enter into a contract; (2) required to do so by a specific law; (3) explicit consent … "*
Low	*"…a privacy law called the **GDPR** … **computers should not have the final say on big life events** … "No, I want a real person to look at this." "*

Table 1: Illustrative excerpts at three declared literacy levels. Full responses and details in Appendix G.

2 Conceptual Foundations

This section outlines the conceptual basis of our audit. Building on the form–substance distinction introduced above, we focus on literacy-conditioned adaptation while holding other demographic factors, such as race, gender, and socioeconomic status, outside the experimental manipulation (Argyle et al., 2023). We then introduce the linguistic, substantive, and stylistic measurement families used in this paper.

2.1 Operationalising Literacy

Literacy can enter LLM interaction in two distinct ways: as a declared user attribute or as an inferred signal from language use. Declared literacy captures cases where a user explicitly states their level of expertise, allowing the model to adapt to a stated need (Weissburg et al., 2025; Huang et al., 2024; Cheng et al., 2023; Drobnjak and Botički, 2025). Inferred literacy captures the more common setting in which the model draws conclusions from the phrasing, structure, or specificity of the user's question (Neplenbroek et al., 2025). This distinction is central to our audit because unequal responses may arise not only when users explicitly request simplification, but also when models infer expertise from surface linguistic cues.

2.2 Service Parity

Functional equivalence across differently worded renderings is a long-standing concern in information, legal, and civic communication research. The plain-language tradition, codified in instruments such as the U.S. Plain Writing Act of 2010 (United States Congress, 2010), holds that simplification should adapt linguistic register while preserving actionable substance (Mellinkoff, 1963; Schriver, 1997; Kimble, 2012). If factual content is reduced alongside linguistic simplification, the LLM is not merely making information easier to read; it is also changing the substantive scope of the response (Maynez et al., 2020; Laban et al., 2023).

2.3 Linguistic Adaptation

Linguistic adaptation refers to how an LLM changes the surface form of a response in relation to a user's apparent literacy level. Such changes may include simplification, shortening, syntactic flattening, and reduced lexical complexity. In this study, we treat Flesch–Kincaid grade level (Kincaid et al., 1975), word count, and ROUGE-Lsum (Lin, 2004) as complementary indicators of this surface-level adaptation. Flesch–Kincaid grade level estimates reading difficulty from sentence length and syllables per word, and is widely used in text-simplification research (Vajjala and Lučić, 2018; Alva-Manchego et al., 2020). Word count

captures response length independently of vocabulary complexity, while ROUGE-Lsum captures lexical and structural overlap with the high-literacy reference.

2.4 Substantive Content Preservation

Substantive content preservation concerns whether the information conveyed by a response remains stable across literacy-conditioned variants. In our setting, this means asking whether a lower-register response retains the factual details, semantic commitments, and inferential content present in the corresponding high-literacy reference, rather than merely becoming shorter or easier to read. We examine this through three complementary dimensions: factual specificity, semantic alignment, and logical entailment. Together, these provide proxies for assessing whether content is preserved across different linguistic registers (Devaraj et al., 2022; Trienes et al., 2024).

Specific entity coverage. Named, dated, and quantified elements index the informational specificity of a response. Such specificity is especially important in legal, medical, and policy contexts, where the usefulness of an answer often depends on concrete entities, thresholds, dates, exceptions, or procedures (Mellinkoff, 1963). Category-driven extraction of these elements has been used as a scalable signal of substantive content in long-form generation (Agrawal et al., 2022; Min et al., 2023). It therefore provides a basis for examining whether literacy-conditioned simplification preserves important factual details or replaces them with more generic formulations.

Semantic divergence: Semantic divergence captures meaning-level shifts between responses to the same topic, independently of surface wording. A response may use simpler vocabulary and shorter sentences while still preserving the same underlying meaning. Conversely, if two responses move farther apart in embedding space, this may indicate that adaptation is changing substantive content rather than merely rephrasing it (Reimers and Gurevych, 2019; Zhang et al., 2020).

Logical entailment: Natural Language Inference (NLI) measures whether the content of one response is supported by another (DAGAN et al., 2010; Maynez et al., 2020). It complements semantic divergence because two responses may remain broadly similar while differing in important conditions, exceptions, or procedural details. Reduced logical alignment with the high-literacy reference, therefore suggests substantive divergence beyond surface-level simplification.

2.5 Stylistic and Informational Posture

Beyond linguistic adaptation and substantive content preservation, responses may also differ in informational and stylistic posture: how comprehensive, formal, and authoritative they appear to the reader. Two responses may preserve similar factual content while projecting different levels of expertise or professionalism. To capture this dimension, we consider two aspects of response style: informational scope, reflecting whether a response appears comprehensive or simplified, and stylistic register, reflecting whether the language appears formal and professional or casual and conversational (Biber, 1995; Heylighen and Dewaele, 1999; Pavlick and Tetreault, 2016). Together, these dimensions provide additional evidence that responses are presented differently across literacy conditions alongside the linguistic and substantive-content measurements in Section 2.4.

3 Methodology

We audit how LLM responses vary as a function of user-signalled literacy. To distinguish surface-level linguistic adaptation from changes in underlying content, we evaluate responses along three complementary dimensions: linguistic register, substantive content, and stylistic and informational posture.

3.1 Measuring Linguistic Adaptation

To quantify how the surface-level formulation of responses varies across literacy levels and explicit versus implicit conditions, we use three complementary metrics capturing lexical complexity and structural verbosity.

Flesch–Kincaid (FK) grade level: FK grade level (Kincaid et al., 1975) provides a standard surface-level estimate of the reading difficulty of a text, derived from average sentence length and average syllables per word. Concurrent work has used FK, alongside related readability indices, to study LLM adaptation to declared educational levels in tutoring-style settings (Drobnjak and Botički, 2025). We use FK to measure linguistic register in a different setting: high-stakes events.

$$FK = 0.39\left(\frac{\text{words}}{\text{sentences}}\right) + 11.8\left(\frac{\text{syllables}}{\text{words}}\right) - 15.59 \quad (1)$$

Average Word Count. Word count complements the Flesch–Kincaid metric by measuring response length independently of vocabulary complexity, helping distinguish simplification from arbitrary truncation.

ROUGE-Lsum. ROUGE-Lsum (Lin, 2004) measures longest-common-subsequence (LCS) overlap between a candidate and a reference response. We treat the high-literacy response, the model's output under the highest-literacy condition, as the reference(ref), and the Mid and Low-literacy responses as candidates(cand):

$$P = \frac{\text{LCS(cand,ref)}}{|\text{cand}|}, \quad R = \frac{\text{LCS(cand,ref)}}{|\text{ref}|}, \quad F_1 = \frac{2PR}{P+R} \quad (2)$$

Precision (P) penalises irrelevant additions; recall (R) penalises omissions; F_1 balances the two. ROUGE-Lsum has been applied as a cross-version overlap measure in text simplification (Alva-Manchego et al., 2020) and abstractive summarisation (See et al., 2017).

3.2 Substantive Content Analysis

Substantive content preservation examines whether information is preserved across literacy-conditioned responses. We evaluate this through three complementary dimensions: factual specificity, semantic alignment, and logical entailment.

Specific Entity Count: Specific entity count quantifies the distinct named, dated, and numerically thresholded entities mentioned in a response. We use a rubric-based extractor prompted over 17 categories with Gemini 3.1 Flash Lite (Google DeepMind, 2026a) at temperature 0, following the LLM-as-extractor paradigm (Agrawal et al., 2022; Wang et al., 2025). We use this extractor as a scalable audit proxy rather than as a substitute for domain-expert adjudication, as recent work supports the use of Gemini-family models for structured annotation and factual evaluation tasks (Calderon et al., 2025; Liu et al., 2025a). Strict deduplication rules ensure each entity is counted only once, isolating variation independent of stylistic rephrasing. Full extractor details are provided in Appendix C.

Semantic similarity loss: Semantic similarity loss captures overall semantic drift between the high-literacy reference and a lower-register response in a dense vector space. We use the BGE-M3 architecture (Chen et al., 2024), which supports inputs up to 8,192 tokens — crucial for our long-form responses — and provides multi-functional representations grounded in the modern sentence-embedding tradition (Reimers and Gurevych, 2019). For each event, the high-literacy response is embedded as the reference $\mathbf{e}_{\text{high}}$, and each of the Mid- and Low-literacy responses is embedded as $\mathbf{e}_{\text{target}}$. Equation 3 reports *semantic similarity loss*; higher values indicate greater semantic divergence from the high-literacy reference.

$$\textit{SimLoss} = 1 - \cos(\mathbf{e}_{\text{high}}, \mathbf{e}_{\text{target}}) \quad (3)$$

Natural Language Inference (NLI): NLI provides a rigorous criterion of logical alignment (Bowman et al., 2015). We use the ModernCE-large-NLI cross-encoder classifier (Miller, 2025), built on ModernBERT-large (Warner et al., 2025) and fine-tuned on AllNLI (the union of SNLI and MultiNLI), which supports 8,192-token inputs and is a good fit for our long-form responses. For each of the three NLI classes $c \in \{\text{entailment}, \text{neutral}, \text{contradiction}\}$, scores from both directions are averaged to obtain a robust, direction-agnostic measure:

$$\textit{NLI}_{\text{c}} = \tfrac{1}{2}\big(P_{\text{c}}(\text{HL}, \text{X}) + P_{\text{c}}(\text{X}, \text{HL})\big) \quad (4)$$

where HL is the high-literacy reference, X is the Mid- or Low-literacy response, and $P_c(p, h)$ is the classifier's class-c probability with premise p and hypothesis h. We use $\textit{NLI}_{\text{entailment}}$ as the headline metric, with $\textit{NLI}_{\text{neutral}}$ and $\textit{NLI}_{\text{contradiction}}$ reported in Appendix B.4 to clarify whether entailment shifts reflect omission (rising neutral) or factual disagreement (rising contradiction). Since our comparison is across literacy signals applied to the same model and topic, the high-literacy response, the output produced under the High-literacy condition, serves as the reference against which the Mid- and Low-literacy outputs are evaluated.

3.3 Stylistic and Informational Posture

We characterise stylistic and informational posture through zero-shot classification over two independent binary axes using the bge-m3-zeroshot-v2.0 model (Laurer, 2024; Laurer et al., 2024), an NLI-based classifier that reframes classification as hypothesis testing and supports 8,192-token inputs. For each response x and each axis, the classifier returns a probability distribution (Pr) over the corresponding pair of labels:

$$\Pr(\ell_1 \mid x), \quad \Pr(\ell_2 \mid x) \quad (5)$$

where the two labels ℓ_1, ℓ_2 are axis-specific:

$$\begin{aligned} \text{Info axis:} \quad & \ell_1 = \text{comprehensive and detailed} \\ & \ell_2 = \text{minimal and simplified} \\ \text{Style axis:} \quad & \ell_1 = \text{formal and professional} \\ & \ell_2 = \text{casual and conversational} \end{aligned} \quad (6)$$

Since each axis defines a binary contrast, the two label probabilities are complementary. We therefore report only the probability associated with ℓ_1 in the analysis that follows. This dual-axis formulation allows us to evaluate whether shifts in stylistic register co-occur with shifts in informational scope.

4 Experimental Settings

We isolate literacy-conditioned variation through model selection, dataset construction, and prompting strategy, addressing provider, domain, and signal modality, respectively.

4.1 Models Evaluated

Following prior work on cross-model behavioural analysis of frontier LLMs (Liu et al., 2025b; Sharma et al., 2024a), we evaluate one representative model from each of several widely used model families: GPT-5.4 (OpenAI, 2026), Claude Opus 4.6 (Anthropic, 2026), and Gemini 3.1 Pro (Google DeepMind, 2026b). This three-model design separates systematic frontier-LLM properties from single-provider idiosyncrasies, strengthening any claim of cross-system service asymmetry.[1]

All three models were accessed through their respective official APIs with default settings. The collected responses were cleaned of markdown artefacts and web-specific formatting, since transformer-based evaluators are demonstrably sensitive to surface-level formatting features, which can introduce spurious variance in semantic similarity, NLI, stylistic classification, and related measurement scores (Moradi and Samwald, 2021).

4.2 Dataset Construction

To detect literacy-conditioned stratification across diverse high-stakes settings, we prepared a dataset of 250 distinct scenarios spanning 32 high-stakes domains. These domains encompass a broad spectrum of critical information areas, including national and international legal rights, public policy directives, institutional and environmental safety protocols, medical guidance and established scientific consensus. The reference data for each scenario was systematically curated from verified, publicly accessible authoritative documents and official repositories. A comprehensive breakdown of the domain taxonomy, alongside the full list of source materials, is provided in Appendix A.

4.3 Literacy-Condition and Prompting Design

We examine LLM behaviour under two literacy-signalling conditions commonly observed in real-world deployments: *explicit* declaration, where the user states their level directly, and *implicit* inference, where the literacy signal is carried only by the user's phrasing. Both follow standard prompting practices for persona-conditioned generation (White et al., 2023; Cheng et al., 2023).

Explicit condition. The system instruction is held constant across all three literacy personas:

> You are a helpful assistant that adapts to the user's literacy level.

The user prompt is constructed as:

> The topic: {topic}
> Additional context or details: {topic_details}
> Source/Reference: {topic_source}
> Persona: {persona_description} ({persona_level})

where {persona_description} and {persona_level} take one of three forms corresponding to High, Mid, or Low Literacy on the topic (full templates in Appendix F). The Source/Reference field grounds the model in the specific legal or regulatory instrument underlying the event, preventing drift toward generic domain commentary that would confound our informational measurements (worked example in Appendix F). This setup mirrors prior work on level-conditioned LLM response adaptation (Weissburg et al., 2025; Huang et al., 2024).

Implicit condition: No explicit literacy label is supplied; the literacy signal is carried entirely by the user question itself, with evaluation proceeding in two isolated stages.

Stage 1: Question generation. For each topic and literacy level, a realistic user question is produced by one of three question-generator LLMs (GPT-5.4, Claude Opus 4.6, or Gemini 3.1 Pro) (Perez et al., 2023), instructed via system prompt to generate persona-appropriate questions, with generation distributed equally across the three so that no single model's stylistic assumptions systematically shape the implicit-condition input (Benedetto et al., 2024; Park et al., 2024; Argyle et al., 2023). The generation prompt is:

> The topic: {topic}
> Additional context or details: {topic_details}
> Source/Reference: {topic_source}
> Persona: {persona_description}

where {persona_description} takes one of three literacy-level forms (full templates in Appendix F).

Stage 2: Answer collection. Each validated question is submitted independently to each of the target models with a neutral system instruction ("You are a helpful assistant.") and a user prompt containing only the generated question, with no meta-data or literacy labels. Any adaptation observed at this stage is attributable to the answering model's own inference from the question's phrasing.

[1] We additionally replicated the audit on two open-source frontier models (Llama 4 Scout (Meta AI, 2025) and Qwen3.6-27B(Qwen Team, Alibaba Group, 2026)) and observed the same directional stratification pattern across metrics and conditions. Results and statistics are reported in Appendix D.

5 Results and Discussion

Our audit reveals systematic, statistically significant variation in LLM responses across literacy levels. We present findings in stages: linguistic register confirms adaptation, substantive measures evaluate content preservation, and informational and stylistic posture capture response shifts.

5.1 Linguistic Register Tracks the Literacy Signal

Before turning to substantive content preservation analysis , here we show that linguistic adaptation tracks the literacy signal: reading difficulty, response length, and lexical overlap with the high-literacy reference all decline as the signal weakens.

Flesch–Kincaid Grade and Word Count. To analyse surface-level linguistic adaptation across literacy levels in terms of register and response length, Table 2 reports cell means for Flesch–Kincaid (FK) grade and word count. FK grade descends monotonically from High to Low literacy in every (model, condition) cell, with concurrent reductions in word count. Claude Opus 4.6 under the explicit condition illustrates this pattern clearly: FK grade descends from 15.81 (roughly college-level prose) at High to 5.49 (roughly 5th-grade) at Low, with word count contracting from 647 to 384 over the same range — a pattern echoed in every other (model, condition) cell.

		FK Grade			Word Count		
Condition	**Model**	**High**	**Mid**	**Low**	**High**	**Mid**	**Low**
Explicit	GPT-5.4	13.11	8.55	6.06	546	295	189
	Claude Opus 4.6	15.81	9.26	5.49	647	445	384
	Gemini 3.1 Pro	16.66	9.34	5.66	524	370	223
Implicit	GPT-5.4	12.32	9.91	8.73	718	403	266
	Claude Opus 4.6	13.70	11.21	9.90	990	366	220
	Gemini 3.1 Pro	14.10	11.40	10.15	760	623	541

Table 2: Mean FK grade and word count across models and conditions.

Paired t-tests (one-tailed, paired by event ID) confirm robust stratification: all (model, condition, level-pair) contrasts are Bonferroni-significant on both metrics, with High→Low paired Cohen's d values ranging 1.69–5.25 for FK and 1.14–2.78 for word count . Repeated-measures ANOVA within each cell yield partial η^2 from 0.49 (word count) to 0.95 (FK grade), all in the conventional *large* regime. (Details analysis in Appendix B.2)

Lexical Structure Retention (ROUGE-Lsum) ROUGE-Lsum F_1 with the high-literacy reference declines monotonically from High–Mid to High–Low comparisons in every (model, condition) cell (Figure 1). Paired t-tests for the High–Mid→High–Low contrast (one-tailed, paired by event ID) yield Cohen's d values ranging from 1.00 (GPT implicit) to 3.09 (Gemini explicit), with all within-condition contrasts Bonferroni-significant. Lexical-and-structural overlap with the reference therefore tracks the same monotonic stratification observed on FK grade and word count. (Details statistical analysis in Appendix B.2).




Figure 1: Box plot of ROUGE-Lsum F_1 across models and conditions.

5.2 Substantive Content Stratification with Literacy Signal

Here, we show that substantive content diverges from the literacy signal: entity counts collapse, embedding-space drift grows, and entailment with the high-literacy reference weakens.

Specific Entity Count We count distinct entities per response using a structured rubric-based extractor (see Appendix C for full extractor design) and Table 3 reports cumulative and per-response mean entity counts. Claude Opus 4.6 under the explicit condition is illustrative: it averages 23.14 entities per response at High, 7.75 at Mid, and 4.87 at Low —Low-literacy responses exhibiting a ∼79% reduction in specific named entity counts relative to High literacy. GPT-5.4 and Gemini 3.1 Pro show comparable contractions. (Per-domain breakdowns are in Appendix C).

		High		Mid		Low	
Condition	**Model**	**total**	**mean**	**total**	**mean**	**total**	**mean**
Explicit	GPT-5.4	2058	8.23	1173	4.69	872	3.49
	Claude Opus 4.6	5785	23.14	1937	7.75	1217	4.87
	Gemini 3.1 Pro	2948	11.79	1269	5.08	825	3.30
Implicit	GPT-5.4	2204	8.82	1586	6.34	1042	4.17
	Claude Opus 4.6	5921	23.68	2251	9.00	1249	5.00
	Gemini 3.1 Pro	4477	17.91	3396	13.58	2902	11.61

Table 3: Cumulative entity count (*total*) and per-response mean across models and conditions.

Semantic Divergence We quantify how far Mid and Low literacy responses drift from the high-literacy reference. A divergence approaching 0.0 indicates near-identical embedding-space content; positive values quantify shifts in conceptual framing relative to the reference register. Figure 2 reports per-response divergence distributions across (model, condition) cells. Within every cell, the

High-Low-literacy box sits visibly higher than the High-Mid-literacy box, with Claude Opus 4.6 explicit showing the most pronounced separation. All twelve one-sample tests against the perfect-preservation baseline (μ=0) reject at Bonferroni-corrected α, with one-sample Cohen's d ranging from 2.69 to 5.58 (all in the *huge* regime). The High-Mid vs High-Low paired contrast is Bonferroni-significant in every cell, with d ranging 1.08 (GPT implicit) to 2.41 (Claude explicit). Importantly, even Mid-literacy responses lie well above the 0.0 baseline — semantic drift is not a Low-literacy-only phenomenon; it begins as soon as the literacy signal weakens at all. (Details statistical analysis in Appendix B.3)




Figure 2: Box Plot of Semantic loss across models, conditions, and literacy levels.

Logical Entailment Figure 3 reports per-pair distributions of $\text{NLI}_{\text{entailment}}$, where values approaching 1.0 indicate near-mutual entailment between the compared responses. Within every (model, condition) cell, the High-Low literacy box sits visibly lower than the High-Mid-literacy box — medians and inter-quartile ranges both shift toward weaker entailment, with Claude Opus 4.6 explicit again showing the most pronounced separation (mean $\text{NLI}_{\text{entailment}}$ drops from 0.61 at High–Mid to 0.48 at High–Low). All twelve one-sample tests against the perfect-entailment baseline (μ=1) reject at Bonferroni-corrected α, with one-sample Cohen's d ranging from -1.46 to -3.76 (all in the *huge* regime). Paired t-tests for the High-Mid vs High-Low contrast (one-tailed, paired by event ID) yield Cohen's d ranging from 0.38 (Gemini explicit) to 1.17 (Claude explicit); all six within-condition contrasts are Bonferroni-significant. The class decomposition (Appendix B.4) clarifies the nature of the failure: across every cell, contradiction probability remains below 0.05, while the entailment drop is mirrored by a near-equal rise in *neutral* probability. The simplified responses are not stating things that disagree with the reference; they are stating less. This omission-not-disagreement pattern is what one would expect if literacy-conditioned adaptation is removing content rather than rephrasing it. (Details statistical analysis in Appendix B.4).




Figure 3: Box plot of NLI entailment distributions across models, conditions, and references.

5.3 Stylistic and Informational Posture Shifts with the Literacy Signal

We assess whether register adaptation induces correlated shifts on two axes: the **Info axis** (*comprehensive and detailed* vs *minimal and simplified*) and the **Style axis** (*formal and professional* vs *casual and conversational*). We report the classifier probability assigned to the first label on each axis.

Comprehensiveness: Figure 4 shows that the comprehensive-and-detailed probability descends monotonically from High to Low literacy within every (model, condition) cell — for Claude explicit, from 0.80 at High to 0.11 at Low. Paired Cohen's d for the High→Low contrast ranges from 0.85 (GPT implicit) to 4.11 (Claude explicit); within-cell repeated-measures ANOVA yields η_p^2 from 0.27 to 0.85, all in the *large* regime. All eighteen within-condition contrasts are Bonferroni-significant. (Details statistical analysis Appendix B.5)




Figure 4: Distribution of the comprehensive and detailed probability across models, conditions, and literacy levels.

Communicative Formality: The Style axis (Figure 5) shows the parallel pattern: the formal-and-professional probability declines with literacy in every cell — again most starkly for Claude explicit, from 0.94 at High to 0.30 at Low. Paired d ranges from 0.50 (Claude implicit) to 3.31 (Claude explicit), with η_p^2 from 0.13 to 0.85; all contrasts are Bonferroni-significant. Co-occurrence of stratification on both axes within every cell provides

convergent evidence that literacy-conditioned stratification operates on stylistic posture in addition to register and content. (Details statistical analysis Appendix B.5).




Figure 5: Distribution of the formal and professional probability across models, conditions, and literacy levels.

In this section, we observe that the AI adapts communicative style across literacy levels by shortening responses and making them less formal and less comprehensive. As shown in the previous sections, however, these changes are not limited to surface-level adaptation alone: the models also exhibit consistent stratification in factual content, semantic alignment, logical entailment, and informational posture. These shifts co-occur across nearly every (model, condition) cell, with most effect sizes falling in the *large*-to-*huge* regime. This dissociation between adapted surface form and reduced substantive content relative to the high-literacy reference is the central observation of this audit.

Moreover, the stratification does not require users to explicitly declare a literacy level: semantic and logical divergence are consistently larger under implicit than explicit signalling, while entity and posture shifts remain Bonferroni-significant in both conditions. Although effect magnitudes vary across models, the directional pattern remains consistent across frontier systems, suggesting a systematic property rather than a single-provider artefact.

6 Recommendations and Best Practices

Based on the findings above, we outline a set of recommendations for deploying LLMs in literacy-sensitive, high-stakes settings.

Audit content fidelity, not only readability. Surface readability metrics confirm that simplification has occurred, but cannot determine whether substantive content survives it. High-stakes deployments should pair register metrics with informational measures — entity retention, NLI entailment, and semantic similarity.

Treat user-signalled literacy as a stylistic adaptation cue, not a reason to remove essential content. Every response should retain a baseline factual specificity; register adaptation should operate around that informational floor, not replace it.

Disclose simplification and offer the higher-register view on demand. When a response has been adapted to a lower register — whether explicitly declared or inferred from phrasing — users should be clearly informed and given the option to view the expert-level version where applicable. Without such disclosure, users may not realise that they are receiving an informationally different version of the same answer.

Include domain experts in high-stakes evaluation. Automated metrics can identify where informational collapse occurs, but they cannot determine which omissions are consequential. Domain-expert review of Low-literacy responses — where our metrics show the steepest degradation — is therefore necessary before deployment in medical, legal, safety-critical, or rights-related contexts (Min et al., 2023).

7 Conclusions

LLMs now mediate access to legal rights, public-policy information, and other high-stakes specialist knowledge, making it essential to ask whether the substantive quality of this service remains stable across users. We addressed this question by evaluating multiple LLMs on 250 high-stakes instances across three literacy levels and two literacy-signalling conditions, using convergent dimensions: linguistic register, substantive Content, and posture analysis.

Our findings reveal a sharp dissociation between linguistic adaptation and substantive preservation. While all models monotonically adapt register to user-signalled literacy, substantive content stratifies as the literacy signal weakens. Informational content, semantic alignment, and logical entailment with the high-literacy reference all decrease in parallel, producing a measurable difference of substance beneath an adapted linguistic surface. This pattern appears even when literacy is inferred only from question phrasing, indicating a service asymmetry that raises serious equity concerns and must be addressed in LLM development.

Future work could extend this audit to more high-stakes domains, add domain-expert review of consequential omissions, and test whether real low-literacy users experience these differences as reduced informational service.

8 Limitations

We detail key limitations in our metrics, dataset, and inferential scope to clarify the boundaries of our analysis.

8.1 Evaluation Metrics

Each tool in our framework carries interpretive caveats, which we report transparently below.

Flesch–Kincaid Grade Level. FK reliably captures surface readability but is sensitive to sentence length and syllables, not lexical specificity or domain terminology. We treat it strictly as a register proxy and pair it with word count, ROUGE-Lsum, and the informational measures.

ROUGE-Lsum. While effective for cross-register lexical overlap, ROUGE-Lsum may not fully capture paraphrastic preservation and may also reward mechanical phrase repetition. We complement it with semantic and entailment measures that capture meaning-level alignment.

Specific Entity Count. While automated extraction with Gemini 3.1 Flash Lite (temperature = 0) provides a scalable solution for our large and heterogeneous domain, LLM-based pipelines may still fail to capture nuanced factual equivalences between paired responses. Future work should complement this approach with domain-stratified human evaluation to validate extraction fidelity across subdomains.

Semantic Similarity (BGE-M3). Cosine distance over BGE-M3 embeddings captures macroscopic semantic drift but does not localise *which* factual elements differ — motivating our complementary specific entity-count and entailment metrics.

NLI Entailment (ModernCE-large-NLI). The cross-encoder is trained on generic-domain text rather than legal or policy text. We nonetheless chose it because our dataset spans 32 high-stakes domains; a domain-specialised classifier would bias entailment toward any single domain's conventions.

Stylistic and Informational Posture Classification. The BGE-M3-zeroshot-v2.0 classifier operationalizes informational density and stylistic register as binary NLI hypotheses. While this simplifies inherently continuous variation, our goal was to capture broad differences in how information is presented across literacy levels rather than to make fine-grained sociolinguistic claims. Because absolute scores remain sensitive to hypothesis wording, we report relative deltas across literacy levels rather than absolute labels; the relative ordering within each cell remains stable across hypothesis phrasings. Future work can incorporate real-user evaluations to better assess how literacy-adaptive responses are perceived and understood in practice.

Length and informational scope. Several measures in our framework are sensitive to response length. ROUGE-Lsum, specific entity count, and NLI-based omission patterns may partly reflect the fact that lower-literacy responses are often shorter. We do not impose length constraints in our prompting design because our audit is scoped to model behaviour as it occurs in deployment: when a user signals a literacy level — whether explicitly or through phrasing — the model's choice of how to respond is itself part of the adaptation. But we do not interpret shorter responses or lower entity counts as standalone evidence of harm; rather, our claim is that literacy-conditioned register adaptation systematically co-varies with informational scope — as responses become simpler and shorter, they also retain fewer specific entities and show weaker semantic and logical alignment with the high-literacy reference. Length-normalised entity rates, matched-length generations, and content-preserving simplification prompts would more directly separate brevity from substantive omission as causal mechanisms. They can be an important direction for future work.

8.2 Operationalisation of Literacy

We operationalise literacy as three discrete labels (High, Mid, Low) to enable controlled paired comparisons, deliberately isolating literacy from other demographic attributes (race, gender, socioeconomic status) that could otherwise confound the observed stratification. Real users vary continuously across reading proficiency, domain knowledge, and procedural familiarity; the three-tier design captures the principal axis of variation while keeping the comparison tractable. The implicit condition is designed to reflect real-world user behaviour, where literacy is conveyed through natural phrasing rather than explicit declaration; this naturalism may introduce variation in how the question is asked at different literacy levels and encourage future work to analyse more closely real users' question style and phrasing shape model responses. The explicit condition is free of this confound: the user prompt is held identical across the three literacy levels, with only the persona descriptor varying.

8.3 Dataset Scope

Our dataset spans 250 high-stakes events across 32 domains drawn from publicly accessible authoritative documents, including legal rights, medical guidance, digital privacy, financial regulation, civic procedures, institutional safety, cybersecurity, and environmental and safety protocols, among others (full taxonomy in Appendix A). While this provides broad coverage, deeper domain-specific extensions — for example, targeted audits within individual domains — could reveal how literacy-conditioned stratification manifests in different professional contexts and further broaden the real-world scope of the framework.

8.4 Inferential Scope

Our framework measures *stratification* relative to the high-literacy response as the reference condition, which isolates the literacy-conditioned effect within each model's own behaviour. Determining whether the observed stratification constitutes conceptual hollowing — by comparing each literacy-level response against expert-verified plain-language renditions of the source instrument at the corresponding level — remains a complementary direction for future work. Relatedly, we used each provider's default decoding parameters to capture each model's behaviour rather than tuned configurations; quantifying generation-level variance across seeds and sampling settings is left to follow-up work.

These limitations bound the precise interpretation of individual metric values but do not weaken the convergent pattern observed across all measurement axes, multiple models, and both literacy-signalling conditions. The robustness of the observed stratification emerges from triangulation across metrics rather than reliance on any single measure.

9 Ethical Considerations

Our audit investigates how frontier LLMs adapt responses to literacy signals across a curated dataset of high-stakes topics. While our primary focus is on quantifiable measurements — linguistic register, substantive content, semantic and logical alignment across literacy level, and stylistic posture — these features can encode meaningful service asymmetries if deployed without oversight. Systematically lower entity and weaker entailment at lower literacy signals may withhold actionable rights information from users least equipped to seek it elsewhere, while register-conditioned content collapse may be misinterpreted as the complete answer rather than a simplified rendering of one. We frame this within the allocational-harm tradition (Weidinger et al., 2022): differential service across literacy-signalled users constitutes a measurable allocation of substantive informational access, not merely a stylistic adaptation.

Our dataset draws on publicly accessible authoritative documents — statutes, treaties, regulatory filings, and official agency guidance — chosen for their high-stakes practical bearing on legal rights and safety procedures. No personally identifiable information appears in any prompt, response, or intermediate artefact, and the literacy personas are conceptual abstractions used to elicit register-conditioned generation, not claims about any real demographic group.

We emphasise that our audit is scoped to lawful, publicly accessible, high-stakes information — legal rights, safety procedures, regulatory protections, and clinical guidance — that all users are entitled to access. The toxicity analysis in Appendix E confirms that responses across all literacy levels remain uniformly non-toxic in our study, indicating that the stratification we document operates entirely within appropriate content boundaries. We do not argue that LLMs should distribute sensitive, restricted, or potentially harmful content uniformly across users, nor that existing content-safety mechanisms should be relaxed. Our claim is: where authoritative information is appropriate to convey, literacy-conditioned register adaptation should not silently reduce its substantive availability.

This work does not argue that simplification is intrinsically harmful — competent plain-language communication remains a long-standing public good; rather, we examine when automatic LLM simplification honours the parity principle that human plain-language drafting upholds. Literacy is not a neutral input; how it is inferred and acted upon shapes what information reaches whom, and requires both analytical rigour and ethical attention.

References

Adobe codemay2025. 2025. ModernBERT-base toxic comment detector. Hugging Face model card. Accessed April 8, 2026.

Monica Agrawal, Stefan Hegselmann, Hunter Lang, Yoon Kim, and David Sontag. 2022. Large language models are few-shot clinical information extractors. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing (EMNLP)*,

pages 1998–2022. Association for Computational Linguistics.

Fernando Alva-Manchego, Carolina Scarton, and Lucia Specia. 2020. Data-driven sentence simplification: Survey and benchmark. *Computational Linguistics*, 46(1):135–187.

Anthropic. 2026. Claude opus 4.6. Accessed April 8, 2026.

Lisa P. Argyle, Ethan C. Busby, Nancy Fulda, Joshua R. Gubler, Christopher Rytting, and David Wingate. 2023. Out of one, many: Using language models to simulate human samples. *Political Analysis*, 31(3):337–351.

Luca Benedetto, Giovanni Aradelli, Antonia Donvito, Alberto Lucchetti, Andrea Cappelli, and Paula Buttery. 2024. Using LLMs to simulate students' responses to exam questions. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 11351–11368. Association for Computational Linguistics.

Douglas Biber. 1995. *Dimensions of Register Variation: A Cross-Linguistic Comparison*. Cambridge University Press, Cambridge, UK.

Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, and 1 others. 2021. On the opportunities and risks of foundation models. *arXiv preprint arXiv:2108.07258*.

Samuel R. Bowman, Gabor Angeli, Christopher Potts, and Christopher D. Manning. 2015. A large annotated corpus for learning natural language inference. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pages 632–642, Lisbon, Portugal. Association for Computational Linguistics.

Erik Brynjolfsson, Danielle Li, and Lindsey Raymond. 2025. Generative ai at work. *The Quarterly Journal of Economics*, 140(2):889–942.

Nitay Calderon, Roi Reichart, and Rotem Dror. 2025. The alternative annotator test for LLM-as-a-judge: How to statistically justify replacing human annotators with LLMs. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 16051–16081, Vienna, Austria. Association for Computational Linguistics.

Yupeng Chang, Xu Wang, Jindong Wang, Yuan Wu, Linyi Yang, Kaijie Zhu, Hao Chen, Xiaoyuan Yi, Cunxiang Wang, Yidong Wang, Wei Ye, Yue Zhang, Yi Chang, Philip S. Yu, Qiang Yang, and Xing Xie. 2024. A survey on evaluation of large language models. *ACM Trans. Intell. Syst. Technol.*, 15(3).

Jianlyu Chen, Shitao Xiao, Peitian Zhang, Kun Luo, Defu Lian, and Zheng Liu. 2024. M3-embedding: Multi-linguality, multi-functionality, multi-granularity text embeddings through self-knowledge distillation. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 2318–2335, Bangkok, Thailand. Association for Computational Linguistics. Model available at `https://huggingface.co/BAAI/bge-m3`, Accessed April 8, 2026.

Myra Cheng, Tiziano Piccardi, and Diyi Yang. 2023. CoMPosT: Characterizing and evaluating caricature in LLM simulations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 10853–10875, Singapore. Association for Computational Linguistics.

Inyoung Cheong, King Xia, K. J. Kevin Feng, Quan Ze Chen, and Amy X. Zhang. 2024. (a)i am not a lawyer, but...: Engaging legal experts towards responsible llm policies for legal advice. In *Proceedings of the 2024 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '24, page 2454–2469, New York, NY, USA. Association for Computing Machinery.

Jacob Cohen. 1988. *Statistical Power Analysis for the Behavioral Sciences*, 2nd edition. Lawrence Erlbaum Associates, Hillsdale, NJ.

IDO DAGAN, BILL DOLAN, BERNARDO MAGNINI, and DAN ROTH. 2010. Recognizing textual entailment: Rational, evaluation and approaches – erratum. *Natural Language Engineering*, 16(1):105–105.

Ashwin Devaraj, William Sheffield, Byron Wallace, and Junyi Jessy Li. 2022. Evaluating factuality in text simplification. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7331–7345, Dublin, Ireland. Association for Computational Linguistics.

Antun Drobnjak and Ivica Botički. 2025. Can we learn together? how large language models adapt content to educational levels. In *Proceedings of the International Conference on Learning Engineering and Analytics (ICLEA)*.

Tyna Eloundou, Sam Manning, Pamela Mishkin, and Daniel Rock. 2024. Gpts are gpts: Labor market impact potential of llms. *Science*, 384(6702):1306–1308.

Google DeepMind. 2026a. Gemini 3.1 flash lite model card. Accessed April 8, 2026.

Google DeepMind. 2026b. Gemini 3.1 pro model card. Accessed April 8, 2026.

Neel Guha, Julian Nyarko, Daniel Ho, Christopher Ré, Adam Chilton, Aditya K, Alex Chohlas-Wood, Austin Peters, Brandon Waldon, Daniel Rockmore, Diego Zambrano, Dmitry Talisman, Enam Hoque,

Faiz Surani, Frank Fagan, Galit Sarfaty, Gregory Dickinson, Haggai Porat, Jason Hegland, and 21 others. 2023. Legalbench: A collaboratively built benchmark for measuring legal reasoning in large language models. In *Advances in Neural Information Processing Systems*, volume 36, pages 44123–44279. Curran Associates, Inc.

Shashank Gupta, Vaishnavi Shrivastava, Ameet Deshpande, Ashwin Kalyan, Peter Clark, Ashish Sabharwal, and Tushar Khot. 2024. Bias runs deep: Implicit reasoning biases in persona-assigned llms. In *International Conference on Learning Representations*, volume 2024, pages 21849–21874.

Francis Heylighen and Jean-Marc Dewaele. 1999. Formality of language: Definition, measurement and behavioral determinants. *Internal Report, Center "Leo Apostel", Free University of Brussels*.

Chieh-Yang Huang, Jing Wei, and Ting-Hao Kenneth Huang. 2024. Generating educational materials with different levels of readability using llms. In *Proceedings of the Third Workshop on Intelligent and Interactive Writing Assistants*, In2Writing '24, page 16–22, New York, NY, USA. Association for Computing Machinery.

Ziwei Ji, Nayeon Lee, Rita Frieske, Tiezheng Yu, Dan Su, Yan Xu, Etsuko Ishii, Ye Jin Bang, Andrea Madotto, and Pascale Fung. 2023. Survey of hallucination in natural language generation. *ACM Computing Surveys*, 55(12):1–38.

Joseph Kimble. 2012. *Writing for Dollars, Writing to Please: The Case for Plain Language in Business, Government, and Law*. Carolina Academic Press, Durham, NC.

J Peter Kincaid, Robert P Fishburne Jr, Richard L Rogers, and Brad S Chissom. 1975. Derivation of new readability formulas (automated readability index, fog count and flesch reading ease formula) for navy enlisted personnel. Technical report.

Philippe Laban, Tobias Schnabel, Paul N. Bennett, and Marti A. Hearst. 2022. SummaC: Re-visiting NLI-based models for inconsistency detection in summarization. *Transactions of the Association for Computational Linguistics*, 10:163–177.

Philippe Laban, Jesse Vig, Wojciech Kryscinski, Shafiq Joty, Caiming Xiong, and Chien-Sheng Wu. 2023. SWiPE: A dataset for document-level simplification of Wikipedia pages. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 10674–10695, Toronto, Canada. Association for Computational Linguistics.

Moritz Laurer. 2024. bge-m3-zeroshot-v2.0: Universal zero-shot classifier. Hugging Face model card. Accessed April 8, 2026.

Moritz Laurer, Wouter van Atteveldt, Andreu Casas, and Kasper Welbers. 2024. Building efficient universal classifiers with natural language inference. *Preprint*, arXiv:2312.17543.

Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain. Association for Computational Linguistics.

Xin Liu, Lechen Zhang, Sheza Munir, Yiyang Gu, and Lu Wang. 2025a. VeriFact: Enhancing long-form factuality evaluation with refined fact extraction and reference facts. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 17908–17925, Suzhou, China. Association for Computational Linguistics.

Yixuan Liu, Abel Elekes, Jianglin Lu, Rodrigo Dorantes-Gilardi, and Albert-Laszlo Barabasi. 2025b. Unequal scientific recognition in the age of LLMs. In *Findings of the Association for Computational Linguistics: EMNLP 2025*, pages 23558–23568, Suzhou, China. Association for Computational Linguistics.

Gary Marchionini. 1995. *Information seeking in electronic environments*. 9. Cambridge university press.

Joshua Maynez, Shashi Narayan, Bernd Bohnet, and Ryan McDonald. 2020. On faithfulness and factuality in abstractive summarization. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1906–1919. Association for Computational Linguistics.

David Mellinkoff. 1963. *The Language of the Law*. Little, Brown and Company, Boston.

Meta AI. 2025. Llama 4 scout. Accessed May 11, 2026.

D. Lee Miller. 2025. Modernce nli: An nli cross encoder model. Accessed April 8, 2026.

Sewon Min, Kalpesh Krishna, Xinxi Lyu, Mike Lewis, Wen-tau Yih, Pang Wei Koh, Mohit Iyyer, Luke Zettlemoyer, and Hannaneh Hajishirzi. 2023. FActScore: Fine-grained atomic evaluation of factual precision in long form text generation. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 12076–12100, Singapore. Association for Computational Linguistics.

Milad Moradi and Matthias Samwald. 2021. Evaluating the robustness of neural language models to input perturbations. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 1558–1570.

Vera Neplenbroek, Arianna Bisazza, and Raquel Fernández. 2025. Reading between the prompts: How stereotypes shape LLM's implicit personalization. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 20367–20400, Suzhou, China. Association for Computational Linguistics.

OpenAI. 2026. GPT-5.4. Accessed April 8, 2026.

Jae-Woo Park, Seong-Jin Park, Hyun-Sik Won, and Kang-Min Kim. 2024. Large language models are students at various levels: Zero-shot question difficulty estimation. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 8157–8177. Association for Computational Linguistics.

Ellie Pavlick and Joel Tetreault. 2016. An empirical analysis of formality in online communication. *Transactions of the Association for Computational Linguistics*, 4:61–74.

Ethan Perez, Sam Ringer, Kamile Lukosiute, Karina Nguyen, Edwin Chen, Scott Heiner, Craig Pettit, Catherine Olsson, Sandipan Kundu, Saurav Kadavath, and 1 others. 2023. Discovering language model behaviors with model-written evaluations. In *Findings of the Association for Computational Linguistics: ACL 2023*, pages 13387–13434, Toronto, Canada. Association for Computational Linguistics.

Elinor Poole-Dayan, Deb Roy, and Jad Kabbara. 2026. Llm targeted underperformance disproportionately impacts vulnerable users. *Proceedings of the AAAI Conference on Artificial Intelligence*, 40(46):39116–39124.

Qwen Team, Alibaba Group. 2026. Qwen3.6-27b. Accessed May 11, 2026.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.

Donya Rooein, Amanda Cercas Curry, and Dirk Hovy. 2023. Know your audience: Do llms adapt to different age and education levels? *arXiv preprint arXiv:2312.02065*.

Alireza Salemi, Sheshera Mysore, Michael Bendersky, and Hamed Zamani. 2024. Lamp: When large language models meet personalization. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 7370–7392.

Reijo Savolainen. 2022. Everyday life as an evolving context of information behaviour. *Aslib Journal of Information Management*, 75(5):940–960.

Karen A. Schriver. 1997. *Dynamics in Document Design: Creating Texts for Readers*. John Wiley & Sons, New York.

Abigail See, Peter J. Liu, and Christopher D. Manning. 2017. Get to the point: Summarization with pointer-generator networks. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1073–1083, Vancouver, Canada. Association for Computational Linguistics.

Andrew D. Selbst, Danah Boyd, Sorelle A. Friedler, Suresh Venkatasubramanian, and Janet Vertesi. 2019. Fairness and abstraction in sociotechnical systems. In *Proceedings of the Conference on Fairness, Accountability, and Transparency*, FAT* '19, page 59–68, New York, NY, USA. Association for Computing Machinery.

Mrinank Sharma, Meg Tong, Tomasz Korbak, David Duvenaud, Amanda Askell, Samuel R. Bowman, Newton Cheng, Esin Durmus, Zac Hatfield-Dodds, Scott R. Johnston, Shauna Kravec, Timothy Maxwell, Sam McCandlish, Kamal Ndousse, Oliver Rausch, Nicholas Schiefer, Da Yan, Miranda Zhang, and Ethan Perez. 2024a. Towards understanding sycophancy in language models. In *Proceedings of the 12th International Conference on Learning Representations (ICLR 2024)*.

Nikhil Sharma, Q. Vera Liao, and Ziang Xiao. 2024b. Generative echo chamber? effect of llm-powered search systems on diverse information seeking. In *Proceedings of the 2024 CHI Conference on Human Factors in Computing Systems*, CHI '24, New York, NY, USA. Association for Computing Machinery.

Karan Singhal, Shekoofeh Azizi, Tao Tu, S. Sara Mahdavi, Jason Wei, Hyung Won Chung, Nathan Scales, Ajay Tanwani, Heather Cole-Lewis, Stephen Pfohl, Perry Payne, Martin Seneviratne, Paul Gamble, Chris Kelly, Abubakr Babiker, Nathanael Schärli, Aakanksha Chowdhery, Philip Mansfield, Dina Demner-Fushman, and 13 others. 2023. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180.

Jan Trienes, Sebastian Joseph, Jörg Schlötterer, Christin Seifert, Kyle Lo, Wei Xu, Byron Wallace, and Junyi Jessy Li. 2024. InfoLossQA: Characterizing and recovering information loss in text simplification. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 4263–4294, Bangkok, Thailand. Association for Computational Linguistics.

United States Congress. 2010. Plain writing act of 2010. Public Law 111–274, 124 Stat. 2861.

Sowmya Vajjala and Ivana Lučić. 2018. OneStopEnglish corpus: A new corpus for automatic readability assessment and text simplification. In *Proceedings of the Thirteenth Workshop on Innovative Use of NLP for Building Educational Applications*, pages 297–304, New Orleans, Louisiana. Association for Computational Linguistics.

Shuhe Wang, Xiaofei Sun, Xiaoya Li, Rongbin Ouyang, Fei Wu, Tianwei Zhang, Jiwei Li, Guoyin Wang, and Chen Guo. 2025. GPT-NER: Named entity recognition via large language models. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 4257–4275, Albuquerque, New Mexico. Association for Computational Linguistics.

Benjamin Warner, Antoine Chaffin, Benjamin Clavié, Orion Weller, Oskar Hallström, Said Taghadouini,

Alexis Gallagher, Raja Biswas, Faisal Ladhak, Tom Aarsen, Griffin Thomas Adams, Jeremy Howard, and Iacopo Poli. 2025. Smarter, better, faster, longer: A modern bidirectional encoder for fast, memory efficient, and long context finetuning and inference. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2526–2547, Vienna, Austria. Association for Computational Linguistics.

Laura Weidinger, Jonathan Uesato, Maribeth Rauh, Conor Griffin, Po-Sen Huang, John Mellor, Amelia Glaese, Myra Cheng, Borja Balle, Atoosa Kasirzadeh, Courtney Biles, Sasha Brown, Zac Kenton, Will Hawkins, Tom Stepleton, Abeba Birhane, Lisa Anne Hendricks, Laura Rimell, William Isaac, and 4 others. 2022. Taxonomy of risks posed by language models. In *Proceedings of the 2022 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '22, page 214–229, New York, NY, USA. Association for Computing Machinery.

Iain Weissburg, Sathvika Anand, Sharon Levy, and Haewon Jeong. 2025. LLMs are biased teachers: Evaluating LLM bias in personalized education. In *Findings of the Association for Computational Linguistics: NAACL 2025*, pages 5665–5713, Albuquerque, New Mexico. Association for Computational Linguistics.

Jules White, Quchen Fu, Sam Hays, Michael Sandborn, Carlos Olea, Henry Gilbert, Ashraf Elnashar, Jesse Spencer-Smith, and Douglas C. Schmidt. 2023. A prompt pattern catalog to enhance prompt engineering with ChatGPT. *arXiv preprint arXiv:2302.11382*.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. BERTScore: Evaluating text generation with BERT. In *International Conference on Learning Representations (ICLR)*.

A Dataset Construction Details

This appendix documents the dataset of 250 high-stakes topics used in the audit. Section A.1 reports the full domain taxonomy and Section A.2 lists the categorised source materials from which the reference data for each scenario was curated.

A.1 Domain Taxonomy

The 250 scenarios span 32 domains drawn from international and national legal instruments, regulatory guidance, technical and safety standards, and scientific consensus documents. The full domain list is: Consumer Rights, Criminal Justice, Cyber Security, Digital Rights, Disability Rights, Drug Safety, Aviation Safety, Chemical Safety, Education Rights, Environmental Rights, Finance, Financial Regulation, First Aid, Food Safety, Health Rights, Housing Rights, Humanitarian Rights, Immigration, Indigenous Rights, Industrial Safety, Intellectual Property, Labor Rights, Maritime Safety, Media Law, Nuclear Safety, Political, Refugee Rights, Safety, Science, Social, Tech Safety, and Travel Safety. Coverage emphasises legal rights and safety-procedural domains where literacy-conditioned response stratification carries the highest deployment relevance.

A.2 Source Materials

For each topic, the reference text was curated from publicly accessible authoritative documents. We list the sources below which we have used to prepare the dataset.

International conventions and treaties. ILO Convention 155 — Occupational Safety and Health Convention, 1981; Universal Declaration of Human Rights (UDHR); International Covenant on Civil and Political Rights (ICCPR); International Covenant on Economic, Social and Cultural Rights (ICESCR); UN Convention on the Rights of Persons with Disabilities (CRPD); UN Declaration on the Rights of Indigenous Peoples (UNDRIP); UN Convention on the Rights of the Child (UNCRC); UN Convention on the Elimination of All Forms of Discrimination against Women (CEDAW); 1951 Convention Relating to the Status of Refugees; UN Convention Against Corruption (UNCAC, 2003); Aarhus Convention; Rio Declaration; Basel Convention; Nagoya Protocol; TRIPS Agreement; WIPO Patent Law Treaty; European Convention on Human Rights (ECHR); UNCITRAL Arbitration Rules (2021); UN Convention on the Law of the Sea (UNCLOS); SOLAS Convention; UN Globally Harmonized System (GHS) Revision 10 (2023); ICPD Declaration.

UN-system policy and humanitarian guidance. UNESCO Recommendation on the Ethics of Artificial Intelligence (2021); ICRC Code of Conduct; ICRC Rules on Personal Data Protection (revised 2020–2025); Sphere Handbook (2018); Core Humanitarian Standard (CHS, 2024 edition); UN Secretary-General's Bulletin ST/SGB/2003/13; Grand Bargain 2.0 (2023); UN OHCHR Eviction Guidelines; UN-Habitat Tenant Protection Guidelines; UN Special Rapporteur on Adequate Housing (2019 Report); UNESCO Declaration on Bioethics and Human Rights (2005); UNESCO Recommendation on Science and Scientific Researchers (2017); UNESCO Convention Against Discrimination in Education (1960); UNESCO Media Development Indicators.

National legislation and regulatory instruments. *Bangladesh:* Constitution; Personal Data Protection Ordinance, 2025 (Ordinance No. 61 of 2025); Labour Act 2006; Consumer Act 2009 (Consumer Rights Protection Act); Premises Rent Control Act 1991; Overseas Employment and Migrants Act 2013; Bangladesh Bank Mobile Financial Services Regulations (2018); Transfer of Property Act 1882. *European Union:* General Data Protection Regulation (GDPR) 2016/679 (with cited Articles and Recitals); Consumer Rights Directive 2011/83/EU; General Product Safety Directive 2001/95/EC; Schengen Borders Code Regulation 2016/399; Whistleblower Protection Directive 2019/1937; Council Regulation 2022/1854; Regulation 1169/2011 (food labelling); Deposit Guarantee Schemes Directive 2014/49/EU. *United States:* Bank Secrecy Act; Securities Exchange Act 1934; Insider Trading Sanctions Act 1984; Lanham Act 15 USC §1064(3); Truth in Lending Act 15 USC §1643 (Regulation Z); Copyright Act; Immigration and Nationality Act (INA); FDA 21 CFR; OSHA 29 CFR §1910.146, §1910.147, §1910.1200; Federal Aviation Regulation FAR 25.841; FAA Advisory Circular 91-74B; National Electrical Code (NFPA 70); SEC Rule 201 / NYSE Rule 7.12; Pasteurized Milk Ordinance (PMO); FDA Microwave Oven Radiation Safety guidance. *Other jurisdictions:* UK Limitation Act 1980; UK Representation of the People Act 1983; Indian Right to Information Act 2005; Indian Consumer Protection Act 2019; Canada Greenhouse Gas Pollution Pricing Act; German Federal Electoral Act (Bundeswahlgesetz); French Press Law of 1881; Philippines Republic Act No. 8042.

International organisations and monitoring bodies. SEC Investor Bulletin — Ponzi Schemes; FINRA Margin Account Guidance; IMF World Economic Outlook; World Health Organization (WHO); International Labour Organization (ILO); International Atomic Energy Agency (IAEA); International Civil Aviation Organization (ICAO); International Air Transport Association (IATA); International Telecommunication Union (ITU); Financial Action Task Force (FATF); UN High Commissioner for Refugees (UNHCR); UNESCO; OECD DAC Guidelines on Transition Financing; Bank for International Settlements (BIS); EU Intellectual Property Office (EUIPO); Hague Conference on Private International Law; US Centers for Disease Control (CDC); NIOSH; US Federal Bureau of Investigation (FBI IC3); US Cybersecurity and Infrastructure Security Agency (CISA); US Customs and Border Protection (CBP); US Citizenship and Immigration Services (USCIS); US Securities and Exchange Commission (SEC); US Federal Deposit Insurance Corporation (FDIC); US Environmental Protection Agency (EPA); US National Transportation Safety Board (NTSB); US Bureau of Labor Statistics (BLS); US Department of Energy; US Department of State; US Internal Revenue Service (IRS).

Regulatory and technical standards. NIST SP 800 Series (Cybersecurity); ICC International Building Code (IBC); OSHA Laser Hazards Standard; ICRP Publication 103 (2007); NIST Special Publications SP 800-77 Rev. 1 and SP 800-63B; NIST Internal Report IR 8408; IETF RFC 6238; BIP-39 (Bitcoin Improvement Proposal 39); IEC Standard 60529; IEC 60034-3; IEEE/NERC Frequency Control Standards; ASME Boiler and Pressure Vessel Code (BPVC); ASME A17.1 / CSA B44 (elevators); AASHTO LRFD Bridge Design Specifications; EN 1991-2; ICH E2A Clinical Safety Data Management; ICH E8(R1) General Considerations for Clinical Studies; EU EudraVigilance; IATA Dangerous Goods Regulations; IATA Timatic; NFPA Alternative Fuel Vehicles Training; IAEA Safety Standards Series GSR Part 7; Codex Alimentarius CAC/RCP 1-1969 and CAC/RCP 57-2004; Basel III Framework (BCBS, 2017 finalization).

Clinical and professional guidelines. Poison Control Center (AAPCC); WHO Preventing and reducing poisoning; WHO International Health Regulations (2005), Annex 7; WHO global strategy for food safety 2022-2030; WHO Global Action Plan on Antimicrobial Resistance (2015); WHO Patient Safety Guidelines; WHO Patient Rights Declaration (1994); WHO Constitution; WHO Guiding Principles on Human Cell, Tissue and Organ Transplantation (2010); American Heart Association (AHA) Guidelines and AHA/ASA Stroke Guidelines; American Diabetes Association (ADA) Guidelines; Red Cross First Aid Manual; Mayo Clinic clinical guidance; Epilepsy Foundation; EpiPen Prescribing Information; CDC: Understanding mRNA COVID-19 Vaccines.

Scientific references. WHO Plastics and Health Initiative; Neuralink — Pioneering Brain Computer Interfaces; Karikó & Weissman (2005), pioneering mRNA work; Jinek et al. (2012, *Science*) on programmable CRISPR-Cas9; IPCC Special Report on Carbon Dioxide Capture and Storage (2005), Chapter 3; Global CCS Institute documentation;

NASA Kepler/TESS Mission Science; ITER Organization documentation; IBM Quantum / Qiskit Textbook.

Statistical, indicator, and monitoring reports. UNHCR Global Trends Report 2024; WFP Global Food Crisis Report 2024; FAO Food Outlook 2024; ILO/Walk Free/IOM Global Estimates of Modern Slavery 2022; World Inequality Lab / Oxfam Inequality Report 2026; WHO World Mental Health Report 2022; Coveware Quarterly Ransomware Report Q4 2024; Pew Research Center 2024; ITU Tech Report; EPA Urban Heat Island Effect.

Service-provider documents (terms of service, privacy policies). Apple Privacy Documentation; Android Permissions Overview; Facebook (Meta) Terms of Service; Instagram (Meta) Privacy Policy; TikTok US Privacy Policy; WhatsApp Business Privacy Protections and Data Processing Terms; Telegram Privacy Policy; Amazon Privacy Notice and Amazon App Privacy Policy; Google Play Store Location Data Disclosure; OpenAI Terms of Use; PayPal Acceptable Use Policy; Uber Service Agreement; Foodpanda Service Agreement.

General topical references. A small number of consumer-facing entries (covering personal finance, household electrical and battery safety, mobile-app permissions, browser-level privacy, home-network and cryptocurrency-wallet practice, and standard residential leases) cite well-established topical knowledge rather than a single named instrument. These are treated as reference categories rather than novel citations, and represent widely-recognised general guidance in their respective domains.

B Statistical Analysis Test Details for Linguistic Register

B.1 Statistical Background and Notation

This subsection defines the inferential machinery used throughout the per-metric appendices below. All terms, variables, and assumptions referenced in subsequent test tables are introduced here.

Hypothesis-testing framework. For each metric we test a directional null and alternative pair. Let X and Y denote two measurements collected under different conditions for the same n subjects (here, the same set of topic (with IDs). The null hypothesis is $H_0 : \mu_X = \mu_Y$ and the alternative is $H_1 : \mu_X > \mu_Y$ (one-tailed). One-tailed testing is used because the direction of expected effect is fixed in advance by the design — higher-literacy responses are expected to retain more substantive content than lower-literacy ones.

One-sample t-test. We use the one-sample t-test to test whether a single cell's measurements differ from a known reference value μ_0. With observations $x_1, \ldots, x_n$, sample mean $\bar{x}$, and sample standard deviation s (denominator $n-1$),

$$t = \frac{\bar{x} - \mu_0}{s/\sqrt{n}}, \qquad \mathrm{df} = n - 1. \tag{7}$$

The reference μ_0 is the value the metric takes when the two compared responses are identical (e.g. $\mu_0 = 0$ for semantic divergence, $\mu_0 = 1$ for NLI average entailment).

Paired t-test. The paired t-test compares two measurements collected on the same subject. Let $\Delta^{(i)} = X^{(i)} - Y^{(i)}$ denote the difference for subject i, with $\bar{\Delta} = \frac{1}{n}\sum_i \Delta^{(i)}$ and s_Δ the sample standard deviation of the differences. The test statistic is

$$t = \frac{\bar{\Delta}}{s_\Delta/\sqrt{n}}, \qquad \mathrm{df} = n - 1. \tag{8}$$

Pairing by event ID controls between-event variability and improves statistical power relative to a between-subjects test.

Cohen's d effect size. We report Cohen's d alongside every t-statistic to communicate effect magnitude independent of sample size. The one-sample variant is $d_{\text{one-sample}} = (\bar{x} - \mu_0)/s$, and the paired variant is $d_{\text{paired}} = \bar{\Delta}/s_\Delta$. We adopt the conventional benchmarks of Cohen (1988): $|d| = 0.2$ is treated as a *small* effect, $|d| = 0.5$ as *medium*, $|d| = 0.8$ as *large*, $|d| \geq 1.2$ as *very large*, and $|d| \geq 2.0$ as *huge*.

Bonferroni correction for multiple testing. When k tests are conducted within a single metric family, the family-wise error rate is controlled by lowering the per-test significance threshold. With family-wise level $\alpha = 0.05$, the corrected threshold is

$$\alpha_{\text{corr}} = \frac{\alpha}{k} = \frac{0.05}{k}. \tag{9}$$

For our design, $k = 18$ for paired contrasts on FK grade, word count, posture analysis(3 level contrasts $\times$ 3 models $\times$ 2 conditions); for ROUGE-Lsum, semantic divergence, and NLI entailment, $k = 6$ (1 level contrast $\times$ 3 models $\times$ 2 conditions). The corresponding corrected thresholds and the minimum $|t|$ required for significance at $\mathrm{df} = 249$ are summarised in Table 4.

Repeated-measures one-way ANOVA. For metrics, which have three literacy levels per event (High, Mid, Low), we also report a one-way repeated-measures ANOVA within each (model,

Test family	Metrics	k	α_{corr}	$\lvert t\rvert_{\min}$
paired	FK, WC, Posture×2	18	2.8×10^{-3}	2.80
paired	RLsum, Sem, NLI	6	8.3×10^{-3}	2.41
one-sample	Sem, NLI	12	4.2×10^{-3}	2.66

Table 4: Bonferroni-corrected thresholds and minimum $|t|$ (FK= Flesch–Kincaid, WC= word count, Posture×2= Posture analysis on two axis, RLsum= ROUGE-Lsum Sem= Semantic Similarity)

condition) cell, with literacy level as the within-subject factor and event ID as the subject. The F-statistic is the ratio of between-level to within-subject error variance,

$$F = \frac{\text{MS}_{\text{between}}}{\text{MS}_{\text{error}}}, \quad \text{df} = (k-1,\ (n-1)(k-1)), \tag{10}$$

where $k = 3$ is the number of literacy levels and $n = 250$ the number of subjects (events), yielding $\text{df} = (2, 498)$ for our design (written $F_{2,498}$). The mean squares are $\text{MS}_{\text{between}} = \text{SS}_{\text{between}}/(k-1)$ and $\text{MS}_{\text{error}} = \text{SS}_{\text{error}}/((n-1)(k-1))$, where

$$\text{SS}_{\text{between}} = n \sum\nolimits_j (\bar{y}_{\cdot j} - \bar{y}_{\cdot\cdot})^2, \tag{11}$$

$$\text{SS}_{\text{error}} = \sum\nolimits_{i,j} (y_{ij} - \bar{y}_{i\cdot} - \bar{y}_{\cdot j} + \bar{y}_{\cdot\cdot})^2. \tag{12}$$

Here y_{ij} is the metric value for event i at level j; $\bar{y}_{i\cdot}$, $\bar{y}_{\cdot j}$, and $\bar{y}_{\cdot\cdot}$ are the per-subject, per-level, and grand means. Effect size is partial eta-squared,

$$\eta_p^2 = \frac{\text{SS}_{\text{between}}}{\text{SS}_{\text{between}} + \text{SS}_{\text{error}}}, \tag{13}$$

with conventional benchmarks $\eta_p^2 = 0.01$ small, 0.06 medium, 0.14 large (Cohen, 1988).

Assumption checks. The three test families used in this paper rely on overlapping but distinct assumption sets, which we verify in turn.

One-sample t-test (Semantic divergence and NLI average entailment, per cell against a fixed reference): requires (i) independent observations, (ii) approximate normality of the sample mean, and (iii) continuous measurement. Independence is satisfied because each event ID corresponds to a distinct curated scenario. Normality of the sample mean is not strictly required at $n = 250$ per cell — by the central limit theorem the sampling distribution of $\bar{x}$ is approximately normal regardless of the distribution of individual observations. Continuous measurement holds for both target quantities (bounded continuous scores in $[0, 1]$).

Paired t-test (every per-metric High-Mid/High-Low or High/Mid/Low contrast in this paper): requires (i) independence of pairs, (ii) approximate normality of the paired differences, and (iii) continuous measurement. Pairs are independent because each event ID is a distinct scenario; the two measurements within a pair are intentionally correlated (same event under different levels) which is the point of pairing. Normality of $\bar{\Delta}$ follows from the central limit theorem at $n = 250$ per cell. Continuous measurement holds for every metric reported (FK grade, word count, ROUGE-Lsum F_1, semantic divergence, NLI average entailment, zero-shot classifier probabilities).

Repeated-measures one-way ANOVA (FK, Word count, Posture analysis metrics, within-subject factor: literacy level): requires (i) independence of subjects, (ii) approximate normality of residuals within each level, and (iii) sphericity — that the variances of paired differences across all level pairs are approximately equal. Subject independence holds by event ID construction. Normality is again addressed by the central limit theorem at $n = 250$. Sphericity was verified using Mauchly's test; Greenhouse–Geisser and Huynh–Feldt corrected p-values remain below 10^{-14} in every cell, so we report the standard $F_{2,498}$.

B.2 Statistical Analysis of Linguistic Registering Metric

Flesch–Kincaid Grade and Word Count Within every (model, condition) cell, the metric value descends monotonically as the literacy signal weakens. All paired tests are one-tailed, paired by event ID, with the larger-literacy condition as the directional reference (H1: higher-literacy member > lower-literacy member). Effect size is reported as paired Cohen's $d = \bar{\Delta}/s_\Delta$, where $\bar{\Delta}$ is the mean of the per-event paired differences and s_Δ their sample standard deviation (Bessel-corrected). We follow the conventional benchmarks of Cohen (1988): $|d| = 0.2$ is treated as a *small* effect, $|d| = 0.5$ as *medium*, $|d| = 0.8$ as *large*, $|d| \geq 1.2$ as *very large*, and $|d| \geq 2.0$ as *huge*. All eighteen within-cell paired contrasts pass Bonferroni correction on both metrics (Tables 5, 6).

The cell-level repeated-measures one-way ANOVA confirms a uniform within-subject literacy effect (Tables 7, 8); per-response distributions are shown in Figures 6, 7.

Model	Cond.	H1	t	d
GPT-5.4	Exp.	H>M	42.83	2.71
		H>L	59.07	3.74
		M>L	33.17	2.10
	Imp.	H>M	21.49	1.36
		H>L	30.88	1.95
		M>L	11.69	0.74
Claude Opus 4.6	Exp.	H>M	57.19	3.62
		H>L	83.06	5.25
		M>L	49.20	3.11
	Imp.	H>M	18.11	1.15
		H>L	26.64	1.69
		M>L	12.40	0.78
Gemini 3.1 Pro	Exp.	H>M	59.81	3.78
		H>L	81.68	5.17
		M>L	42.09	2.66
	Imp.	H>M	21.20	1.34
		H>L	28.85	1.82
		M>L	12.01	0.76

Table 5: Paired t and Cohen's d for FK grade. (Cond.= Condition, H1= alternative Hypothesis; Exp.= Explicit, Imp.= Implicit; H= High, M= Mid, L= Low literacy level)

Model	Cond.	H1	t	d
GPT-5.4	Exp.	H>M	19.46	1.23
		H>L	25.93	1.64
		M>L	18.32	1.16
	Imp.	H>M	13.59	0.86
		H>L	18.00	1.14
		M>L	9.59	0.61
Claude Opus 4.6	Exp.	H>M	26.78	1.69
		H>L	30.60	1.94
		M>L	12.78	0.81
	Imp.	H>M	22.17	1.40
		H>L	26.44	1.67
		M>L	14.38	0.91
Gemini 3.1 Pro	Exp.	H>M	23.78	1.50
		H>L	43.93	2.78
		M>L	37.12	2.35
	Imp.	H>M	14.11	0.89
		H>L	20.82	1.32
		M>L	8.90	0.56

Table 6: Paired t and Cohen's d for word count. Cond.= Condition, H1= alternative Hypothesis; Exp.= Explicit, Imp.= Implicit; H= High, M= Mid, L= Low literacy level.

Model	Cond.	$F_{2,498}$	p	η_p^2
GPT-5.4	Exp.	2457.4	$1{\cdot}10^{-258}$	0.91
GPT-5.4	Imp.	553.8	$3{\cdot}10^{-127}$	0.69
Claude Opus 4.6	Exp.	4752.9	$<10^{-308}$	0.95
Claude Opus 4.6	Imp.	443.2	$3{\cdot}10^{-111}$	0.64
Gemini 3.1 Pro	Exp.	4617.1	$4{\cdot}10^{-322}$	0.95
Gemini 3.1 Pro	Imp.	534.4	$1{\cdot}10^{-124}$	0.68

Table 7: Repeated-measures one-way ANOVA on FK grade. (Cond.=Condition, Exp.=Explicit, Imp.=Implicit)

Model	Cond.	$F_{2,498}$	p	η_p^2
GPT-5.4	Exp.	517.8	$2{\cdot}10^{-122}$	0.68
GPT-5.4	Imp.	234.8	$1{\cdot}10^{-72}$	0.49
Claude Opus 4.6	Exp.	739.4	$8{\cdot}10^{-150}$	0.75
Claude Opus 4.6	Imp.	575.6	$3{\cdot}10^{-130}$	0.70
Gemini 3.1 Pro	Exp.	1301.5	$2{\cdot}10^{-198}$	0.84
Gemini 3.1 Pro	Imp.	252.9	$2{\cdot}10^{-76}$	0.50

Table 8: Repeated-measures one-way ANOVA on word count.(Cond.=Condition, Exp.=Explicit, Imp.=Implicit)




Figure 6: FK grade distribution across model, condition, level




Figure 7: Word count distribution across model, condition, level

The minimum effect size observed across our paired contrasts is $d = 0.56$ (word count, Gemini Implicit Mid→Low) and the maximum is $d = 5.25$ (FK grade, Claude Explicit High→Low); all eighteen contrasts on both metrics fall at or above the *medium*-effect threshold, and the majority fall in the *large* or *very large* regime. Bonferroni correction is applied within each metric: with k=18 paired contrasts per metric, the corrected threshold is $\alpha_{\text{corr}} = 0.05/18 \approx 2.78{\cdot}10^{-3}$, which translates to a minimum $|t|$ of approximately 2.80 at df=249 to declare a contrast Bonferroni-significant; all observed $|t|$ in Tables 5–6 substantially exceed this threshold. The repeated-measures one-way ANOVA (Tables 7, 8) uses literacy level as a within-subject factor within each (model, condition) cell, with subjects defined by event ID; reported η_p^2 ranges from 0.49 to 0.95, all in the conventional "large" regime.

Statistical Analysis for ROUGE-Lsum Across every (model, condition) cell, Precision, Recall,

and F_1 all decline as the candidate's literacy register descends from High-Mid to High-Low (Table 9); the within-cell High-Mid vs High-Low paired contrast is Bonferroni-significant in every cell with effect sizes spanning the *large* to *huge* regime ($d = 1.00$–3.09; Table 10). ROUGE-Lsum is computed for two reference–candidate pairs per event ID within each (model, condition) cell: (High, Mid) and (High, Low).

Model	Condition	Precision	Recall	F_1
GPT-5.4	Exp. H-M	$.63 \pm .09$	$.36 \pm .10$	$.44 \pm .07$
	Exp. H-L	$.60 \pm .08$	$.23 \pm .08$	$.32 \pm .07$
	Imp. H-M	$.56 \pm .14$	$.34 \pm .14$	$.39 \pm .10$
	Imp. H-L	$.52 \pm .14$	$.23 \pm .12$	$.29 \pm .09$
Claude Opus 4.6	Exp. H-M	$.48 \pm .06$	$.33 \pm .05$	$.39 \pm .04$
	Exp. H-L	$.38 \pm .05$	$.22 \pm .05$	$.28 \pm .04$
	Imp. H-M	$.57 \pm .10$	$.23 \pm .10$	$.31 \pm .10$
	Imp. H-L	$.53 \pm .10$	$.14 \pm .07$	$.21 \pm .08$
Gemini 3.1 Pro	Exp. H-M	$.46 \pm .06$	$.32 \pm .06$	$.37 \pm .04$
	Exp. H-L	$.42 \pm .06$	$.18 \pm .04$	$.24 \pm .04$
	Imp. H-M	$.50 \pm .09$	$.41 \pm .09$	$.44 \pm .08$
	Imp. H-L	$.46 \pm .08$	$.33 \pm .08$	$.37 \pm .07$

Table 9: Mean $\pm$ standard deviation of ROUGE-Lsum Precision, Recall, and F_1. (H-M= ROUGE-Lsum(High, Mid), H-L=ROUGE-Lsum(High, Low); Exp.= Explicit, Imp.=Implicit)

Paired t-tests follow the framework of Section B.1, with $k = 6$ tests in this metric family and corresponding $\alpha_{\text{corr}} \approx 0.01$ ($|t|_{\min} \approx 2.41$ at df=249). The directional hypothesis is $H_1 : \mu_{F_1,\text{High}-\text{Mid}} > \mu_{F_1,\text{High}-\text{Low}}$ against $H_0 : \mu_{F_1,\text{High}-\text{Mid}} = \mu_{F_1,\text{High}-\text{Low}}$. All observed $|t|$ in Table 10 substantially exceed the corrected threshold; effect sizes range from $d = 1.00$ (GPT Implicit) to $d = 3.09$ (Gemini Explicit), spanning the *large*-to-*huge* regime in every cell.

Model	Condition	t	d
GPT-5.4	Exp.	35.04	2.22
	Imp.	15.75	1.00
Claude Opus 4.6	Exp.	43.40	2.74
	Imp.	18.18	1.15
Gemini 3.1 Pro	Exp.	48.87	3.09
	Imp.	16.72	1.06

Table 10: Paired t and Cohen's d tests for ROUGE-Lsum F_1 (High-Mid vs High-Low).

ROUGE-Lsum F_1 decreases monotonically across literacy level from High-Mid to High-Low candidate in every (model, condition) cell; per-response distributions are shown in Figure 1.

B.3 Statistical Analysis for Semantic Similarity

We measure semantic loss as $\text{SimLoss} = 1 - \cos(\mathbf{e}_{\text{High}}, \mathbf{e}_{\text{target}})$ for each (High, Mid) and (High, Low) pair per event ID; perfect preservation of high-literacy content corresponds to a loss of 0.0. Across every (model, condition) cell, both High $\rightarrow$ Mid and High$\rightarrow$Low losses are well above zero, and the within-cell High-Mid vs High-Low contrast widens this gap further: the one-sample tests against perfect preservation (Table 12) and the paired High-Mid vs High-Low tests (Table 13) are Bonferroni-significant in every cell.

Descriptive Statistics Table 11 reports the per-cell mean and standard deviation of semantic loss. Loss increases as the candidate literacy register descends from Mid to Low in every cell, with the implicit condition producing markedly larger loss than the explicit condition.

Model	Cond.	H–M Loss	H–L Loss
GPT-5.4	Exp.	0.11 ± 0.04	0.16 ± 0.04
	Imp.	0.23 ± 0.09	0.31 ± 0.09
Claude Opus 4.6	Exp.	0.16 ± 0.04	0.24 ± 0.05
	Imp.	0.25 ± 0.09	0.33 ± 0.08
Gemini 3.1 Pro	Exp.	0.17 ± 0.04	0.25 ± 0.05
	Imp.	0.23 ± 0.08	0.30 ± 0.08

Table 11: Per-cell mean $\pm$ standard deviation of semantic loss. (Exp.= Explicit, Imp.= Implicit; H-L=High-Low, H-M= High-Mid semantic loss.)

One-Sample t-Test Against Perfect Preservation One-sample t-tests follow the framework of Section B.1, with $k = 12$ tests in this metric family and $\alpha_{\text{corr}} \approx 4.2 \cdot 10^{-3}$ ($|t|_{\min} \approx 2.66$ at df=249). For each cell we test $H_1 : \mu_{\text{loss}} > 0$ against $H_0 : \mu_{\text{loss}} = 0$ (perfect semantic preservation). All observed t in Table 12 massively exceed the corrected threshold (range 42–88); one-sample Cohen's d ranges from 2.69 to 5.58, all in the *huge* regime.

Within-Condition Paired Test Paired t-tests follow the framework of Section B.1, with $k = 6$ tests in this metric family and $\alpha_{\text{corr}} \approx 0.01$ ($|t|_{\min} \approx 2.41$ at df=249). The directional hypothesis is $H_1 : \text{loss}(\text{High}, \text{Low}) > \text{loss}(\text{High}, \text{Mid})$: deeper literacy reduction yields greater semantic divergence. All observed t in Table 13 substantially exceed the corrected threshold; effect sizes range from $d = 1.08$ (GPT Implicit) to $d = 2.41$ (Claude Explicit), spanning the *very large*-to-*huge* regime in every cell.

Model	Cond.	Pair	t	d
GPT-5.4	Exp.	H–M	50.82	3.21
		H–L	58.43	3.70
	Imp.	H–M	42.52	2.69
		H–L	55.47	3.51
Claude Opus 4.6	Exp.	H–M	59.16	3.74
		H–L	81.31	5.14
	Imp.	H–M	45.65	2.89
		H–L	64.07	4.05
Gemini 3.1 Pro	Exp.	H–M	68.48	4.33
		H–L	88.20	5.58
	Imp.	H–M	43.20	2.73
		H–L	55.60	3.52

Table 12: One-sample t and Cohen's d test results comparing semantic loss. (Cond.= Condition; Exp.= Explicit, Imp.= Implicit; H-M= High-Mid, H-L= High-Low semantic loss)

Model	Condition	t	d
GPT-5.4	Exp.	24.14	1.53
	Imp.	17.12	1.08
Claude Opus 4.6	Exp.	38.10	2.41
	Imp.	17.68	1.12
Gemini 3.1 Pro	Exp.	35.16	2.22
	Imp.	17.85	1.13

Table 13: Paired t and Cohen's d tests for semantic loss (High-Mid vs High-Low contrast within each model and condition). Exp.= Explicit, Imp.= Implicit.

Figure 2 in the main body shows the per-pair distributions for all (model, condition, level) cells.

B.4 Statistical Analysis for Logical Entailment

Across every (model, condition) cell, NLI (entailment) drops as the partner literacy register descends; the decline is driven by a rise in neutral probability rather than by contradiction (Table 14). Both the one-sample tests against the perfect-entailment baseline (Table 15) and the within-cell paired High-Mid vs High-Low contrasts (Table 16) are Bonferroni-significant in every cell.

Class Decomposition: Entailment, Neutral, Contradiction Table 14 reports the per-cell means of all three NLI output classes, averaged across forward and reverse directions each pairs. Across every cell, contradiction stays low (≤ 0.05); the entailment decline from Mid to Low is mirrored by a near-equal rise in neutral probability rather than by an increase in contradiction. This pattern is consistent with literacy-conditioned stratification proceeding via *omission* of reference-register content rather than via factual disagreement with it.

Model	Pair	Explicit			Implicit		
		Ent	Neu	Con	Ent	Neu	Con
GPT-5.4	H–M	0.81	0.19	0.00	0.60	0.38	0.02
	H–L	0.75	0.25	0.00	0.51	0.47	0.02
Claude Opus 4.6	H–M	0.61	0.37	0.02	0.49	0.48	0.04
	H–L	0.48	0.50	0.03	0.41	0.54	0.05
Gemini 3.1 Pro	H–M	0.48	0.52	0.01	0.45	0.54	0.01
	H–L	0.43	0.56	0.02	0.38	0.61	0.02

Table 14: Per-cell mean entailment (Ent), neutral (Neu), and contradiction (Con) probabilities for each (model, partner-level, condition). (H-M= NLI(High,Mid), H-L= NLI(High,Low)

One-Sample t-Test Against Perfect Entailment One-sample t-tests follow the framework of Section B.1, with $k = 12$ tests in this metric family and corresponding $\alpha_{\text{corr}} \approx 4.2{\cdot}10^{-3}$ ($|t|_{\min} \approx 2.66$ at df=249). For each cell we test $H_1 : \mu_{\text{NLI}_{\text{entailment}}} < 1$ against $H_0 : \mu = 1$ (perfect entailment). All observed $|t|$ in Table 15 massively exceed the corrected threshold (range 23–59); one-sample Cohen's d ranges from -1.46 to -3.76, all in the *huge* regime.

Model	Cond.	Pair	t	d
GPT-5.4	Exp.	H–M	-23.11	-1.46
		H–L	-29.22	-1.85
	Imp.	H–M	-30.48	-1.93
		H–L	-39.38	-2.49
Claude Opus 4.6	Exp.	H–M	-41.26	-2.61
		H–L	-57.43	-3.63
	Imp.	H–M	-48.24	-3.05
		H–L	-59.39	-3.76
Gemini 3.1 Pro	Exp.	H–M	-53.43	-3.38
		H–L	-56.57	-3.58
	Imp.	H–M	-47.67	-3.01
		H–L	-58.86	-3.72

Table 15: One-sample t and Cohen's d test results comparing $\text{NLI}_{\text{entailment}}$ against the perfect-entailment baseline ($\mu = 1$).(Cond.= Condition; Exp.= Explicit, Imp.= Implicit; H–M= NLI(High, Mid), H–L= NLI(High, Low).

Within-Condition Paired Test Paired t-tests follow the framework of Section B.1, with $k = 6$ tests in this metric family and $\alpha_{\text{corr}} \approx 0.01$ ($|t|_{\min} \approx 2.41$ at df=249). The directional hypothesis is $H_1 : \text{NLI}_{\text{entailment}}(\text{High}, \text{Mid}) > \text{NLI}_{\text{entailment}}(\text{High}, \text{Low})$. All observed $|t|$ in Table 16 substantially exceed the corrected threshold; effect sizes range from $d = 0.38$ (Gemini Explicit) to $d = 1.17$ (Claude Explicit), spanning the *medium*-to-*very large* regime.

Figure 3 in the main body shows the per-pair $\text{NLI}_{\text{entailment}}$ distributions.

Model	Condition	t	d
GPT-5.4	Exp.	8.34	0.53
	Imp.	8.79	0.56
Claude Opus 4.6	Exp.	18.54	1.17
	Imp.	7.94	0.50
Gemini 3.1 Pro	Exp.	6.02	0.38
	Imp.	7.03	0.44

Table 16: Paired t and Cohen's d tests for $\mathrm{NLI}_{\mathrm{entailment}}$ (High-Mid vs High-Low contrast within each model and condition) Exp.= Explicit, Imp.= Implicit.

B.5 Statistical Analysis for Stylistic and Informational Posture Shifts

We measure the comprehensiveness–minimalism axis (Info) and the formality–casualness axis (Style) as the binary classifier probabilities across literacy level. (Table 17); all eighteen within-cell paired contrasts on each axis pass Bonferroni correction (Table 18), and the cell-level repeated-measures ANOVA confirms a uniform within-subject literacy effect (Table 19). Per-response distributions appear in Figures 4, 5 in the main body.

Model	Cond.	Level	Info (l_1)	Style (l_1)
GPT-5.4	Exp.	High	0.63 ± 0.19	0.90 ± 0.06
		Mid	0.24 ± 0.17	0.65 ± 0.19
		Low	0.12 ± 0.11	0.46 ± 0.24
	Imp.	High	0.54 ± 0.18	0.87 ± 0.08
		Mid	0.41 ± 0.19	0.79 ± 0.14
		Low	0.32 ± 0.19	0.72 ± 0.19
Claude Opus 4.6	Exp.	High	0.80 ± 0.13	0.94 ± 0.05
		Mid	0.49 ± 0.21	0.78 ± 0.16
		Low	0.11 ± 0.10	0.30 ± 0.19
	Imp.	High	0.69 ± 0.16	0.89 ± 0.07
		Mid	0.56 ± 0.23	0.85 ± 0.13
		Low	0.44 ± 0.25	0.80 ± 0.17
Gemini 3.1 Pro	Exp.	High	0.85 ± 0.10	0.96 ± 0.03
		Mid	0.36 ± 0.21	0.65 ± 0.22
		Low	0.26 ± 0.21	0.45 ± 0.27
	Imp.	High	0.72 ± 0.14	0.89 ± 0.09
		Mid	0.57 ± 0.20	0.80 ± 0.15
		Low	0.49 ± 0.22	0.75 ± 0.19

Table 17: Per-cell mean $\pm$ standard deviation for the Info axis l_1= probability of *comprehensive-and-detailed information* and the Style axis l_1 =probability of *formal-and-professional*

Statistical methodology. Paired t-tests follow the framework of Section B.1, with $k = 18$ tests per axis and $\alpha_{\mathrm{corr}} \approx 2.8{\cdot}10^{-3}$ ($|t|_{\mathrm{min}} \approx 2.80$ at df=249). The directional hypothesis is $H_1 : \mu_{\text{higher level}} > \mu_{\text{lower level}}$ for each of the three within-cell contrasts (High>Mid, High>Low, Mid>Low literacy level). All eighteen contrasts on each axis substantially exceed the corrected threshold (Table 18); paired Cohen's d on the Info axis ranges from 0.31 to 4.11 and on the Style axis from 0.26 to 3.31, spanning the *small*-to-*huge* regime. The repeated-measures one-way ANOVA (Table 19) uses literacy level as a within-subject factor; reported η_p^2 ranges from 0.13 to 0.85, all in the conventional *large* regime ($\eta_p^2 \geq 0.14$) except Claude Implicit Style ($\eta_p^2 = 0.13$, on the boundary).

Model	Cond.	Contrast	Info Axis		Style Axis	
			t	d	t	d
GPT-5.4	Exp.	H>M	27.54	1.74	21.13	1.34
		H>L	39.40	2.49	29.86	1.89
		M>L	10.32	0.65	12.91	0.82
	Imp.	H>M	8.33	0.53	8.02	0.51
		H>L	13.44	0.85	11.50	0.73
		M>L	5.35	0.34	5.50	0.35
Claude Opus 4.6	Exp.	H>M	21.38	1.35	16.23	1.03
		H>L	65.03	4.11	52.27	3.31
		M>L	27.37	1.73	33.04	2.09
	Imp.	H>M	8.04	0.51	4.78	0.30
		H>L	13.52	0.86	7.97	0.50
		M>L	6.02	0.38	4.25	0.27
Gemini 3.1 Pro	Exp.	H>M	36.34	2.30	22.47	1.42
		H>L	39.95	2.53	29.52	1.87
		M>L	6.45	0.41	11.87	0.75
	Imp.	H>M	12.91	0.82	9.42	0.60
		H>L	16.38	1.04	11.81	0.75
		M>L	4.96	0.31	4.11	0.26

Table 18: Paired t and cohen's d tests for the Info axis l_1= probability of *comprehensive-and-detailed information* and the Style axis l_1 =probability of *formal-and-professional* (Cond.= Condition, H1= alternative Hypothesis; Exp.= Explicit, Imp.= Implicit; H= High, M= Mid, L= Low literacy level)

Model	Cond.	Info(l_1)		Style (l_1)	
		$F_{2,498}$	η_p^2	$F_{2,498}$	η_p^2
GPT-5.4	Exp.	852.98	0.77	505.78	0.67
	Imp.	93.69	0.27	77.44	0.24
Claude Opus 4.6	Exp.	1387.91	0.85	1454.19	0.85
	Imp.	93.70	0.27	36.82	0.13
Gemini 3.1 Pro	Exp.	922.80	0.79	514.48	0.67
	Imp.	144.38	0.37	77.80	0.24

Table 19: Repeated-measures one-way ANOVA the Info axis l_1= probability of *comprehensive-and-detailed information* and the Style axis l_1= probability of *formal-and-professional* (Cond.= Condition, Exp.= Explicit, Imp.= Implicit)

C Details of Specific Entity Extraction

Extractor Design To quantify substantive entity content independently of stylistic variation, we developed a structured rubric-based extractor using Gemini 3.1 Flash Lite (Google DeepMind, 2026a) as the backbone, prompted at temperature 0 for deterministic behaviour. The extractor reads each response holistically and then enumerates every specific, named, dated, or quantified real-world entity across seventeen categories: law and policy names, section or article references, organization names, specific penalties, monetary amounts, durations and deadlines, quantitative measures and thresholds, scientific terms, named standards and protocols, case-law citations, medical conditions, real-person names, standalone dates, geographic references, technical identifiers, numeric safety/operational thresholds, and other specific real-world entities not fitting the above.

De-duplication Rules To ensure counts reflect informational breadth rather than surface repetition, the same entity is counted at most once per response regardless of how often it appears or in which form (acronym, full form, or partial mention); years embedded in a law's official title are not additionally extracted as standalone dates; named entities fully subsumed within a larger extracted entity (e.g., party names within a case citation) are not double-counted; and generic references such as "the law" or "the relevant section" are excluded.

Per-Domain Breakdown of Specific Entity Count Table 3 in the main body shows us cumulative count and per-response mean. Here Figure 8 reports the mean per-response entity count broken down by domain × model × condition × literacy level. Rows are 32 high-stakes domains, sorted by overall High Literacy entity volume (descending). Columns are 18 cells: 3 models × 2 conditions × 3 literacy levels. Each cell is annotated with the mean entity count per response in that (domain, model, condition, literacy-level) bin.

The High→Mid→Low descent observed in Table 3 holds across the great majority of domains in every model and condition, demonstrating that the cross-cell ordering is not driven by a small set of high-density domains. A small number of implicit cells in a few domains exhibit a Mid or Low literacy entity count higher than the corresponding High count; this stems from question-style variation under implicit signalling, where a more focused user-style question can elicit a more entity-dense response than the broader expert-targeted prompt. However the dominant pattern across the heatmap is High > Mid > Low literacy.

D Open-Source Models Verification: Llama 4 Scout and Qwen3.6-27B

D.1 Experimental Setup

To verify that the literacy-conditioned stratification pattern is not specific to commercial frontier models, we replicate the audit on two open-source frontier models — Meta's **Llama 4 Scout** (Meta AI, 2025) (17B active / 109B total mixture-of-experts; Apache-compatible weights released April 2025) and Alibaba's **Qwen3.6-27B** (Qwen Team, Alibaba Group, 2026) (27B dense; Apache 2.0; accessed). We use the same two-condition prompting design, dataset and the same metrics as in the main study.

D.2 Results Analysis

Tables 20 through 26 report cell means for the open-source verification on the full 250-event run. Across all eight metrics and both conditions, both open-source models reproduce the audit's central direction-of-stratification: High > Mid > Low on FK grade, word count, stylistic and informational Posture Shifts, and High-Mid > High-Low (i.e., Mid responses are closer to High than Low responses are) on ROUGE-Lsum, Semantic Similarity and NLI (entailment). Magnitudes vary — Qwen3.6-27B produces longer responses and richer entity inventories than Llama 4 Scout, and explicit-condition gaps are systematically larger than implicit-condition gaps in both models, mirroring the pattern observed for commercial frontier in the main results.

		FK Grade			Word Count		
Condition	**Model**	High	Mid	Low	High	Mid	Low
Explicit	Llama 4 Scout	15.24	9.62	6.74	465	305	256
	Qwen3.6-27B	18.17	11.73	6.07	743	554	291
Implicit	Llama 4 Scout	15.79	13.55	12.84	426	379	341
	Qwen3.6-27B	14.72	12.50	11.76	777	553	434

Table 20: Mean Flesch–Kincaid grade and mean word count across models and conditions.

Condition	**Model**	High-Mid	High-Low
Explicit	Llama 4 Scout	0.45	0.35
	Qwen3.6-27B	0.37	0.20
Implicit	Llama 4 Scout	0.40	0.35
	Qwen3.6-27B	0.39	0.32

Table 21: Mean ROUGE-Lsum F_1 for paired comparisons against the high-literacy reference.




Figure 8: Per-domain mean specific entity count per response across models and conditions

		High		Mid		Low	
Condition	**Model**	total	mean	total	mean	total	mean
Explicit	Llama 4 Scout	1446	5.78	983	3.93	838	3.35
	Qwen3.6-27B	6118	24.47	2231	8.92	943	3.77
Implicit	Llama 4 Scout	1843	7.37	1724	6.90	1508	6.03
	Qwen3.6-27B	5671	22.68	4000	16.00	2923	11.69

Table 22: Cumulative specific entity count (*total*) and per-response mean across models and conditions.

Condition	**Model**	High-Mid	High-Low
Explicit	Llama 4 Scout	0.11	0.15
	Qwen3.6-27B	0.18	0.31
Implicit	Llama 4 Scout	0.22	0.29
	Qwen3.6-27B	0.23	0.30

Table 23: Mean BGE-M3 semantic loss (SimLoss $= 1 - \cos$) for paired comparisons against the high-literacy reference.

		High-Mid			High-Low		
Condition	**Model**	Ent	Neu	Con	Ent	Neu	Con
Explicit	Llama 4 Scout	0.69	0.29	0.01	0.60	0.36	0.03
	Qwen3.6-27B	0.55	0.39	0.07	0.45	0.49	0.07
Implicit	Llama 4 Scout	0.55	0.44	0.01	0.47	0.51	0.01
	Qwen3.6-27B	0.51	0.46	0.03	0.43	0.53	0.05

Table 24: Mean NLI average probabilities (forward + reverse) per class — entailment (Ent), neutral (Neu), contradiction (Con) — for paired comparisons against the high-literacy reference.

Condition	**Model**	High	Mid	Low
Explicit	Llama 4 Scout	0.83	0.33	0.12
	Qwen3.6-27B	0.77	0.42	0.10
Implicit	Llama 4 Scout	0.63	0.53	0.50
	Qwen3.6-27B	0.69	0.54	0.46

Table 25: Mean information-axis probability ($\Pr(\textit{comprehensive and detailed})$) across models and conditions.

Condition	**Model**	High	Mid	Low
Explicit	Llama 4 Scout	0.91	0.56	0.29
	Qwen3.6-27B	0.94	0.81	0.33
Implicit	Llama 4 Scout	0.90	0.85	0.81
	Qwen3.6-27B	0.90	0.83	0.77

Table 26: Mean style-axis probability ($\Pr(\textit{formal and professional})$) across models and conditions.

E Toxicity Analysis

To verify that the literacy-conditioned stratification documented in the main body does not co-occur with a stratification in harmful language, we computed toxicity scores on every collected response using a ModernBERT-base fine-tuned toxic-comment classifier (Adobe codemay2025, 2025), built on the ModernBERT encoder backbone (Warner et al., 2025). Tables 27 and 28 report per-cell mean, median, and standard deviation of the toxicity probability for explicit and implicit responses respectively (n=750 per literacy level per condition, pooled across the three frontier models).

Literacy	n	Mean	Median	Std
High Literacy	750	0.000344	0.000200	0.000444
Mid Literacy	750	0.001085	0.000500	0.001914
Low Literacy	750	0.003045	0.001000	0.010359

Table 27: Toxicity probability for explicit-condition responses (pooled across three models).

Literacy	n	Mean	Median	Std
High Literacy	750	0.000410	0.000200	0.001333
Mid Literacy	750	0.000684	0.000300	0.001255
Low Literacy	750	0.001097	0.000400	0.002632

Table 28: Toxicity probability for implicit-condition responses (pooled across three models).

Toxicity probabilities are essentially zero across every (condition, literacy-level) cell: the largest cell mean (Low Literacy, explicit) is 0.003, with a median of 0.001, indicating that responses are uniformly non-toxic regardless of the user's signalled literacy. The stratification we document on linguistic register, substantive content, semantic alignment, and stylistic posture therefore does not coincide with a stratification in harmful language — consistent with the audit framing that literacy-conditioned response stratification proceeds via *omission* rather than via the production of toxic or harmful content. The near-zero toxicity is unsurprising given our high-stakes setting, where queries and reference texts are inherently formal and non-adversarial; whether the same pattern holds in domains where toxicity is more naturally elicited (e.g., social, political, opinion-laden, or conversational contexts) is a question for future replication outside this setting.

F Prompt Templates and Worked Example

This appendix provides the full prompt templates used in both experimental conditions and a worked example illustrating the role of the Source/Reference grounding field.

Explicit Condition Templates The system instruction is held constant across all three literacy personas:

> You are a helpful assistant that adapts to the user's literacy level.

The user prompt is constructed as:

> The topic: {topic}
> Additional context or details: {topic_details}
> Source/Reference: {topic_source}
> Persona: {persona_description} ({persona_level})

where {persona_description} takes one of three forms:

- *High Literacy*: "I have high literacy on this topic. Explain the topic according to my level."
- *Mid Literacy*: "I have mid literacy on this topic. Explain the topic according to my level."
- *Low Literacy*: "I have low literacy on this topic. Explain the topic according to my level."

and {persona_level} is the corresponding label "High Literacy", "Mid Literacy", or "Low Literacy".

Implicit Condition — Stage 1: Question Generation The system instruction is held constant across the three question-generator LLMs:

> You are a question generator. Given a topic, its additional context, source/reference, and a persona with a literacy level, generate a realistic question that a person with that literacy level on that topic would naturally ask.

The generation prompt is constructed as:

> The topic: {topic}
> Additional context or details: {topic_details}
> Source/Reference: {topic_source}
> Target Persona: {persona_description}

where {persona_description} takes one of three forms:

- *High Literacy*: "Has high literacy on this topic; knowledgeable or experienced in this domain."

- *Mid Literacy*: "Has mid literacy on this topic; has some general awareness of the domain but is not an expert."
- *Low Literacy*: "Has low literacy on this topic; unfamiliar with the domain."

Implicit Condition — Stage 2: Answer Collection The system instruction is reduced to a neutral baseline:

> You are a helpful assistant.

The user prompt contains only the generated question:

> {generated_user_question}

G Illustrative Example: Full Responses

This appendix reproduces the full Gemini 3.1 Pro responses (explicit condition) excerpted in Table 1 for event DIG_15 at the three declared literacy levels.

The Topic: Automated Decision-Making
Additional context or details: Users have the right not to be subject to solely automated decisions that significantly affect them, including AI-driven inferences about creditworthiness or employment.
Source/Reference: GDPR

High-Literacy response. Under the General Data Protection Regulation (GDPR), the framework governing Automated Decision-Making (ADM) and profiling is primarily enshrined in Article 22, supported by transparency requirements in Articles 13, 14, and 15, and further contextualized by Recital 71.

Given your high literacy on this topic, here is a granular breakdown of the regulatory mechanisms, thresholds, and compliance implications surrounding ADM, specifically concerning AI-driven inferences in high-stakes domains like credit and employment.

1. The Article 22 Prohibition and Thresholds. Article 22(1) establishes a baseline prohibition rather than merely a right to object. It states that a data subject has the right not to be subject to a decision based solely on automated processing, including profiling, which produces legal effects concerning them or similarly significantly affects them. To trigger Article 22, two specific thresholds must be met. Solely Automated: The European Data Protection Board (EDPB) strictly interprets "solely." For a process to fall outside the scope of Article 22, human intervention cannot be a mere token gesture or a "rubber stamp." The human reviewer must have the authority, competence, and underlying data to alter the decision, and must actively evaluate the algorithmic recommendation. Legal or Similarly Significant Effects: Legal effects impact a person's legal status or rights (e.g., cancellation of a contract, denial of a statutory benefit). Similarly significant effects must have an equivalent impact on the data subject's circumstances, behavior, or choices. The GDPR explicitly targets AI-driven inferences in areas like creditworthiness (e.g., automated rejection of a mortgage or loan) and employment (e.g., automated CV filtering, AI-driven recruitment platforms, or algorithmic termination).

2. Derogations (Exceptions) to the Prohibition. Data controllers may only bypass the Article 22(1) prohibition if the ADM falls under one of three derogations outlined in Article 22(2): (1) Contractual Necessity: The ADM is strictly necessary for entering into, or performing, a contract between the data subject and the controller (e.g., a real-time decision on an instant loan). (2) Legal Authorization: Authorized by Union or Member State law to which the controller is subject, which must also lay down suitable measures to safeguard the data subject's rights. (3) Explicit Consent: The data subject has provided unambiguous, explicitly informed consent to the automated processing. Note: Under Article 22(4), if special categories of data (Article 9) are processed, ADM is only permissible under explicit consent or substantial public interest, coupled with robust safeguards.

3. Mandatory Safeguards and "Human in the Loop" (HITL). If a controller relies on contractual necessity or explicit consent to deploy ADM, Article 22(3) mandates strict safeguards. The data controller must implement measures ensuring the data subject's right to obtain meaningful human intervention, express their point of view regarding the decision, and contest the decision directly to the controller.

4. Algorithmic Explainability and Transparency. A critical component of the GDPR's stance on AI-driven ADM is the intersecting transparency obligation. Articles 13(2)(f), 14(2)(g), and 15(1)(h) mandate that controllers must proactively inform data subjects about the existence of ADM. Crucially, controllers must provide "meaningful information about the logic involved, as well as the significance and the envisaged consequences of such processing." The "Right to Explanation": While the exact legal bindingness of a "right to explanation" is heavily debated in legal tech literature (as

it appears explicitly in Recital 71 rather than an operative Article), the EDPB asserts that controllers must explain the rationale behind a decision. Impact on AI/ML Models: This poses a significant challenge for complex, non-linear AI models (like deep neural networks) used for credit scoring or HR screening. The "black box" nature of these models makes compliance difficult, as controllers must translate complex algorithmic inferences into comprehensible terms for the data subject without necessarily revealing trade secrets.

Summary. For sophisticated AI deployments in creditworthiness or employment, controllers cannot rely on algorithmic opacity. They must map their data flows to determine if human intervention is legally sufficient to bypass Article 22. If the process is "solely" automated and carries "significant effects," they must establish a valid Article 22(2) derogation, implement rigorous HITL safeguards, and build explainability into their models to satisfy the GDPR's stringent transparency requirements.

Mid-Literacy response. Here is an explanation of Automated Decision-Making under the GDPR, tailored to a mid-level understanding.

What is Automated Decision-Making? Automated decision-making happens when a computer, algorithm, or Artificial Intelligence (AI) system makes a choice about you without any human involvement. The machine looks at your data, runs its calculations, and makes a final call.

What is Your Right Under the GDPR? The GDPR (a major European privacy law that sets a global standard) includes a very specific rule to protect people from out-of-control algorithms. Essentially, you have the "right to a human." The law states that you have the right not to be subjected to a decision based solely on automated processing if that decision has a significant impact on your life.

Real-World Examples. To understand what a "significant impact" means, let's look at two common areas where AI is heavily used today. Getting a Loan (Creditworthiness): Imagine you apply for a mortgage to buy a house. The bank uses an AI system to look at your financial history. If the computer instantly denies your loan—and no human loan officer ever looks at your file—that is a solely automated decision. Because getting a home is a major life event, the GDPR says a human should be involved. Getting a Job (Employment): You apply for a job online, and a computer program scans your resume. If the AI determines you aren't a good fit and automatically throws your application in the trash without a recruiter ever seeing it, you are being subjected to a solely automated decision.

Why Does This Rule Exist? While AI can process information much faster than humans, it isn't perfect. Algorithms can carry hidden biases, lack common sense, or fail to understand the unique context of your situation. This rule prevents "computer says no" scenarios where a machine gets the final, unquestioned say over important parts of your life.

How Does It Work in Practice? There are a few exceptions to this rule. A company can use solely automated decisions if: (1) it is necessary to enter into a contract with you, (2) they are required to do so by a specific law, or (3) you have given them your clear, explicit consent to let a computer decide. However, even if one of these exceptions applies, the company must still protect your rights. In most cases, if the computer makes a decision you don't agree with, you have the right to contest it, express your point of view, and demand that a real, live human review the decision.

Low-Literacy response. Your Right to a Human Decision. Have you ever applied for a job or a loan, and a computer instantly said "no"? This is called Automated Decision-Making. It just means a computer program makes a choice about you without any human being involved. Sometimes, computers make choices about very big things, like whether you get hired for a job, or whether you are allowed to get a loan or a credit card. Because these decisions can change your life, there is a privacy law called the GDPR that protects you.

What the Law Says. The law says that computers should not have the final say on big life events. If a computer makes a major decision about you all by itself, you have a special right. You have the right to say, "No, I want a real person to look at this."

Why this matters to you. Computers are just machines. They can make mistakes, or they might not understand your whole story. Thanks to this law, if a computer rejects you for a job or a loan, you can speak up and ask for a human to review your application fairly.

H Supplementary Materials

The dataset, implementation code, supplementary README documentation, and license file are provided as separate anonymized supplementary files submitted with this paper.