

Totally Integrated Automation Portal						
--------------------------------------	--	--	--	--	--	--

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]

PLC za simuliranje rada objekta					
General\Project information					
Name	PLC za simuliranje rada objekta	Author	Korisnik	Comment	
Slot	1	Rack	0		
General\Catalog information					
Short designation	CPU 1214C DC/DC/DC	Description	Work memory 100 KB; 24VDC power supply with DI14 x 24VDC SINK/ SOURCE, DQ10 x 24VDC and AI2 on board; 6 high-speed counters and 4 pulse outputs on-board; signal board expands on-board I/O; up to 3 communication modules for serial communication; up to 8 signal modules for I/O expansion; PROFINET IO controller, I-device, transport protocol TCP/IP, secure Open User Communication, S7 communication, Web server, OPC UA: Server DA	Article number	6ES7 214-1AG40-0XB0
Firmware version	V4.4				
General\Identification & Maintenance					
Plant designation		Location identifier		Installation date	2026-08-19 14:56:46.979
Additional information					
General\Checksums					
Text lists	FA 70 E8 75 1D 5A 8E 29	Software	15 69 F9 26 E6 73 38 7B		
PROFINET interface [X1]\General					
Name	PROFINET interface_1	Author	Korisnik	Comment	
PROFINET interface [X1]\General\Project information					
Name	DI 14/DQ 10_1	Comment		Name	AI 2_1
Comment					
PROFINET interface [X1]\Ethernet addresses\Interface networked with					
Subnet:	PN/IE_1				
PROFINET interface [X1]\Ethernet addresses\IP protocol					
IP configuration	Set IP address in the project	IP address:	192.168.0.1	Subnet mask:	255.255.255.0
Use router	False				
PROFINET interface [X1]\Ethernet addresses\PROFINET					
PROFINET device name is set directly at the device	False	Generate PROFINET device name automatically	True	PROFINET device name:	plc za simuliranje rada objekta
Converted name:	plcxazaxasimuliranjexaradaxaobjek-ta66ed	Device number:	0		
PROFINET interface [X1]\Time synchronization					
Enable time synchronization via NTP server	Enable time synchronization via NTP server		IP addresses	Server 1	0.0.0.0
Server 2	0.0.0.0	Server 3	0.0.0.0	Server 4	0.0.0.0
Update interval	10sec			CPU synchronizes the modules of the device.	No synchronization
PROFINET interface [X1]\Digital inputs\Channel0					
Channel address	I0.0	Input filters	6.4 millise	Enable pulse catch	0
PROFINET interface [X1]\Digital inputs\Channel0\					
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49152	Event name:	0
Hardware interrupt:	0	Rising edge0	Rising edge0		
PROFINET interface [X1]\Digital inputs\Channel0\					
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49280	Event name:	0
Hardware interrupt:	0	Falling edge0	Falling edge0		
PROFINET interface [X1]\Digital inputs\Channel1					
Channel address	I0.1	Input filters	6.4 millise	Enable pulse catch	0
PROFINET interface [X1]\Digital inputs\Channel1\					
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49153	Event name:	0
Hardware interrupt:	0	Rising edge1	Rising edge1		
PROFINET interface [X1]\Digital inputs\Channel1\					
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49281	Event name:	0
Hardware interrupt:	0	Falling edge1	Falling edge1		
PROFINET interface [X1]\Digital inputs\Channel2					
Channel address	I0.2	Input filters	6.4 millise	Enable pulse catch	0
PROFINET interface [X1]\Digital inputs\Channel2\					
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49154	Event name:	0
Hardware interrupt:	0	Rising edge2	Rising edge2		
PROFINET interface [X1]\Digital inputs\Channel2\					
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49282	Event name:	0
Hardware interrupt:	0	Falling edge2	Falling edge2		
PROFINET interface [X1]\Digital inputs\Channel3					
Channel address	I0.3	Input filters	6.4 millise	Enable pulse catch	0
PROFINET interface [X1]\Digital inputs\Channel3\					
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49155	Event name:	0
Hardware interrupt:	0	Rising edge3	Rising edge3		

--	--	--	--	--	--

Totally Integrated Automation Portal						
PROFINET interface [X1]\Digital inputs\Channel3\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49283	Event name:	0	
Hardware interrupt:	0	Falling edge3	Falling edge3			
PROFINET interface [X1]\Digital inputs\Channel4						
Channel address	I0.4	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel4\						
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49156	Event name:	0	
Hardware interrupt:	0	Rising edge4	Rising edge4			
PROFINET interface [X1]\Digital inputs\Channel4\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49284	Event name:	0	
Hardware interrupt:	0	Falling edge4	Falling edge4			
PROFINET interface [X1]\Digital inputs\Channel5						
Channel address	I0.5	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel5\						
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49157	Event name:	0	
Hardware interrupt:	0	Rising edge5	Rising edge5			
PROFINET interface [X1]\Digital inputs\Channel5\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49285	Event name:	0	
Hardware interrupt:	0	Falling edge5	Falling edge5			
PROFINET interface [X1]\Digital inputs\Channel6						
Channel address	I0.6	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel6\						
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49158	Event name:	0	
Hardware interrupt:	0	Rising edge6	Rising edge6			
PROFINET interface [X1]\Digital inputs\Channel6\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49286	Event name:	0	
Hardware interrupt:	0	Falling edge6	Falling edge6			
PROFINET interface [X1]\Digital inputs\Channel7						
Channel address	I0.7	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel7\						
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49159	Event name:	0	
Hardware interrupt:	0	Rising edge7	Rising edge7			
PROFINET interface [X1]\Digital inputs\Channel7\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49287	Event name:	0	
Hardware interrupt:	0	Falling edge7	Falling edge7			
PROFINET interface [X1]\Digital inputs\Channel8						
Channel address	I1.0	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel8\						
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49160	Event name:	0	
Hardware interrupt:	0	Rising edge8	Rising edge8			
PROFINET interface [X1]\Digital inputs\Channel8\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49288	Event name:	0	
Hardware interrupt:	0	Falling edge8	Falling edge8			
PROFINET interface [X1]\Digital inputs\Channel9						
Channel address	I1.1	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel9\						
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49161	Event name:	0	
Hardware interrupt:	0	Rising edge9	Rising edge9			
PROFINET interface [X1]\Digital inputs\Channel9\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49289	Event name:	0	
Hardware interrupt:	0	Falling edge9	Falling edge9			
PROFINET interface [X1]\Digital inputs\Channel10						
Channel address	I1.2	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel10\						
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49162	Event name:	0	
Hardware interrupt:	0	Rising edge10	Rising edge10			
PROFINET interface [X1]\Digital inputs\Channel10\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49290	Event name:	0	
Hardware interrupt:	0	Falling edge10	Falling edge10			
PROFINET interface [X1]\Digital inputs\Channel11						
Channel address	I1.3	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel11\						
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49163	Event name:	0	
Hardware interrupt:	0	Rising edge11	Rising edge11			
PROFINET interface [X1]\Digital inputs\Channel11\						
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49291	Event name:	0	
Hardware interrupt:	0	Falling edge11	Falling edge11			
PROFINET interface [X1]\Digital inputs\Channel12						
Channel address	I1.4	Input filters	6.4 millisec	Enable pulse catch	0	
PROFINET interface [X1]\Digital inputs\Channel13						
Channel address	I1.5	Input filters	6.4 millisec	Enable pulse catch	0	

Totally Integrated Automation Portal						
PROFINET interface [X1]\Analog inputs\Noise reduction						
Integration time	50 Hz (20 ms)					
PROFINET interface [X1]\Analog inputs\Channel0						
Channel address	IW64	Measurement type	Voltage	Voltage range	0..10 V	
Smoothing	Weak (4 cycles)			Enable overflow diagnostics	1	
PROFINET interface [X1]\Analog inputs\Channel1						
Channel address	IW66	Measurement type	Voltage	Voltage range	0..10 V	
Smoothing	Weak (4 cycles)			Enable overflow diagnostics	1	
PROFINET interface [X1]\Digital outputs						
Reaction to CPU STOP	Use substitute value					
PROFINET interface [X1]\Digital outputs\Channel0						
Channel address	Q0.0	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel1						
Channel address	Q0.1	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel2						
Channel address	Q0.2	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel3						
Channel address	Q0.3	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel4						
Channel address	Q0.4	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel5						
Channel address	Q0.5	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel6						
Channel address	Q0.6	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel7						
Channel address	Q0.7	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel8						
Channel address	Q1.0	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel9						
Channel address	Q1.1	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Operating mode						
IO controller	True	IO system		Device number	0	
IO device	False					
PROFINET interface [X1]\I/O addresses\Input addresses						
Start address	0.0	End address	1.7	Organization block	0	
Process image	0					
PROFINET interface [X1]\I/O addresses\Input addresses						
Start address	64	End address	67	Organization block	0	
Process image	0					
PROFINET interface [X1]\I/O addresses\Output addresses						
Start address	0.0	End address	1.7	Organization block	0	
Process image	0					
PROFINET interface [X1]\Advanced options\Interface options						
Support device replacement without exchangeable medium	True	Permit overwriting of device names of all assigned IO devices	False	Use IEC V2.2 LLDP mode	False	
Keep-Alive connection monitoring:	30s					
PROFINET interface [X1]\Advanced options\Real time settings\IO communication						
Send clock:	1.000ms					
PROFINET interface [X1]\Advanced options\Real time settings\Real time options						
Calculated bandwidth for cyclic IO data:	0.000ms	Calculated bandwidth for cyclic IO data:	0.000%			
PROFINET interface [X1]\Advanced options\Port [X1 P1]\General						
Name	Port_1	Author	Korisnik	Comment		
PROFINET interface [X1]\Advanced options\Port [X1 P1]\Port interconnection\Local port:						
Local port:	PLC za simuliranje rada objekta\PROFINET interface_1 [X1]\Port_1 [X1 P1]	Medium:	Copper	Cable name:	---	
						

Totally Integrated Automation Portal						
PROFINET interface [X1]\Advanced options\Port [X1 P1]\Port interconnection\Partner port:						
	Monitoring of partner port is not possible	Partner port:	Any partner			
PROFINET interface [X1]\Advanced options\Port [X1 P1]\Port options\Activate						
Activate this port for use	True					
PROFINET interface [X1]\Advanced options\Port [X1 P1]\Port options\Connection						
Transmission rate / duplex:	Automatic	Monitor	False	Enable autonegotiation	True	
PROFINET interface [X1]\Advanced options\Port [X1 P1]\Port options\Boundaries						
End of detection of accessible devices	False	End of topology discovery	False	End of the sync domain	False	
PROFINET interface [X1]\Web server access						
Enable Web server for the IP address of this interface	False	The Web server must also be activated in the properties of the PLC.				
High speed counters (HSC)\HSC1\General\Enable						
Enable this high speed counter	0	Enable this high speed counter	0	Enable this high speed counter	0	
Enable this high speed counter	0	Enable this high speed counter	0	Enable this high speed counter	0	
High speed counters (HSC)\HSC1\General\Project information						
Name	HSC_1	Comment		Name	HSC_2	
Comment		Name	HSC_3	Comment		
Name	HSC_4	Comment		Name	HSC_5	
Comment		Name	HSC_6	Comment		
High speed counters (HSC)\HSC1\I/O addresses\Input addresses						
Start address	1000.0	End address	1003.7	Start address	1004.0	
End address	1007.7	Organization block	0	Start address	1008.0	
End address	1011.7	Organization block	0	Process image	0	
Start address	1012.0	End address	1015.7	Organization block	0	
Process image	0	Start address	1016.0	End address	1019.7	
Organization block	0	Process image	0	Start address	1020.0	
End address	1023.7	Organization block	0	Process image	0	
Organization block	0	Process image	0	Process image	0	
Pulse generators (PTO/PWM)\PTO1/PWM1\General\Enable						
Enable this pulse generator	0	Enable this pulse generator	0			
Pulse generators (PTO/PWM)\PTO1/PWM1\General\Project information						
Name	Pulse_1	Comment		Name	Pulse_2	
Comment						
Pulse generators (PTO/PWM)\PTO1/PWM1\I/O addresses\Output addresses						
Start address	1000.0	End address	1001.7	Start address	1002.0	
End address	1003.7	Organization block	0	Organization block	0	
Process image	0	Process image	0			
Startup						
Startup after POWER ON	Warm restart - mode before POWER OFF	Comparison preset to actual configuration	Startup CPU even if mismatch	Configuration time	60000ms	
OBs should be interruptible	1					
Cycle						
Cycle monitoring time	150ms			Enable minimum cycle time for cyclic OBs	0	
Minimum cycle time	1ms					
Communication load						
Cycle load due to communication	20%					
System and clock memory\System memory bits						
Enable the use of system memory byte	0	Address of system memory byte (MBx)	1	First cycle		
Diagnostic status changed		Always 1 (high)		Always 0 (low)		
System and clock memory\Clock memory bits						
Enable the use of clock memory byte	0	Address of clock memory byte (MBx)	0	10 Hz clock		
5 Hz clock		2.5 Hz clock		2 Hz clock		
1.25 Hz clock		1 Hz clock		0.625 Hz clock		
0.5 Hz clock						
Web server\General						
Activate Web server on all modules of this device	False	Permit access only with HTTPS	True			
Web server\Automatic update						
Enable automatic update	True	Update interval	0s			
Web server\User management						
User name			User rights			
Everybody						
Web server\User-defined web pages						
Application name	HTML source path	Default HTML page	Files with dynamic content	Web DB number	Fragment DB number	
		index.htm	.htm;.html	333	334	
Web server\Overview of interfaces						
Device		Interface		Enabled web server access		
PLC za simuliranje rada objekta		PROFINET interface_1		False		

Totally Integrated Automation Portal

User interface languages

Assign project language

User interface languages

English (United States)

English (United States)

English (United States)

English (United States)

English (United States)

English (United States)

English (United States)

German

English

French

Spanish

Italian

Chinese (simplified)

Time of day\Local time

Time zone

(UTC +01:00) Berlin, Bern, Brussels, Rome, Stockholm, Vienna

Time of day\Daylight saving time

Activate daylight saving time

1

Difference between standard and daylight saving time

60mins

Time of day\Daylight saving time\Start of daylight saving time

Starting week of the month:

Last

Sunday

of

March

at

01:00 a.m.

Time of day\Daylight saving time\Start of standard time

Last

Sunday

of

October

at

02:00 a.m.

Protection & Security

Level of protection

No protection

Protection & Security\Connection mechanisms

Permit access with PUT/GET communication from remote partner

False

Protection & Security\Security event

Summarize diagnostics in case of high message volume

True

Length of an interval

20

Unit

seconds

Protection & Security\External load memory

Disable copying from internal load memory to external load memory

False

Configuration control\Configuration control for central configuration

Allow to reconfigure the device via the user program

0

Connection resources\

	Station resources - Reserved - Maximum	Station resources - Reserved - Configured	Station resources - Dynamic - Configured	Module resources - PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] - Configured
Maximum number of resources:		62	6	68
	Maximum	Configured	Configured	Configured
PG communication:	4	-	-	-
HMI communication:	12	2	0	2
S7 communication:	8	0	0	0
Open user communication:	8	0	0	0
Web communication:	30	-	-	-
Other communication:	-	-	0	0
Total resources used:		2	0	2
Available resources:		60	6	66

Overview of addresses\Overview of addresses\Overview of addresses

Inputs

True

Outputs

True

Address gaps

False

Slot

True

Totally Integrated Automation Portal											
Type	Addr. from	Addr. to	Module	PIP	Device name	Device number	Size	Master / IO system	Rack	Slot	
I	0	1	DI 14/DQ 10_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 1	
O	0	1	DI 14/DQ 10_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 1	
I	64	67	AI 2_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 2	
I	1000	1003	HSC_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 16	
I	1004	1007	HSC_2	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 17	
I	1008	1011	HSC_3	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 18	
I	1012	1015	HSC_4	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 19	
I	1016	1019	HSC_5	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 20	
I	1020	1023	HSC_6	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 21	
O	1000	1001	Pulse_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 32	
O	1002	1003	Pulse_2	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 33	
O	1004	1005	Pulse_3	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 34	
O	1006	1007	Pulse_4	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 35	

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Program blocks

Main [OB1]

Main Properties

General

Name	Main	Number	1	Type	OB	Language	LAD
Numbering	Automatic						

Information

Title	"Main Program Sweep (Cycle)"	Author		Comment		Family	
Version	0.1	User-defined ID					

Name	Data type	Default value	Comment
▼ Input			
Initial_Call	Bool		Initial call of this OB
Remanence	Bool		=True, if remanent data are available
Temp			
Constant			

Network 1:

```
0001 // Supervizor logika
0002 IF NOT "mod_motora" THEN
0003     "izlazna_vrednost_objekta" := 0.0;
0004     "matematicko_upravljanje" := 0.0;
0005     "greska_pracenja" := 0.0;
0006     "vrednost_integrala" := 0.0;
0007     "proporcionalno_dejstvo" := 0.0;
0008 END_IF;
```

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Program blocks

Cyclic interrupt [OB30]

Cyclic interrupt Properties

General

Name	Cyclic interrupt	Number	30	Type	OB	Language	SCL
Numbering	Automatic						

Information

Title		Author		Comment		Family	
Version	0.1	User-defined ID					

Name	Data type	Default value	Comment
▼ Input			
Initial_Call	Bool		Initial call of this OB
Event_Count	Int		Events discarded
Temp			
Constant			

0001 "Kontrolerski blok_DB"(enable:="mod_motora",

0002 open_loop:="izbor_zadatka",

0003 pi_mode:="izbor_rezima_regulatora",

0004 w_setpoint:="referentna_vrednost",

0005 y_actual:="izlazna_vrednost_objekta",

0006 Kc_in:="Kc_HMI_input",

0007 Ki_in:="Ki_HMI_input",

0008 u_out=>"matematicko_upravljanje",

0009 e_out=>"greska_pracenja",

0010 u_p_out=>"proporcionalno_dejstvo",

0011 u_i_out=>"vrednost_integrala",

0012 Kc_P_out=>"Kc_P",

0013 Kc_PI_out=>"Kc_PI",

0014 Ki_step_out=>"Ki_step");

0015 "FB_Plant_DB"(enable := "mod_motora",

0016 u_in := "matematicko_upravljanje",

0017 y_out => "izlazna_vrednost_objekta");

0018

Symbol	Address	Type	Comment
"greska_pracenja"	%MD30	Real	
"izbor_rezima_regulatora"	%M0.1	Bool	
"izbor_zadatka"	%M0.2	Bool	
"izlazna_vrednost_objekta"	%MD14	Real	
"Kc_HMI_input"	%MD46	Real	
"Kc_P"	%MD34	Real	
"Kc_PI"	%MD38	Real	
"Ki_HMI_input"	%MD50	Real	
"Ki_step"	%MD42	Real	
"matematicko_upravljanje"	%MD18	Real	
"mod_motora"	%M0.0	Bool	
"proporcionalno_dejstvo"	%MD26	Real	
"referentna_vrednost"	%MD10	Real	
"vrednost_integrala"	%MD22	Real	

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Program blocks

Kontrolerski blok [FB1]

Kontrolerski blok Properties							
General							
Name	Kontrolerski blok	Number	1	Type	FB	Language	SCL
Numbering	Automatic						
Information							
Title		Author		Comment		Family	
Version	0.1	User-defined ID					

Name	Data type	Default value	Retain	Accessible from HMI/OPC UA/Web API	Writ-able from HMI/OPC UA/ Web API	Visible in HMI engi-neering	Setpoint	Supervi-sion	Comment
▼ Input									
enable	Bool	false	Non-retain	True	True	True	False		
open_loop	Bool	false	Non-retain	True	True	True	False		
pi_mode	Bool	false	Non-retain	True	True	True	False		
w_setpoint	Real	0.0	Non-retain	True	True	True	False		
y_actual	Real	0.0	Non-retain	True	True	True	False		
Kc_in	Real	0.0	Non-retain	True	True	True	False		
Ki_in	Real	0.0	Non-retain	True	True	True	False		
▼ Output									
u_out	Real	0.0	Non-retain	True	True	True	False		
e_out	Real	0.0	Non-retain	True	True	True	False		
u_p_out	Real	0.0	Non-retain	True	True	True	False		
u_i_out	Real	0.0	Non-retain	True	True	True	False		
Kc_P_out	Real	0.0	Non-retain	True	True	True	False		
Kc_PI_out	Real	0.0	Non-retain	True	True	True	False		
Ki_step_out	Real	0.0	Non-retain	True	True	True	False		
InOut									
▼ Static									
u_integral_stat	Real	0.0	Non-retain	True	True	True	False		
Temp									
Constant									

```
0001 IF NOT #enable THEN
0002     #e_out := 0.0;
0003     #u_p_out := 0.0;
0004     #u_integral_stat := 0.0;
0005     #u_i_out := 0.0;
0006     #u_out := 0.0;
0007 ELSE
0008     IF #open_loop THEN
0009         // Otvorena petlja
0010         #e_out := 0.0;
0011         #u_p_out := 0.0;
0012         #u_integral_stat := 0.0;
0013         #u_i_out := 0.0;
0014         #u_out := #w_setpoint;
0015
0016     ELSIF NOT #pi_mode THEN
0017         // P rezim
0018         #Kc_P_out := #Kc_in;
0019         #e_out := #w_setpoint - #y_actual;
0020         #u_p_out := #Kc_P_out * #e_out;
0021         #u_integral_stat := 0.0;
0022         #u_i_out := 0.0;
0023         #u_out := #u_p_out;
0024
0025     ELSE
0026         // PI rezim
0027         #Kc_PI_out := #Kc_in;
0028         #Ki_step_out := #Ki_in * 0.04; // Ts = 0.04 s
0029
0030         #e_out := #w_setpoint - #y_actual;
0031         #u_p_out := #Kc_PI_out * #e_out;
0032         #u_integral_stat := #u_integral_stat + (#Ki_step_out * #e_out);
0033
0034         // Anti-Reset Windup (ARW)
0035         IF #u_integral_stat > 125.0 THEN
0036             #u_integral_stat := 125.0;
0037         ELSIF #u_integral_stat < 0.0 THEN
0038             #u_integral_stat := 0.0;
0039         END_IF;
0040
0041         #u_i_out := #u_integral_stat;
0042         #u_out := #u_p_out + #u_i_out;
0043     END_IF;
```

Totally Integrated Automation Portal

```
0044
0045 // Saturacija
0046 IF #u_out > 125.0 THEN
0047     #u_out := 125.0;
0048 ELSIF #u_out < 0.0 THEN
0049     #u_out := 0.0;
0050 END_IF;
0051 END_IF;
```

Symbol	Address	Type	Comment
#e_out		Real	
#enable		Bool	
#Kc_in		Real	
#Kc_P_out		Real	
#Kc_PI_out		Real	
#Ki_in		Real	
#Ki_step_out		Real	
#open_loop		Bool	
#pi_mode		Bool	
#u_i_out		Real	
#u_integral_stat		Real	
#u_out		Real	
#u_p_out		Real	
#w_setpoint		Real	
#y_actual		Real	

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Program blocks

FB_Plant [FB2]

FB_Plant Properties							
General							
Name	FB_Plant	Number	2	Type	FB	Language	SCL
Numbering	Automatic						
Information							
Title		Author		Comment		Family	
Version	0.1	User-defined ID					

Name	Data type	Default value	Retain	Accessible from HMI/OPC UA/Web API	Writ-able from HMI/OPC UA/ Web API	Visible in HMI engi-neering	Setpoint	Supervi-sion	Comment
▼ Input									
enable	Bool	false	Non-retain	True	True	True	False		
u_in	Real	0.0	Non-retain	True	True	True	False		
▼ Output									
y_out	Real	0.0	Non-retain	True	True	True	False		
InOut									
▼ Static									
u_stat	Real	0.0	Non-retain	True	True	True	False		
y_stat	Real	0.0	Non-retain	True	True	True	False		
Temp									
Constant									

```
0001 IF NOT #enable THEN
0002     #y_stat := 0.0;
0003     #y_out := 0.0;
0004     #u_stat := 0.0;
0005 ELSE
0006     // Diskretni model objekta prvog reda: y(k) = 0.87517 * y(k-1) + 0.09986 * u(k-1)
0007     #y_stat := (0.87517 * #y_stat) + (0.09986 * #u_stat);
0008     #y_out := #y_stat;
0009     #u_stat := #u_in;
0010 END_IF;
```

Symbol	Address	Type	Comment
#enable		Bool	
#u_in		Real	
#u_stat		Real	
#y_out		Real	
#y_stat		Real	

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Program blocks

Kontrolerski blok_DB [DB1]

Kontrolerski blok_DB Properties

General

Name	Kontrolerski blok_DB	Number	1	Type	DB	Language	DB
Numbering	Automatic						

Information

Title		Author		Comment		Family	
Version	0.1	User-defined ID					

Name	Data type	Start value	Retain	Accessible from HMI/OPC UA/Web API	Writ-able from HMI/ OPC UA/ Web API	Visible in HMI engi-neering	Setpoint	Supervi-sion	Comment
▼ Input									
enable	Bool	false	False	True	True	True	False		
open_loop	Bool	false	False	True	True	True	False		
pi_mode	Bool	false	False	True	True	True	False		
w_setpoint	Real	0.0	False	True	True	True	False		
y_actual	Real	0.0	False	True	True	True	False		
Kc_in	Real	0.0	False	True	True	True	False		
Ki_in	Real	0.0	False	True	True	True	False		
▼ Output									
u_out	Real	0.0	False	True	True	True	False		
e_out	Real	0.0	False	True	True	True	False		
u_p_out	Real	0.0	False	True	True	True	False		
u_i_out	Real	0.0	False	True	True	True	False		
Kc_P_out	Real	0.0	False	True	True	True	False		
Kc_PI_out	Real	0.0	False	True	True	True	False		
Ki_step_out	Real	0.0	False	True	True	True	False		
InOut									
▼ Static									
u_integral_stat	Real	0.0	False	True	True	True	False		

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Program blocks

FB_Plant_DB [DB2]

FB_Plant_DB Properties

General

Name	FB_Plant_DB	Number	2	Type	DB	Language	DB
Numbering	Automatic						

Information

Title		Author		Comment		Family	
Version	0.1	User-defined ID					

Name	Data type	Start value	Retain	Accessible from HMI/OPC UA/Web API	Writ-able from HMI/ OPC UA/ Web API	Visible in HMI engi-neering	Setpoint	Supervi-sion	Comment
▼ Input									
enable	Bool	false	False	True	True	True	False		
u_in	Real	0.0	False	True	True	True	False		
▼ Output									
y_out	Real	0.0	False	True	True	True	False		
InOut									
▼ Static									
u_stat	Real	0.0	False	True	True	True	False		
y_stat	Real	0.0	False	True	True	True	False		

Totally Integrated Automation Portal		
PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] Technology objects This folder is empty.		

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / PLC tags / Default tag table [44]

PLC tags

PLC tags									
	Name	Data type	Address	Retain	Accessi-ble from HMI/OPC UA/Web API	Writable from HMI/OPC UA/Web API	Visible in HMI engi-neering	Supervision	Comment
	referentna_vrednost	Real	%MD10	False	True	True	True		
	izlazna_vrednost_objekta	Real	%MD14	False	True	True	True		
	matematicko_upravljanje	Real	%MD18	False	True	True	True		
	greska_pracenja	Real	%MD30	False	True	True	True		
	vrednost_integrala	Real	%MD22	False	True	True	True		
	izbor_rezima_regulatora	Bool	%M0.1	True	True	True	True		
	mod_motora	Bool	%M0.0	True	True	True	True		
	proporcionalno_dejstvo	Real	%MD26	False	True	True	True		
	Kc_P	Real	%MD34	False	True	True	True		
	Kc_PI	Real	%MD38	False	True	True	True		
	Ki_step	Real	%MD42	False	True	True	True		
	izbor_zadatka	Bool	%M0.2	True	True	True	True		
	Kc_HMI_input	Real	%MD46	False	True	True	True		
	Ki_HMI_input	Real	%MD50	False	True	True	True		

Totally Integrated Automation Portal		
PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] PLC data types This folder is empty.		

Totally Integrated Automation Portal							
PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Watch and force tables Force table <table><thead><tr><th>Name</th><th>Address</th><th>Display format</th><th>Force value</th><th>Comment</th></tr></thead><tbody></tbody></table>			Name	Address	Display format	Force value	Comment
Name	Address	Display format	Force value	Comment			

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Watch and force tables

Watch table_1

Name	Address	Display format	Modify value	Comment
"motor_on"	%M0.0	Bool		
"mode_PI"	%M0.1	Bool		
"w_setpoint"	%MD10	Floating-point number		
"y_objekat"	%MD14	Floating-point number		
"u_upravljanje"	%MD18	Floating-point number		
"u_integral"	%MD22	Floating-point number		
"u_proporcionalni"	%MD26	Floating-point number		
"e_greska"	%MD30	Floating-point number		
"Kc_P"	%MD34	Floating-point number	5.0	
"Kc_PI"	%MD38	Floating-point number	5.0	
"Ki_step"	%MD42	Floating-point number	0.4	
"mode_open_loop"	%M0.2	Bool		

Totally Integrated Automation Portal				
PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] Traces <table><tr><th>Name</th></tr><tr><td>Trace</td></tr></table>			Name	Trace
Name				
Trace				

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Traces / Measurements

open_loop_trace

Signals

Name	Data type	Address	Unit	Comment
"matemacko_upravljanje"	Real	%MD18		
"izlazna_vrednost_objekta"	Real	%MD14		
"referentna_vrednost"	Real	%MD10		

Snapshots

Name	Time stamp	Comment
------	------------	---------

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Traces / Measurements

closed_loop_P_trace

Signals

Name	Data type	Address	Unit	Comment
"matemacko_upravljanje"	Real	%MD18		
"izlazna_vrednost_objekta"	Real	%MD14		
"referentna_vrednost"	Real	%MD10		

Snapshots

Name	Time stamp	Comment
------	------------	---------

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Traces / Measurements

closed_loop_PI_trace

Signals

Name	Data type	Address	Unit	Comment
"matemacko_upravljanje"	Real	%MD18		
"izlazna_vrednost_objekta"	Real	%MD14		
"referentna_vrednost"	Real	%MD10		

Snapshots

Name	Time stamp	Comment
------	------------	---------

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Traces / Measurements

ARW_trace

Signals

Name	Data type	Address	Unit	Comment
"matematicko_upravljanje"	Real	%MD18		
"izlazna_vrednost_objekta"	Real	%MD14		
"referentna_vrednost"	Real	%MD10		

Snapshots

Name	Time stamp	Comment
------	------------	---------

Totally Integrated Automation Portal		
PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Traces Combined measurements Name		

Totally Integrated Automation Portal		
PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / OPC UA communication Server interfaces This folder is empty.		

Totally Integrated Automation Portal		
PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] PLC alarm text lists This folder is empty.		

Totally Integrated Automation Portal

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] / Local modules

PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]

PLC za simuliranje rada objekta

General\Project information

Name	PLC za simuliranje rada objekta	Author	Korisnik	Comment	
Slot	1	Rack	0		

General\Catalog information

Short designation	CPU 1214C DC/DC/DC	Description	Work memory 100 KB; 24VDC power supply with DI14 x 24VDC SINK/ SOURCE, DQ10 x 24VDC and AI2 on board; 6 high-speed counters and 4 pulse outputs on-board; signal board expands on-board I/O; up to 3 communication modules for serial communication; up to 8 signal modules for I/O expansion; PROFINET IO controller, I-device, transport protocol TCP/IP, secure Open User Communication, S7 communication, Web server, OPC UA: Server DA	Article number	6ES7 214-1AG40-0XB0
Firmware version	V4.4				

General\Identification & Maintenance

Plant designation		Location identifier		Installation date	2026-08-19 14:56:46.979
Additional information					

General\Checksums

Text lists	FA 70 E8 75 1D 5A 8E 29	Software	15 69 F9 26 E6 73 38 7B		
------------	-------------------------	----------	-------------------------	--	--

PROFINET interface [X1]\General

Name	PROFINET interface_1	Author	Korisnik	Comment	
------	----------------------	--------	----------	---------	--

PROFINET interface [X1]\General\Project information

Name	DI 14/DQ 10_1	Comment		Name	AI 2_1
Comment					

PROFINET interface [X1]\Ethernet addresses\Interface networked with

Subnet:	PN/IE_1				
---------	---------	--	--	--	--

PROFINET interface [X1]\Ethernet addresses\IP protocol

IP configuration	Set IP address in the project	IP address:	192.168.0.1	Subnet mask:	255.255.255.0
Use router	False				

PROFINET interface [X1]\Ethernet addresses\PROFINET

PROFINET device name is set directly at the device	False	Generate PROFINET device name automatically	True	PROFINET device name:	plc za simuliranje rada objekta
Converted name:	plcxazaxasimuliranjexaradaxaobjek-ta66ed	Device number:	0		

PROFINET interface [X1]\Time synchronization

Enable time synchronization via NTP server	Enable time synchronization via NTP server		IP addresses	Server 1	0.0.0.0
Server 2	0.0.0.0	Server 3	0.0.0.0	Server 4	0.0.0.0
Update interval	10sec			CPU synchronizes the modules of the device.	No synchronization

PROFINET interface [X1]\Digital inputs\Channel0

Channel address	I0.0	Input filters	6.4 millisec	Enable pulse catch	0
-----------------	------	---------------	--------------	--------------------	---

PROFINET interface [X1]\Digital inputs\Channel0\

Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49152	Event name:	0
Hardware interrupt:	0	Rising edge0	Rising edge0		

PROFINET interface [X1]\Digital inputs\Channel0\

Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49280	Event name:	0
Hardware interrupt:	0	Falling edge0	Falling edge0		

PROFINET interface [X1]\Digital inputs\Channel1

Channel address	I0.1	Input filters	6.4 millisec	Enable pulse catch	0
-----------------	------	---------------	--------------	--------------------	---

PROFINET interface [X1]\Digital inputs\Channel1\

Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49153	Event name:	0
Hardware interrupt:	0	Rising edge1	Rising edge1		

PROFINET interface [X1]\Digital inputs\Channel1\

Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49281	Event name:	0
Hardware interrupt:	0	Falling edge1	Falling edge1		

PROFINET interface [X1]\Digital inputs\Channel2

Channel address	I0.2	Input filters	6.4 millisec	Enable pulse catch	0
-----------------	------	---------------	--------------	--------------------	---

PROFINET interface [X1]\Digital inputs\Channel2\

Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49154	Event name:	0
Hardware interrupt:	0	Rising edge2	Rising edge2		

PROFINET interface [X1]\Digital inputs\Channel2\

Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49282	Event name:	0
Hardware interrupt:	0	Falling edge2	Falling edge2		

PROFINET interface [X1]\Digital inputs\Channel3

Channel address	I0.3	Input filters	6.4 millisec	Enable pulse catch	0
-----------------	------	---------------	--------------	--------------------	---

PROFINET interface [X1]\Digital inputs\Channel3\

Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49155	Event name:	0
------------------------------	---	--------------------------	-------	-------------	---

Totally Integrated Automation Portal							
Hardware interrupt:	0	Rising edge3	Rising edge3				
PROFINET interface [X1]\Digital inputs\Channel3\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49283	Event name:	0		
Hardware interrupt:	0	Falling edge3	Falling edge3				
PROFINET interface [X1]\Digital inputs\Channel4							
Channel address	I0.4	Input filters	6.4 millise	Enable pulse catch	0		
PROFINET interface [X1]\Digital inputs\Channel4\							
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49156	Event name:	0		
Hardware interrupt:	0	Rising edge4	Rising edge4				
PROFINET interface [X1]\Digital inputs\Channel4\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49284	Event name:	0		
Hardware interrupt:	0	Falling edge4	Falling edge4				
PROFINET interface [X1]\Digital inputs\Channel5							
Channel address	I0.5	Input filters	6.4 millise	Enable pulse catch	0		
PROFINET interface [X1]\Digital inputs\Channel5\							
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49157	Event name:	0		
Hardware interrupt:	0	Rising edge5	Rising edge5				
PROFINET interface [X1]\Digital inputs\Channel5\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49285	Event name:	0		
Hardware interrupt:	0	Falling edge5	Falling edge5				
PROFINET interface [X1]\Digital inputs\Channel6							
Channel address	I0.6	Input filters	6.4 millise	Enable pulse catch	0		
PROFINET interface [X1]\Digital inputs\Channel6\							
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49158	Event name:	0		
Hardware interrupt:	0	Rising edge6	Rising edge6				
PROFINET interface [X1]\Digital inputs\Channel6\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49286	Event name:	0		
Hardware interrupt:	0	Falling edge6	Falling edge6				
PROFINET interface [X1]\Digital inputs\Channel7							
Channel address	I0.7	Input filters	6.4 millise	Enable pulse catch	0		
PROFINET interface [X1]\Digital inputs\Channel7\							
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49159	Event name:	0		
Hardware interrupt:	0	Rising edge7	Rising edge7				
PROFINET interface [X1]\Digital inputs\Channel7\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49287	Event name:	0		
Hardware interrupt:	0	Falling edge7	Falling edge7				
PROFINET interface [X1]\Digital inputs\Channel8							
Channel address	I1.0	Input filters	6.4 millise	Enable pulse catch	0		
PROFINET interface [X1]\Digital inputs\Channel8\							
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49160	Event name:	0		
Hardware interrupt:	0	Rising edge8	Rising edge8				
PROFINET interface [X1]\Digital inputs\Channel8\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49288	Event name:	0		
Hardware interrupt:	0	Falling edge8	Falling edge8				
PROFINET interface [X1]\Digital inputs\Channel9							
Channel address	I1.1	Input filters	6.4 millise	Enable pulse catch	0		
PROFINET interface [X1]\Digital inputs\Channel9\							
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49161	Event name:	0		
Hardware interrupt:	0	Rising edge9	Rising edge9				
PROFINET interface [X1]\Digital inputs\Channel9\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49289	Event name:	0		
Hardware interrupt:	0	Falling edge9	Falling edge9				
PROFINET interface [X1]\Digital inputs\Channel10							
Channel address	I1.2	Input filters	6.4 millise	Enable pulse catch	0		
PROFINET interface [X1]\Digital inputs\Channel10\							
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49162	Event name:	0		
Hardware interrupt:	0	Rising edge10	Rising edge10				
PROFINET interface [X1]\Digital inputs\Channel10\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49290	Event name:	0		
Hardware interrupt:	0	Falling edge10	Falling edge10				
PROFINET interface [X1]\Digital inputs\Channel11							
Channel address	I1.3	Input filters	6.4 millise	Enable pulse catch	0		
PROFINET interface [X1]\Digital inputs\Channel11\							
Enable rising edge detection	0	RidPrefixRisingEdgeEvent	49163	Event name:	0		
Hardware interrupt:	0	Rising edge11	Rising edge11				
PROFINET interface [X1]\Digital inputs\Channel11\							
Enable falling edge detection	0	RidPrefixFallingEdgeEvent	49291	Event name:	0		
Hardware interrupt:	0	Falling edge11	Falling edge11				
PROFINET interface [X1]\Digital inputs\Channel12							
Channel address	I1.4	Input filters	6.4 millise	Enable pulse catch	0		

Totally Integrated Automation Portal						
PROFINET interface [X1]\Digital inputs\Channel13						
Channel address	I1.5	Input filters	6.4 millise	Enable pulse catch	0	
PROFINET interface [X1]\Analog inputs\Noise reduction						
Integration time	50 Hz (20 ms)					
PROFINET interface [X1]\Analog inputs\Channel0						
Channel address	IW64	Measurement type	Voltage	Voltage range	0..10 V	
Smoothing	Weak (4 cycles)			Enable overflow diagnostics	1	
PROFINET interface [X1]\Analog inputs\Channel1						
Channel address	IW66	Measurement type	Voltage	Voltage range	0..10 V	
Smoothing	Weak (4 cycles)			Enable overflow diagnostics	1	
PROFINET interface [X1]\Digital outputs						
Reaction to CPU STOP	Use substitute value					
PROFINET interface [X1]\Digital outputs\Channel0						
Channel address	Q0.0	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel1						
Channel address	Q0.1	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel2						
Channel address	Q0.2	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel3						
Channel address	Q0.3	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel4						
Channel address	Q0.4	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel5						
Channel address	Q0.5	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel6						
Channel address	Q0.6	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel7						
Channel address	Q0.7	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel8						
Channel address	Q1.0	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Digital outputs\Channel9						
Channel address	Q1.1	Substitute a value of 1 on a change from RUN to STOP.	0			
PROFINET interface [X1]\Operating mode						
IO controller	True	IO system		Device number	0	
IO device	False					
PROFINET interface [X1]\I/O addresses\Input addresses						
Start address	0.0	End address	1.7	Organization block	0	
Process image	0					
PROFINET interface [X1]\I/O addresses\Input addresses						
Start address	64	End address	67	Organization block	0	
Process image	0					
PROFINET interface [X1]\I/O addresses\Output addresses						
Start address	0.0	End address	1.7	Organization block	0	
Process image	0					
PROFINET interface [X1]\Advanced options\Interface options						
Support device replacement without exchangeable medium	True	Permit overwriting of device names of all assigned IO devices	False	Use IEC V2.2 LLDP mode	False	
Keep-Alive connection monitoring:	30s					
PROFINET interface [X1]\Advanced options\Real time settings\IO communication						
Send clock:	1.000ms					
PROFINET interface [X1]\Advanced options\Real time settings\Real time options						
Calculated bandwidth for cyclic IO data:	0.000ms	Calculated bandwidth for cyclic IO data:	0.000%			
PROFINET interface [X1]\Advanced options\Port [X1 P1]\General						
Name	Port_1	Author	Korisnik	Comment		
PROFINET interface [X1]\Advanced options\Port [X1 P1]\Port interconnection\Local port:						
Local port:	PLC za simuliranje rada objekta\PROFINET interface_1 [X1]\Port_1 [X1 P1]	Medium:	Copper	Cable name:	---	

Totally Integrated Automation Portal						
Web server\						
User-defined web pages						
Application name		HTML source path	Default HTML page	Files with dynamic content	Web DB number	Fragment DB number
			index.htm	.htm;.html	333	334
Web server\						
Overview of interfaces						
Device		Interface			Enabled web server access	
PLC za simuliranje rada objekta		PROFINET interface_1			False	
User interface languages						
Assign project language				User interface languages		
English (United States)				German		
English (United States)				English		
English (United States)				French		
English (United States)				Spanish		
English (United States)				Italian		
English (United States)				Chinese (simplified)		
Time of day\						
Local time						
Time zone		(UTC +01:00) Berlin, Bern, Brussels, Rome, Stockholm, Vienna				
Time of day\						
Daylight saving time						
Activate daylight saving time		1	Difference between standard and daylight saving time	60mins		
Time of day\						
Daylight saving time\						
Start of daylight saving time						
Starting week of the month:		Last		Sunday	of	March
at		01:00 a.m.				
Time of day\						
Daylight saving time\						
Start of standard time						
		Last		Sunday	of	October
at		02:00 a.m.				
Protection & Security						
Level of protection		No protection				
Protection & Security\						
Connection mechanisms						
Permit access with PUT/GET communication from remote partner		False				
Protection & Security\						
Security event						
Summarize diagnostics in case of high message volume		True	Length of an interval	20	Unit	seconds
Protection & Security\						
External load memory						
Disable copying from internal load memory to external load memory		False				
Configuration control\						
Configuration control for central configuration						
Allow to reconfigure the device via the user program		0				
Connection resources\						
		Station resources - Reserved - Maximum	Station resources - Reserved - Configured	Station resources - Dynamic - Configured	Module resources - PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC] - Configured	
Maximum number of resources:			62	6	68	
		Maximum	Configured	Configured	Configured	
PG communication:		4	-	-	-	
HMI communication:		12	2	0	2	
S7 communication:		8	0	0	0	
Open user communication:		8	0	0	0	
Web communication:		30	-	-	-	
Other communication:		-	-	0	0	
Total resources used:			2	0	2	
Available resources:			60	6	66	
Overview of addresses\						
Overview of addresses\						
Overview of addresses						
Inputs		True	Outputs	True	Address gaps	False
Slot		True				

Totally Integrated Automation Portal											
Type	Addr. from	Addr. to	Module	PIP	Device name	Device number	Size	Master / IO system	Rack	Slot	
I	0	1	DI 14/DQ 10_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 1	
O	0	1	DI 14/DQ 10_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 1	
I	64	67	AI 2_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 2	
I	1000	1003	HSC_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 16	
I	1004	1007	HSC_2	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 17	
I	1008	1011	HSC_3	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 18	
I	1012	1015	HSC_4	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 19	
I	1016	1019	HSC_5	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 20	
I	1020	1023	HSC_6	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	4 Bytes	-	0	1 21	
O	1000	1001	Pulse_1	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 32	
O	1002	1003	Pulse_2	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 33	
O	1004	1005	Pulse_3	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 34	
O	1006	1007	Pulse_4	Automatic update	PLC za simuliranje rada objekta [CPU 1214C DC/DC/DC]	-	2 Bytes	-	0	1 35	